

ChatGPT

Independent Cascade Model

Independent Cascade models Show moreShow less.	2
diff between working of SIR and Independent models Show moreShow less.	10



Independent Cascade models

The **Independent Cascade (IC) Model** is one of the most important models in **network diffusion** and **influence propagation** in social networks.

It is widely used to model:

- Viral marketing
- Spread of information
- Rumors
- Memes
- Product adoption
- Fake news
- Social influence

It is closely related to epidemic spreading models like **SIR**, but adapted for influence in graphs.

1. Core Idea

In the IC model:

- A node can be either:
 - **Inactive** (not influenced)
 - **Active** (influenced)
- Once a node becomes active:
 - it gets **ONE chance** to activate each inactive neighbor.
 - after trying once, it can never try again.

This creates a cascading spread of influence across the network.

2. Intuition

Imagine:

- You post a viral reel.
- Your followers may repost it.
- Their followers may repost it.
- and so on...

Each person independently decides whether to spread the content.


That is why it is called:

Independent Cascade

because each activation attempt is independent.

3. Graph Representation

Suppose we have graph:



Edges represent social connections.

Each edge has a probability:

$P(A \rightarrow B) = 0.4$
 $P(A \rightarrow C) = 0.7$
 $P(B \rightarrow C) = 0.5$
 $P(B \rightarrow D) = 0.6$

4. Rules of IC Model

At time $t = 0$:

- Some initial nodes are active.
- Called **seed nodes**.

Then diffusion proceeds in discrete time steps.

Rule 1: Newly active nodes try to influence neighbors

If node u becomes active at time t :

- it gets one chance to activate inactive neighbor v
- with probability p_{uv}

Rule 2: Success is probabilistic

Each attempt succeeds independently.

Example:

- If $p_{uv} = 0.8$
- then there is 80% chance of activation.

Rule 3: Only one attempt allowed

Even if activation fails:

- u cannot retry later.

This is a major difference from epidemic models.

Rule 4: Process stops when no new activations occur

Eventually no more nodes activate.

Cascade ends.

5. Step-by-Step Example

Suppose:

```
A → B (0.5)
A → C (0.7)
B → D (0.6)
```

Initial seed:

```
A active
```

Time $t = 0$

Active nodes:

```
{A}
```

Time $t = 1$

A tries:

- activate B with probability 0.5
- activate C with probability 0.7

Suppose:

- B succeeds
- C fails

Now active:

{A, B}

Time $t = 2$

B tries to activate D.

Suppose success.

Now active:

{A, B, D}

Time $t = 3$

No new activations.

Process stops.

6. Mathematical Definition

If:

- $G = (V, E)$
- p_{uv} = probability on edge (u, v)

Then:

For every newly activated node u :

$$P(u \text{ activates } v) = p_{uv}$$

Each edge attempt is independent.

7. Visualization of Cascade

t=0: A
t=1: A → B
t=2: A → B → D

Influence spreads like falling dominoes.

8. Characteristics of IC Model

Property	IC Model
Time	Discrete
Activation	Probabilistic
Retry allowed?	No
State change	Inactive → Active
Active forever?	Yes
Edge weights	Activation probabilities

9. Relation to SIR Epidemic Model

The IC model is very similar to the SIR model.

SIR Epidemic	IC Model
Infected person	Active node
Infect neighbor	Influence neighbor
Infection probability	Activation probability
One infectious period	One activation attempt
Recovered state	Usually omitted

Difference:

- IC focuses on **influence propagation**
- SIR focuses on **disease spread**

10. Applications

A. Viral Marketing

Companies choose seed users to maximize spread.

Example:

- Giving free iPhones to influencers.

This leads to:

Influence Maximization Problem

B. Rumor Spread

Tracks misinformation diffusion.

C. Recommendation Systems

Model how trends spread.

D. Political Campaigns

How opinions propagate through communities.

11. Influence Maximization

One of the biggest uses of IC model.

Goal:

Find k seed nodes that maximize expected spread.

Important algorithms:

- Greedy influence maximization
 - CELF
 - IMM
 - TIM/TIM+
 - Reverse Reachable Sets
-

12. Communities and IC Model

Communities strongly affect cascades.

Inside communities:

- dense connections
- higher propagation

Across communities:

- weak bridges

So influential bridge nodes become very important.

This connects IC model with:

- community detection
 - k-shell decomposition
 - centrality measures
 - multilayer networks
-

13. IC Model in Multilayer Networks

In multilayer graphs:

- activation may spread:
 - within same layer
 - across layers

Example:

Instagram layer
Twitter layer
YouTube layer

A user becoming active on Instagram may activate their Twitter identity.

So multilayer IC models use:

- intra-layer probabilities
- inter-layer probabilities

14. IC vs Linear Threshold (LT) Model

Another famous diffusion model is the **Linear Threshold Model**.

IC Model	LT Model
Probabilistic edge influence	Threshold-based
One neighbor may activate	Combined neighbors activate
Random edge attempts	Accumulated pressure
Local independent trials	Global threshold effect

IC is more suitable for:

- viral spread
- stochastic diffusion

LT is better for:

- peer pressure
- adoption after social reinforcement

15. Advantages

- ✓ Simple and intuitive
- ✓ Models randomness well
- ✓ Works on large networks

- ✓ Widely used in research
- ✓ Good for viral diffusion

16. Limitations

- ✗ Real humans retry influence multiple times
- ✗ Probabilities hard to estimate
- ✗ Assumes independence
- ✗ No temporal memory
- ✗ Simplified behavior model

17. Simple Pseudocode

```
Python
active = seed_nodes
new_active = seed_nodes

while new_active:
    temp = []

    for u in new_active:
        for v in neighbors(u):
            if v is inactive:
                if random() < p[u][v]:
                    activate(v)
                    temp.append(v)

    new_active = temp
```

18. Conceptual Interpretation

The IC model represents:

“Each influenced individual independently gets one opportunity to influence others.”

This captures:

- uncertainty
- virality
- stochastic diffusion
- social contagion

very effectively.

19. Important Research Areas

The IC model is foundational in:

- Network Science

- Social Network Analysis
- Graph Mining
- Diffusion Modeling
- Geometric Deep Learning
- Influence Maximization
- Epidemic Forecasting
- Information Cascades

20. Connection to Your Multilayer Influence Project

For your influential node detection project:

IC model is important because:

- You can evaluate how influential a node truly is.
- Start cascade from node v
- Measure:
 - spread size
 - cascade depth
 - cross-layer influence

Many papers use:

Average cascade size under IC model

as the ground-truth influence score.

So IC simulation is often used to validate:

- centrality algorithms
- k-shell methods
- multilayer influence measures
- GNN-based influence predictors



diff between working of SIR and Independent models

The SIR model and the **Independent Cascade (IC) Model** are very similar mathematically, but they were designed for different purposes and have different diffusion mechanics.

The biggest difference is:

SIR models disease dynamics, while
IC models influence propagation in networks.

High-Level Difference

Aspect	SIR Model	Independent Cascade (IC)
Main use	Epidemics	Social influence
States	Susceptible, Infected, Recovered	Inactive, Active
Retry attempts	Infection possible while infected	Only ONE attempt
Recovery	Yes	Usually no recovery
Time active	Temporary	Permanent
Spread type	Biological infection	Information diffusion

1. Core Working Mechanism

A. SIR Model Working

In SIR:

Each node has 3 states:

S → I → R

Where:

- **S (Susceptible)** → healthy but can be infected
- **I (Infected)** → currently spreading disease
- **R (Recovered)** → immune/removed

Process

Step 1:

An infected node infects neighbors.

Step 2:

After some time, infected node recovers.

Step 3:

Recovered node stops spreading forever.

Important Point

While a node is infected:

- it can infect neighbors multiple times across multiple timesteps.

This is the major difference from IC.

B. Independent Cascade (IC) Working

In IC:

States are simpler:

Inactive → Active

When a node becomes active:

- it gets exactly ONE chance
- to activate each inactive neighbor.

After trying once:

- it never tries again.

Node remains active forever.

2. Timeline Comparison

Suppose:

A → B → C

Seed node = A

A. SIR Timeline

t = 0

A infected

t = 1

A infects B.

A infected
B infected

A may still remain infected.

t = 2

A can AGAIN attempt infection.

B infects C.

Eventually:

```
A recovered
B infected
C infected
```

Key Feature

An infected node may spread infection for multiple time steps before recovery.

B. IC Timeline

t = 0

```
A active
```

t = 1

A gets ONE chance:

- activate B

After this:

- A can never attempt again.
-

t = 2

If B became active:

- B gets ONE chance to activate C.
-

Key Feature

Each node spreads influence only once.

3. State Transition Difference

SIR

Susceptible → Infected → Recovered

Nodes eventually stop participating.

IC

Inactive → Active

No recovery stage.

Activated nodes stay active forever.

4. Retry Mechanism

This is the MOST IMPORTANT distinction.

SIR

While infected:

- node continuously infects neighbors
- until recovery.

Example:

**A infects B at t=1
A may infect C at t=2
A may infect D at t=3**

IC

Only one attempt allowed.

Example:

**A tries B once
A tries C once
Done forever**

No second chance.

5. Mathematical Difference

A. SIR

Two parameters:

Infection rate

$$\beta$$

Probability of spreading infection.

Recovery rate

$$\gamma$$

Probability of recovery.

Dynamics:

$$S \rightarrow I \rightarrow R$$

B. IC

Single edge probability:

$$p_{uv}$$

Probability node u activates node v .

No recovery parameter.

6. Example Comparison

Suppose:

A $\rightarrow$ B

Probability = 0.5

In SIR

If A remains infected for 5 timesteps:

A may try infecting B repeatedly:

t1 $\rightarrow$ fail
t2 $\rightarrow$ fail

t3 → success

Eventually B likely infected.

In IC

A gets one attempt only:

t1 → fail
Done forever

B never activates.

7. Interpretation Difference

SIR

Models:

- viruses
- pandemics
- epidemics
- biological contagion

Because diseases spread continuously during infection period.

IC

Models:

- social sharing
- reposting
- influence
- recommendations
- viral content

Because people often:

- share content once
 - recommend once
 - repost once
-

8. Visualization

SIR

```
A infected
↓
B infected
↓
A recovers
```

Continuous infection period.

IC

```
A activates B once
B activates C once
```

Like falling dominoes.

9. Memory of the Process

SIR

Process has temporal duration:

- infection lasts for time.
-

IC

Memoryless after attempt:

- once tried, edge becomes inactive forever.
-

10. Practical Difference in Networks

SIR Spread

Usually produces:

- slower sustained spread
 - epidemic waves
-

IC Spread

Usually produces:

- sharp cascades

- rapid viral bursts

11. Relation Between Them

Interestingly:

IC model is often considered a simplified discrete-time version of epidemic spreading.

In fact:

$IC \approx SIR$ with infection duration = 1 timestep

because:

- node spreads once
- then effectively stops influencing.

12. Which One is Used Where?

Domain	Preferred Model
COVID spread	SIR
Viral tweet spread	IC
Fake news diffusion	IC
Disease forecasting	SIR
Marketing campaigns	IC
Social influence maximization	IC

13. In Your Multilayer Influence Project

You will likely use:

IC model for:

- influence maximization
- influential node ranking
- information diffusion evaluation

because papers in:

- social network analysis
- graph mining
- multilayer influence detection

mostly evaluate nodes using IC cascades.

SIR may still be used when:

- studying epidemic robustness
 - resilience analysis
 - spreading dynamics
-

Final Intuition

SIR

Disease keeps spreading while infected.

IC

A node gets one shot to influence neighbors.

That “one-shot propagation” is the defining property of the Independent Cascade model.