

# **FORTRAN IV Instruction Manual**

# **FORTRAN IV Instruction Manual**

# **FORTRAN IV Instruction Manual**

---

## **Preface**

**Cromemco FORTRAN IV** is a universal, problem-oriented programming language designed to simplify the preparation and check-out of computer programs. The name of the language—FORTRAN—is an acronym for FORmula TRANslator. The syntactical rules for using the language are rigorous and require the programmer to define fully the characteristics of his problem in a series of precise statements. These statements, called the *source program*, are translated by a system program called the FORTRAN Processor into an *object program* in the machine language of the computer on which the program is to be executed.

This manual defines the FORTRAN source language for the Z-80 microcomputer. This language includes the American National Standard FORTRAN language as described in ANSI document X3.9—1966, approved on March 7, 1966, plus a number of language extensions. These language extensions are described in the text of this document and listed in Appendix A. Examples are included throughout the manual to illustrate the construction and use of the language elements. The programmer should be familiar with all aspects of the language to take full advantage of its capabilities.

Section 2 describes the form and components of the FORTRAN source program. Sections 3 and 4 define data types and their expressional relationships. Sections 5 through 9 describe the proper construction and usage of the various statement classes.

---

# **FORTRAN IV Instruction Manual**

# **FORTRAN IV Instruction Manual**

# **FORTRAN IV Instruction Manual**

## Table Of Contents

<b>SECTION 1 INTRODUCTION .....</b>	1
<b>SECTION 2 FORTRAN PROGRAM FORM .....</b>	1
<b>FORTRAN Character Set</b>	
Letters	
Digits	
Alphanumerics	
Special Characters	
<b>FORTRAN Line Format</b>	
Statements	
<b>SECTION 3 DATA REPRESENTATION/STORAGE FORMAT .....</b>	3
<b>Data Names And Types</b>	
Names	
Types	
<b>Constants</b>	
<b>Variables</b>	
<b>Arrays And Array Elements</b>	
Subscripts	
Data Storage Allocation	
<b>SECTION 4 FORTRAN EXPRESSIONS .....</b>	6
Arithmetic Expressions	
Expression Evaluation	
Logical Expressions	
Relational Expressions	
Logical Operators	
<b>SECTION 5 REPLACEMENT STATEMENTS .....</b>	8
<b>SECTION 6 SPECIFICATION STATEMENTS .....</b>	9
Specification Statements	
Array Declarators	
Type Statements	
EXTERNAL Statements	
DIMENSION Statements	
COMMON Statements	
EQUIVALENCE Statements	
DATA Initialization Statement	
DEFINE FILE Statements	
<b>SECTION 7 FORTRAN CONTROL STATEMENTS .....</b>	12
The GOTO Statements	
Unconditional GOTO	
Computed GOTO	
Assigned GOTO	
ASSIGN Statement	
The IF Statement	
Arithmetic IF	
Logical IF	
DO Statement	
CONTINUE Statement	
STOP Statement	
Pause Statement	
Call Statement	
Return Statement	
END Statement	

## Table Of Contents Continued

<b>SECTION 8 INPUT/OUTPUT .....</b>	15
<b>Unformatted READ/WRITE</b>	
<b>Auxiliary I/O Statements</b>	
<b>Input/Output List Specifications</b>	
List Item Types	
Special Notes On List Specifications	
<b>FORMAT Statements</b>	
Field Descriptors	
Numeric Conversions	
Hollerith Conversions	
Logical Conversion	
The X Descriptor	
The P Descriptor	
Special Control Features of FORMAT Statements	
<i>Repeat Specifications</i>	
<i>Field Separators</i>	
FORMAT Control, List Specifications And Record Demarcation	
FORMAT Control For Line Printer Operation	
FORMAT Specifications In Arrays	
<b>SECTION 9 FUNCTIONS AND SUBPROGRAMS .....</b>	22
<b>Statement Functions</b>	
<b>Library Functions</b>	
<b>Function Subprograms</b>	
Construction Of Function Subprograms	
Referencing A Function Subprogram	
<b>Subroutine Subprograms</b>	
Construction Of Subroutine Subprograms	
Referencing A Subroutine Subprogram	
<b>RETURN From Function And Subroutine Subprograms</b>	
<b>Processing Arrays In Subprograms</b>	
<b>Block Data Subroutine</b>	
<b>Appendix A—Language Extensions</b>	
<b>Appendix B—I/O Interface</b>	
<b>Appendix C—Subprogram Linkages</b>	
<b>Appendix D—ASCII Character Codes</b>	

©Copyright 1978. All rights reserved.





---

## Section 1 Introduction

---

Cromemco FORTRAN IV provides new capabilities for users of Z-80 based microcomputer systems. Cromemco FORTRAN IV is comparable to FORTRAN compilers on large main-frame and mini computers, and includes all of ANSI standard FORTRAN X3.9—1966, except for double precision and complex data types. Therefore, users can take advantage of the large number of applications already written in FORTRAN. Cromemco FORTRAN IV is supplied on diskette for use with Cromemco disk systems.

### RELOCATABLE CODE AND LIBRARY FEATURES

Cromemco FORTRAN IV is unique in that it provides a microprocessor FORTRAN development package that generates relocatable object modules. This means that only the subroutines and system routines required to run Cromemco FORTRAN IV programs are loaded before execution. Subroutines can be placed in a system library so that the user can develop a common set of subroutines that are used in his programs. Also, if the user changes only one module of his program, he has to re-compile only that module.

The standard library of subroutines supplied with Cromemco FORTRAN IV includes the following.

ABS	IABS	AINT
INT	AMOD	MOD
AMAX0	AMAX1	MAX0
MAX 1	AMIN0	AMIN1
MIN0	MIN1	FLOAT
IFIX	SIGN	ISIGN
DIM	IDIM	EXP
ALOG	ALOG10	SIN
COS	TANH	SQRT
ATAN	ATAN2	PEEK
POKE	INP	OUT

The library also contains routines for 32-bit floating point addition, subtraction, multiplication and division, etc. These routines are among the fastest available for performing these functions on the Z-80

### ENHANCEMENTS

The Cromemco FORTRAN IV compiler has a number of enhancements of the ANSI standard:

- LOGICAL variables which can be used as integer quantities in the range of +127 to -128.
- LOGICAL DO loops for tighter, faster execution of small valued integer loops.
- Mixed mode arithmetic
- Hexadecimal constants
- Logical operations on integer data—.AND., .OR., .NOT., .XOR. can be used for 16-bit or 8-bit boolean operations.
- READ/WRITE End of file or Error Condition Transfer—END = n and ERR = n (where n is the statement number) can be included in READ or WRITE statements to transfer control to the specified statement on detection of an error or an end of file condition.

### CROMEMCO FORTRAN IV COMPILER CHARACTERISTICS

The Cromemco FORTRAN IV compiler can compile several hundred statements a minute in a single pass and needs less than 32K of memory to compile most programs. Any available memory above the 32K minimum will be used by the compiler if it needs the extra room. In spite of its small size, the Cromemco FORTRAN IV compiler optimizes the generated object code in a number of ways:

- *Common subexpression elimination*—Common Subexpressions are evaluated once, and the value is substituted in later occurrences of the subexpression.
- *Peephole Optimization*—small sections of code are replaced by smaller and faster code in certain special cases. Example: I = I+1 uses an INX H instruction instead of a DAD.
- *Constant folding*—Integer constant expressions are evaluated at compile time.
- *Branch Optimizations*—The number of conditional jumps in arithmetic and logical IFs is minimized.

Long descriptive error messages are another feature of the compiler. For instance:

? Statement unrecognizable

would be printed if the compiler scanned a statement which was not an assignment or other FORTRAN statement. The last twenty characters scanned before the error is detected are also printed.

---

## Section 2 FORTRAN Program Form

---

Z-80 FORTRAN source programs consist of one program unit called the *main program* and any number of program units called *subprograms*. A discussion of subprogram types and methods of writing and using them is in Section 9 of this manual. Programs and program units are constructed of an ordered set of statements which precisely describe procedures for solving problems and which also define information to be used by the FORTRAN processor during

compilation of the object program. Each statement is written using the FORTRAN character set and following a prescribed line format.

### FORTRAN CHARACTER SET

To simplify reference and explanation, the FORTRAN character set is divided into four subsets and a name is given to each.

## Letters

A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X, Y, Z, \$

### Note

No distinction is made between upper and lower case letters. However, for clarity and legibility, exclusive use of upper case letters is recommended.

## Digits

0, 1, 2, 3, 4, 5, 6, 7, 8, 9

### Note

Strings of digits representing numeric quantity are normally interpreted as decimal numbers. However, in certain statements, the interpretation is in the hexadecimal number system in which case the letters A, B, C, D, E, F may also be used as hexadecimal digits. Hexadecimal usage is defined in the description of statements in which such notation is allowed.

## Alphanumerics

A sub-set of characters made up of all letters and all digits.

## Special Characters

Blank
= Equality Sign
+
- Minus Sign
*
/ Asterisk
( Slash
) Left Parenthesis
) Right Parenthesis
,
.
Comma
.
Decimal Point

### Notes

- FORTRAN program lines consist of 80 character positions or columns, numbered 1 through 80. They are divided into four fields.
- The following special characters are classified as Arithmetic operators and are significant in the unambiguous statement of arithmetic expressions.
  - . Index arithmetic operators
  - +
  - Subtraction or negative value
  - \*
  - / Multiplication
  - \*\* Division
  - Exponentiation
- The other special characters have specific application in the syntactical expression of the FORTRAN language and in the construction of FORTRAN statements.
- Any printable character may appear in a Hollerith or literal field.

## FORTRAN LINE FORMAT

The FORTRAN coding form shows the format of FORTRAN

program lines. The lines of the form consist of 80 character positions or columns, numbered 1 through 80, and are divided into four fields.

- *Statement Label* (or Number) field—Columns 1 through 5 (See definition of statement labels).
- *Continuation character field*—Column 6.
- *Statement field*—Columns 7 through 72
- *Identification field*—Columns 73 through 80.

The identification field is available for any purpose the FORTRAN programmer may desire and is ignored by the FORTRAN Processor. The lines of a FORTRAN statement are placed in Columns 1 through 72 formatted according to line types. The four line types, their definitions, and column formats are:

## Comment Line

Used for source program annotation at the convenience of the programmer.

- Column 1 contains the letter C.
- Columns 2-72 are used in any desired format to express the comment or they may be left blank.
- A comment line may be followed only by an initial line, an END line, or another comment line.
- Comment lines have no effect on the object program and are ignored by the FORTRAN Processor except for display purposes in the listing of the program.

### EXAMPLE:

C COMMENT LINES ARE INDICATED BY THE  
C CHARACTER C IN COLUMN 1.  
C THESE ARE COMMENT LINES

## END Line

The last line of a program unit.

- Columns 1-6 contain blank characters.
- Columns 7-72 contain one each of the characters E-N-D in that order in Columns 7 through 72, preceded by, interspersed with, or followed by blank characters.
- Each FORTRAN program unit must have an END line as its last line to inform the Processor that it is at the physical end of the program unit.
- An END line may follow any other type line.

### EXAMPLE:

END

## Initial Line

The first or only line of each statement.

- Columns 1-5 may contain a statement label to identify the statement.
- Column 6 must contain a zero or blank.
- Columns 7-72 contain all or part of the statement.
- An initial line may begin anywhere within the statement field.

**EXAMPLE:**

C THE STATEMENT BELOW CONSISTS  
C OF AN INITIAL LINE  
C  
C        A = .5\*SQRT(3-2.\*C)

**Continuation Line**

Used when additional lines of coding are required to complete a statement originating with an initial line.

- Columns 1–5 are ignored.
- Column 6 must contain a character *other than* zero or blank.
- Columns 7–72 contain the continuation of the statement.
- There may be as many continuation lines as needed to complete the statement.

**EXAMPLE:**

C THE STATEMENTS BELOW ARE AN INITIAL LINE  
C            AND 2 CONTINUATION LINES  
C

63    BETA(1,2) =  
1        A6BAR\*\*7-(BETA(2,2)-A5BAR\*50  
2        +SQRT(BETA)2,1))

A statement label may be placed in columns 1–5 of a FORTRAN statement initial line and is used for reference purposes in other statements. The following considerations govern the use of statement labels:

- The label is an integer from 1 to 99999.
- The numeric value of the label, leading zeroes and blanks are not significant.
- A label must be unique within a program unit.
- A label on a continuation line is ignored by the FORTRAN Processor.

**EXAMPLE:**

C EXAMPLES OF STATEMENT LABELS  
C  
1  
1 01  
99999  
763

**STATEMENTS**

Individually statements deal with specific aspects of a procedure described in a program unit and are classified as either *executable* or *non-executable*. Executable statements specify actions and cause the FORTRAN Processor to generate object program instructions. There are three types of executable statements:

- Replacement statements.
- Control statements.
- Input/Output statements.

*Non-executable* statements describe to the Processor the nature and arrangement of data and provide information about input/output formats and data initialization to the object program during program loading and execution. There are five types of non-executable statements:

- Specification statements.
- Data Initialization statements.
- FORMAT statements.
- Function defining statements.
- Subprogram statements.

The proper usage and construction of the various types of statements are described in Sections 5 through 9.

## Section 3 Data Representation/Storage Format

The FORTRAN language prescribes a definitive method for identifying data used in FORTRAN programs by *name* and *type*.

### DATA NAMES AND TYPES

#### Names

- *Constant*—An explicitly stated datum.
- *Variable*—A symbolically identified datum.
- *Array*—An ordered set of data in 1, 2, or 3 dimensions.
- *Array Element*—One member of the set of data of an array.

#### Types

- *Integer*. Precise representation of integral numbers (positive, negative or zero) having precision to five digits in the range -32768 to +32767 inclusive (-2\*\*15 to 2\*\*15-1).
- *Real*. Approximations of real numbers (positive, negative or zero) represented in computer storage in 4-byte, floating-

point form. Real data are precise to 7+ significant digits and their magnitude may lie between the approximate limits of 10\*\*-38 and 10\*\*38 (2\*\*-127 and 2\*\*127).

- *Logical*. One byte representations of the truth values "TRUE" or "FALSE" with "FALSE" defined to have an internal representation of zero. The constant .TRUE. has the value -1, however any non-zero value will be treated as .TRUE. in a LOGICAL IF Statement. In addition, Logical types may be used as one byte signed integers in the range -128 to +127, inclusive.

- *Hollerith*. A string of any number of characters from the computer's character set. All characters including blanks are significant. Hollerith data require one byte for storage of each character in the string.

#### CONSTANTS

FORTRAN constants are identified explicitly by stating their actual value. The plus (+) character need not precede positive

valued constants. Formats for writing constants are shown in Table 3-1.

## VARIABLES

Variable data are identified in FORTRAN statements by *symbolic names*. The names are unique strings of from 1 to 6 alphanumeric characters of which the first is a letter.

### Note:

System variable names and runtime subprogram names are distinguished from other variable names in that they begin with the dollar sign character (\$). It is therefore strongly recommended that in order to avoid conflicts, symbolic names in FORTRAN source programs begin with some letter other than "\$".

**Table 3-1 Constant Formats**

Type	Formats And Rules Of Use	Examples
<i>Integer</i>	<ul style="list-style-type: none"> <li>• 1 to 5 decimal digits interpreted as a decimal number.</li> <li>• A preceding plus(+) or minus (-) sign is optional.</li> <li>• No decimal point (.) or comma (,) is allowed</li> <li>• Value range: -32768 through + 32767 (-2**15 through 2**15-1).</li> </ul>	-763 1 +00672 -32768 +32767
<i>Real</i>	<ul style="list-style-type: none"> <li>• A decimal number with precision to 7 digits and represented in one of the following forms:           <ul style="list-style-type: none"> <li>(a) + or -f; + or -i.f; 22.E-1</li> <li>(b) + or -i.E+ or -e; + or -fE+ or -e; + or -i.fEe;</li> <li>+ or -iE+ or -e</li> </ul>           where i, f, and e are each strings representing integer, fraction, and exponent respectively.         </li> <li>• Plus (+) and (-) characters are optional.</li> <li>1 above, if r represents any of the forms preceding E+ or -e, i.e., rE+ or -e, the value of the constants is interpreted as r times 10**e, where -38&lt;=e&lt;=38.</li> <li>• If the constant preceding E+ or -e contains more significant digits than the precision for real data allows, truncation occurs, and only the most significant digits in the range will be represented.</li> </ul>	345. .345678 +345.678 +.3E3 -73E4
<i>Logical</i>	<ul style="list-style-type: none"> <li>• .TRUE. generates a non-zero byte (hexadecimal FF) and .FALSE. generates a word in which all bits are 0. If the logical values are used as 1-byte integers, the rules for use are the same as for type INTEGER, except that the range is -128 to +127, inclusive.</li> </ul>	.TRUE. .FALSE.
<i>Literal</i>	In the literal form, any number of characters may be enclosed by single quotation marks. The form is 'X1X2X3...Xn', where each Xi is any character other than '. Two quotation marks in succession may be used to represent the quotation mark character within the string, i.e., if X2 is to be the quotation mark character, the string appears as 'X1''X3...Xn'. Literal constants are used only in DATA initialization and FORMAT statements or as parameters to subprograms.	
<i>Hexadecimal</i>	<ul style="list-style-type: none"> <li>• The letter Z followed by a single quote, up to 5 hexadecimal digits (0-9 and A-F) and a single quote recognized as hexadecimal values.</li> <li>• A hexadecimal constant is right justified in its storage value.</li> <li>• Hexadecimal data may be used only in DATA initialization statements.</li> </ul>	Z'12' Z'AB12F' Z'1001' Z'FFFFF' Z'1F'

**EXAMPLES:**

I5, TBAR, B23, ARRAY, XFM79, MAX A1\$C.

Variable data are classified into three types: INTEGER, REAL and LOGICAL. The specification of type is accomplished in one of the following ways.

- Implicit typing in which the first letter of the symbolic name specifies Integer or Real Type. Unless explicitly typed, symbolic names beginning with I, J, K, L, M, or N represent integer variables, and symbolic names beginning with letters other than I, J, K, L, M or N represent Real Variables. *Integer Variables*: ITEM, J1, MODE, K123, N2. *Real Variables*: BETA, H2, ZAP, AMAT, XID.
- Variables may be typed explicitly, i.e., they may be given a particular type without reference to the first letter of their names. Variables may be explicitly typed as INTEGER, REAL or LOGICAL. The specific statements used in explicitly typing data are described in Section 6. Variable data receive their numeric value assignments during program execution or, initially, in a DATA statement (Section 6). Hollerith data

may be assigned to any type variable. The sub-section on Data Storage Allocation (following the next sub-section) contains a discussion of Hollerith data storage.

**ARRAYS AND ARRAY ELEMENTS**

An array is an ordered set of data characterized by the property of *dimension*. An array may have 1, 2 or 3 dimensions and is identified and typed by a symbolic name in the same manner as a variable except that an array name must be so declared by an "array indicator." Complete discussions of the array declarators appear in Section 6 of this manual. An array declarator also indicates the dimensionality and size of the array. An array element is one member of the data set that makes up any array. Reference to an array element in a FORTRAN statement is made by appending a subscript to the array name. The term array element is synonymous with the term subscripted variable used in some FORTRAN texts and reference manuals. An initial value may be assigned to any array element by a DATA statement or its value may be derived and defined during program execution.

**Table 3-2 Storage Allocation By Data Types**

Type	Allocation
<i>INTEGER</i>	2 bytes/ 1/2 storage unit <i>SIGN/</i> Binary Value Negative numbers are the 2's complement of positive representations.
<i>LOGICAL</i>	1 byte/ 1/4 storage unit Zeroes (false) or non-zero (true) A non-zero valued byte indicates true (the logical constant .TRUE. is represented by the hexadecimal value FF). A zero valued byte indicates false. When used as an arithmetic value, a Logical datum is treated as an Integer in the range of -128 to +127.
<i>REAL</i>	4 bytes/ 1 storage unit Characteristic      S <i>IGN/</i> Mantissa Mantissa            (continued)  The first byte is the characteristic expressed in excess 200 (octal) notation; i.e., a value of 200 octal corresponds to a binary exponent of 0. Values less than 200 octal correspond to negative exponents, and values greater than 200 correspond to positive exponents. By definition, if the characteristic is zero, the entire number is zero.  The next three bytes constitute the mantissa. The mantissa is always normalized such that the high-order bit is one, eliminating the need to actually save that bit. The high bit is used instead to indicate the sign of the number. A one indicates a negative number, and zero indicates a positive number. The mantissa is assumed to be a binary fraction whose binary point is to the left of the mantissa.

## **SUBSCRIPTS**

A subscript follows an array name to uniquely identify an array element. In use, a subscript in a FORTRAN statement takes on the same representational meaning as do subscripts in familiar algebraic notation. Rules that govern the use of subscripts are as follows:

- A subscript contains 1, 2 or 3 subscript expressions enclosed in parentheses.
- If there are two or three subscript expressions within the parentheses, they must be separated by commas.
- The number of subscript expressions must be the same as the specified dimensionality of the Array Declarator except in EQUIVALENCE statements (Section 6).
- A subscript expression is written in one of the following forms:

K	$C^*V+K$
V	$V-K$
$V+K$	$C^*V-K$
$C^*V$	

where C and K are integer constants and V is an integer variable name (see Section 4 for a discussion of expression evaluation).

- Subscripts themselves may *not* be subscripted.

### **EXAMPLE:**

$X(2^*J-3,7)$ ;  $A(I,J,K)$ ;  $I(20)$ ;  $C(L-2)$ ;  $Y(I)$

## **DATA STORAGE ALLOCATION**

Allocation of storage for FORTRAN data is made in numbers of *storage units*. A storage unit is the memory space required to store one real data value (4 bytes). Table 3-2 defines the word formats of the three data types. Hexadecimal data may be associated (via a DATA statement) with any data type. Its storage allocation is the same as the associated datum.

Hollerith or literal data may be associated with any data type by use of DATA initialization statements (Section 6). Up to four Hollerith characters may be associated with Real type storage, up to two with Integer and one with Logical type storage.

## **Section 4 FORTRAN Expressions**

A FORTRAN expression is composed of a single operand or a string of operands connected by operators. Two expression types—Arithmetic and Logical—are provided by FORTRAN. The operands, operators and rules of use for both types are described in the following paragraphs.

### **ARITHMETIC EXPRESSIONS**

The following rules define all permissible arithmetic expression forms.

- A constant, variable name, array element reference or function reference (Section 9) standing alone is an expression.

#### **EXAMPLES:**

$S(I)$     JOBNO    217    17.26     $\text{SQRT}(A+B)$

- If E is an expression whose first character is not an operator, the +E and -E are called signed expressions.

#### **EXAMPLES:**

-S    +JOBNO    -217    +17.26    - $\text{SQRT}(A+B)$

- If E is an expression, then (E) means the quantity resulting when E is evaluated.

#### **EXAMPLES:**

$(-A)$      $-(\text{JOBNO})$      $-(X+1)$      $(A-\text{SQRT}(A+B))$

- If E is an unsigned expression and F is any expression, then: f+E, F-E, F\*E, F/E and F\*\*E are all expressions.

#### **EXAMPLES:**

$-(B(I,J)+\text{SQRT}(A+B(K,L)))$   
 $1.7E-2^{**}(X+5.0)$   
 $-(B(I+3,3^*J+5)+A)$

- An evaluated expression may be integer or Real. The type is determined by the data type of the elements of the expression. If the elements of the expression are not all of the same type, the type of the expression is determined by the element having the highest type. The type hierarchy (highest to lowest) is as follows: REAL, INTEGER, LOGICAL.

- Expressions may contain nested parenthesized elements as in the following:

$$A^*(Z-((Y+X)/T))^{**}J$$

where Y+X is the innermost element, (Y+X)/T is the next innermost, Z-((Y+X)/T) the next. In such expressions, care should be taken to see that the number of left parentheses and the number of right parentheses are equal.

### **EXPRESSION EVALUATION**

Arithmetic expressions are evaluated according to the following rules:

- Parenthesized expression elements are evaluated first. If parenthesized elements are nested, the innermost elements are evaluated, then the next innermost until the entire expression has been evaluated.

- Within parentheses and/or wherever parentheses do not govern the order of evaluation, the hierarchy of operations in order of precedence is as follows:

*Function evaluation*

*Exponentiation*

*Multiplication and Division*

*Addition and Subtraction*

#### **EXAMPLE:**

The expression

$$A^*(Z-((Y+R)/T))^{**}J+\text{VAL}$$

is evaluated in the following sequence:

$Y+R = e1$   
 $(e1)/T = e2$   
 $Z-e2 = e3$   
 $e3**J = e4$   
 $A*e4 = e5$   
 $e5+VAL = e6$

- Wherever operations of equal hierarchy are involved, evaluation proceeds from left to right.

#### EXAMPLES:

Expression:

$W*X/Y*Z$   
 $B^{**}Z-4.*A*C$   
 $X-Y-Z$   
 $X/Y/Z$   
 $-X^{**}3$

Evaluated as:

$(W*X)/Y*Z$   
 $(B^{**}Z)-((4.*A)*C)$   
 $(X-Y)-Z$   
 $((X/Y)/Z$   
 $-(X^{**}3)$

- The expression  $X^{**}Y^{**}Z$  is not allowed. It should be written as  $X^{**}(Y^{**}Z)$  or  $(X^{**}Y)^{**}Z$ .
- Use of an array element reference requires the evaluation of its subscript. Subscript expressions are evaluated under the same rules as other expressions.

## LOGICAL EXPRESSIONS

A logical expression may be any of the following:

- A single Logical Constant (.TRUE. or .FALSE.), a Logical variable, Logical Array Element or Logical function reference (see Function, Section 9).
- Two arithmetic expressions separated by a *relational operator*, i.e., a relational expression.

- Logical operators acting upon logical constants, logical variables, logical array elements, logical functions, relational expressions or other logical expressions. The value of a logical expression is always either .TRUE. or .FALSE.

### Relational Expressions

The general form of a relational expression is as follows:

$e1 \ r \ e2$

where  $e1$  and  $e2$  are arithmetic expressions and  $r$  is a *relational operator*. The six relational operators are as follows:

.LT. Less than  
.LE. Less than or equal to  
.EQ. Equal to  
.NE. Not equal to  
.GT. Greater than  
.GE. Greater than or equal to

The value of the relational expression is .TRUE. if the condition defined by the operator is met. Otherwise, the value is .FALSE.

#### EXAMPLES:

$A.EQ.B$   
 $(A^{**}J).GT.(ZAP^{*(RHO*TAU-ALPH)})$

### Logical Operators

Table 4-1 lists the logical operations. U and V denote logical expressions.

#### EXAMPLES:

If  $U = 01101100$  and  $V = 11001001$ , then

.NOT.U = 10010011  
U.AND.V = 01001000  
U.OR.V = 11101101  
U.XOR.V = 10100101

The following are additional considerations for construction of logical expressions:

- Any logical expression may be enclosed in parentheses;

Table 4-1

.NOT. U	The value of this expression is the logical complement of U, i.e., 1 bits become 0 and 0 bits become 1.
U.AND.V	The value of this expression is the logical product of U and V, i.e., there is a 1 bit in the result only where the corresponding bits in both U and V are 1.
U.OR.V	The value of this expression is the logical sum of U and V, i.e., there is a 1 in the result if the corresponding bit in U or V is 1 or if the corresponding bits in both U and V are one.
U.XOR.V	The value of this expression is the exclusive OR of U and V, i.e., there is a one in the result if the corresponding bits in U and V are 1 and 0 or 0 and 1 respectively.

however, a logical expression to which the .NOT. operator applies must be enclosed in parentheses if it contains two or more elements.

- In the hierarchy of operations, parentheses may be used to specify the ordering of the expression evaluation. Within parentheses, and where parentheses do not dictate evaluation order, the order is understood to be as follows:

Function Reference  
 Exponentiation (\*\*)  
 Multiplication and Division (\* and /)  
 Addition and Subtraction (+ and -)  
 .LT., .LE., .EQ., .NE., .GT., .GE.  
 .NOT.  
 .AND.  
 .OR., .XOR.

#### EXAMPLES:

The expression

X .AND. Y .OR. B(3,2) .GT. z

is evaluated as

e1 = B(3,2).GT.Z  
 e2 = X .AND. Y  
 e3 = e2 .OR. e1

The expression

X .AND. (Y .OR. B(3,2) .GT. Z)

is evaluated as

e1 = B(3,2) .GT. Z  
 e2 = Y .OR. e1  
 e3 = X .AND. e2

- It is invalid to have two contiguous logical operators except when the second operator is .NOT. That is, ".AND..NOT." and ".OR..NOT." are permitted.

#### EXAMPLE:

A.AND..NOT.B is permitted  
 A.AND..OR.B is not permitted.

## Section 5 Replacement Statements

Replacement statements define computations and are used similarly to equations in normal mathematical notation. They are of the following form:

v = e

where v is any variable or array element and e is an expression.

FORTRAN semantics defines the equality sign (=) as meaning *to be replaced by* rather than the normal *is equivalent to*. Thus, the object program instructions generated by a replacement statement will, when executed, evaluate the expression on the right of the equality sign and place that result in the storage space allocated to the variable or array element on the left of the equality sign.

The following conditions apply to replacement statements:

- Both v and the equality sign must appear on the same line. This holds even when the statement is part of a logical IF statement (Section 7).

#### EXAMPLE:

C IN A REPLACEMENT STATEMENT THE '='  
 C MUST BE IN THE INITIAL LINE.  
 A(5,3) =  
 1 B(7,2) + SIN(C)

The line containing v= must be the initial line of the statement unless the statement is part of a logical IF statement. In that case, the v= must occur no later than the end of the first line after the end of the IF.

- If the data types of the variables, v, and the expressions, e, are different, then the value determined by the expression will be converted, if possible, to conform to the typing of the variable. Table 5-1 shows which type expression may be equated to which type of variable. Y indicates a valid

replacement and N indicates an invalid replacement. Footnotes to Y indicate conversion considerations.

Table 5-1 Replacement By Type

Variable Types	Expression Types (e)		
	Integer	Real	Logical
Integer	Y	Ya	Yb
Real	Yc	Y	Yc
Logical	Yd	Ya	Y

a The Real expression is converted to Integer, truncated if necessary to conform to the range of Integer data.

b The sign is extended through the second byte.

c The variable is assigned the Real approximation of the Integer value of the expression.

d The variable is assigned the truncated value of the Integer expression (the low-order byte is used, regardless of sign.)

---

## Section 6 Specification Statements

---

Specification Statements are non-executable, non-generative statements which define data types of variables and arrays, specify array dimensionality and size, allocate data storage or otherwise supply determinative information to the FORTRAN processor. Data initialization statements are non-executable, but generate object program data and establish initial values for variable data.

### SPECIFICATION STATEMENTS

There are six kinds of specification statements. They are as follows:

- Type statements
- EXTERNAL statements
- DIMENSION, COMMON and EQUIVALENCE statements
- DATA initialization statements

All specification statements are grouped at the beginning of a program unit and must be ordered as they appear above. Specification statements may be preceded only by a FUNCTION, SUBROUTINE, PROGRAM or BLOCK DATA statement. All specification statements must precede statement functions and the first executable FORMAT statement.

### ARRAY DECLARATORS

Three kinds of specification statements may specify array declarators. These statements are the following:

- TYPE statements
- DIMENSION statements
- COMMON statements

Of these, DIMENSION statements have the declaration of arrays as their sole function. The other two serve dual purposes. These statements are defined in the following paragraphs. Array declarators are used to specify the name, dimensionality and sizes of arrays. An array may be declared only once in a program unit. An array declarator has one of the following forms:

- ui (k)
- ui (k1,k2)
- ui (k1,k2,k3)

where ui is the name of the array, called the declarator name, and the k's are integer constants.

Array storage allocation is established upon appearance of the array declarator. Such storage is allocated linearly by the FORTRAN processor where the order of ascendancy is determined by the first subscript varying most rapidly and the last subscript varying least rapidly.

For example, if the array declarator AMAT(3,2,1) appears, storage is allocated for the 12 elements in the following order:

AMAT(1,1,1), AMAT(2,1,1), AMAT(3,1,1), AMAT(1,2,1),  
AMAT(2,2,1), AMAT(3,2,1), AMAT(1,1,2), AMAT(2,1,2),  
AMAT(3,1,2), AMAT(1,2,2), AMAT(2,2,2), AMAT(3,2,2).

### TYPE STATEMENTS

Variable, array and function names are automatically typed Integer or Real by the 'predefined' convention unless they are changed by Type statements. For example, the type is Integer if the first letter of an item is I, J, K, L, M or N. Otherwise, the type is Real.

Type statements provide for overriding or confirming the pre-defined convention by specifying the type of an item. In addition, these statements may be used to declare arrays. Type statements have the following general form:

t v1,v2,...vn

where t represents one of the terms INTEGER, REAL or LOGICAL and each v is an array declarator or a variable, array or function name.

#### EXAMPLE:

REAL AMAT(3,3,5),BX,IETA, KLPH

#### Note

- AMAT and BX are redundantly typed.
- IETA and KLPH are unconditionally declared REAL.
- AMAT(3,3,5) is a constant array declarator specifying an array of 45 elements.

#### EXAMPLE:

INTEGER M1, HT, JMP(15), FL

#### Note

M1 is redundantly typed here. Typing of HT and FL by the predefined convention is overridden by their appearance in the INTEGER statement. JMP(15) is a constant array declarator. It redundantly types the array elements as integer and communicates to the Processor the storage requirements and dimensionality of the array.

#### EXAMPLE:

LOGICAL L1, TEMP

#### Note

All variables, arrays or functions required to be typed Logical must appear in a LOGICAL statement, since no starting letter indicates a logical type variable by the default convention.

### EXTERNAL STATEMENTS

EXTERNAL statements have the following form:

EXTERNAL u1,u2,...,un

where each ui is a SUBROUTINE, BLOCK DATA or FUNCTION name. When the name of a subprogram is used as an argument in a subprogram reference, it must have appeared in a preceding EXTERNAL statement.

When a BLOCK DATA subprogram is to be included in a program load, its name must have appeared in the EXTERNAL statement within the main program unit. For example, if SUM and AFUNC are subprogram names to be

used as arguments in the subroutine SUBR, the following statements would appear in the calling program unit:

EXTERNAL SUM, AFUNC

CALL SUBR(SUM, AFUNC,X,Y)

## DIMENSION STATEMENTS

A DIMENSION statement has the following form:

DIMENSION u1,u2,u3,...,un

where each ui is an array declarator.

### EXAMPLE:

DIMENSION RAT(5,5), BAR(BAR20)

This statement declares two arrays—the 25 element array RAT and the 20 element array BAR.

## COMMON STATEMENTS

COMMON statements are non-executable, storage allocating statements which assign variables and arrays to a storage area called COMMON storage and provide the facility for various program units to share the use of the same storage area. COMMON statements are expressed in the following form:

COMMON/Y1/A1/Y2/A2/.../Yn/An

where each Yi is a COMMON block storage name and each Ai is a sequence of variable names, array names of constant array declarators, separated by commas. The elements in Ai make up the COMMON block storage area specified by the name Yi. If any Yi is omitted leaving two consecutive slash characters (//), the block storage so indicated is called blank common. If the first block name (Yi) is omitted, the two slashes may be omitted.

### EXAMPLE:

COMMON /AREA/A,B,C/BDATA/X,Y,Z  
X FL,ZAP(30)

In this example, two blocks of common storage are allocated—AREA with space for three variables and BDATA, with space for four variables and the 30 element array ZAP.

COMMON //A1,B1/CDATA/ZOT(3,3)  
X //T2,Z3

In this example, A1, B1, T2 and Z3 are assigned to blank COMMON in that order. The pair of slashes preceding A1 could have been omitted. CDATA names COMMON block storage for the nine element array, ZOT and thus ZOT(3,3) is an array declarator. ZOT(3,3) must not have been previously declared. (See "Array Declarators.")

### Note

- The name of a common block may appear more than once in the same COMMON statement, or in more than one common statement.
- A COMMON block name is made up of from 1 to 6 alphanumeric characters, the first of which must be a letter.

- A COMMON block name must be different from any subprogram names used throughout the program.
- The size of a common area may be increased by the use of EQUIVALENCE statements. (See "EQUIVALENCE Statements.")
- The length of labeled COMMON blocks of the same name must be the same in all program units where the name appears. Unlabeled COMMON blocks need not be the same length. The length of a COMMON area is the number of storage units required to contain the variables and arrays declared in the COMMON statement (or statements) unless expanded by the use of EQUIVALENCE statements.

## EQUIVALENCE STATEMENTS

Use of EQUIVALENCE statements permits the sharing of the same storage unit by two or more entities. The general form of the statement is as follows:

EQUIVALENCE (u1),(u2),...(un)

where each ui represents a sequence of two or more variable or array elements, separated by commas. Each element in the sequence is assigned the same storage unit (or portion of a storage unit) by the processor. The order in which the elements appear is not significant.

### EXAMPLE:

EQUIVALENCE (A,B,C)

The variables A, B and C will share the same storage unit during object program execution. If an array element is used in an EQUIVALENCE statements, the number of subscripts must be either the same as the number of dimensions established by the array declarator, or if one, where the one subscript specifies the array element's number relative to the first element of the array.

### EXAMPLE:

If the dimensionality of any array, Z, has been declared as Z(3,3) then in an EQUIVALENCE statement Z(6) and Z(3,2) have the same meaning.

### Additional Considerations

- The subscripts of array elements must be integer constants.
- An element of a multi-dimensional array may be referred to by a single subscript, if desired.
- Variables may be assigned to a common block through EQUIVALENCE statements.

### EXAMPLE:

COMMON /X/A,B,C  
EQUIVALENCE (A,D)

In this case, the variables A and D share the first storage unit in common block X.

- EQUIVALENCE statements can increase the size of a block indicated by a COMMON statement by adding more elements to the end of the block.

### EXAMPLE:

DIMENSION R(2,2)  
COMMON /A/W,X,Y  
EQUIVALENCE (Y,R(3))

The resulting common block will have the following configuration:

Variable	Storage Unit
W = L(1,1)	Ø
X = R(2,1)	1
Y = R(1,2)	2
R(2,2)	3

The common block established by the COMMON statement contains 3 storage units. It is expanded to 4 storage units by the EQUIVALENCE statement. COMMON block size may be increase only from the last element established by the COMMON statement forward, not from its first element backward.

Note that EQUIVALENCE (X,R(3)) would be invalid in the example. The COMMON statement established W as the first element in the COMMON block and an attempt to make X and R(3) equivalent would be an attempt to make R(1) the first element.

- It is invalid to equivalence two elements of the same array or two elements belonging to the same or different COMMON blocks.

#### EXAMPLE:

```
DIMENSION XTABLE (20), D(5)
COMMON A,B(4)/ZAP/C,X
```

```
Equivalence (XTABLE (6), A(7)
X      B(3),XTABLE(5)),
Y      (B(3),D(5))
```

This equivalence statement has the following errors:

- It attempts to EQUIVALENCE two elements of the same array, XTABLE(6) and XTABLE(15).
- It attempts to EQUIVALENCE two elements of the same COMMON block, A(7) and B(3).
- Since A is not an array, A(7) is an illegal reference.
- Making B(3) equivalent to D(5) extends COMMON backwards from its defined starting point.

## DATA INITIALIZATION STATEMENT

The DATA initialization statement is a non-executable statement which provides a means of compiling data values into the object program and assigning these data to variables and array elements referenced by other statements. This statement is of the following form:

```
DATA list/u1,u2,...,un/,list.../uk,uk+1,...uk+n/
```

where "list" represents a list of variable, array or array element names, and the ui are constants corresponding in number to the elements in the list. An exception to the one-for-one correspondence of list items to constants is that an array name (unsubscripted) may appear in the list, and as

many constants as necessary to fill the array may appear in the corresponding position between slashes. Instead of ui, it is permissible to write k\*ui in order to declare the same constant, ui, k times in succession. k must be a positive integer. Dummy arguments may not appear in the list.

#### EXAMPLE:

```
DIMENSION C(7)
DATA A, B, C(1),C(3)/14.73,
X      -8.1,72*7.5/
```

This implies that A=14.73, B=-8.1, C(1)=7.5, C(3)=7.5

The type of each constant ui must match the type of the corresponding item in the list, except that a Hollerith or Literal constant may be paired with an item of any type.

When a Hollerith or Literal constant is used, the number of characters in its string should be no greater than four times the number of storage units required by the corresponding item, i.e., 1 character for a Logical variable, up to 2 characters for an Integer variable and 4 or fewer characters for a Real variable. If fewer Hollerith or Literal characters are specified, trailing blanks are added to fill the remainder of storage. Hexadecimal data are stored in a similar fashion. If fewer hexadecimal characters are used, sufficient leading zeroes are added to fill the remainder of the storage unit.

A DATA statement may not be used to initialize a variable or array in blank common storage or in a named common block with one exception—a DATA statement may initialize data in a named COMMON block when used in a BLOCK DATA subprogram (Section 9). The examples below illustrate many of the features of the DATA statement.

```
DIMENSION HARY (2)
DATA HARY,B/ 4HTHIS, 4H OK
1           ,7.86
```

```
REAL LIT(2)
LOGICAL LT,LF
DIMENSION H4(2,2), PI3(3)
DATA A1,B1,K1,LT,LF,H4(1,1),H4(2,1),
1      H4(1,2),H4(2,2),PI3/5.9,2.5E-4,
2      64.,FALSE.,TRUE.,1.75E-3,
3      0.85E-1,2*75.0,1.,2.,3.14159/
4      LIT(1)/*NOGO*/
```

---

## Section 7 FORTRAN Control Statements

---

FORTRAN control statements are executable statements which affect and guide the logical flow of a FORTRAN program. The statements in this category are as follows:

- The GO TO statements:
  - Unconditional GO TO
  - Computed GO TO
  - Assigned GO TO
- ASSIGN
- The IF statements:
  - Arithmetic IF
  - Logical IF
- DO
- CONTINUE
- STOP
- PAUSE
- CALL
- RETURN

When statement labels of other statements are a part of a control statement, such statement labels must be associated with executable statements within the same program unit in which the control statement appears.

### **THE GO TO STATEMENTS**

#### **Unconditional GO TO**

Unconditional GO TO statements are used whenever control is to be transferred unconditionally to some other statement within the program unit. The statement is of the following form:

GO TO k

where k is the statement label of an executable statement in the same program unit.

*EXAMPLE:*

```
GO TO 376
310 A(7) = V1 -(3)
```

```
376 A(2) = VECT
      GO TO 310
```

#### **Computed GO TO**

Computed GO TO statements are of the form:

GO TO (k<sub>1</sub>,k<sub>2</sub>,...,k<sub>n</sub>),j

where the k<sub>i</sub> are statement labels, and j is an integer variable,  $1 \leq j \leq n$ . This statement causes transfer of control to the statement labeled k<sub>j</sub>. If  $j < 1$  or  $j > n$ , an error message will be output during program execution, and control will be transferred to K1 if  $j < 1$  and to Kn if  $j > n$ .

*EXAMPLE:*

J=3

```
GO TO (7, 70, 700, 7000, 70000), J
310 J=5
      GO TO 325
```

When  $J = 3$ , the computed GO TO transfers control to statement 700. Changing J to equal 5 changes the transfer to statement 7000. Making  $J = 0$  or  $J = 6$  would be an error since these values are outside the allowable range,  $1 \leq J \leq n$ .

#### **Assigned GO TO**

Assigned GO TO statements are of the following form:

GO TO j,(k<sub>1</sub>,k<sub>2</sub>,...,k<sub>n</sub>)
 or
 GOTO j

where j is an integer variable name, and the k<sub>i</sub> are statement labels of executable statements. This statement causes transfer of control to the statement whose label is equal to the current value of j.

#### **Qualifications**

- The ASSIGN statement must logically precede an assigned GO TO.
- The ASSIGN statement must assign a value of j which is a statement label included in the list of k's, if the list is specified.

*EXAMPLE:*

GO TO LABEL,(80,90,100)

Only the statement labels 80, 90 or 100 may be assigned to LABEL.

#### **ASSIGN Statement**

This statement is of the following form:

ASSIGN j TO i

where j is a statement label of an executable statement and i is an integer variable. The statement is used in conjunction with each assigned GO TO statement that contains the integer variable i. When the assigned GO TO is executed, control will be transferred to the statement labeled j.

*EXAMPLE:*

ASSIGN 100 TO LABEL

80

ASSIGN 90 TO LABEL
 GO TO LABEL, (80,90,100)

### **THE IF STATEMENT**

IF statements transfer control to one of a series of statements depending upon a condition. Two types of IF statements are provided:

Arithmetic IF
 Logical IF

#### **Arithmetic IF**

The arithmetic IF statement is of the form:

IF(e) m<sub>1</sub>,m<sub>2</sub>,m<sub>3</sub>

where e is an arithmetic expression and m<sub>1</sub>, m<sub>2</sub> and m<sub>3</sub> are statement labels. Evaluation of expression e determines one of three transfer possibilities:

If e is:	Transfer to:
< 0	m <sub>1</sub>
= 0	m <sub>2</sub>
> 0	m <sub>3</sub>

## EXAMPLES:

Statement	Expression Value	Transfer To
IF (A)3,4,5	15	5
IF (N-1)50,73,9	0	73
IF (AMTX(2,1,2))7,2,1	-256	7

## Logical IF

The Logical IF statement is of the form:

IF (u)s

where u is a logical expression and s is any executable statement except a DO statement (see next sub-section) or another Logical IF statement. The logical expression u is evaluated as true or false. Section 4 contains a discussion of logical expressions.

*Control Conditions:* If u is FALSE, the statement s is ignored and control goes to the next statement following the Logical IF statement. If, however, the expression is TRUE, then control goes to the statement s, and subsequent program control follows normal conditions.

If s is a replacement statement ( $v = e$ , Section 5), the variable and equality sign (=) must be on the same line, either immediately following IF(u) or on a separate continuation line with the line spaces following IF(u) left blank.

## EXAMPLES:

```
IF(I.GT.20) GO TO 115
IF(Q.AND.R) ASSIGN 10 to J
IF(Z) CALL DECL(A,B,C)
IF(A.OR.B.LE.PI/2.)I=J
IF(A.OR.B.LE.PI/2)
X      I=J
```

## DO STATEMENT

The DO statement, as implemented in FORTRAN, provides a method for repetitively executing a series of statements. The statement is of one of the two following forms:

```
DO k i = m1,m2,m3
      or
      DO k i = m1,m2
```

where k is a statement label, i is an integer variable, and m1, m2 and m3 are integer constants or integer variables. If m3 is a 1, it may be omitted, as in the second form above. The following conditions and restrictions govern the use of DO statements:

- The DO and the first comma must appear on the initial line.
- The statement labeled k, called the terminal statement, must be an executable statement.
- The terminal statement must physically follow its associated DO, and the executable statements following the DO, up to and including the terminal statement, constitute the range of the DO statement.
- The terminal statement may not be an Arithmetic IF, GO TO, RETURN, STOP, PAUSE or another DO.

- If the terminal statement is a logical IF and its expression is .FALSE., then the statements in the DO range are reiterated. If the expression is .TRUE., the statement of the logical IF is executed and then the statements in the DO range are reiterated. The statement of the logical IF may not be a GO TO, Arithmetic IF, RETURN, STOP or PAUSE.

- The controlling integer variable, i, is called the index of the DO range. The index must be positive and may not be modified by any statement in the range.

- During the first execution of the statements in the DO range, i is equal to m1; the second execution, i=m1+m3; the third, i = m1+2\*m3, etc., until i is equal to the highest value in this sequence less than or equal to m2, and then the DO is said to be satisfied. The statements in the DO range will always be executed at least once, even if m1 ≤ m2. When the DO has been satisfied, control passes to the statement following the terminal statement, otherwise control transfers back to the first executable statement following the DO statement.

## EXAMPLE:

The following example computes the sum of the elements of A:

100 DIMENSION A(100)

SUM = A(1)

DO 31 I = 2,100

31 SUM = SUM + A(I)

END

- The range of a DO statement may be extended to include all statements which may logically be executed between the DO and its terminal statement. Thus, parts of the DO range may be situated such that they are not physically between the DO statement and its terminal statement but are executed logically in the DO range. This is called the extended range.

## EXAMPLE:

DIMENSION A(500), B(500)

DO 50 I = 10, 327, 3

IF (V7-C\*C) 20,15,31

30

20 C = C - .05

GO TO 50

31

C = C + .0125

GO TO 30

*A(1)=B(3)\*C*

- It is invalid to transfer control into the range of a DO statement not itself in the range or extended range of the same DO statement.
- Within the range of a DO statement, there may be other DO statements, in which case the DO's must be nested. That is, if the range of one DO contains another DO, then the range of the inner DO must be entirely included in the range of the outer DO. The terminal statement of the inner DO may also be the terminal statement of the outer DO.

For example, given a two-dimensional array A of 15 rows and 15 columns, and a 15 element one-dimensional array B, the following statements compute the 15 elements of array C to the formula:

$$C_k = \sum_{j=1}^{15} A_{kj} B_m, k = 1, 2, \dots, 15$$

#### **EXAMPLE:**

DIMENSION A(15,15), B(15), C(15)

```
DO 80 K = 1,15
C(K) = 0.0
DO 80 J = 1,15
80 C(K) = C(K) + A(K,J) * B(J)
```

#### **CONTINUE STATEMENT**

CONTINUE is classified as an executable statement. However, its execution does nothing. The form of the CONTINUE statement is as follows:

CONTINUE

CONTINUE is frequently used as the terminal statement in a DO statement range when the statement which would normally be the terminal statement is one of those which are not allowed or is only executed conditionally.

#### **EXAMPLE:**

DO 5 K = 1,10

```
IF (C2) 5,6,6
6 CONTINUE
```

```
C2 = C2 + .005
5 CONTINUE
```

#### **STOP STATEMENT**

A STOP statement has one of the following forms:

STOP  
or  
STOP c

where c is any string of one to six characters. When STOP is encountered during execution of the object program, the characters c (if present) are displayed on the operator control console and execution of the program terminates. The STOP statement, therefore, constitutes the logical end of the program.

#### **PAUSE STATEMENT**

A PAUSE statement has one of the following forms:

PAUSE  
or  
PAUSE c

where c is any string of up to six characters. When PAUSE is encountered during execution of the object program, the characters c (if present) are displayed on the operator control console and execution of the program ceases. The decision to continue execution of the program is not under control of the program. If execution is resumed through intervention of an operator without otherwise changing the state of the Processor, the normal execution sequence, following PAUSE, is continued. Execution may be terminated by typing a "T" at the operator console. Typing any other character will cause execution to resume.

#### **CALL STATEMENT**

CALL statements control transfers into SUBROUTINE subprograms and provide parameters for use by the subprograms. The general forms and detailed discussion of CALL statements appear in Section 9.

#### **RETURN STATEMENT**

The form, use and interpretation of the RETURN statement are described in Section 9.

#### **END STATEMENT**

The END statement must physically be the last statement of any FORTRAN program. It has the following form:

END

The END statement is an executable statement and may have a statement label. It causes a transfer of control to be made to the system exit routine which returns control to the Operating System.

## Section 8 Input/Output

FORTRAN provides a series of statements which define the control and conditions of data transmission between computer memory and external data handling or mass storage devices such as magnetic tape, disk, line printer, punched card processor, keyboard printers, etc. The statements are grouped as follows:

- Formatted READ and WRITE statements which cause formatted information to be transmitted between the computer and I/O devices.
- Unformatted READ and WRITE statements which transmit unformatted binary data in a form similar to internal storage.
- Auxiliary I/O statements for positioning and demarcation of files.
- FORMAT statements used in conjunction with formatted record transmission to provide data conversion and editing information between internal data representation and external character string forms.

### FORMATTED READ/WRITE STATEMENTS

#### Formatted READ Statements

A formatted READ statement is used to transfer information from an input device to the computer. Two forms of the statement are available, as follows:

```
READ(u,f)k  
or  
READ(u,f)k
```

where u specifies a Physical and Logical Unit Number and may be either an unsigned integer or an integer variable in the range 1 through 255. If an Integer variable is used, an Integer value must be assigned to it prior to execution of the READ statement. Units 1—10 are preassigned to the console Teletypewriter. These units, as well as units 11—255, may be re-assigned by the user (see Appendix B).

The letter f is the statement label of the FORMAT statement describing the type of data conversion to be used within the input transmission or it may be an array name, in which case the formatting information may be input to the program at the execution time. The letter k is a list of variable names, separated by commas, specifying the input data.

READ (u,f)k is used to input a number of items, corresponding to the names in the list (k), from the file on logical unit u, and using the FORMAT statement f to specify the external representation of these items (see FORMAT statements). The following notes further define the function of the READ (u,f)k statement:

- Each time execution of the READ statement begins, a new record from the input file is read.
- The number of records to be input by a single READ statement is determined by the list k and format specifications.
- Any number of items may appear in a single list and the items may be of different data types.

- If there are more quantities in an input record than there are items in the list, only the number of quantities equal to the number of items in the list are transmitted. Remaining quantities are ignored.
- Exact specifications for the list k are given later in this chapter in the subsection on "Input/Output List Specifications."

#### EXAMPLES:

Assume that four data entries are punched on a card, with three blank columns separating each, and that the data have field widths of 3, 4, 2 and 5 characters respectively starting in column 1 of the card. The statements

```
READ(5,20)K,L,M,N
```

will read the card (assuming the Logical unit number 5 has been assigned to the card reader) and assign the input data to the variables K, L, M and N. The FORMAT statement could also be

```
20 FORMAT(I3,3X,I4,3X,I2,3X,I5)
```

Input the quantities of an array (ARRY):

```
READ(6,21)ARRY
```

Only the name of the array needs to appear in the list (see Input/Output list Specifications). All elements of the array ARRY will be read and stored using the formatting specified by the FORMAT statement labeled 21.

READ(u,k) also may be used in conjunction with a FORMAT statement to read H-type alphanumeric data into an existing H-type field (see subsection on Hollerith Conversions). For example, the statements:

```
READ(1,25)
```

.

.

.

```
25 FORMAT(10HABCDEFGHI)
```

cause the next 10 characters of the file on input device 1 to be read and replace the characters ABCDEFGHI in the FORMAT statement.

#### Formatted WRITE Statements

A formatted WRITE statement is used to transfer information from the computer to an output device. Two forms of the statement are available, as follows:

```
WRITE(u,f)k  
or  
WRITE(u,f)
```

where u specifies a Logical Unit Number; f is the statement label of the FORMAT statement describing the type of data conversion to be used with the output transmission; and k is a list of variable names separated by commas, specifying the output data.

WRITE(u,f)k is used to output the data specified in the list k to a file on logical unit u using the FORMAT statement f to specify the external representation of the data (see FORMAT statements). The following notes further define the function of the WRITE statement:

- Several records may be output with a single WRITE statement, with the number determined by the list and FORMAT specifications.
- Successive data are output until the data specified in the list are exhausted.
- If output is to a device which specifies fixed length records and the data specified in the list do not fill the record, the remainder of the record is filled with blanks.

#### EXAMPLE:

WRITE(2,10) A,B,C,D

The data assigned to the variables A, B, C and D are output to Logical Unit Number 2, formatted according to FORMAT statement labeled 10.

WRITE (u,f) may be used to write alphanumeric information when the characters to be written are specified within the FORMAT statement. In this case, a variable list is not required. For example, to write the characters H CONVERSION on unit 1,

WRITE(1,26)

.

.

26 FORMAT (12HCONVERSION)

## UNFORMATTED READ/WRITE

Unformatted I/O, i.e. without data conversion, is accomplished using the statements:

READ(u)k  
WRITE(u)k

where u specifies a Logical Unit Number and k is a list of variable names, separated by commas, specifying the I/O data. The following notes define the functions of unformatted I/O statements.

- Unformatted READ/WRITE statements perform memory-image transmission of data with no data conversion or editing.
- The amount of data transmitted corresponds to the number of variables in the list k.
- The total length of the list of variable names in an unformatted READ must not be longer than the record length. If the logical record length and the length of the list are not the same, the entire record is read; if the length of the list is shorter than the logical record length the unread items in the record are skipped.
- The WRITE(u)k statement writes one logical record.
- A logical record may extend across more than one physical record.

## AUXILIARY I/O STATEMENTS

Three auxilliary I/O statements are provided:

BACKSPACE(u)  
REWIND(u)  
ENDFILE(u) *NO BRACKETS*

Initially, the actions of all three statements are defined as no-ops. They may, however, be redefined (see Appendix B).

## INPUT/OUTPUT LIST SPECIFICATIONS

Most forms of READ/WRITE statements may contain an

ordered list of data names which identify the data to be transmitted. The order in which the list items appear must be the same as that in which the corresponding data exists (Input), or will exist (Output) in the external I/O medium. Lists have the following form:

m1,m2,...mn

where the mi are list items separated by commas, as shown.

#### List Item Types

A list item may be a single datum identifier or a multiple data identifier.

- A single datum identifier item is the name of a variable or array element. One or more of these items may be enclosed in parentheses without changing their intended meaning.

#### EXAMPLES:

A  
C(26,1),R,K,D,(I,J)  
B,I(10,10),S,(R,K),F(1,25)

#### Note

The entry (I,J) defines two items in a list while (26,1) is a subscript.

- Multiple data identifier items are in two forms: (1) An array name appearing in a list without subscript(s) is considered equivalent to the listing of each successive element of the array.

#### EXAMPLE:

If B is a two-dimensional array, the list item B is equivalent to B(1,1), B(2,1), B(3,1),..., B(1,2), B(2,2),..., B(j,k). where j and k are the subscript limits of B.

(2) DO-implied items are lists of one or more single datum identifiers or other DO-implied items followed by a comma character and an expression of the form:

i = m1,m2,m3  
or  
i = m1,m2

and enclosed in parentheses. The elements i, m1, m2, m3 have the same meaning as defined for the DO statement. The DO implication applies to all list items enclosed in parentheses with the implication.

#### EXAMPLES:

##### DO-implied Lists

(X(I),I=1,4)  
(Q(J),R(J),J=1,2)  
(G(K),K=1,7,3)  
((A(I,J),I=3,5),J=1,9,4)  
(R(M),M=1,2),I,ZAP(3)  
(R(3),T(I),I=1,3)

##### Equivalent Lists

X(1),X(2),X(3),X(4)  
Q(1),R(1),Q(2),R(2)  
G(1),G(4),G(7)  
A(3,1),A(4,1),A(5,1)  
A(3,5),A(4,5),A(5,5)  
A(3,9),A(4,9),A(5,9)  
R(1),R(2),I,ZAP(3)  
R(3),T(1),R(3),T(2)  
R(3),T(3)

Thus, the elements of a matrix, for example, may be transmitted in an order different from the order in which they

appear in storage. The array A(3,3) occupies storage in the order A(1,1), A(2,1), A(3,1), A(1,2), A(2,2), A(3,2), A(1,3), A(2,3), A(3,3). By specifying the transmission of the array with the DO-implied list item ((A(I,J),J=1,3),I=1,3), the order of transmission is A(1,1), A(1,2), A(1,3), A(2,1), A(2,2), A(2,3), A(3,1), A(3,2), A(3,3).

### Special Notes On List Specifications

- The ordering of a list is from left to right with repetition of items enclosed in parentheses (other than as subscripts) when accompanied by controlling DO-implied index parameters.
- Arrays are transmitted by the appearance of the array name (unsubscripted) in an input/output list.
- Constants may appear in an input/output list only as subscripts or as indexing parameters.
- For input lists, the DO-implying elements i, m1, m2 and m3 may not appear within the parentheses as list items.

#### EXAMPLES:

READ (1,20) (I,J,A(I), I=1,J,2) is not allowed.  
 READ (1,20) I,J,(A(I),I=1,J,2) is allowed.  
 WRITE (1,20) (I,J,A(I), I=1,J,2) is allowed.

Consider the following examples:

DIMENSION A(25)

A(1) = 2.1  
 A(3) = 2.2  
 A(5) = 2.3  
 J = 5

WRITE (1,20) J,(I,A(I),I=1,J,2)

.

.

.

The output of this WRITE statement is 5,1,2,1,3,2,2,5,2,3.

- Any number of items may appear in a single list.
- In a formatted transmission—READ(u,f)k or WRITE(u,f)—each item must have the correct type as specified by a FORMAT statement.

### FORMAT STATEMENTS

FORMAT statements are non-executable, generative statements used in conjunction with formatted READ and WRITE statements. They specify conversion methods and data editing information as the data is transmitted between computer storage and external media representation. FORMAT statements require statement labels for reference (f) in the READ(u,f)k or WRITE(u,f)k statements. The general form of a FORMAT statement is as follows:

n FORMAT (s1,s2,...,sn/s1',s2',...,sn'...)

where n is the statement label and each si is a field descriptor. The word FORMAT and the parentheses must be present as shown. The slash (/) and comma (,) characters are field separators and are described in a separate subparagraph. The field is defined as that part of an external record occupied by one transmitted line.

### Field Descriptors

Field descriptors describe the sizes of data fields and specify the type of conversion to be performed upon each transmitted datum. The format field descriptors may have any of the following forms:

Descriptor	Classification
rFw.d	Numeric Conversion
rGw.d	
rEw.d	
rIw	
rLw	Logical Conversion
rAw	
nHh1h2...hn	Hollerith Conversion
nX	Spacing Specification
mP	Scaling Factor

where:

- w and n are positive integer constants defining the field width (including digits, decimal points, algebraic signs) in the external data representation
- d is an integer specifying the number of fractional digits appearing in the external data representation.
- The characters F, G, E, I, A and L indicate the type of conversion to be applied to the items in an input/output list.
- r is an optional, positive integer indicating that the descriptor will be repeated r times.
- The hi are characters from the FORTRAN character set.
- m is an integer constant (positive, negative or zero) indicating scaling.

### Numeric Conversions

**F-TYPE CONVERSIONS** Form: Fw.d—Real type data are processed using this conversion. w characters are processed of which d are considered fractional.

**F-Output:** Values are converted and output as minus sign (if negative), followed by the integer portion of the number, a decimal point and d digits of the fractional portion of the number. If a value does not fill the field, it is right justified in the field and enough preceding blanks to fill the field are inserted. If a value requires more field positions than allowed by w, the first w-1 digits of the value are output, preceded by an asterisk.

#### EXAMPLES:

FORMAT Descriptor	Internal Value	Output (b = blank)
F10.4	368.42	bb388.4200
F7.1	-4786.361	-4786.4
F8.4	8.7E-2	bb0.0870
F6.4	4739.76	*.7600
F7.3	-5.6	b-5.600

\*Note the loss of leading digits in the 4th line above.

## F-Input: (see description under E-Input below).

**E-TYPE CONVERSIONS** Form: Ew.d—Real type data are processed using this conversion. w characters are processed of which d are considered fractional.

**E-Output:** Values are converted, rounded to d digits, and output as:

- a minus sign (if negative)
- a zero and a decimal point,
- d decimal digits,
- the letter E,
- the sign of the exponent (minus or blank),
- two exponent digits,

in that order. The values as described are right justified in the field w with preceding blanks to fill the field if necessary. The field width w should satisfy the relationship:

$$w > d + 7$$

Otherwise significant characters may be lost. Some E-Output examples follow:

FORMAT Descriptor	Internal Value	Output (b = blank)
E12.5	76.573	b0.76573Eb02
E13.7	-32672.354	0.3267235Eb05
E7.3	56.93	* 0.569E
E13.4	-0.0012321	bb-0.1232E-02
E8.2	76321.73	0.76Eb05

**E-Input:** Data values which are to be processed under E, F, or G conversion can be a relatively loose format in the external input medium. The format is identical for either conversion and is as follows:

- Leading spaces (ignored)
- A + or - sign (an unsigned input is assumed positive)
- A string of digits
- A decimal point
- A second string of digits
- The character E
- A + or - sign
- A decimal exponent

Each item in the list above is optional; but the following conditions must be observed:

- If format items 3 and 5 (above) are present, then 4 is required.
- If format item 8 is present, then 6 or 7 or both are required.
- All non-leading spaces are considered zero.

Input data can be any number of digits in length, and correct magnitudes will be developed, but precision will be maintained only to the extent specified in Section 3 for Real data. Following are E- and F- and G-Input examples:

FORMAT Descriptor	Internal Value	Input (b = blank)
E10.3	+2375.60	+0.23756+4
E10.3	+17.631	bbbbbb17631
F8.3	+1628.911	b1628911
F12.4	-632.1132	bbbb-6321132

**Note in the before examples that if no decimal point is given among the input characters, the d in the format specification establishes the decimal point in conjunction with an exponent, if given. If a decimal point is included in the input characters, the d specification is ignored. The letters E, F and G are interchangeable in format specifications. The end result is the same.**

**G-TYPE CONVERSIONS** Form: Gw.d—Real type data are processed using this conversion. w characters are processed of which d are considered significant.

**G-Input:** (See the description under E-Input)

**G-Output:** The method of output conversion is a function of the magnitude of the number being output. Let N be the magnitude of the number. The following shows how the number will be output:

Magnitude	Equivalent Conversion
.1 ≤ N < 1	F(w-4).d,4X
1 ≤ N < 10	F(w-4).(d-1),4X
.....	.....
.....	.....
.....	.....
$10^{d-2} \leq N < 10^{d-1}$	F(w-4).1,4X
$10^{d-1} \leq N < 10^d$	F(w-4).0,4X
Otherwise	Ew.d

**I-TYPE CONVERSION** Form: Iw—Only Integer or Logical data may be converted by this form of conversion. w specifies field width.

**I-Output:** Values are converted to Integer constants. Negative values are preceded by a minus sign. If the value does not fill the field, it is right justified in the field and enough preceding blanks to fill the field are inserted. If the value exceeds the field width, only the least significant w-1 characters are output preceded by an asterisk.

## EXAMPLES:

FORMAT Descriptor	Internal Value	Output (b = blank)
I6	+281	bbb281
I6	-23261	-23261
I3	126	126
I3	-226	226
I3	26931	*31
I3	1234	*34

**I-Input:** A field of w characters is input and converted to internal integer format. A minus sign may precede the integer

digits. If a sign is not present, the value is considered positive. Integer values in the range -32768 to 32767 are accepted. Non-leading spaces are treated as zeros.

#### EXAMPLES:

FORMAT Descriptor	Input (b = blank)	Internal Value
I4	b124	124
I4	-124	-124
I7	bb6732b	67320
I4	1b2b	1020

#### Hollerith Conversion

**A-TYPE CONVERSION** The form of the A conversion is: Aw. This descriptor causes unmodified Hollerith characters to be read into or written from a specified list item. The maximum number of actual characters which may be transmitted between internal and external representation using Aw is four times the numbering list item, i.e., 1 character for Logical items, 2 characters for Integer items and 4 characters for Real items.

**A-Output:** If w is greater than 4n (where n is the number of storage units required by the list item), the external output field will consist of w-4n blanks followed by the 4n characters from the internal representation. If w is less than 4n, the external output field will consist of the leftmost w characters from the internal representation.

#### EXAMPLES:

FORMAT Descriptor	Internal	Type	Output (b = blanks)
A1	A1	Integer	A
A2	AB	Integer	AB
A3	ABCD	Real	ABC
A4	ABCD	Real	ABCD
A7	ABCD	Real	bbbABCD

**A-Input:** If w is greater than 4n (where n is the number of storage units required by the corresponding list item), the rightmost 4n characters are taken from the external input field. If w is less than 4n, the w characters appear left justified with w-4n trailing blanks in the internal representation.

#### EXAMPLES:

FORMAT Descriptor	Input Characters	Type	Internal (b = blanks)
A1	A	Integer	Ab
A3	ABC	Integer	AB
A4	ABCD	Integer	AB
A1	A	Real	Abbb
A7	ABCDEFG	Real	DEFG

**H-CONVERSION** The forms of H conversion are: nHh1h2... hn 'h1h2...hn'

These descriptors process Hollerith character strings between the descriptor and the external field, where each h represents any character from the ASCII character set.

#### Note

Special consideration is required if an apostrophe ('') is to be used within the literal string in the second form. An apostrophe character within the string is represented by two successive apostrophes. See the example below.

**H-Output:** The n characters hi are placed in the external field. In the nHh1h2...hn form, the number of characters in the string must be exactly as specified by n. Otherwise, characters from other descriptors will be taken as part of the string. In both forms, blanks are counted as characters.

#### EXAMPLES:

FORMAT Descriptor	Output (b = blanks)
1HA or 'A'	A
8HbSTRINGb or 'bSTRINGb'	bSTRINGb
11HX(2,3)=12.0 or 'X(2,3)=12.0'	X(2,3)=12.0
11HibSHOULDN'T or 'bSHOULDN'T'	bSHOULDN'T

**H-Input:** The n characters of the string hi are replaced by the next n characters from the input record. This results in a new string of characters in the field descriptor.

FORMAT Descriptor	Input (b = blank)
4H1234 or '1234'	ABCD
7HbFALSE or 'bbFALSE'	bFALSEb
6Hbbbb or 'bbbbbb'	MATRIX
Resultant Descriptor	
4HABCD or 'ABCD'	
7HbFALSEb or 'bFALSEb'	
6HMATRIX or 'MATRIX'	

#### Logical Conversion

The form of the logical conversion is: Lw

**L-Output:** If the value of an item in an output list corresponding to this descriptor is 0, an "F" will be output; otherwise, a "T" will be output. If w is greater than 1, w-1 leading blanks precede the letters.

#### EXAMPLES:

FORMAT Descriptor	Internal Value	Output (b = blank)
L1	= 0	F
L1	<> 0	T
L5	<> 0	bbbbT
L7	= 0	bbbbbbF

**L-Input:** The external representation occupies w positions. It consists of optional blanks followed by a "T" or "F" followed by optional characters.

### The X Descriptor

The form of X conversion is nX.

This descriptor causes no conversion to occur, nor does it correspond to an item in an input/output list. When used for output, it causes n blanks to be inserted in the output record. Under input circumstances, this descriptor causes the next n characters of the input record to be skipped.

### OUTPUT EXAMPLES:

FORMAT Statement	Output (b = blanks)
3 FORMAT (1HA,4X,2HBC)	AbbbbBC
7 FORMAT (3X,4HABCD,1X)	bbbABCDb

### INPUT EXAMPLES:

FORMAT Statement	Input String	Resultant Input
10 FORMAT (F4.1,3X,F3.0)	12.5ABC120	12.5,120
5 FORMAT (7X,I3)	1234567012	012

### The P Descriptor

The P descriptor is used to specify a scaling factor for real conversions (F, E, G). The form is nP where n is an integer constant (positive, negative or zero). The scaling factor is automatically set to zero at the beginning of each formatted I/O call (each READ or WRITE statement). If a P descriptor is encountered while scanning a FORMAT, the scale factor is changed to n. The scale factor remains changed until another P descriptor is encountered or the I/O terminates.

#### Effects Of The Scale Factor On Input:

During E, F, or G input, the scale factor takes effect only if no exponent is present in the external representation. In that case, the internal value will be a factor of  $10^{**n}$  less than the external value (the number will be divided by  $10^{**n}$  before being stored).

#### Effect Of Scale Factor On Output:

**E-Output:** The coefficient is shifted left n places relative to the decimal point, and the exponent is reduced by n (the value remains the same).

**F-Output:** The external value will be  $10^{**n}$  times the internal value.

**G-Output:** The scale factor is ignored if the internal value is small enough to be output using F conversion. Otherwise, the effect is the same as for E-Output.

### Special Control Features Of FORMAT Statements

#### REPEAT SPECIFICATIONS

- The E, F, G, H, I, L and A field descriptors may be indicated as repetitive descriptors by using a repeat count r in the form

rEw.d, rFw.d, rGw.d, rIw, rLw, rAw. The following pairs of FORMAT statements are equivalent:

- 66 FORMAT (3F8.3,F9.2)  
C IS EQUIVALENT TO:  
66 FORMAT (F8.3,F8.3,F8.3,F9.2)
- 14 FORMAT (2I3,2A5,2E10.5)  
C IS EQUIVALENT TO:  
14 FORMAT (I3,I3,A5,A5,E10.5,E10.5)

- Repetition of a group of field descriptors is accomplished by enclosing the group in parentheses preceded by repeat count. Absence of a repeat count indicates a count of one. Up to two levels of parentheses, not counting the parentheses required by the FORMAT statement, are permitted. Note the following equivalent statements:

- 22 FORMAT (I3,4(F6.1,2X))  
C IS EQUIVALENT TO:  
22 FORMAT (I3,F6.1,2X,F6.1,2X,F6.1,2X  
1 F6.1,2X)

- Repetition of FORMAT descriptors is also initiated when all descriptors in the FORMAT statement have been used but there are still items in the input/output list that have not been processed. When this occurs the format descriptors are re-used starting at the opening parenthesis that matches the last closing parenthesis in the FORMAT statement. The parentheses enclosing the entire list of descriptors are not considered unless there are no other parentheses in the list. A repeat count preceding the parenthesized descriptor(s) to be re-used is also active in the re-use. This type of repetitive use of FORMAT descriptors terminates processing of the current record and initiates the processing of a new record each time the re-use begins. Record demarcation under these circumstances is the same as in the Field Separators paragraph below.

#### INPUT EXAMPLE:

```
DIMENSION A(100)
READ (3,13) A
```

```
.
```

```
13 FORMAT (5F7.3)
```

In this example, the first 5 quantities from each of 20 records are input and assigned to the array elements of the array A.

#### OUTPUT EXAMPLE:

```
.
```

```
WRITE (6,12) E,F,K,L,M,KK,LL,MM,K3,L3,
1 M3
```

```
.
```

```
12 FORMAT (2F9.4,(3I7))
```

In this example, three records are written. Record 1 contains E, F, K, L and M. Because the descriptor 3I7 is reused twice,

Record 2 contains KK, LL and MM and record 3 contains K3, L3 and M3.

#### **FIELD SEPARATORS**

Two adjacent descriptors must be separated in the FORMAT statement by either a comma or one or more slashes.

#### **EXAMPLE:**

2H0K/F6.3 or 2H0K,F6.6

The slash not only separates field descriptors, but it also specifies the demarcation of formatted records. Each slash terminates a record and sets up the next record for processing. The remainder of an input record is ignored; the remainder of an output record is filled with blanks. Successive slashes (//...) cause successive blank records to be written on output.

#### **OUTPUT EXAMPLE:**

DIMENSION A(100),J(20)

WRITE (7,8) J,A  
8 FORMAT (10I7/10I7/50F7.3/50F7.3)

In this example, the data specified by the list of the WRITE statement are output to unit 7 according to the specifications of FORMAT statement 8. Four records are written as follows:

Record 1	Record 2	Record 3	Record 4
J(1)	J(11)	A(1)	A(51)
J(2)	J(12)	A(2)	A(52)
.	.	.	.
J(10)	J(20)	A(50)	A(100)

#### **INPUT EXAMPLE:**

DIMENSION B(10)

READ (4,17) B  
17 FORMAT (F10.2/F10//8F10.2)

In this example, the two array elements B(1) and B(2) receive their values from the first data fields of successive records (the remainders of the two records are ignored). The third and fourth records are ignored and the remaining elements of the array are filled from the fifth record.

#### **Format Control, List Specifications And Record Demarcation**

The following relationships and interactions between FORMAT control, input/output lists and record demarcation should be noted:

- Execution of a formatted READ or WRITE statement initiates FORMAT control.

- The conversion performed on data depends on information jointly provided by the elements in the input/output list and field descriptors in the FORMAT statement.
- If there is an input/output list, at least one descriptor of types E, F, G, I, L, or A must be present in the FORMAT statement.
- Each execution of a formatted READ statement causes a new record to be input.
- Each item in an input list corresponds to a string of characters in the record and to a descriptor of the types E, F, G, I, L, or A in the FORMAT statement.
- H and X descriptors communicate information directly between the external record and the field descriptors without reference to list items.
- On input whenever a slash is encountered in the FORMAT statement or the FORMAT descriptors have been exhausted and re-use of descriptors is initiated, processing of the current record is terminated and the following occurs: Any unprocessed characters in the record are ignored. If more input is necessary to satisfy list requirements, the next record is read.
- A READ statement is terminated when all items in the input list have been satisfied if the next FORMAT descriptor is E, F, G, I, L or A and if the format control has reached the last outer right parenthesis of the FORMAT statement. If the input list has been satisfied, but the next FORMAT descriptor is H or X, more data is processed (with the possibility of new records being input) until one of the above conditions exists.
- If FORMAT control reaches the last right parenthesis of the FORMAT statement but there are more list items to be processed, all or part of the descriptors are reused. (See description of Repeat Specifications.)
- When a Formatted WRITE statement is executed, records are written each time a slash is encountered in the FORMAT statement or FORMAT control has reached the rightmost right parenthesis. The FORMAT control terminates in one of the two methods described for READ termination above. Incomplete records are filled with blanks to maintain record lengths.

#### **FORMAT Specifications In Arrays**

The FORMAT reference, f, of a formatted READ or WRITE statement (See Formatted READ/WRITE Statements) may be an array name instead of a statement label. If such reference is made, at the time of execution of the READ/WRITE statement the first part of the information contained in the array, taken in natural order, must constitute a valid FORMAT specification. The array may contain non-format information following the right parenthesis that ends the format specification.

The format specification which is to be inserted in the array has the same form as defined for a FORMAT statement, i.e., it begins with a left parenthesis and ends with a right parenthesis. The format specification may be inserted in the array by use of a data initialization statement, or by use of a READ statement together with an Aw format.

#### **EXAMPLE:**

Assume the format specification (3F10.3,4I6) or a similar 12 character specification is to be stored into an array. The array must allow a minimum of 3 storage files. The FORTRAN

coding below shows the various methods of establishing the format specification and then referencing the array for a formatted READ or WRITE.

```

C  DECLARE A REAL ARRAY
    DIMENSION A(3), B(3), M(4)
C  INITIALIZE FORMAT WITH DATA STATEMENT
    DATA A/'(3F1.0,3,4I6)'/
.
.
.
C  READ DATA USING FORMAT SPECIFICATIONS
C      IN ARRAY A
    READ(6,A) B, M
.
.
.
C  DECLARE AN INTEGER ARRAY

```

DIMENSION IA(4), B(3), M(4)

```

C  READ FORMAT SPECIFICATIONS
    READ (7,15) IA
C  FORMAT FOR INPUT OF FORMAT SPECIFICATIONS
    15  FORMAT (4A2)
.
.
.
C  READ DATA USING PREVIOUSLY INPUT
C      FORMAT SPECIFICATION
    READ (7,IA) B,M
.
.
.
```

## Section 9 Functions And Subprograms

The FORTRAN language provides a means for defining and using often needed programming procedures such that the statement or statements of the procedures need appear in a program only once but may be referenced and brought into the logical execution sequence of the program wherever and as often as needed. The procedures are as follows:

- Statement functions
- Library functions
- FUNCTION subprograms
- SUBROUTINE subprograms

Each of these procedures has its own unique requirements for reference and defining purposes. These requirements are discussed in subsequent paragraphs of this section. However, certain features are common to the whole group or to two or more of the procedures. These common features are as follows:

- Each of these procedures is referenced by its name which, in all cases, is one to six alphanumeric characters of which the first is a letter.
- The first three are designated as "functions" and are alike in that:

They are always single valued, i.e., they return one value to the program unit from which they are referenced.

They are referred to by an expression containing a function name.

They must be typed by type specification statements if the data type of the single-valued result is to be different from that indicated by the pre-defined convention.

- FUNCTION subprograms and SUBROUTINE subprograms are considered program units.

In the following description of these procedures, the term "calling program" means the program unit or procedure in which a reference to a procedure is made, and the term "called program" means the procedure to which a reference is made.

### STATEMENT FUNCTIONS

Statement functions are defined by a single arithmetic or logical assignment statement and are relevant only to the program unit in which they appear. The general form of a statement function is as follows:

$$f(a_1, a_2, \dots, a_n) = e$$

where  $f$  is the function name, the  $a_i$  are dummy arguments and  $e$  is an arithmetic or logical expression. Rules for ordering, structure and use of statement functions are as follows:

- Statement function definitions, if they exist in a program unit, must precede all executable statements in the unit and follow all specification statements.
- The  $a_i$  are distinct variable names, but, being dummy variables, they may have the same names as variables of the same type appearing elsewhere in the program unit.
- The expression  $e$  is constructed according to the rules in Section 4 and may contain only references to the dummy arguments and non-Literal constants, variable and array element references, utility and mathematical function references and references to previously defined statement functions.
- The type of any statement function name or argument that differs from its pre-defined convention type must be declared by a type specification statement.
- The relationship between  $f$  and  $e$  must conform to the replacement rules in Section 5.
- A statement function is called by its name followed by a parenthesized list of arguments. The expression is evaluated using the arguments specified in the call, and the reference is replaced by the result.
- The  $i$ th parameter in every argument list must agree in type with the  $i$ th dummy in the statement function.

The example below shows a statement function and a statement call.

### C STATEMENT FUNCTION DEFINITION

```

C      FUNC1(A,B,C,D) = ((A+B)**C)/D
C STATEMENT FUNCTION CALL
C      A12=A1-FUNC1(X,Y,Z7,C7)

```

## LIBRARY FUNCTIONS

Library functions are a group of utility and mathematical functions which are "built-in" to the FORTRAN system. Their names are pre-defined to the Processor and automatically typed. The functions are listed in Tables 9-1 and 9-2. In the tables, arguments are denoted as  $a_1, a_2, \dots, a_n$ , if more than one argument is required; or as  $a$  if only one is required. A library function is called when its name is used in an arithmetic expression. Such a reference takes the following form:

$f(a_1, a_2, \dots, a_n)$

where  $f$  is the name of the function and  $a_i$  are actual arguments. The arguments must agree in type number and order with the specifications indicated in Tables 9-1 and 9-2.

Table 9-1 Intrinsic Functions

Function Name	Definition	Types	
		Argument	Function
ABS	$ a $	Real	Real
IABS		Integer	Integer
AINT	Sign of $a$ times largest integer $\leq  a $	Real	Real
INT		Real	Integer
AMOD	$a_1(\text{mod } a_2)$	Real	Real
MOD		Integer	Integer
AMAX0	Max( $a_1, a_2, \dots$ )	Integer	Real
AMAX1		Real	Real
MAX0		Integer	Integer
MAX1		Real	Integer
FLOAT	Conversion from Integer to Real	Integer	Real
IFIX	Conversion from Real to Integer	Real	Integer
SIGN		Real	Real
ISIGN	Sign of $a_2$ times $ a_1 $	Integer	Integer
DIM	$a_1 - \text{Min}(a_1, a_2)$	Real	Real
IDIM		Integer	Integer

## EXAMPLES:

```

A1 = B+FLOAT (I7)
MAGNI = ABS(KBAR)
PDIF = DIM(C,D)
S3 = SIN(T12)
ROOT = (-B+SQRT(B**2-4.*A*C))/  

1          (2.*A)

```

## FUNCTION SUBPROGRAMS

A program unit which begins with a FUNCTION statement is called a FUNCTION subprogram

A function statement has one of the following forms:

t FUNCTION f( $a_1, a_2, \dots, a_n$ )  
or  
FUNCTION f( $a_1, a_2, \dots, a_n$ )

where  $t$  is either INTEGER, REAL or LOGICAL or is empty as shown in the second form;  $f$  is the name of the FUNCTION subprogram; and the  $a_i$  are dummy arguments of which there must be at least one and which represent variable names, array names or dummy names of SUBROUTINE or other FUNCTION subprograms.

## CONSTRUCTION OF FUNCTION SUBPROGRAMS

Construction of FUNCTION subprograms must comply with the following restrictions:

- The FUNCTION statement must be the first statement of the program unit.
- Within the FUNCTION subprogram, the FUNCTION name must appear at least once on the left side of the equality sign of an assignment statement or as an item in the input list of an input statement. This defines the value of the function so that it may be returned to the calling program. Additional values may be returned to the calling program through assignment of values to dummy arguments.

Table 9-2 Basic External Functions

Name	Number Of Arguments	Definition	Type	
			Argument	Function
EXP	1	$e^a$	REAL	REAL
ALOG	1	$\ln(a)$	REAL	REAL
SIN	1	$\sin(a)$	REAL	REAL
COS	1	$\cos(a)$	REAL	REAL
TANH	1	$\tanh(a)$	REAL	REAL
SQRT	1	$(a)^{1/2}$	REAL	REAL
ATAN	1	$\arctan(a)$	REAL	REAL
ATAN2	2	$\arctan(a_1/a_2)$	REAL	REAL

**EXAMPLE:**

```

FUNCTION Z7(A,B,C)
.
.
.
Z7 = 5.*(A-B) + SQRT(C)
.
.
.

C  REDEFINE ARGUMENT
B=B+Z7
.
.
.

RETURN
.
.
.

END

```

- The names in the dummy argument list may not appear in EQUIVALENCE, COMMON or DATA statements in the FUNCTION subprogram.
- If a dummy argument is an array name, then an array declarator must appear in the subprogram with dimensioning information consistent with that in the calling program.
- A FUNCTION subprogram may contain any defined FORTRAN statements other than BLOCK DATA statements, SUBROUTINE statements, another FUNCTION statement or any statement which references either the function being defined or another subprogram that references the function being defined.
- The logical termination of a FUNCTION subprogram is a RETURN statement and there must be at least one of them.
- A FUNCTION subprogram must physically terminate with an END statement.

**EXAMPLE:**

```

FUNCTION SUM (BARY,I,J)
DIMENSION BARY(10,20)
SUM = 0.0
DO 8 K=1,I
8  SUM = SUM + BARY(K,M)
RETURN
END

```

**REFERENCING A FUNCTION SUBPROGRAM**

FUNCTION subprograms are called whenever the function name, accompanied by an argument list, is used as an operand in an expression. Such references take the following form:

$$f(a_1, a_2, \dots, a_n)$$

where  $f$  is a function name and the  $a_i$  are actual arguments. Parentheses must be present in the form shown. The arguments,  $a_i$ , must agree in type, order and number with the dummy arguments in the FUNCTION statement of the called FUNCTION subprogram. They may be any of the following:

- A variable name.
- An array element name.
- An array name.

- An expression.

- A SUBROUTINE or function SUBPROGRAM name.
- A Hollerith or Literal constant

If an  $a_i$  is a subprogram name, that name must have previously been distinguished from ordinary variables by appearing in an EXTERNAL statement and the corresponding dummy arguments in the called FUNCTION subprograms must be used in subprogram references.

If the  $a_i$  is a Hollerith or Literal constant, the corresponding dummy variable should encompass enough storage units to correspond exactly to the amount of storage needed by the constant.

When a FUNCTION subprogram is called, program control goes to the first executable statement following the FUNCTION statement. The following examples show references to function subprograms:

$$Z10 = FT1+Z7(D,T3,RHO)$$

$$\text{DIMENSION DAT}(5,5)$$

$$S1 = TOT1 + \text{SUM}(\text{DAT},5,5)$$
**SUBROUTINE SUBPROGRAMS**

A program unit which begins with a SUBROUTINE statement is called a SUBROUTINE subprogram. The SUBROUTINE statement has one of the following forms:

SUBROUTINE  $s(a_1, a_2, \dots, a_n)$   
or  
SUBROUTINE  $s$

where  $s$  is the name of the SUBROUTINE subprogram and each  $a_i$  is a dummy argument which represents a variable or array name or another SUBROUTINE or FUNCTION name.

**CONSTRUCTION OF SUBROUTINE SUBPROGRAMS**

- The SUBROUTINE statement must be the first statement of the subprogram.
- The SUBROUTINE subprogram name must not appear in any statement other than the initial SUBROUTINE statement.
- The dummy argument names must not appear in EQUIVALENCE, COMMON or DATA statements in the subprogram.
- If a dummy argument is an array name then an array declarator must appear in the subprogram with dimensioning information consistent with that in the calling program.
- If any of the dummy arguments represent values that are to be determined by the SUBROUTINE subprogram and returned to the calling program, these dummy arguments must appear within the subprogram on the left side of the equality sign in a replacement statement, in the input list of an input statement or as a parameter within a subprogram reference.

- A SUBROUTINE may contain any FORTRAN statements other than BLOCK DATA statements, FUNCTION statements, another SUBROUTINE statement, a PROGRAM statement or any statement which references the SUBROUTINE subprogram being defined or another subprogram which references the SUBROUTINE subprogram being defined.
- A SUBROUTINE subprogram may contain any number of RETURN statements. It must have at least one.
- The RETURN statement(s) is the logical termination point of the subprogram.
- The physical termination of a SUBROUTINE subprogram is an END statement.
- If an actual argument transmitted to a SUBROUTINE subprogram by the calling program is the name of a SUBROUTINE or FUNCTION subprogram, the corresponding dummy argument must be used in the called SUBROUTINE subprogram as a subprogram reference.

**EXAMPLE:**

```
C SUBROUTINE TO COUNT POSITIVE ELEMENTS
C   IN AN ARRAY
      SUBROUTINE COUNTP(ARRY,I,CNT)
      DIMENSION ARRY(7)
      CNT = 0
      DO 9 J=1,I
         IF(ARRY(J))9,5,5
9      CONTINUE
      RETURN
5      CNT = CNT+1.0
      GO TO 9
      END
```

## REFERENCING A SUBROUTINE SUBPROGRAM

A SUBROUTINE subprogram may be called by using a CALL statement. A CALL statement has one of the following forms:

```
CALL s(a1,a2,...,an)
      or
      CALL s
```

where s is a SUBROUTINE subprogram name and the ai are the actual arguments to be used by the subprogram. The ai must agree in type, order and number with the corresponding dummy arguments in the subprogram-defining SUBROUTINE statement. The arguments in a CALL statement must comply with the following rules:

- FUNCTIONS and SUBROUTINE names appearing in the argument list must have previously appeared in an EXTERNAL statement.
- If the called SUBROUTINE subprogram contains a variable array declarator, then the CALL statement must contain the actual name of the array and the actual dimension specifications as arguments.
- If an item in the SUBROUTINE subprogram dummy argument list is an array, the corresponding item in the CALL statement argument list must be an array.

When a SUBROUTINE subprogram is called, program control goes to the first executable statement following the SUBROUTINE statement.

**EXAMPLE:**

```
DIMENSION DATA(10)
```

```
. . .
C   THE STATEMENT BELOW CALLS THE
C   SUBROUTINE IN THE PREVIOUS PARAGRAPH
C
      CALL COUNTP(DATA,10,CPOS)
```

## RETURN FROM FUNCTION AND SUBROUTINE SUBPROGRAMS

The logical termination of a FUNCTION or subroutine subprogram is a RETURN statement which transfers control back to the calling program. The general form of the RETURN statement is simply the word

```
      RETURN
```

The following rules govern the use of the RETURN statement:

- There must be at least one RETURN statement in each SUBROUTINE or FUNCTION subprogram.
- RETURN from a FUNCTION subprogram is to the instruction sequence of the calling program following the FUNCTION reference.
- RETURN from a SUBROUTINE subprogram is to the next executable statement in the calling program which would logically follow the CALL statement.
- UPON return from a FUNCTION subprogram the single-valued result of the subprogram is available to the evaluation of the expression from which the FUNCTION call was made.
- Upon return from a SUBROUTINE subprogram the values assigned to the arguments in the subroutines are available for use by the calling program.

**EXAMPLE:**

Calling Program Unit

```
. . .
      CALL SUBR(Z9,B7,R1)
. . .

```

Called Program Unit

```
SUBROUTINE SUBR(A,B,C)
      READ(3,7) B
      A = B**C
      RETURN
7      FORMAT(F9.2)
      END
```

In this example, Z9 and B7 are made available to the calling program when return occurs.

## PROCESSING ARRAYS IN SUBPROGRAMS

If a calling program passes an array name to a subprogram, the subprogram must contain the dimension information pertinent to the array. A subprogram must contain array

declarators if any of its dummy arguments represent arrays or array elements. For example, a FUNCTION subprogram designed to compute the average of the elements of any one dimension array might be the following:

Calling Program Unit

```
DIMENSION Z1(50),Z2(25)
```

```
.
```

```
A1 = AVG(Z1,50)
```

```
.
```

```
A2 = A1-AVG(Z1,50)
```

```
.
```

```
.
```

Called Program Unit

```
FUNCTION AVG(ARG,I)
DIMENSION ARG(50)
SUM = 0.0
DO 20 J=1,I
20 SUM = SUM + ARG(J)
AVG = SUM/FLOAT(I)
RETURN
END
```

Note that actual arrays to be processed by the FUNCTION subprogram are dimensioned in the calling program and the array names and their actual dimensions are transmitted to the FUNCTION subprogram by the FUNCTION subprogram

reference. The FUNCTION subprogram itself contains a dummy array and specifies an array declarator.

### BLOCK DATA SUBPROGRAMS

A BLOCK DATA subprogram has as its only purpose the initialization of data in a COMMON block during loading of a FORTRAN object program. (There is no way to initialize data in blank common.) BLOCK DATA subprograms begin with a BLOCK DATA statement of the following form:

```
BLOCK DATA (subprogram-name)
```

and end with an END statement. Such subprograms may contain only Type, EQUIVALENCE, DATA, COMMON, and DIMENSION statements and are subject to the following considerations.

- If any element in a COMMON block is to be initialized, all elements of the block must be listed in the COMMON statement even though they might not all be initialized.
- Initialization of data in more than one COMMON block may be accomplished in one BLOCK DATA subprogram.
- There may be more than one BLOCK DATA subprogram loaded at any given time.
- A COMMON block item should only be initialized by one program unit.

#### EXAMPLE:

```
BLOCK DATA
LOGICAL A1
COMMON/BETA/B(3,3)/GAM/C(4)
COMMON/ALPHA/A1,C,E,D
DATA B/1.1,2.5,3.8,3*4.96,
X2*0.52,1.1/,C/1.2E0,3*4.0/
DATA A1/.TRUE./,E/-5.6/
```

---

## Appendix A Language Extensions

---

Cromemco FORTRAN IV includes the following extensions to ANSI Standard FORTRAN (X3.9-1966).

- Statement functions may use subscripted variables.
- Hexadecimal constants may be used in DATA statements.
- The literal form of Hollerith data (character string between apostrophe characters) is permitted within DATA and

FORMAT statements, and as a subprogram argument.

- There is no restriction to the number of continuation lines.
- Mixed mode expressions and assignments are allowed.

Descriptions of these language extensions are included at the appropriate points in the text of this document.

---

## Appendix B I/O Interface

---

Input/Output operations are table-dispatched to the driver routine for the proper Logical Unit Number. \$LUNTB is the dispatch table. It contains one 2-byte driver address for each possible LUN. It also has a 1-byte entry at the beginning, which contains the maximum LUN plus one. The initial runtime package provides for 10 LUN's (1 - 10), all of which correspond to the TTY. Any of these may be redefined by the user, or more added, simply by changing the appropriate

entries in \$LUNTB and adding more drivers. The runtime system uses LUN 3 for errors and other user communication. Therefore, LUN 3 should correspond to the operator console. The initial structure of \$LUNTB is shown in the listings following this appendix.

The device drivers also contain local dispatch tables. Note that \$LUNTB contains one address for each device, yet there

are really seven possible operations per device.

- Formatted Read
- Formatted Write
- Binary Read
- Binary Write
- Rewind
- Backspace
- Endfile

Each device driver contains up to seven routines. The starting addresses of each of these seven routines are placed at the beginning of the driver, in the exact order listed above. The entry in \$LUNTB then points to this local table, and the runtime system indexes into it to get the address of the appropriate routine to handle the requested I/O operation. The following conventions apply to the individual I/O routines:

- Location \$BF contains the data buffer address for Reads and Writes.
- For a Write, the number of bytes to write is in location \$BL.
- For a Read, the number of bytes read should be returned in \$BL.
- All I/O operations set the condition codes before exit to

indicate an error condition, end-of-file condition, or normal return:

- CY=1, Z=don't care—I/O error
- CY=0, Z=0—end-of-file encountered
- CY=0, Z=1—normal return

The runtime system checks the condition codes after calling the driver. If they indicate a non-normal condition, control is passed to the label specified by "ERR=" or "END=". If no label is specified, a fatal error results.

- \$IOERR is a global routine which prints an "Illegal I/O Operation" message (non-fatal). This routine may be used if there are some operations not allowed on a particular device, i.e. binary I/O on a TTY.

#### Note

The I/O buffer has a fixed maximum length of 128 bytes unless it is changed at installation time. If a driver allows an input operation to write past the end of the buffer, essential runtime variables may be affected. The consequences are unpredictable, but certainly not desirable.

The listings following this appendix contain an example driver for a TTY. Rewind, Backspace and Endfile are implemented as No-ops and Binary I/O as an error. This is the TTY driver provided with the runtime package.

```

;          TTY I/O DRIVER
;
DRV3:    DW      DRV3FR
          DW      DRV3FW
          DW      DRV3BR
          DW      DRV3BW
          DW      DRV3RE
          DW      DRV3BA
          DW      DRV3EN

;          ; FORMATTED READ
;          ; FORMATTED WRITE
;          ; BINARY READ
;          ; BINARY WRITE
;          ; REWIND
;          ; BACKSPACE
;          ; ENDFILE

;
DRV3RE:  XOR    A
DRV3BA:  RET
DRV3EN:  XOR    A
          RET

;
DRV3BR:  JP      $IOERR
DRV3BW:  JP      $IOERR

;
DRV3FR:  XOR    A
          LD      (BL), A
          LD      A, ???
          OUT   TTYOUT, A
;
```

; THESE OPERATIONS ARE NO-OPTS  
; FOR TTY

; ILLEGAL OPERATIONS (PRINT  
; ERROR AND RETURN)

; READ
; ZERO BUFFER LENGTH
; OUTPUT A ???

```

DRV31: IN      A, TTYIN          ; INPUT A CHARACTER
       PUSH   AF              ; SAVE IT
       OUT    TTYOUT, A        ; ECHO IT
       LD     HL, (BL)         ; GET CHARACTER POSITION IN BUFFER
       LD     H, O             ; ONLY 1 BYTE
       EX     DE, HL
       LD     HL, (BF)         ; GET BUFFER ADDRESS
       ADD   HL, DE           ; ADD OFFSET
       POP   AF              ; GET CHARACTER
       LD     (HL), A          ; PUT IT IN BUFFER
       INC   DE              ; INCREMENT BL
       EX     DE, HL
       LD     (BL), HL         ; SAVE IT
       CP     15              ; CR?
       RET   Z               ; YES--DONE
       LD     A, L             ; BL
       CP     171             ; MAXIMUM IS DECIMAL 120
       JP     C, DRV31         ; GET NEXT CHARACTER
       CALL  ERR
       IRECER
       XOR   A               ; CLEAR FLAGS
       RET

DRV3FW: LD     A, 15            ; `CR'
       OUT   TTYOUT, A        ; `LF'
       LD     A, 12
       OUT   TTYOUT, A
       LD     HL, (BF)
       LD     A, (BL)          ; NUMBER OF CHARACTERS TO WRITE
       OR    A
       OR    A
       RET   Z               ; DONE
       PUSH  AF              ; SAVE CHARACTER COUNT
       LD     A, (HL)          ; GET CHARACTER FROM BUFFER
       INC   HL              ; INCREMENT BUFFER POINTER
       PUSH  HL              ; SAVE IT
       OUT   TTYOUT, A          ; OUTPUT CHARACTER
       POP   HL              ; BUFFER POINTER
       POP   AF              ; CHARACTER COUNT
       DEC   A               ; DECREMENT IT
       JP    DRV32            ; NEXT CHARACTER

```

---

## Appendix C Subprogram Linkages

---

This appendix defines a normal subprogram call as generated by the FORTRAN compiler. It is included to facilitate linkages between FORTRAN programs and those written in other languages, such as Z-80 Assembly.

A program reference with no parameters generates a simple "CALL" instruction. The corresponding subprogram should return via a simple "RET." (CALL and RET are Z-80 opcodes—see the assembly manual or Z-80 reference manual for explanations.)

A subprogram reference with parameters causes a somewhat more complicated calling sequence. Parameters are always passed by reference, i.e., the thing passed is actually the address of the low byte of the actual argument. Therefore, parameters always occupy two bytes each, regardless of type. The method of passing parameters depends upon the number of parameters to pass:

- If the number of parameters is less than or equal to 3, they are passed in the registers. Parameter 1 will be in HL, 2 in DE

(if present), and 3 in BC (if present).

- If the number of parameters is greater than 3, they are passed as follows: Parameter 1 in HL; parameter 2 in DE; parameters 3 through n in a contiguous data block. BC will point to the low byte of this data block, i.e., to the low byte of parameter 3.

Note that, with this scheme, the subprogram must know how many parameters to expect in order to find them. Conversely, the calling program is responsible for passing the correct number of parameters. *Neither the compiler nor the runtime*

*system checks for the correct number of parameters.*

If the subprogram expects more than 3 parameters, and needs to transfer them to a local data area, there is a system subroutine which will perform this transfer. This argument transfer routine is \$AT, and is called with HL pointing to the local data area, BC pointing to the third parameter, and A containing the number of arguments to transfer, i.e. the total number of arguments minus 2. The subprogram is responsible for saving the first two parameters before calling \$AT. For example, if a subprogram expects 5 parameters, it should look like:

---

SUBR:	SHLD XCHG SHLD MVI LXI CALL	P1 P2 A,3 H,P3 \$AT	;SAVE PARAMETER 1 ;SAVE PARAMETER 2 ;NO. OF PARAMETERS LEFT ;POINTER TO LOCAL AREA ;TRANSFER THE OTHER 3 PARAMETERS
.			
(BODY OF SUBPROGRAM)			
.			
RET			;RETURN TO CALLER
P1: DS		2	;SPACE FOR PARAMETER 1
P2: DS		2	;SPACE FOR PARAMETER 2
P3: DS		6	;SPACE FOR PARAMETERS 3-5

---

When accessing parameters in a subprogram, don't forget that they are *pointers* to the actual arguments passed.

#### Note

It is entirely up to the programmer to see to it that the arguments in the calling program match in number, type and length with the parameters expected by the subprogram. This applies to FORTRAN subprograms, as well as those written in assembly language.

## Appendix D ASCII Character Codes

Decimal	Character	Decimal	Character	Decimal	Character.
000	NUL	043	+	086	V
001	SOH	044	,	087	W
002	STX	045	-	088	X
003	ETX	046	.	089	Y
004	EOT	047	/	090	Z
005	ENQ	048	Ø	091	[
006	ACK	049	1	092	\]
007	BEL	050	2	093	^
008	BS	051	3	094	~
009	HT	052	4	095	a
010	LF	053	5	096	b
011	VT	054	6	097	c
012	FF	055	7	098	d
013	CR	056	8	099	e
014	SO	057	9	100	f
015	SI	058	:	101	g
016	DLE	059	;	102	h
017	DC1	060	<	103	i
018	DC2	061	=	104	j
019	DC3	062	>	105	k
020	DC4	063	?	106	l
021	NAK	064	@	107	m
022	SYN	065	A	108	n
023	ETB	066	B	109	o
024	CAN	067	C	110	p
025	EM	068	D	111	q
026	SUB	069	E	112	r
027	ESCAPE	070	F	113	s
028	FS	071	G	114	t
029	GS	072	H	115	u
030	RS	073	I	116	v
031	US	074	J	117	w
032	SPACE	075	K	118	x
033	!	076	L	119	y
034	"	077	M	120	z
035	#	078	N	121	{
036	\$	079	O	122	}
037	%	080	P	123	?
038	&	081	Q	124	~
039	,	082	R	125	DEL
040	(	083	S	126	
041	)	084	T	127	
042	*	085	U		

LF = Line Feed

FF = Form Feed

CR = Carriage Return

DEL = Rubout

**Index**

Arithmetic Expression ..... 6  
 Arithmetic IF ..... 12, 13  
 Array ..... 3, 5, 9, 25, 26  
 Array Declarator ..... 5  
 Array Element ..... 3, 5, 8  
 ASCII Character Codes ..... 30  
 ASSIGN ..... 12  
 Assigned GOTO ..... 12  
  
 Backspace ..... 16  
 BLOCK DATA ..... 9, 11, 26  
  
 CALL ..... 14, 25  
 Character Set ..... 1, 2  
 Characteristic ..... 5  
 Comment ..... 2  
 COMMON ..... 9, 10, 11, 24, 26  
 Computed GOTO ..... 12  
 Constant ..... 3, 4  
 Continuation ..... 2, 3  
 Continue ..... 14  
 Control Statements ..... 12  
  
 DATA ..... 9, 11, 23, 24  
 Data Representation ..... 3  
 Data Storage ..... 6  
 DIMENSION ..... 5, 9, 10  
 DO ..... 12, 13  
 DO-implied Lists ..... 16  
  
 END ..... 2, 14  
 ENDFILE ..... 16  
 EQUIVALENCE ..... 9, 10, 24  
 Executable ..... 3  
 Expression ..... 6, 8, 12, 13  
 Extended Range ..... 13  
 EXTERNAL ..... 9, 25  
  
 FORMAT ..... 15, 17  
 Formatted READ ..... 15  
 Formatted WRITE ..... 15  
 FUNCTION ..... 9, 14, 22, 23, 25  
  
 GOTO ..... 12, 13  
  
 Hexadecimal ..... 11  
 Hollerith ..... 2, 3, 6, 19

I/O ..... 15  
 I/O List ..... 16  
 Index ..... 13  
 Integer ..... 3, 4, 5  
 Label ..... 2, 3, 12, 13  
 Library Function ..... 22  
 Line Format ..... 2  
 Literal ..... 2, 6  
 Logical ..... 3, 4, 5, 19, 20  
 Logical Expression ..... 7, 8  
 Logical IF ..... 12, 13  
 Logical Operator ..... 7, 8  
 Logical Unit Number ..... 15  
 LUN ..... 15  
  
 Mantissa ..... 5  
  
 Nested ..... 13, 14  
 Non-executable ..... 3  
  
 PAUSE ..... 13, 14  
 Procedure ..... 22  
  
 Range ..... 13  
 Real ..... 3, 4, 5  
 Relational Expression ..... 7  
 Relational Operator ..... 7  
 Replacement Statement ..... 8, 13  
 RETURN ..... 13, 14, 24, 25  
 REWIND ..... 16  
  
 Scale Factor ..... 20  
 Specification Statement ..... 9  
 Statement Function ..... 22  
 STOP ..... 13, 14  
 Storage Format ..... 3  
 Storage Unit ..... 6, 10  
 Subprogram ..... 14, 22, 28, 29  
 SUBROUTINE ..... 9, 14, 22, 24, 25  
 Subscript ..... 6  
 Subscript Expression ..... 6, 7  
  
 Type ..... 9  
  
 Unformatted I/O ..... 16  
  
 Variable ..... 3, 4, 5, 8

