

HyperionSolarNet Solar Panel Detection from Aerial Images

Nathan Nusaputra | Poonam Parhar | Ryan Sawasaki | Felipe Vergara

UC Berkeley
Capstone Showcase

Motivation




- Fight climate change by integrating solar energy
- Idea originated from Professor Paolo D'Odorico, Chair of the Department of Environmental Science at UC Berkeley
- Solar energy output determined by:
 - Solar irradiance
 - Solar panel location and size (HyperionSolarNet)
- HyperionSolarNet uses deep learning methods and satellite imagery to identify solar panel locations and estimate their total surface area
- Target users include energy companies, policy makers, environmental agencies, market analysts, and solar panel companies.



HyperionSolarNet



- Start with input data of satellite images from Google Maps
- Binary image classification model separating into solar and no-solar classes
- Segmentation model performs the task of classifying each pixel to its specific class
- Predicted masks are further processed to determine the area and number of solar panels



Data



INTRODUCTION

DATA

MODELS

EXPERIMENT

APPLICATION

CONCLUSION

- Images from Arizona, California, Colorado, Florida, Hawaii, Idaho, Louisiana, Massachusetts, Nevada, New Jersey, New York, Oregon, Texas, Washington
- Zoom 20 and 21
- Sizes 416x416 and 600x600
- Residential and Commercial
- For no-solar images, focus on objects that could be misclassified as solar panels, for example:

Classification Dataset					
Solar No-Solar Total					
Training	668	1295	1963		
Validation	168	324	492		
Berkeley Testset	321	1922	2243		

Segmentation Dataset			
Training	668		
Validation	168		
Berkeley Testset	321		





Crosswalks



Side of tall buildings



Data Labeling



INTRODUCTION

DATA

MODELS

EXPERIMENT

APPLICATION

CONCLUSION

Classification:

- Manually grouped images into solar and no-solar classes
- Time spent locating quality and diverse solar panel images

Segmentation:

- Used LabelBox platform to annotate solar panel images and create segmentation masks (labels)
- Labeling of 1,200 images required additional resources

Solar





No-solar









Human annotated images in LabelBox





Classification Model



NTRODUCTION DATA MODELS


EXPERIMENT


APPLICATION

CONCLUSION

Transfer Learning

Fine-tuned EfficientNet-B7 for solar panel images





Semantic Segmentation Model



INTRODUCTION

DATA


MODELS

EXPERIMENT

APPLICATION

CONCLUSION


- U-Net is one of the most popular deep learning based semantic segmentation method
- U-Net architecture with EfficientNet-B7 backbone
- Images augmentation using Albumentations library
- Model training using Segmentation Models library



Performance Metrics



- Accuracy, Precision, Recall and F1-score for the Classification Model
- IoU and F1-score for the Segmentation Model



Classification Model Performance



INTRODUCTION

DATA


MODELS


EXPERIMENT

APPLICATION

CONCLUSION


Model	Accuracy Precision		Recall	F1 Score
Baseline	0.7240	0.66	0.81	0.73
HyperionSolarNet	0.9764	0.95	0.98	0.97





Segmentation Model Performance





Segmentation Examples



INTRODUCTION


DATA

MODELS

EXPERIMENT

APPLICATION

CONCLUSION



Number and Size Estimation



INTRODUCTION

DATA

MODELS

EXPERIMENT


APPLICATION

CONCLUSION

- Segmentation model produces 600x600 matrix of 1's and 0's
- Function inputs are latitude, zoom and matrix from segmentation model
- Meters per pixel calculation is derived from Mercator Projection


```
meters_per_pixel = 156543.03392 * math.cos(latitude * math.pi / 180) / math.pow(2, zoom)
```

• Output is the total area and number of solar panels in the image



Berkeley Testset






Class	Precision	Recall	F1	Support
no-solar	0.98	0.97	0.98	1922
solar	0.82	0.91	0.86	321


Berkeley Testset




Segmentation	IoU	F1
Berkeley Testset Evaluation	0.8243	0.8922


100	N				
200					
300 -			N	查	
400 -			V		1
500 - Google 0	100	200	300	400	500






Berkeley Testset	Area (sq. ft.)	Number of Solar Panels
Actual	101,765.48	5,787
Predicted	102,609.72	5,828








Berkeley Final Results






Berkeley City	Area (sq. ft.)	Number of Solar Panels
Estimated Berkeley Solar Panels	1,082,431.98	61,480


System Architecture





Offline Inference








API	Input	Output	Method	Example curl
api/classification	Form-data: bounds	 JSON with tiles information Prediction whether image tiles contain solar panels 	POST	curllocationrequest POST 'http://www.hyperionsolarnet.com//api/cl
api/segmentation	Form-data: bounds	 JSON with tiles information Number of solar panels within bounds Total area of solar panels within bounds 	POST	curllocationrequest POST 'http://www.hyperionsolarnet.com/api/se

Web Application Demo





Conclusion



INTRODUCTION

DATA

MODELS

EXPERIMENT

APPLICATION

CONCLUSION

- Future Work includes:
 - Applying HyperionSolarNet to diverse locations around the world
 - Use results for further improvement of model
 - Integrate solar irradiance models to predict total solar energy output
- For additional information, please see:

WEBSITE

https://groups.ischool.berkeley.edu/HyperionSolarNet



RESEARCH PAPER



WEB APPLICATION

http://hyperionsolarnet.com





Thank you! Any Questions?

Acknowledgements

- Alberto Todeschini
- Puya Vahabi
- Colorado Reed
- Professor Paolo D'Odorico, Chair of the Department of Environmental Science at UC Berkeley
 - Our colleagues at UC Berkeley MIDS
 - Jia Lu, Gunnar Mein, Thaddeus Segura, Karen Wong
 - William Sawasaki
 - Alexandra Gray