

```

CREATE DATABASE HealthClinicApp;
USE HealthClinicApp;
-- Table to store patient details
CREATE TABLE Patients (
patient_id INT IDENTITY(1,1) PRIMARY KEY,
name VARCHAR(100) NOT NULL,
dob DATE NOT NULL,
phone BIGINT UNIQUE NOT NULL,
email VARCHAR(100) UNIQUE NOT NULL,
address VARCHAR(200),
blood_group VARCHAR(10)
);
-- Lookup table for doctor specialties
CREATE TABLE Specialties (
specialty_id INT IDENTITY(1,1) PRIMARY KEY,
specialty_name VARCHAR(100) UNIQUE NOT NULL
);
-- Doctors table with foreign key to specialties
CREATE TABLE Doctors (
doctor_id INT IDENTITY(1,1) PRIMARY KEY,
name VARCHAR(100) NOT NULL,
specialty_id INT,
phone BIGINT UNIQUE,
consultation_fee DECIMAL(10,2),
is_active BIT DEFAULT 1,
CONSTRAINT fk_doctor_specialty
FOREIGN KEY (specialty_id) REFERENCES Specialties(specialty_id)
);
-- Appointments table
CREATE TABLE Appointments (
appointment_id INT IDENTITY(1,1) PRIMARY KEY,
patient_id INT,
doctor_id INT,
appointment_date DATE,
appointment_time TIME,
status VARCHAR(20) DEFAULT 'SCHEDULED',
CONSTRAINT fk_app_patient
FOREIGN KEY (patient_id) REFERENCES Patients(patient_id),
CONSTRAINT fk_app_doctor
FOREIGN KEY (doctor_id) REFERENCES Doctors(doctor_id)
);
-- Visits table
CREATE TABLE Visits (
visit_id INT IDENTITY(1,1) PRIMARY KEY,
appointment_id INT,
diagnosis VARCHAR(255),
notes VARCHAR(500),
visit_date DATETIME DEFAULT GETDATE(),
CONSTRAINT fk_visit_app
FOREIGN KEY (appointment_id) REFERENCES Appointments(appointment_id)
);
-- Prescriptions table
CREATE TABLE Prescriptions (
prescription_id INT IDENTITY(1,1) PRIMARY KEY,
visit_id INT,
medicine_name VARCHAR(100),
dosage VARCHAR(50),
duration VARCHAR(50),
CONSTRAINT fk_presc_visit
FOREIGN KEY (visit_id) REFERENCES Visits(visit_id)
);
-- Bills table
CREATE TABLE Bills (
bill_id INT IDENTITY(1,1) PRIMARY KEY,
visit_id INT,
total_amount DECIMAL(10,2),
payment_status VARCHAR(20) DEFAULT 'UNPAID',
payment_date DATE NULL,
payment_mode VARCHAR(20) NULL,
CONSTRAINT fk_bill_visit
FOREIGN KEY (visit_id) REFERENCES Visits(visit_id)
);
-- Payment transactions log table
CREATE TABLE Payment_Transactions (
transaction_id INT IDENTITY(1,1) PRIMARY KEY,
bill_id INT,
payment_mode VARCHAR(20),

```

```
payment_date DATETIME DEFAULT GETDATE(),  
CONSTRAINT fk_pay_bill  
FOREIGN KEY (bill_id) REFERENCES Bills(bill_id)  
);  
-- Audit log table  
CREATE TABLE Audit_Log (  
log_id INT IDENTITY(1,1) PRIMARY KEY,  
table_name VARCHAR(100),  
operation VARCHAR(20),  
changed_by VARCHAR(50) DEFAULT SYSTEM_USER,  
changed_at DATETIME DEFAULT GETDATE()  
);
```