



Broadcast

Requirements, User Experience, and Architecture Specification

Dr. Ralf S. Engelschall

Version: 0.9.0
Created: 2026-06-18
Modified: 2026-09-14

Broadcast is a Web application which complements a broadcasted video stream with several features to achieve an enterprise-grade “townhall” event experience. It embeds the video stream with an external video player and surrounds it with additional user interface controls for chat and stream control. This allows the attendees to select between several stream variants, mainly meant to carry different language translations of the audio content.

Broadcast offers a chat as a backchannel from the audience to the presenters. It allows an attendee to send messages and see messages sent by other attendees or a moderator. Sent messages may be reviewed by an artificial or human operator before they are allowed to spread to the audience. Attendees may like specific messages to signal their support. Additionally, a moderator can select questions coming from the audience which are then forwarded to the video production studio to be answered by the presenters with a small time delay. **Broadcast** can also optionally embed an external application, for instance to provide live voting. Here the attendee’s choice is transferred back to the video production studio, aggregated there and presented to moderators and presenters as the audience’s opinion.

Broadcast optionally enforces a closed group policy by only allowing a certain list of people (identified by their e-mail addresses) to join. It seamlessly switches to an alternative video stream provider if requested by the people overseeing the event production. This helps to overcome video quality or scaling issues without interrupting the broadcasting of the program. It supports an audience of up to 10,000 attendees, specifically employing a fast join process and swift delivery of chat messages.

Broadcast provides several statistics to assess the technical reception of the event program by the audience (number of viewers, used client setup, event-wide counts). None of this data can be linked to specific persons. **Broadcast** complies with data protection rules by reliably deleting personal data after the event. Chat content including likes may be saved for later review (e.g. for assessing information needs, detecting unanswered questions), but here, too, no link to specific persons is ever provided.


Table of Contents

01	● REQS: Solution Vision	6
02	● REQS: Solution Premises	7
03	● REQS: Domain Glossary	12
04	● REQS: User Personas	23
05	● REQS: User Journey	27
05.01	● JOURNEY: Attend a Broadcast event	27
05.02	● JOURNEY: Operate a Broadcast Event	28
05.03	● JOURNEY: Moderate a Broadcast Event	28
06	● REQS: Functional Requirements	29
07	● REQS: Non-Functional Requirements	34
08	● REQS: Domain Rules	43
09	● REQS: Domain Workflows	48
09.01	● WORKFLOW: Run Broadcast Event	48
10	● REQS: Use Cases	51
10.01	● USE-CASE: Join Event and Watch Stream	52
10.02	● USE-CASE: Authenticate via Email Token	54
10.03	● USE-CASE: Ask a Question	55
10.04	● USE-CASE: Chat During the Event	57
10.05	● USE-CASE: Moderate and Forward Messages	60
10.06	● USE-CASE: Moderate the Chat Conversation	61
10.07	● USE-CASE: Steer the Presenter	63
10.08	● USE-CASE: Configure the Event	64
10.09	● USE-CASE: Switch Streaming Provider	66
10.10	● USE-CASE: Create Event from Registration Import	66
10.11	● USE-CASE: Publish, Start, and Finish Event	67
10.12	● USE-CASE: Export Anonymized Event Data	68
10.13	● USE-CASE: Present Forwarded Questions	69
10.14	● USE-CASE: Administer Any Event	71
11	● DATA: Data Model	72
11.01	● ENTITY: Event	74
11.02	● ENTITY: AgendaPoint	78
11.03	● ENTITY: Channel	79
11.04	● ENTITY: Resource	80
11.05	● ENTITY: ResourceProviderParam	81
11.06	● ENTITY: Role	81
11.07	● ENTITY: User	82
11.08	● ENTITY: Message	84

11.09	● ENTITY: MessageText	86
11.10	● ENTITY: QuestionTag	87
11.11	● ENTITY: AuthorizationToken	88
11.12	● ENTITY: SessionToken	89
11.13	● ENTITY: EventStatistic	90
11.14	● ENTITY: ChannelStatistic	91
11.15	● ENTITY: UserStatistic	91
12	● DATA: State Model	92
12.01	● LIFECYCLE: Event	93
12.02	● LIFECYCLE: Message	94
12.03	● LIFECYCLE: AuthorizationToken	96
12.04	● LIFECYCLE: UserStatistic	97
13	● DATA: Authorization Model	98
14	● APIS: Interface Model	113
15	● APIS: Interface Datatypes	113
15.01	● TYPE: LogLevel	114
15.02	● TYPE: Configuration	114
16	● APIS: Interface Endpoints	115
16.01	● ENDPOINT: broadcast-server	116
17	● UXUI: Interaction Concept	118
18	● UXUI: Language Conventions	122
19	● UXUI: Dialog Patterns	124
20	● UXUI: Dialog Storyboard	128
20.01	● STORYBOARD: Attendee Joins and Watches	128
20.02	● STORYBOARD: Attendee Asks a Tagged Question	129
20.03	● STORYBOARD: Attendee Reads and Posts Chat	130
20.04	● STORYBOARD: Attendee Gets Support from a Moderator	130
20.05	● STORYBOARD: Chat Moderator Triage Messages	131
20.06	● STORYBOARD: Moderator Forwards to Presenter	132
20.07	● STORYBOARD: Manager Switches Provider Live	133
20.08	● STORYBOARD: Manager Imports Registration Sheet	133
21	● UXUI: Visual Design	134
21.01	● MOCKUP: Attendee Chat View	138
21.02	● MOCKUP: Attendee Q&A View	138
21.03	● MOCKUP: Attendee Support View	139
21.04	● MOCKUP: Administrator Event Creation	140
21.05	● MOCKUP: Chat Moderation Board	140
21.06	● MOCKUP: Q&A Moderation Board	141
21.07	● MOCKUP: Presenter View	142
22	● ARCH: Context View	142

23	● ARCH: Functionality View	146
24	● ARCH: Technology Stack	154
24.01	● TIER: Common	154
24.02	● TIER: Client	158
24.03	● TIER: Middleware	162
24.04	● TIER: Server	163
24.05	● TIER: Database	165
25	● ARCH: Development Aspects	166
26	● ARCH: Concurrency View	168
27	● ARCH: Deployment View	171
28	● ARCH: Operations View	178
29	● ARCH: Quality Perspectives	182
30	● ARCH: Design Decisions	190
31	● TEST: Test Cases	203

Diagram of Contents



01 ● REQS: Solution Vision (SV)

○ PURPOSE	Broadcast exists to let organizations stream live video events to thousands of attendees while keeping the audience engaged through moderated chat, questions, and likes, all under full control of who may watch and interact.
○ TARGET-AUDIENCE	The solution serves event organizers (managers), live-event moderators and presenters, and large invited audiences of attendees, ranging from small internal lectures of 75 people up to digital town halls of 10,000 simultaneous attendees.
○ SOLUTION	Broadcast is a live-event platform that joins an embedded video player of an external streaming provider with an email-verified access control and a moderated interaction channel in a single web application.
○ VALUE-PROPOSITION	Organizers keep full control over who watches and who may interact, and receive all attendee input in a form they can moderate, forward to the presenter, and export afterwards. Attendees reach the event through a single personal link in any recent browser, without installation or accounts, and see their questions reach the presenters within seconds.
○ DIFFERENTIATORS	Compared to public streaming portals, Broadcast admits only invited (and optionally authenticated) attendees and enforces per-attendee access limits. It stays independent of any single streaming provider and switches providers live during a running event without user interaction. Compared to the status quo of renting a third-party event platform per event, it runs on self-operated infrastructure, keeps all personal data under the organization's own GDPR responsibility, and anonymizes it on event finish.
○ SCOPE	Broadcast covers anonymous and authenticated event access, video playback, moderated interaction, and event statistics. It deliberately neither produces nor encodes nor hosts the video streams itself — ingest and delivery stay with the external streaming providers — and it is neither a conferencing tool with attendee audio and video, nor a video-on-demand archive.
○ SUCCESS-CRITERIA	Broadcast is achieved once an organization can run its large-scale events on it end-to-end: events of up to 10,000 simultaneous attendees are carried without a stream interruption visible to the audience.
○ FUTURE-STATE	Once adopted, live events are no longer bought per event from external platforms but can be held on an organization's own channel: the attendee data never leaves its control, the streaming provider becomes an exchangeable supplier instead of the platform, and organizers reuse one familiar event setup instead of a different tool for every occasion.

02 ● REQS: Solution Premises (SP)

Registered Audience Known in Advance TYPE: Assumption FAILURE-LIKELIHOOD: Low FAILURE-IMPACT: High	Attendees Read Their Email While Logging In TYPE: Assumption FAILURE-LIKELIHOOD: Medium FAILURE-IMPACT: Medium	Ten Thousand Attendees Is the Upper Bound TYPE: Assumption FAILURE-LIKELIHOOD: Low FAILURE-IMPACT: High	Attendee Networks Pass WebSocket Traffic TYPE: Assumption FAILURE-LIKELIHOOD: Medium FAILURE-IMPACT: High
German and English Cover All Events TYPE: Assumption FAILURE-LIKELIHOOD: Low FAILURE-IMPACT: Low	Streaming Providers Deliver the Video TYPE: Dependency FAILURE-LIKELIHOOD: Medium FAILURE-IMPACT: High	Registration System Exchanges Attendee Data TYPE: Dependency FAILURE-LIKELIHOOD: Low FAILURE-IMPACT: Medium	Email Gateway Delivers Tokens Within Minutes TYPE: Dependency FAILURE-LIKELIHOOD: Medium FAILURE-IMPACT: High
Translation Service Available During Events TYPE: Dependency FAILURE-LIKELIHOOD: Medium FAILURE-IMPACT: Low	EU Hosting on Self-Operated Infrastructure TYPE: Dependency FAILURE-LIKELIHOOD: Low FAILURE-IMPACT: High	Connection Surge at Event Start TYPE: Risk FAILURE-LIKELIHOOD: High FAILURE-IMPACT: High	Access URLs Forwarded Beyond the Audience TYPE: Risk FAILURE-LIKELIHOOD: Medium FAILURE-IMPACT: Medium
Message Texts Contain Personal Data TYPE: Risk FAILURE-LIKELIHOOD: High FAILURE-IMPACT: Medium	Abusive Interaction from the Audience TYPE: Risk FAILURE-LIKELIHOOD: Medium FAILURE-IMPACT: Medium		

● PREMISE	Properties & Description			
Registered Audience Known in Advance 	○ TYPE	○ FAILURE-LIKELIHOOD	○ FAILURE-IMPACT	○ CONSEQUENCE
	Assumption	Low	High	Without an attendee list ahead of the event, no individual access URLs can be generated and returned, so the event has to fall back onto an access email pattern or onto anonymous access.
	○ MITIGATION	Description		
	Access email patterns and anonymous access remain available as fallback access modes of an event.	The audience of an event is registered in the Event Registration System before the event takes place, so that its attendee list is available for import while the event is planned — BECAUSE the organization invites its events through the registration system and never on the day of the event itself.		
Attendees Read Their Email While Logging In 	○ TYPE	○ FAILURE-LIKELIHOOD	○ FAILURE-IMPACT	○ CONSEQUENCE
	Assumption	Medium	Medium	An attendee without access to their mailbox at login time cannot consume the authorization token within its validity of 5 minutes and is locked out of the event.

● PREMISE	Properties & Description			
Ten Thousand Attendees Is the Upper Bound 	○ MITIGATION Personalized and automatic access URLs let a pre-verified attendee skip the token step, and the token validity is configurable per event.	Description An attendee has their mailbox at hand on the device (or next to it) while logging in, so that the one-time authorization token reaches them within its validity — BECAUSE the invitation itself arrives by email and attendees join from the same workplace or home context.		
	○ TYPE Assumption	○ FAILURE-LIKELIHOOD Low	○ FAILURE-IMPACT High	○ CONSEQUENCE An event exceeding 10,000 simultaneous attendees exhausts the dimensioned relay and proxy capacity, degrading or refusing the connections of the excess audience.
Attendee Networks Pass WebSocket Traffic 	○ MITIGATION The horizontal scaling of proxy, relay, and server instances leaves headroom, which is confirmed by a load test before each larger event.	Description No single event gathers more than 10,000 simultaneous attendees, the size of the largest digital town hall of the organization — BECAUSE the invited audience is bounded by the workforce of the organization and its registration figures.		
	○ TYPE Assumption	○ FAILURE-LIKELIHOOD Medium	○ FAILURE-IMPACT High	○ CONSEQUENCE An attendee behind a proxy or firewall which blocks long-lived WebSocket connections sees the video but receives neither the live interaction nor the configuration updates.
German and English Cover All Events 	○ MITIGATION All connections use the standard HTTPS port with a WebSocket upgrade, and the client reports a failed real-time connection to the attendee.	Description The corporate and home networks of the attendees permit long-lived WebSocket connections over HTTPS — BECAUSE the live interaction and the configuration propagation are carried over MQTT-over-WebSocket rather than over plain HTTP requests.		
	○ TYPE Assumption	○ FAILURE-LIKELIHOOD Low	○ FAILURE-IMPACT Low	○ CONSEQUENCE An event held in a third language needs a further translation target and user interface locale,

● PREMISE	Properties & Description			
				which the solution does not offer.
	○ MITIGATION	Description		
	∅	Every event is held in German or English and its audience reads at least one of the two — BECAUSE these are the working languages of the organization.		
Streaming Providers Deliver the Video 	○ TYPE	○ FAILURE-LIKELIHOOD	○ FAILURE-IMPACT	○ CONSEQUENCE
	Dependency	Medium	High	Without a working provider resource there is no video, and the event degrades to an interaction channel without a stream.
	○ MITIGATION	Description		
	Every event is configured with at least one fallback provider resource, and the operators switch providers live without user interaction.	The external streaming providers (such as msg Filmstudio, YouTube, Cloudflare, or 3Q) ingest, encode, and deliver the video and expose an embeddable playback URL in the required 1080p30 quality — BECAUSE the solution deliberately neither produces nor hosts the video streams itself.		
Registration System Exchanges Attendee Data 	○ TYPE	○ FAILURE-LIKELIHOOD	○ FAILURE-IMPACT	○ CONSEQUENCE
	Dependency	Low	Medium	A changed export format of the registration system breaks the attendee import, and the invitation emails cannot carry the individual access URLs.
	○ MITIGATION	Description		
	The exchange uses plain Excel sheets in an agreed column layout, which the manager can adjust by hand in the worst case.	The Event Registration System exports the attendee registrations of an event as an Excel sheet, accepts the generated access URLs in return, and sends the invitation emails itself — BECAUSE the organization provisions its events from its existing registration system and the solution does not send invitations.		
Email Gateway Delivers Tokens Within Minutes 	○ TYPE	○ FAILURE-LIKELIHOOD	○ FAILURE-IMPACT	○ CONSEQUENCE
	Dependency	Medium	High	A delayed or undelivered token email locks the attendee out, as the token expires after 5 minutes, and at the event start thousands of attendees are affected at once.

● PREMISE	Properties & Description			
Translation Service Available During Events 	○ MITIGATION The token validity is configurable per event, and automatic access URLs let pre-verified attendees enter without a token email.	Description The external email gateway accepts the one-time authorization token emails at the burst rate of an event start and delivers them to the attendees within a minute — BECAUSE the email token is the first-factor authentication of the solution.		
	○ TYPE Dependency	○ FAILURE-LIKELIHOOD Medium	○ FAILURE-IMPACT Low	○ CONSEQUENCE Without the service, messages remain in their source language only, so the attendees of the other language read untranslated chat and questions.
EU Hosting on Self-Operated Infrastructure 	○ MITIGATION Messages are stored and shown in their source language regardless, and the translation is added asynchronously once the service responds.	Description The external AI/LLM service translates message texts between German and English on the fly within a few seconds — BECAUSE the two-language audience expects to read chat and questions in their own language.		
	○ TYPE Dependency	○ FAILURE-LIKELIHOOD Low	○ FAILURE-IMPACT High	○ CONSEQUENCE Hosting outside the EU or on a public cloud without an EU data-processing agreement violates the GDPR obligations of the operator and voids the cost advantage of the solution.
Connection Surge at Event Start 	○ MITIGATION The hosting contract fixes the data center location, and the containerized deployment is portable to any other EU hoster.	Description The Hetzner data center in Nürnberg, Germany, provides the virtual machines the solution runs on, within the EU and at a price below the equivalent public cloud offerings — BECAUSE self-hosting within the EU is both the legal and the economic foundation of the solution.		
	○ TYPE Risk	○ FAILURE-LIKELIHOOD High	○ FAILURE-IMPACT High	○ CONSEQUENCE Thousands of attendees logging in within the same minute overload the token issuing, the email gateway, and the relays, so that the first minutes of the



● PREMISE	Properties & Description			
				event are lost for a part of the audience.
	○ MITIGATION Proxy, relay, and server instances are scaled out before the event, and personalized and automatic access URLs let most attendees bypass the token step.	Description The audience of a large event connects within a very short window around the announced start rather than spread over time — BECAUSE attendees open their invitation link only when the event begins.		
Access URLs Forwarded Beyond the Audience ⚓	○ TYPE Risk	○ FAILURE-LIKELIHOOD Medium	○ FAILURE-IMPACT Medium	○ CONSEQUENCE Uninvited persons watch a confidential event and take part in its interaction under the identity of an invited attendee.
	○ MITIGATION Access is granted to listed or pattern-matching email addresses only, each attendee holds a single active session, and unguessable URLs with time-limited tokens shorten the window of a leaked link.	Description An invited attendee forwards their individual access URL to colleagues or posts it publicly — BECAUSE personal links are easily shared and attendees do not perceive them as secrets.		
Message Texts Contain Personal Data ⚓	○ TYPE Risk	○ FAILURE-LIKELIHOOD High	○ FAILURE-IMPACT Medium	○ CONSEQUENCE Personal data written into chat and questions is exported to the organizers and sent to the external translation service, so that a retention or transfer beyond the given consent violates the GDPR.
	○ MITIGATION Attendees give explicit consent before interacting, the finish procedure anonymizes all attendee data, and the translation service is contracted under an EU data-	Description Attendees write personal data of themselves or of others into chat messages and questions — BECAUSE free-text interaction cannot be constrained to non-personal content.		

● PREMISE	Properties & Description			
Abusive Interaction from the Audience ⚓	processing agreement.			
	○ TYPE	○ FAILURE-LIKELIHOOD	○ FAILURE-IMPACT	○ CONSEQUENCE
	Risk	Medium	Medium	Spam, floods, or offensive messages drown the legitimate questions and put the moderators under pressure during the live event.
	○ MITIGATION	Description		
	Messages are moderated before becoming visible, submissions are throttled per attendee, and the sentiment analysis flags offensive content automatically.	A part of the audience misuses the chat and question channels with spam, floods, or offensive content — BECAUSE large invited audiences are never free of disruptive participants.		

03 ● REQS: Domain Glossary (DG) [⚓](#)

Event TYPE: Entity	Attendee TYPE: Actor	User TYPE: Entity	Manager TYPE: Actor
Moderator TYPE: Actor	Presenter TYPE: Actor	Administrator TYPE: Actor	Role TYPE: Entity
Channel TYPE: Entity	Resource TYPE: Entity	Streaming Provider TYPE: Actor	Message TYPE: Entity
Question TYPE: Entity	Chat TYPE: Entity	Support TYPE: Entity	Like TYPE: Entity
Authorization Token TYPE: Entity	Session Token TYPE: Entity	Access List TYPE: Entity	Event Registration System TYPE: Actor
Anonymization TYPE: Activity	Sentiment Analysis TYPE: Activity		

● TERM	Properties & Description		
	Attendee Networks Pass WebSocket Traffic ⓘ, ● PREMISE: Connection Surge at Event Start ⓘ, ● PREMISE: Access URLs Forwarded Beyond the Audience ⓘ		
User ⓘ	Diagram <pre> graph LR subgraph Rules R1[Single Active Session per Event] R2[Access Requires List or Pattern Match] R3[Anonymization on Event Finish] R4[No Permanent User Accounts] R5[Administrator Bypasses the Access List] end subgraph Entities U[User] end R1 -- governs --> U R2 -- governs --> U R3 -- governs --> U R4 -- governs --> U R5 -- terms --> U U -- terms --> U </pre>		
○ TYPE	○ SYNONYMS	○ BROADER	○ DISTINCT-FROM
Entity	∅	∅	∅
○ PREMISES	Description		
∅	A person identified by their email address within a specific ● Event, holding the ● Roles granted to them and existing only while granted a ● Role, present on the ● Access List, or joining via the access email pattern of the ● Event, except the holder of the ● Administrator ● Role, who exists permanently and outside any ● Event; any other User is never a permanent account, and an ● Attendee is a User logged into the ● Event		
Manager ⓘ	Diagram <pre> graph LR subgraph Terms T1[Administrator] T2[Manager Retained for Export] T3[Manager] T4[Event Operator] end subgraph Rules R1[Anonymization on Event Finish] end subgraph Entities E1[Role] E2[Manfred] end subgraph ManagerEntity [TERM Manager] M[Manager] end subgraph DistinctFromBox [TERM Administrator] AD[Administrator] end subgraph BroaderBox [TERM Role] BR[Role] end T1 -- distinct-from --> M T2 -- governs --> M T3 -- terms --> M T4 -- terms --> M R1 -- governs --> M E1 -- terms --> M E2 -- terms --> M M -- distinct-from --> AD M -- broader --> BR </pre>		
○ TYPE	○ SYNONYMS	○ BROADER	○ DISTINCT-FROM
Actor	∅	● TERM: Role ⓘ	● TERM: Administrator ⓘ
○ PREMISES	Description		
∅	An event-level ● Role that can edit, start, stop, and delete an ● Event and export its anonymized data; the Manager role is retained after the		


● TERM	Properties & Description		
	● Event finishes until the ● Event is deleted		
Moderator ⚓	Diagram		
			
	○ TYPE Actor	○ SYNONYMS ∅	○ BROADER ● TERM: Role ⓘ ○ DISTINCT-FROM ● TERM: Presenter ⓘ
	○ PREMISES ● PREMISE: Abusive Interaction from the Audience ⓘ	Description An event-specific ● Role that moderates chat and question ● Messages by rejecting, approving, and forwarding them, and that supports the ● Presenter with hints and curated input	
Presenter ⚓	Diagram		
			
	○ TYPE Actor	○ SYNONYMS ∅	○ BROADER ● TERM: Role ⓘ ○ DISTINCT-FROM ● TERM: Moderator ⓘ
	○ PREMISES ∅	Description An event-specific ● Role held by the person on stage in a recorded video ● Event, receiving the ● Messages forwarded by the ● Moderator and marking them answered or suspended after processing them live; unlike the ● Moderator, the Presenter curates nothing and sees only the forwarded subset	


● TERM Administrator 	Properties & Description			
	Diagram			
○ TYPE		○ SYNONYMS	○ BROADER	○ DISTINCT-FROM
Actor		Software Administrator, Hardware Administrator	● TERM: Role 	● TERM: Manager 
○ PREMISES		Description		
∅		A permanent ● Role independent of any ● Event and bootstrapped from the software configuration, whose holder needs no ● Access List entry and may perform every operation on every entity of every ● Event; the Hardware Administrator manages the physical server while the Software Administrator manages the software configuration and creates ● Events		

Role 	Diagram			
○ TYPE		○ SYNONYMS	○ BROADER	○ DISTINCT-FROM
Entity		Event Role	∅	∅
○ PREMISES		Description		
∅		A grant of rights held by a ● User (usually within a specific ● Event), of type ● Attendee, ● Manager, ● Moderator, ● Presenter or ● Administrator. A role is a permanent entity		

● TERM	Properties & Description																
Channel	Diagram																
	<table><tr><td>○ TYPE</td><td>○ SYNONYMS</td><td>○ BROADER</td><td>○ DISTINCT-FROM</td></tr><tr><td>Entity</td><td>∅</td><td>∅</td><td>● TERM: Resource ①</td></tr><tr><td>○ PREMISES</td><td colspan="3">Description</td></tr><tr><td>∅</td><td colspan="3">A logical content stream of an ● Event grouping language- and resolution-specific ● Resources; exactly one Channel of an ● Event is active at a time</td></tr></table>	○ TYPE	○ SYNONYMS	○ BROADER	○ DISTINCT-FROM	Entity	∅	∅	● TERM: Resource ①	○ PREMISES	Description			∅	A logical content stream of an ● Event grouping language- and resolution-specific ● Resources; exactly one Channel of an ● Event is active at a time		
○ TYPE	○ SYNONYMS	○ BROADER	○ DISTINCT-FROM														
Entity	∅	∅	● TERM: Resource ①														
○ PREMISES	Description																
∅	A logical content stream of an ● Event grouping language- and resolution-specific ● Resources; exactly one Channel of an ● Event is active at a time																
Resource	Diagram																
	<table><tr><td>○ TYPE</td><td>○ SYNONYMS</td><td>○ BROADER</td><td>○ DISTINCT-FROM</td></tr><tr><td>Entity</td><td>∅</td><td>∅</td><td>● TERM: Channel ①</td></tr><tr><td>○ PREMISES</td><td colspan="3">Description</td></tr><tr><td>● PREMISE: Streaming Providers Deliver the Video ①</td><td colspan="3">A physical content delivery endpoint backing a ● Channel, such as a provider video stream or a static website; exactly one Resource of a ● Channel is active at a time</td></tr></table>	○ TYPE	○ SYNONYMS	○ BROADER	○ DISTINCT-FROM	Entity	∅	∅	● TERM: Channel ①	○ PREMISES	Description			● PREMISE: Streaming Providers Deliver the Video ①	A physical content delivery endpoint backing a ● Channel, such as a provider video stream or a static website; exactly one Resource of a ● Channel is active at a time		
○ TYPE	○ SYNONYMS	○ BROADER	○ DISTINCT-FROM														
Entity	∅	∅	● TERM: Channel ①														
○ PREMISES	Description																
● PREMISE: Streaming Providers Deliver the Video ①	A physical content delivery endpoint backing a ● Channel, such as a provider video stream or a static website; exactly one Resource of a ● Channel is active at a time																
Streaming Provider	Diagram																

● TERM	Properties & Description			
	○ TYPE	○ SYNONYMS	○ BROADER	○ DISTINCT-FROM
	Actor	Provider, CDN Provider	∅	∅
	○ PREMISES	Description		
	● PREMISE: Streaming Providers Deliver the Video ⓘ	An external service such as msg Filmstudio, YouTube, Cloudflare, Twitch, or 3Q that ingests and delivers the video stream addressed by a ● Resource through configured provider parameters		

Message ⓘ	Diagram			
				
	○ TYPE	○ SYNONYMS	○ BROADER	○ DISTINCT-FROM
	Entity	∅	∅	∅
	○ PREMISES	Description		
	● PREMISE: German and English Cover All Events ⓘ, ● PREMISE: Translation Service Available During Events ⓘ, ● PREMISE: Message Texts Contain Personal Data ⓘ, ● PREMISE: Abusive Interaction from the Audience ⓘ	A single unit of ● Event interaction of type ● Chat , ● Question , or ● Support , carrying language-specific texts and moving through a moderation and presentation lifecycle		

Question ⓘ	Diagram			
				
	○ TYPE	○ SYNONYMS	○ BROADER	○ DISTINCT-FROM


● TERM	Properties & Description			
	○ PREMISES	Description		
	∅	The marking of a ● Question or ● Chat as relevant by an ● Attendee, tracked per ● User and revocable until the ● Event finishes, thereafter conserved as a bare count by the ● Anonymization		
Authorization Token ⚓	Diagram			
	TERM Session Token RULE Anonymization on Event Finish RULE Token Format and Validity ENTITY AuthorizationToken CONVENTION Token Display Format distinct-from governs governs terms terms TERM Authorization Token distinct-from premises premises TERM Session Token PREMISE Attendees Read Their Email While Logging In PREMISE Email Gateway Delivers Tokens Within Minutes			
	○ TYPE	○ SYNONYMS	○ BROADER	○ DISTINCT-FROM
	Entity	Access Token	∅	● TERM: Session Token ⌵
	○ PREMISES	Description		
	● PREMISE: Attendees Read Their Email While Logging In ⌵ , ● PREMISE: Email Gateway Delivers Tokens Within Minutes ⌵	A one-time, time-limited “NNN-NNN” six-digit second factor proving an ● Attendee controls their email address; it may be pre-generated for automatic access		
Session Token ⚓	Diagram			
	TERM AuthorizationToken RULE Single Active Session per Event RULE Anonymization on Event Finish ENTITY SessionToken distinct-from governs governs terms TERM Session Token distinct-from premises TERM AuthorizationToken PREMISE Access URLs Forwarded Beyond the Audience			
	○ TYPE	○ SYNONYMS	○ BROADER	○ DISTINCT-FROM
	Entity	∅	∅	● TERM: AuthorizationToken ⌵
	○ PREMISES	Description		
	● PREMISE: Access URLs Forwarded Beyond the Audience ⌵	The result of a successful login granting an ● Attendee an active connection to an ● Event; only one Session Token per User per ● Event may be active at a time		

● TERM

Access List 

Properties & Description

Diagram



○ TYPE	○ SYNONYMS	○ BROADER	○ DISTINCT-FROM
Entity	∅	∅	∅

○ PREMISES

● PREMISE:

Registered Audience Known in Advance



,

● PREMISE:

Registration System Exchanges Attendee Data



,

● PREMISE:

Access URLs Forwarded Beyond the Audience




Description

The set of Users, identified by email, invited to a specific ● Event; together with the access email pattern it determines who may be granted ● Event access

Event Registration System 

Diagram



○ TYPE	○ SYNONYMS	○ BROADER	○ DISTINCT-FROM
Actor	∅	∅	∅

○ PREMISES

● PREMISE:

Registered Audience Known in Advance



,

● PREMISE:

Registration System Exchanges Attendee Data



Description

The external registration platform from which ● Attendee data is imported via Excel and to which generated access URLs are returned

● TERM

Anonymization

Properties & Description

Diagram

RULE

Anonymization on Event Finish

RULE

Likes Conserved as Count on Finish

RULE

Manager Retained for Export

WORKFLOW

Run Broadcast Event

CONVENTION

Anonymous Placeholder

TERM

Anonymization

PREMISE

Message Texts Contain Personal Data

governs

governs

governs

terms

terms

premises

○ TYPE

Activity

○ SYNONYMS

Privacy by Design Finish

○ BROADER

∅

○ DISTINCT-FROM

∅

○ PREMISES

● PREMISE: Message Texts Contain Personal Data

Description

The automated procedure on ● Event finish that reduces ● Messages to like counts, anonymizes sender names, drops personal relations, deletes tokens and Users, unlinks the viewer statistics from their Users, and removes ● Moderator roles

Sentiment Analysis

Diagram

RULE

Sentiment Auto-Decision Threshold

ENTITY

Message

TERM

Sentiment Analysis

PREMISE

Abusive Interaction from the Audience

governs

terms

premises

○ TYPE

Activity

○ SYNONYMS

Profanity Check

○ BROADER

∅

○ DISTINCT-FROM

∅


○ PREMISES


● PREMISE: Abusive Interaction from the Audience



Description



The optional client-side or server-side evaluation of ● Message text yielding a sentiment score used to prevent, auto-accept, or auto-reject improper input

04 ● REQS: User Personas (UP) ⚓



● ROLE		Properties & Description	
Attendee 		Diagram	
			
○ TYPE	○ TERM	Description	
Person	● TERM: Attendee 	The attendee watches the stream of the event they were invited to and takes part in its interaction with messages and likes of their own — BECAUSE the audience has to participate without ever gaining a view on the moderation or on the personal data of other attendees.	

● ROLE	Properties & Description		
Moderator 	Diagram		
			
Presenter 	Diagram		
			
○ TYPE	○ TERM	Description	
Person	● TERM: Moderator 	The moderator gatekeeps the interaction of a running event by deciding, answering, forwarding, and seeding messages and by steering the presenter, where the Q&A moderator and the chat moderator hold the very same role and split the work by message type by convention only — BECAUSE the audience has to see only what the organizers approve while the presenter receives a curated selection.	
Person	● TERM: Presenter 	The presenter receives the curated questions on stage and records their processing, seeing nothing else of the interaction — BECAUSE the person on air has to be shielded from the raw audience input.	

● ROLE Manager 	Properties & Description Diagram  ○ TYPE Person ○ TERM ● TERM: Manager  Description The manager owns an event from its configuration through its live run to its archived export, without taking part in the moderation — BECAUSE one accountable role has to control the visibility, the audience, and the lifecycle of the event.			
Administrator 	Diagram  ○ TYPE Person ○ TERM ● TERM: Administrator  Description The administrator provisions the events and the streaming providers through the configuration of the software and, as the permanent bootstrap identity, enters every event without an access list entry and edits everything in it — BECAUSE the operation of the platform has to be reproducible from configuration and recoverable by one role that depends on no event-specific grant.			
● PERSONA Anna 	Properties & Description ○ ROLES ● ROLE: Attendee  ○ TERMS ● TERM: Attendee  ○ GOAL Watch the live event effortlessly and get her questions answered. ○ FRUSTRATION Streaming tools that demand accounts, apps, or plugins before she can even watch. Description “I just want to watch the town hall and ask my question without jumping through hoops.”			

● PERSONA	Properties & Description			
Markus 	○ ROLES ● ROLE: Moderator 	○ TERMS ● TERM: Moderator  , ● TERM: Chat 	○ GOAL Keep the chat conversation civil and on-topic with minimal effort.	○ FRUSTRATION Chat tools without moderation support, letting spam and off-topic noise drown the conversation.
	Description			
	“I keep the Chat conversation clean.”			
Peter 	○ ROLES ● ROLE: Moderator 	○ TERMS ● TERM: Moderator  , ● TERM: Question 	○ GOAL Filter the incoming questions and forward only the relevant ones to the presenter.	○ FRUSTRATION Unfiltered question streams where duplicates and noise bury the questions that truly matter.
	Description			
	“I keep the Q&A funnel clean and feed the presenter only questions which truly matter.”			
Petra 	○ ROLES ● ROLE: Presenter 	○ TERMS ● TERM: Presenter 	○ GOAL Deliver her talk while receiving the curated questions at the right moment.	○ FRUSTRATION Being distracted on stage by raw chat noise instead of a few curated questions.
	Description			
	“On stage I need the right questions in front of me at the right moment, and nothing else.”			
Manfred 	○ ROLES ● ROLE: Manager 	○ TERMS ● TERM: Manager  , ● TERM: Event Registration System 	○ GOAL Set up events quickly and hand the access URLs back to the Event Registration System.	○ FRUSTRATION Manual, error-prone event setup with access URLs that have to be copied around by hand.
	Description			
	“Setting up an event and getting the access URLs back to the Event Registration System has to be quick and repeatable.”			
Sven 	○ ROLES ● ROLE: Administrator 	○ TERMS ● TERM: Administrator  , ● TERM: Streaming Provider 	○ GOAL Provision events and streaming providers reproducibly via configuration, and fix anything in any event when the organizers are stuck.	○ FRUSTRATION Platforms that require per-event manual clicks and lock him out of the events he provisioned.
	Description			
	“I provision events and streaming providers via config, and when something is stuck I step into any event and fix it.”			

05 ● REQS: User Journey (UJ)

Attend a Broadcast event

ACTORS: Anna

Operate a Broadcast Event

ACTORS: Manfred

Moderate a Broadcast Event

ACTORS: Markus, Peter

05.01 ● JOURNEY: Attend a Broadcast event

○ ACTORS

● PERSONA: Anna 

● STEP	Properties		
Receive personal event invitation URL 	○ STAGE	○ GOAL	○ TOUCHPOINT
	Awareness	Learn that an event is happening and that access is granted	Invitation email containing the individual event URL
	○ ACTION	○ EMOTION	○ PAIN-POINT
	The attendee reads the invitation and clicks the personalized event link.	Curious (+1)	∅
Open event page and review login info 	○ OPPORTUNITY	∅	
	○ STAGE	○ GOAL	○ TOUCHPOINT
	Consideration	Understand what the event is and how to join	Event landing screen in the web browser
	○ ACTION	○ EMOTION	○ PAIN-POINT
Authenticate via email token 	The attendee reads the optional login message and any links before deciding to log in.	Interested (+1)	Uncertainty whether the link is genuine and what data will be collected.
		○ OPPORTUNITY	The event landing screen states organizer, purpose, and data handling upfront, so the attendee can trust the link.
	○ STAGE	○ GOAL	○ TOUCHPOINT
	Decision	Gain access to the live video stream	Login dialog with email and token challenge
Watch stream and interact 	○ ACTION	○ EMOTION	○ PAIN-POINT
	The attendee enters the email, receives a 6-digit token by mail, and submits it.	Slightly impatient (-1)	Waiting for the token email and re-checking the inbox adds friction before the event.
	○ OPPORTUNITY	The token email arrives within seconds and the token field accepts a pasted value, so the wait before the event stays minimal.	
	○ STAGE	○ GOAL	○ TOUCHPOINT
	Usage	Follow the event and contribute questions, chat, and likes	Main attendee screen with video and interaction sidebar

● STEP	Properties		
	○ ACTION	○ EMOTION	○ PAIN-POINT
	The attendee watches the stream, posts questions or chat messages, and likes others' messages.	Engaged (+2)	Messages may be delayed by moderation, so the attendee is unsure whether input arrived.
	○ OPPORTUNITY		
	Submitted messages appear immediately in a pending state, so the attendee knows the input arrived.		

05.02 ● JOURNEY: Operate a Broadcast Event

○ ACTORS ● PERSONA: Manfred 

● STEP	Properties		
Configure and run the event 	○ STAGE	○ GOAL	○ TOUCHPOINT
	Usage	Set up, start, and control an event end-to-end	Manager configuration screen and Event Registration System Excel import/export
	○ ACTION	○ EMOTION	○ PAIN-POINT
	The manager imports attendees, configures channels and options, and starts the event.	Focused (0)	Coordinating streaming providers, access lists, and tokens before going live is error-prone.
	○ OPPORTUNITY		
	The configuration screen validates the imported attendee list and the streaming settings before the event goes live.		
Export anonymized results after event 	○ STAGE	○ GOAL	○ TOUCHPOINT
	Usage	Capture and share the event's interaction outcomes	Manager export function producing a downloadable file
	○ ACTION	○ EMOTION	○ PAIN-POINT
	The manager exports anonymized messages with timestamps, states, and like counts.	Satisfied (+2)	∅
	○ OPPORTUNITY		
	∅		

05.03 ● JOURNEY: Moderate a Broadcast Event

○ ACTORS ● PERSONA: Markus , ● PERSONA: Peter 

● STEP	Properties		
Moderate and support the presenter 	○ STAGE	○ GOAL	○ TOUCHPOINT
	Usage	Keep interaction clean and forward the best questions	Moderator Kanban board of chat and question messages

● STEP	Properties		
		to the presenter	
	○ ACTION	○ EMOTION	○ PAIN-POINT
	The moderator approves, rejects, and forwards messages and sends hints to the presenter.	Pressured (-2)	High message volume under time pressure makes it hard to keep an overview.
	○ OPPORTUNITY		
	The Kanban board groups messages by state and highlights new arrivals, so the moderator keeps an overview under load.		

06 ● REQS: Functional Requirements (FR)

User Authentication PRIORITY: MUST	Limit Parallel Access PRIORITY: MUST	Ask Questions PRIORITY: MUST	Chat Messages PRIORITY: MUST
Like Messages PRIORITY: MUST	Reply to Chat Messages PRIORITY: SHOULD	Configurable Name Appearance PRIORITY: MUST	Personal Display Filtering PRIORITY: SHOULD
Client-Side Sentiment Analysis PRIORITY: COULD	Server-Side Sentiment Analysis PRIORITY: COULD	Edit and Delete Messages PRIORITY: SHOULD	Tag Question Messages PRIORITY: SHOULD
Moderate Chat and Questions PRIORITY: MUST	Forward Inputs to Presenter PRIORITY: MUST	Answer Attendee Inputs PRIORITY: SHOULD	Moderator-Authored Messages PRIORITY: SHOULD
Export Attendee Inputs PRIORITY: MUST	Presenter Hints and Alerts PRIORITY: SHOULD	Sort and Filter Messages PRIORITY: SHOULD	Manage Embedded Application PRIORITY: COULD
Browser Access PRIORITY: MUST	Individual Event Access URL PRIORITY: MUST	Personalized Event Access URL PRIORITY: SHOULD	Automatic Event Access URL PRIORITY: SHOULD
Direct Resource Access URL PRIORITY: SHOULD	GDPR-Compliant EU Processing PRIORITY: MUST	Explicit User Consent PRIORITY: MUST	Login and Interaction Messages PRIORITY: SHOULD
Multiple Streaming Providers PRIORITY: MUST	Live Provider Switching PRIORITY: MUST	Import Registered Attendees PRIORITY: MUST	Return Access URLs to Registration PRIORITY: MUST
Import and Export Event PRIORITY: SHOULD	General Event Statistics PRIORITY: MUST	Debugging Statistics PRIORITY: SHOULD	Channel Statistics PRIORITY: SHOULD
User Statistics PRIORITY: SHOULD	Periodic Statistics Snapshots PRIORITY: MUST	Live Configuration Propagation PRIORITY: MUST	Presenter Dashboard PRIORITY: COULD
Multiple-Choice Feedback PRIORITY: COULD	Mobile Device Support PRIORITY: COULD	In-Session Language Switching PRIORITY: SHOULD	Light and Dark Theme PRIORITY: COULD
Deleted Message Placeholder PRIORITY: SHOULD			

● REQUIREMENT	○ PRIORITY	○ PREMISES	Description
User Authentication ⚓	MUST	● PREMISE: Attendees Read Their Email While Logging In ⌕, ● PREMISE: Email Gateway Delivers Tokens Within Minutes ⌕, ● PREMISE: Connection Surge at Event Start ⌕	The system MUST authenticate participants via their email address before showing the video stream or, at minimum, before allowing participation in questions and chat, re-checking on every access that the event still lists the user even when the user is already authenticated — BECAUSE access must be restricted to invited participants to minimize foreign viewers
Limit Parallel Access ⚓	MUST	● PREMISE: Access URLs Forwarded Beyond the Audience ⌕	When participants must be authenticated to watch, the system MUST allow an event to be viewed only once per participant at a time, closing the prior connection on a new login — BECAUSE single concurrent sessions minimize unauthorized outside viewing
Ask Questions ⚓	MUST	● PREMISE: Attendee Networks Pass WebSocket Traffic ⌕	The system MUST let attendees submit questions as a dedicated feedback channel feeding the Q&A rounds — BECAUSE structured audience questions are a core interaction the event format depends on
Chat Messages ⚓	MUST	● PREMISE: Attendee Networks Pass WebSocket Traffic ⌕	The system MUST let attendees send chat messages for direct comment on the event — BECAUSE live commentary keeps the audience engaged during the broadcast
Like Messages ⚓	MUST	∅	The system MUST let attendees like questions and chat messages and undo the like — BECAUSE liking surfaces the most relevant audience input for moderators and presenters
Reply to Chat Messages ⚓	SHOULD	∅	Where replies are enabled for an event, the system SHOULD let attendees reply to chat messages — BECAUSE threaded replies aid discussion but are not appropriate for every event format
Configurable Name Appearance ⚓	MUST	∅	The system MUST display an attendee's name on messages as full "Firstname Lastname", first name only, or anonymous per event configuration, always exposing the email address (at least on hover) and optionally deriving the name from the email if none is given — BECAUSE events differ in how much attendee identity should be revealed
Personal Display Filtering ⚓	SHOULD	∅	The system SHOULD let an attendee choose to see only their own messages and questions or also those of others — BECAUSE attendees want to track their own contributions without distraction
Client-Side Sentiment Analysis ⚓	COULD	∅	The system COULD perform configurable client-side sentiment analysis that checks attendee input before it is sent and may prevent improper submissions — BECAUSE filtering at the source reduces server moderation load and discourages misconduct
Server-Side Sentiment Analysis	COULD	● PREMISE: Abusive Interaction from the	The system COULD perform configurable server-side sentiment analysis that checks attendee input

● REQUIREMENT	○ PRIORITY	○ PREMISES	Description
		Audience 	before it is stored, auto-accepting positive and auto-rejecting negative input — BECAUSE automated triage assists moderators with high message volume
Edit and Delete Messages 	SHOULD	∅	The system SHOULD let attendees edit and delete their own chat and question messages, mark edited messages for others, and re-run moderation on edits where required — BECAUSE attendees must correct mistakes without bypassing moderation
Tag Question Messages 	SHOULD	∅	The system SHOULD let attendees tag question messages with predefined tags to give context such as the addressed person or agenda point — BECAUSE tags help moderators and presenters route and group questions
Moderate Chat and Questions 	MUST	● PREMISE: Abusive Interaction from the Audience 	The system MUST support optional moderation in which moderators reject, approve, or forward attendee input, with messages held pending until approved when moderation is enabled — BECAUSE organizers need control over what becomes publicly visible
Forward Inputs to Presenter 	MUST	∅	The system MUST let moderators forward approved inputs to a presenter so the presenter sees only a curated subset rather than all approved messages — BECAUSE the presenter on stage can only process a focused set of items
Answer Attendee Inputs 	SHOULD	∅	The system SHOULD let moderators reply to an attendee's input, including non-visible direct messages — BECAUSE moderators need to clarify details or provide support privately
Moderator-Authored Messages 	SHOULD	∅	The system SHOULD let moderators author chats and questions visible to others under a sender name defaulting to “Moderator” but overridable on send — BECAUSE prepared questions are needed to seed Q&A sessions
Export Attendee Inputs 	MUST	∅	After an event finishes, the system MUST let managers export all attendee inputs including at least timestamp, state, number of likes, and message text — BECAUSE organizers need a durable record of audience interaction
Presenter Hints and Alerts 	SHOULD	∅	The system SHOULD let moderators send textual hints to the presenter and raise an alert the presenter can confirm — BECAUSE the moderator must steer the live presenter with timing and routing guidance
Sort and Filter Messages 	SHOULD	∅	The system SHOULD let moderators filter messages and manually order forwarded questions — BECAUSE moderators need a clear overview and a defined order for the presenter to ask questions
Manage Embedded Application 	COULD	∅	The system COULD let moderators administer an embedded third-party application when it exposes an administration view — BECAUSE some events

● REQUIREMENT	○ PRIORITY	○ PREMISES	Description
Browser Access ↕	MUST	● PREMISE: Attendee Networks Pass WebSocket Traffic ⌘	integrate interactive apps that the moderator must control The system MUST be accessible from any reasonably recent web browser without installation — BECAUSE attendees use both managed and unmanaged devices with no common client software
Individual Event Access URL ↕	MUST	● PREMISE: Registered Audience Known in Advance ⌘	The system MUST allow accessing an event via an individual, unguessable URL of the form <code>#/event=<event></code> — BECAUSE an obscure entry point minimizes access by external viewers
Personalized Event Access URL ↕	SHOULD	∅	The system SHOULD support an event URL that also carries the user email (<code>&user=<email></code>), making the email read-only in the login dialog — BECAUSE pre-filling the identity streamlines the attendee login
Automatic Event Access URL ↕	SHOULD	∅	The system SHOULD support an event URL carrying a pre-generated access token (<code>&token=<token></code>) that auto-authenticates the user without a login dialog, with single or multiple use governed by event settings — BECAUSE automated access enables frictionless joining for trusted distributions
Direct Resource Access URL ↕	SHOULD	∅	The system SHOULD support a <code>&resource=<resource></code> URL parameter that selects a specific event resource on access — BECAUSE attendees reloading the page must return to the same stream or static resource
GDPR-Compliant EU Processing ↕	MUST	● PREMISE: EU Hosting on Self- Operated Infrastructure ⌘	The system MUST provide all services in compliance with GDPR within the EU — BECAUSE the audience and operator are subject to European data-protection law
Explicit User Consent ↕	MUST	● PREMISE: Message Texts Contain Personal Data ⌘	The system MUST require event attendees to give explicit consent before participating under defined conditions, in addition to prior platform consent — BECAUSE consent is both a legal safeguard and a psychological hurdle against prohibited stream sharing
Login and Interaction Messages ↕	SHOULD	∅	The system SHOULD optionally display configurable text with one or two links at login and at interaction time — BECAUSE organizers communicate event information and conduct rules at these moments
Multiple Streaming Providers ↕	MUST	● PREMISE: Streaming Providers Deliver the Video ⌘	The system MUST allow multiple streaming providers to be configured per event — BECAUSE a configured fallback is required to recover from provider problems even during a running event
Live Provider Switching ↕	MUST	● PREMISE: Streaming Providers Deliver the Video ⌘	The system MUST allow switching the active streaming provider during an event, with attendee clients following the switch without user interaction — BECAUSE provider outages must be mitigated without disrupting the audience

● REQUIREMENT	○ PRIORITY	○ PREMISES	Description
Import Registered Attendees ↗	MUST	● PREMISE: Registered Audience Known in Advance ↗ , ● PREMISE: Registration System Exchanges Attendee Data ↗	The system MUST import an Excel sheet of the Event Registration System to populate an event's access list and generate authorization tokens, avoiding duplicate invitations on repeated imports — BECAUSE events are provisioned from the Event Registration System
Return Access URLs to Registration ↗	MUST	● PREMISE: Registered Audience Known in Advance ↗ , ● PREMISE: Registration System Exchanges Attendee Data ↗	The system MUST generate each attendee's personal access URL containing event, user, and a "NNN-NNN" six-digit token and return it in an Excel sheet to the Event Registration System — BECAUSE the Event Registration System distributes the join URLs to attendees
Import and Export Event ↗	SHOULD	∅	The system SHOULD export an event with its related entities to a serialized format such as YAML and re-import it — BECAUSE this eases development, demonstration, and creation of recurring production events
General Event Statistics ↗	MUST	∅	The system MUST provide an attendee statistics curve of logged-in users over time — BECAUSE organizers need to observe audience size and trend during the event
Debugging Statistics ↗	SHOULD	∅	The system SHOULD record login-challenge statistics including issued, sent, and used authorization tokens — BECAUSE operators need visibility into the authentication flow for diagnosis
Channel Statistics ↗	SHOULD	∅	The system SHOULD show the number of viewers per channel of an event — BECAUSE organizers want to know the relative popularity of language and resolution variants
User Statistics ↗	SHOULD	∅	The system SHOULD record viewer statistics including country, browser, device, and viewport, using country to select the default application language on first use — BECAUSE audience composition informs both reporting and localization
Periodic Statistics Snapshots ↗	MUST	∅	While an event is running, the system MUST capture a cumulative snapshot of its event and channel statistics every five minutes, independent of any user activity — BECAUSE a trend curve needs regularly sampled counts and not just the counts at the moments someone looks
Live Configuration Propagation ↗	MUST	∅	The system MUST propagate event configuration changes directly to all connected participants — BECAUSE toggles such as enabling chat must take effect for the live audience without a reload
Presenter Dashboard ↗	COULD	∅	The system COULD provide a dedicated presenter dashboard showing forwarded inputs for processing on stage — BECAUSE the presenter needs a focused working view, though its design is not yet finalized

● REQUIREMENT	○ PRIORITY	○ PREMISES	Description
Multiple-Choice Feedback	COULD	∅	The system COULD provide real-time multiple-choice questions answered by attendees — BECAUSE polls add interaction during the event
Mobile Device Support	COULD	∅	The system COULD let participants take part on mobile phones, at least for video with possible interaction restrictions — BECAUSE many attendees join from mobile devices
In-Session Language Switching	SHOULD	● PREMISE: German and English Cover All Events ● PREMISE: Translation Service Available During Events	The system SHOULD let an attendee switch the display and content language between German and English at any time from the header, applying the change immediately — BECAUSE attendees expect to read the interface and translated messages in their preferred one of the two supported languages
Light and Dark Theme	COULD	∅	The system COULD let an attendee toggle a light or dark theme from the header, applying it immediately across the interface — BECAUSE attendees view events under varied lighting and prefer a comfortable appearance
Deleted Message Placeholder	SHOULD	∅	When an attendee deletes a message, the system SHOULD retain its position in the stream and show a “This message was deleted” placeholder instead of removing it — BECAUSE preserving the gap keeps the surrounding conversation coherent for readers

07 ● REQS: Non-Functional Requirements (NR)


Concurrent Attendee Scale PRIORITY: MUST CATEGORY: Performance	Horizontal Scalability PRIORITY: MUST CATEGORY: Performance	Streaming Quality PRIORITY: MUST CATEGORY: Performance	Provider Failover Continuity PRIORITY: MUST CATEGORY: Reliability
Cross-Browser Compatibility PRIORITY: MUST CATEGORY: Compatibility	GDPR Compliance PRIORITY: MUST CATEGORY: Compliance	Privacy by Design PRIORITY: MUST CATEGORY: Security	Unguessable Access Tokens PRIORITY: MUST CATEGORY: Security
Isolated Persistence Node PRIORITY: MUST CATEGORY: Security	Event Setup Recovery PRIORITY: MUST CATEGORY: Reliability	Event-Safe Maintenance PRIORITY: MUST CATEGORY: Reliability	Live Configuration Latency PRIORITY: SHOULD CATEGORY: Performance
Per-Event Cost Efficiency PRIORITY: SHOULD CATEGORY: Constraint	Interaction Abuse Throttling PRIORITY: SHOULD CATEGORY: Security	Start-Surge Asset Delivery PRIORITY: SHOULD CATEGORY: Performance	Compile-Time Contract Safety PRIORITY: SHOULD CATEGORY: Maintainability
Live Diagnosability PRIORITY: SHOULD CATEGORY: Maintainability	Mobile Usability PRIORITY: COULD CATEGORY: Usability		

● REQUIREMENT

Concurrent Attendee Scale [⚓](#)

Properties & Description


Diagram



PRIORITY	CATEGORY	QUALIFIES
MUST	Performance	∅
PREMISES	METRIC	Description
● PREMISE: Ten Thousand Attendees Is the Upper Bound Ⓢ, ● PREMISE: Connection Surge at Event Start Ⓢ	2500 to 10000 concurrently connected attendees per event	The system MUST support between 2500 and 10000 attendees connected to a single event at the same time — BECAUSE msg Filmstudio video productions must reach an audience of this size simultaneously

Horizontal Scalability [⚓](#)

Diagram




PRIORITY	CATEGORY	QUALIFIES
MUST	Performance	∅
PREMISES	METRIC	Description
● PREMISE: Ten Thousand Attendees Is the Upper Bound Ⓢ, ● PREMISE: Connection Surge at Event Start Ⓢ	10000 concurrent WebSocket connections per event	The system MUST scale horizontally by running multiple proxy, relay, and server instances per runtime environment so that 10000 concurrent WebSocket connections are served per event — BECAUSE a single instance cannot handle the required connection volume and response times

● REQUIREMENT

Streaming Quality [📌](#)

Properties & Description

Diagram



○ PRIORITY

MUST

○ CATEGORY

Performance

○ QUALIFIES

∅

○ PREMISES

● **PREMISE: German and English Cover All Events** [📌](#), ● **PREMISE: Streaming Providers Deliver the Video** [📌](#)

○ METRIC

1920x1080 pixels at 30 fps in 2 languages

Description

The system **MUST** process and distribute video at 1080p30 (1920x1080 at 30 fps) in both German and English — **BECAUSE** productions are delivered in this defined quality and the two required languages

Provider Failover Continuity [📌](#)

Diagram



○ PRIORITY

MUST

○ CATEGORY

Reliability

○ QUALIFIES

● **REQUIREMENT: Live Provider Switching** [📌](#)

○ PREMISES

● **PREMISE: Streaming Providers Deliver the Video** [📌](#)

○ METRIC


all attendee clients on the fallback provider within 10 seconds

Description

The system **MUST** switch to a fallback streaming provider during a running event with attendee clients following the switch automatically within seconds and without user interaction — **BECAUSE** provider outages must not interrupt the live audience

Cross-Browser Compatibility [📌](#)

Diagram



○ PRIORITY

MUST

○ CATEGORY

Compatibility

○ QUALIFIES

● **REQUIREMENT: Browser Access** [📌](#)

○ PREMISES

● **PREMISE: Attendee Networks Pass WebSocket Traffic** [📌](#)

○ METRIC

the last 2 major versions of Chrome, Edge, Firefox, and Safari

Description

The system **MUST** run in any reasonably recent version of the major web browsers (Chrome, Edge, Firefox,

● REQUIREMENT	Properties & Description	
		Safari) without plugins — BECAUSE attendees use heterogeneous managed and unmanaged devices
GDPR Compliance ⚓	Diagram	
	○ PRIORITY MUST	○ CATEGORY Compliance
	○ PREMISES ● PREMISE: EU Hosting on Self-Operated Infrastructure ⓘ, ● PREMISE: Message Texts Contain Personal Data ⓘ	○ QUALIFIES ● REQUIREMENT: GDPR-Compliant EU Processing ⓘ
	○ METRIC 100 % of personal data processed and hosted within the EU	Description The system MUST process all personal data in compliance with GDPR and host it exclusively within the EU (data center in Nürnberg, Germany) — BECAUSE the operator is legally bound to European data-protection requirements
Privacy by Design ⚓	Diagram	
	○ PRIORITY MUST	○ CATEGORY Security
	○ PREMISES ● PREMISE: Message Texts Contain Personal Data ⓘ	○ QUALIFIES ∅
	○ METRIC 0 attendee personal-data records retained after the event finish procedure	Description The system MUST retain attendee personal data only while an event runs, anonymizing or deleting all of it within the automated finish procedure when the event finishes — BECAUSE minimizing personal-data retention is the core privacy guarantee of the product

● REQUIREMENT

Unguessable Access Tokens

Properties & Description

Diagram

TACTIC

Email-Verified Access

DECISION

Email one-time token as the authentication factor

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by

addresses

driven-by


addresses

● REQUIREMENT

Event Setup Recovery [⚓](#)

Properties & Description

Diagram



○ PRIORITY

MUST

○ CATEGORY

Reliability

○ QUALIFIES

∅

○ PREMISES

● **PREMISE:** EU Hosting on Self-Operated Infrastructure [Ⓢ](#)

○ METRIC


RPO ≤ 24 hours (≤ 1 hour right before an event) and RTO ≤ 2 hours

Description

The system **MUST** allow the event setups and their messages to be restored after a database loss within 2 hours from a backup at most 24 hours old, and at most 1 hour old right before an event — **BECAUSE** a prepared event must not have to be re-entered under time pressure on the day of the broadcast

Event-Safe Maintenance [⚓](#)

Diagram



○ PRIORITY

MUST

○ CATEGORY

Reliability

○ QUALIFIES

∅

○ PREMISES

∅

○ METRIC


0 rollouts or reconfigurations while an event runs

Description


The system **MUST** be upgraded and reconfigured only while no event runs — **BECAUSE** a live audience cannot be asked to wait for a restart

Live Configuration Latency [⚓](#)

Diagram



● REQUIREMENT	Properties & Description		
	○ PRIORITY SHOULD	○ CATEGORY Performance	○ QUALIFIES ● REQUIREMENT: Live Configuration Propagation Ⓢ
	○ PREMISES ∅	○ METRIC propagation to all connected clients <= 2 seconds	Description The system SHOULD propagate an event configuration change to all connected clients within 2 seconds — BECAUSE operators expect toggles such as enabling chat to take effect near-instantly for the live audience
Per-Event Cost Efficiency ⚓	Diagram		
	<pre>graph LR subgraph Decisions D1[DECISION: Self-host on Hetzner instead of public cloud] D2[DECISION: Embed provider-delivered video instead of self-hosted streaming] D3[DECISION: One modular service process instead of microservices] D4[DECISION: Single-host Docker Compose instead of a cluster orchestrator] D5[DECISION: PostgreSQL as the single self-hosted relational store] D6[DECISION: Logical dumps instead of continuous archiving for backup] end D1 -- driven-by --> R[REQUIREMENT: Per-Event Cost Efficiency] D2 -- driven-by --> R D3 -- driven-by --> R D4 -- driven-by --> R D5 -- driven-by --> R D6 -- driven-by --> R P[PREMISE: EU Hosting on Self-Operated Infrastructure] -- premises --> R</pre>		
	○ PRIORITY SHOULD	○ CATEGORY Constraint	○ QUALIFIES ∅
	○ PREMISES ● PREMISE: EU Hosting on Self-Operated Infrastructure Ⓢ	○ METRIC recurring cost per event below the equivalent Azure or AWS hosting cost	Description The system SHOULD minimize the recurring cost per event by self-hosting on Hetzner infrastructure rather than Azure or AWS, excluding one-off development cost — BECAUSE low operating cost per event is a primary economic justification for building the solution
Interaction Abuse Throttling ⚓	Diagram		
	<pre>graph LR T[TACTIC: Abuse Resistance] -- addresses --> R[REQUIREMENT: Interaction Abuse Throttling] TC[TEST-CASE: Throttled Submission Not Stored] -- verifies --> R R -- qualifies --> R1[REQUIREMENT: Ask Questions] R -- qualifies --> R2[REQUIREMENT: Chat Messages] P[PREMISE: Abusive Interaction from the Audience] -- premises --> R</pre>		

● REQUIREMENT	Properties & Description		
	○ PRIORITY SHOULD	○ CATEGORY Security	○ QUALIFIES ● REQUIREMENT: Chat Messages ⓘ, ● REQUIREMENT: Ask Questions ⓘ
	○ PREMISES ● PREMISE: Abusive Interaction from the Audience ⓘ	○ METRIC <= 10 submissions per user per minute by default, configurable per event	Description The system SHOULD throttle chat and question submissions to a configurable maximum per user per minute — BECAUSE rate limiting prevents denial-of-service abuse of the interaction channels
	Diagram		
Start-Surge Asset Delivery ⓘ			
	○ PRIORITY SHOULD	○ CATEGORY Performance	○ QUALIFIES ● REQUIREMENT: Browser Access ⓘ
	○ PREMISES ● PREMISE: Connection Surge at Event Start ⓘ	○ METRIC client bundle delivered within 3 seconds at 10000 simultaneous joins	Description The system SHOULD deliver the static client bundle to each of 10000 attendees joining within the same minute in at most 3 seconds — BECAUSE the audience arrives in a surge right at the start of the event and must not be held back by the download
	Diagram		
			
Compile-Time Contract Safety ⓘ	○ PRIORITY SHOULD	○ CATEGORY Maintainability	○ QUALIFIES ∅
	○ PREMISES ∅	○ METRIC 100 % of the client/server message contracts type-	Description The system SHOULD catch every mismatch between

● REQUIREMENT	Properties & Description		
		checked at build time	the message contracts of client and server at build time instead of at runtime — BECAUSE a contract slip surfacing only during a live event is the costliest defect the solution can have
Live Diagnosability ⚓	Diagram <pre>graph LR; TO[TACTIC Snapshot Observability] -- addresses --> LD[REQUIREMENT Live Diagnosability]; LSM[CONCERN Live Statistics Monitoring] -- addresses --> LD; AD[CONCERN Authentication Diagnostics] -- addresses --> LD; LD -- qualifies --> GES[REQUIREMENT General Event Statistics]; LD -- qualifies --> DS[REQUIREMENT Debugging Statistics];</pre>		
○ PRIORITY	○ CATEGORY	○ QUALIFIES	
SHOULD	Maintainability	● REQUIREMENT: General Event Statistics ⓘ, ● REQUIREMENT: Debugging Statistics ⓘ	
○ PREMISES	○ METRIC	Description	
∅	event counters at most 5 minutes old, every login failure traceable from token states and log	The system SHOULD let the administrator see the attendee, channel, and authentication-flow counters of a running event with at most 5 minutes delay and trace every login failure from the recorded token states and the log — BECAUSE capacity and access problems must be diagnosed while the audience is still online	
Mobile Usability ⚓	Diagram <pre>graph LR; UBR[TACTIC Universal Browser Reach] -- addresses --> MU[REQUIREMENT Mobile Usability]; VJS[DECISION Vue.js single-page client with headless widgets] -- driven-by --> MU; MU -- qualifies --> MDS[REQUIREMENT Mobile Device Support];</pre>		
○ PRIORITY	○ CATEGORY	○ QUALIFIES	
COULD	Usability	● REQUIREMENT: Mobile Device Support ⓘ	
○ PREMISES	○ METRIC	Description	
∅	attendee screens fully usable at 360 px viewport width in portrait and landscape	The system COULD render the attendee experience responsively for mobile phones in landscape and portrait orientation — BECAUSE a substantial share of attendees join from mobile devices	

08 ● REQS: Domain Rules (DR)

Single Active Session per Event CATEGORY: Constraint SOURCE: Business	Access Requires List or Pattern Match CATEGORY: Constraint SOURCE: Business	Single Active Channel CATEGORY: Constraint SOURCE: Domain	Initial Channel Becomes Active CATEGORY: Derivation SOURCE: Domain
Single Active Resource per Channel CATEGORY: Constraint SOURCE: Domain	Initial Resource Becomes Active CATEGORY: Derivation SOURCE: Domain	Moderation Determines Initial Visibility CATEGORY: Action SOURCE: Business	Moderator Messages Auto-Accepted CATEGORY: Action SOURCE: Business
Forwarded Messages Are Immutable CATEGORY: Constraint SOURCE: Business	State Set Depends on Message Type CATEGORY: Constraint SOURCE: Domain	Sentiment Auto-Decision Threshold CATEGORY: Derivation SOURCE: Business	Anonymization on Event Finish CATEGORY: Action SOURCE: Law
Likes Conserved as Count on Finish CATEGORY: Action SOURCE: Business	Token Format and Validity CATEGORY: Constraint SOURCE: Business	No Permanent User Accounts CATEGORY: Constraint SOURCE: Law	Manager Retained for Export CATEGORY: Constraint SOURCE: Business
Administrator Bypasses the Access List CATEGORY: Constraint SOURCE: Business	Administrator Bootstrapped by Configuration CATEGORY: Constraint SOURCE: Business		

● RULE	Properties & Description			
Single Active Session per Event 	○ CATEGORY Constraint	○ SOURCE Business	○ GOVERNS ● TERM: User  , ● TERM: Session Token  , ● TERM: Event 	○ CONSTRAINS ● REQUIREMENT: Limit Parallel Access 
	○ PREMISES ● PREMISE: Access URLs Forwarded Beyond the Audience 	Description A ● User MUST have at most one active ● Session Token per ● Event at any time; a new login MUST delete any existing ● Session Token and close its connection — BECAUSE concurrent sessions would allow access sharing beyond the invited ● Attendee.		
Access Requires List or Pattern Match 	○ CATEGORY Constraint	○ SOURCE Business	○ GOVERNS ● TERM: User  , ● TERM: Event  , ● TERM: Access List 	○ CONSTRAINS ● REQUIREMENT: User Authentication 
	○ PREMISES ● PREMISE: Access URLs Forwarded Beyond the Audience 	Description A ● User not holding the ● Administrator ● Role (see ● Administrator Bypasses the Access List) MUST be granted access to an ● Event only according to the first matching case: 1. The email of the ● User is on the ● Access List of the ● Event: access is granted. 2. The email of the ● User matches the access email pattern of the ● Event: access is granted. 3. The ● Event allows anonymous access: access is granted. Otherwise the ● User MUST NOT be granted access		

● RULE	Properties & Description			
Single Active Channel ⚓		— BECAUSE access must be limited to the audience the organizer intends.		
	○ CATEGORY Constraint	○ SOURCE Domain	○ GOVERNS ● TERM: Channel ⌘ , ● TERM: Event ⌘	○ CONSTRAINS ● REQUIREMENT: Live Provider Switching ⌘
	○ PREMISES	Description		
	∅	Exactly one ● Channel of an ● Event MUST be active at any time once the ● Event has at least one ● Channel , so the active ● Channel MUST NOT be deactivated directly and MUST NOT be deleted while another ● Channel of the ● Event exists — BECAUSE ● Attendees follow one logical content stream that defines the current ● Event feed.		
Initial Channel Becomes Active ⚓	○ CATEGORY Derivation	○ SOURCE Domain	○ GOVERNS ● TERM: Channel ⌘ , ● TERM: Event ⌘	○ CONSTRAINS ● REQUIREMENT: Live Provider Switching ⌘
	○ PREMISES	Description		
	∅	A ● Channel created for an ● Event without an active ● Channel MUST become the active ● Channel of the ● Event — BECAUSE ● Single Active Channel has to hold from the first ● Channel on, without a ● Manager having to activate it.		
Single Active Resource per Channel ⚓	○ CATEGORY Constraint	○ SOURCE Domain	○ GOVERNS ● TERM: Resource ⌘ , ● TERM: Channel ⌘ , ● TERM: Streaming Provider ⌘	○ CONSTRAINS ● REQUIREMENT: Live Provider Switching ⌘ , ● REQUIREMENT: Multiple Streaming Providers ⌘
	○ PREMISES	Description		
	∅	Exactly one ● Resource of a ● Channel MUST be active at any time once the ● Channel has at least one ● Resource , so the active ● Resource MUST NOT be deactivated directly and MUST NOT be deleted while another ● Resource of the ● Channel exists — BECAUSE switching the active ● Resource is the mechanism by which the live ● Streaming Provider is changed.		
Initial Resource Becomes Active ⚓	○ CATEGORY Derivation	○ SOURCE Domain	○ GOVERNS ● TERM: Resource ⌘ , ● TERM: Channel ⌘	○ CONSTRAINS ● REQUIREMENT: Live Provider Switching ⌘ , ● REQUIREMENT: Multiple Streaming Providers ⌘
	○ PREMISES	Description		
	∅	A ● Resource created for a ● Channel without an active ● Resource MUST become the active ● Resource of the ● Channel — BECAUSE ● Single Active Resource per Channel has to hold from the first ● Resource on, without a ● Manager having to activate it.		
Moderation Determines Initial Visibility ⚓	○ CATEGORY Action	○ SOURCE Business	○ GOVERNS ● TERM: Message ⌘ , ● TERM: Chat ⌘ , ● TERM:	○ CONSTRAINS ● REQUIREMENT: Moderate Chat and Questions ⌘ ,

● RULE	Properties & Description			
			Question ⓘ, ● TERM: Attendee ⓘ	● REQUIREMENT: Chat Messages ⓘ, ● REQUIREMENT: Ask Questions ⓘ
	○ PREMISES	Description		
	● PREMISE: Abusive Interaction from the Audience ⓘ	When moderation is enabled for ● Chats or ● Questions, a ● Message of that type sent by an ● Attendee MUST stay in state pending and become visible only once accepted; when disabled, it MUST be accepted at once upon creation — BECAUSE organizers must control what the audience sees.		
Moderator Messages Auto-Accepted ⓘ	○ CATEGORY	○ SOURCE	○ GOVERNS	○ CONSTRAINS
	Action	Business	● TERM: Message ⓘ, ● TERM: Moderator ⓘ	● REQUIREMENT: Moderator-Authored Messages ⓘ
	○ PREMISES	Description		
	∅	A ● Message authored by a ● Moderator MUST be accepted at once upon creation and carry the sender name “Moderator” unless overridden — BECAUSE ● Moderator-authored content is trusted and needs no further approval.		
Forwarded Messages Are Immutable ⓘ	○ CATEGORY	○ SOURCE	○ GOVERNS	○ CONSTRAINS
	Constraint	Business	● TERM: Message ⓘ, ● TERM: Attendee ⓘ, ● TERM: Presenter ⓘ	● REQUIREMENT: Edit and Delete Messages ⓘ, ● REQUIREMENT: Forward Inputs to Presenter ⓘ
	○ PREMISES	Description		
	∅	Once a ● Message reaches state forwarded, the ● Attendee MUST NOT edit or delete it — BECAUSE the ● Presenter relies on the forwarded content remaining stable for live processing.		
State Set Depends on Message Type ⓘ	○ CATEGORY	○ SOURCE	○ GOVERNS	○ CONSTRAINS
	Constraint	Domain	● TERM: Message ⓘ, ● TERM: Question ⓘ, ● TERM: Chat ⓘ, ● TERM: Support ⓘ	● REQUIREMENT: Moderate Chat and Questions ⓘ
	○ PREMISES	Description		
	∅	A ● Message MUST use only the states its type permits: 1. The ● Message is a ● Question: pending, accepted, rejected, forwarded, answered, and suspended. 2. The ● Message is a ● Chat: pending, accepted, and rejected. 3. The ● Message is a ● Support message: accepted. No other combination of ● Message type and state is permitted — BECAUSE each ● Message type has a different interaction lifecycle.		
Sentiment Auto-Decision Threshold ⓘ	○ CATEGORY	○ SOURCE	○ GOVERNS	○ CONSTRAINS
	Derivation	Business	● TERM: Sentiment Analysis ⓘ, ● TERM: Message ⓘ	● REQUIREMENT: Server-Side Sentiment Analysis ⓘ


● RULE	Properties & Description			
Anonymization on Event Finish ⚓	○ PREMISES	Description		
	○	When server-side ● Sentiment Analysis is enabled, a sentiment score of a ● Message below -0.1 MUST be treated as improper and a score at or above it as proper for auto-accept and auto-reject decisions — BECAUSE a defined threshold makes automated moderation predictable.		
	○ CATEGORY	○ SOURCE	○ GOVERNS	○ CONSTRAINS
Likes Conserved as Count on Finish ⚓	Action	Law	● TERM: Anonymization ⌘ , ● TERM: Event ⌘ , ● TERM: Message ⌘ , ● TERM: Chat ⌘ , ● TERM: Question ⌘ , ● TERM: Like ⌘ , ● TERM: Authorization Token ⌘ , ● TERM: Session Token ⌘ , ● TERM: Access List ⌘ , ● TERM: User ⌘ , ● TERM: Role ⌘ , ● TERM: Moderator ⌘ , ● TERM: Manager ⌘	● REQUIREMENT: Explicit User Consent ⌘ , ● REQUIREMENT: GDPR-Compliant EU Processing ⌘ , ● REQUIREMENT: User Statistics ⌘
	○ PREMISES	Description		
	● PREMISE: Message Texts Contain Personal Data ⌘	When an ● Event finishes, its ● Anonymization MUST reduce its ● Messages to a bare ● Like count with ● Chat and ● Question sender names set to “Anonymous” and liker and sender relations dropped, delete its ● Authorization Tokens and ● Session Tokens, clear its ● Access List and delete the referenced ● Users while retaining their viewer statistics unlinked from any ● User, and delete its ● Moderator ● Roles while retaining its ● Manager ● Roles — BECAUSE personal data must not be retained beyond the ● Event (GDPR Art. 5(1)(e), storage limitation).		
Token Format and Validity ⚓	○ CATEGORY	○ SOURCE	○ GOVERNS	○ CONSTRAINS
	Action	Business	● TERM: Like ⌘ , ● TERM: Message ⌘ , ● TERM: Event ⌘ , ● TERM: Anonymization ⌘	● REQUIREMENT: Like Messages ⌘ , ● REQUIREMENT: Export Attendee Inputs ⌘
	○ PREMISES	Description		
	○	When an ● Event finishes, the number of ● Likes of each ● Message MUST be computed and stored as its bare ● Like count before the liker relations are removed — BECAUSE ● Like totals must survive the ● Anonymization for the exported record.		
	○ CATEGORY	○ SOURCE	○ GOVERNS	○ CONSTRAINS
	Constraint	Business	● TERM: Authorization Token ⌘ , ● TERM: Event ⌘ , ● TERM: Event Registration System ⌘	● REQUIREMENT: Return Access URLs to Registration ⌘ , ● REQUIREMENT: Automatic Event Access URL ⌘

● RULE	Properties & Description			
No Permanent User Accounts ⚓	○ PREMISES ● PREMISE: Attendees Read Their Email While Logging In ⌘ , ● PREMISE: Email Gateway Delivers Tokens Within Minutes ⌘	Description An ● Authorization Token MUST be formatted as six digits “NNN-NNN”; a normal login token MUST expire within 5 minutes while a token pre-generated for the ● Event Registration System lasts until the ● Event ends, expiring on first use only if the ● Event so configures — BECAUSE token strength and lifetime balance security against convenient automated access.		
	○ CATEGORY Constraint	○ SOURCE Law	○ GOVERNS ● TERM: User ⌘ , ● TERM: Role ⌘ , ● TERM: Administrator ⌘ , ● TERM: Event ⌘ , ● TERM: Access List ⌘	○ CONSTRAINS ∅
Manager Retained for Export ⚓	○ PREMISES ∅	Description A ● User MUST NOT exist as a permanent account, except the holder of the ● Administrator ● Role bootstrapped from the configuration: any other ● User exists only while granted a ● Role , present on the ● Access List of an ● Event , or joining via a matching access email pattern — BECAUSE privacy by design (GDPR Art. 25) forbids persistent personal data beyond operational need.		
	○ CATEGORY Constraint	○ SOURCE Business	○ GOVERNS ● TERM: Role ⌘ , ● TERM: Manager ⌘ , ● TERM: Event ⌘ , ● TERM: Anonymization ⌘	○ CONSTRAINS ● REQUIREMENT: Export Attendee Inputs ⌘
Administrator Bypasses the Access List ⚓	○ PREMISES ∅	Description A ● Manager ● Role MUST be retained after an ● Event finishes until the ● Event is deleted entirely — BECAUSE ● Managers must still export the ● Event data left by the ● Anonymization .		
	○ CATEGORY Constraint	○ SOURCE Business	○ GOVERNS ● TERM: Administrator ⌘ , ● TERM: User ⌘ , ● TERM: Event ⌘ , ● TERM: Access List ⌘	○ CONSTRAINS ● REQUIREMENT: User Authentication ⌘
Administrator Bootstrapped by Configuration ⚓	○ PREMISES ∅	Description A ● User holding the ● Administrator ● Role MUST be granted access to every ● Event through the ordinary login challenge of the configured email address, without an ● Access List entry, an access email pattern match, or anonymous access — BECAUSE the ● Administrator exists before any ● Event and hence cannot be enrolled on its ● Access List .		
	○ CATEGORY Constraint	○ SOURCE Business	○ GOVERNS ● TERM: Administrator ⌘ , ● TERM: Role ⌘	○ CONSTRAINS ∅

● RULE	Properties & Description	
	○ PREMISES	Description
	∅	An ● Administrator ● Role MUST be granted and revoked through the software configuration only, never through the solution itself — BECAUSE the ● Administrator is the bootstrap identity from which every ● Event and ● Manager originates and hence cannot depend on a grant inside the solution.

09 ● REQS: Domain Workflows (DW) ⚓

09.01 ● WORKFLOW: Run Broadcast Event ⚓



○ ACTORS	● ROLE: Manager ⓘ, ● ROLE: Presenter ⓘ, ● ROLE: Moderator ⓘ, ● ROLE: Attendee ⓘ
○ TRIGGER	The manager receives the attendee list of an upcoming event, exported by the Event Registration System.
○ OUTCOME	The event took place, its personal data is anonymized, and its interaction results are exported.
○ JOURNEYS	● JOURNEY: Attend a Broadcast event ⓘ, ● JOURNEY: Operate a Broadcast Event ⓘ, ● JOURNEY: Moderate a Broadcast Event ⓘ
○ TERMS	● TERM: Anonymization ⓘ
○ RULES	● RULE: No Permanent User Accounts ⓘ

The manager prepares and populates the event, the operators rehearse it, the audience attends it live while the moderators and the presenter handle the interaction, and the manager finishes and archives it afterwards — **BECAUSE** a broadcast event is a collaboration of several roles across days, of which each sitting with the solution covers only a part.


● ACTIVITY	○ ACTOR	○ INITIAL	○ FINAL	Description
Plan Event ⚓	● ROLE: Manager ⓘ	true	∅	The manager configures the event and its channel and imports the attendee list of the Event Registration System, which yields the individual access URLs


● ACTIVITY	○ ACTOR	○ INITIAL	○ FINAL	Description
Invite Attendees ⚓	● ROLE: Manager ②	∅	∅	The manager hands the individual access URLs back to the Event Registration System, which sends the invitation emails (outside the solution)
Rehearse Event ⚓	● ROLE: Presenter ②, ● ROLE: Moderator ②	∅	∅	The presenter and the moderators walk through the unpublished event together, checking the stream, the question flow, and the chat
Start Event ⚓	● ROLE: Manager ②	∅	∅	The manager publishes and starts the event when the stream goes on air and keeps the streaming resource healthy
Attend Event ⚓	● ROLE: Attendee ②	∅	∅	The attendees join via their individual URLs, watch the stream, and raise questions and chat messages
Moderate Interaction ⚓	● ROLE: Moderator ②	∅	∅	The moderators accept, reject, answer, and forward the incoming messages throughout the live event
Present and Answer ⚓	● ROLE: Presenter ②	∅	∅	The presenter delivers the talk and answers the forwarded questions on air
Finish Event ⚓	● ROLE: Manager ②	∅	∅	The manager finishes the event once the stream is off air, which closes the access and anonymizes the personal data
Archive Results ⚓	● ROLE: Manager ②	∅	true	The manager exports the anonymized messages and statistics and hands them over to the organizer

● HANDOFF	○ FROM	○ TO	○ CONDITION	○ RULES	Description
import ⚓	● ACTIVITY: Plan Event ②	● ACTIVITY: Invite Attendees ②	∅	∅	The generated individual access URLs are returned as a sheet the manager passes on to the Event Registration System
notify ⚓	● ACTIVITY: Invite Attendees ②	● ACTIVITY: Rehearse Event ②	∅	∅	The presenter and the moderators receive their access URLs and the rehearsal date by email
rework ⚓	● ACTIVITY: Rehearse Event ②	● ACTIVITY: Plan Event ②	The rehearsal revealed a defect in the event configuration.	∅	The presenter reports the defect to the manager, who corrects the configuration before a further rehearsal
approve ⚓	● ACTIVITY: Rehearse Event ②	● ACTIVITY: Start Event ②	The rehearsal passed.	∅	The presenter confirms the readiness of the event to the manager
admit ⚓	● ACTIVITY: Start Event ②	● ACTIVITY: Attend Event ②	∅	∅	The started event admits the invited attendees through their individual URLs
staff ⚓	● ACTIVITY: Start Event ②	● ACTIVITY: Moderate Interaction ②	∅	∅	The started event opens the moderation views to the moderators

● HANDOFF	○ FROM	○ TO	○ CONDITION	○ RULES	Description
cue 	● ACTIVITY: Start Event 	● ACTIVITY: Present and Answer 	∅	∅	The manager cues the presenter once the stream is on air
forward 	● ACTIVITY: Moderate Interaction 	● ACTIVITY: Present and Answer 	∅	● RULE: Forwarded Messages Are Immutable 	The moderator forwards an accepted question, which appears in the presenter's view
disperse 	● ACTIVITY: Attend Event 	● ACTIVITY: Finish Event 	∅	∅	The audience leaves when the stream ends, which the manager sees in the attendance statistics
wrap 	● ACTIVITY: Moderate Interaction 	● ACTIVITY: Finish Event 	∅	∅	The moderators report the interaction as settled to the manager
sign-off 	● ACTIVITY: Present and Answer 	● ACTIVITY: Finish Event 	∅	∅	The presenter signs off and the stream goes off air
hand-over 	● ACTIVITY: Finish Event 	● ACTIVITY: Archive Results 	∅	● RULE: Anonymization on Event Finish  , ● RULE: Manager Retained for Export 	The finished event keeps the anonymized data and the manager role for the export

10 ● REQS: Use Cases (UC)




10.01 ● **USE-CASE: Join Event and Watch Stream** 

○ ACTOR	● ROLE: Attendee 
○ JOURNEYS	● STEP: Open event page and review login info  , ● STEP: Watch stream and interact 
○ ACTIVITIES	● ACTIVITY: Attend Event 
○ REQUIREMENTS	● REQUIREMENT: Individual Event Access URL  , ● REQUIREMENT: User Authentication  , ● REQUIREMENT: Browser Access  , ● REQUIREMENT: Direct Resource Access URL  , ● REQUIREMENT: Mobile Device Support  , ● REQUIREMENT: In-Session Language Switching  , ● REQUIREMENT: Light and Dark Theme 
○ INCLUDES	● USE-CASE: Authenticate via Email Token 
○ PRE-CONDITION	The attendee holds an event URL and their email is granted access.
○ TRIGGER	The attendee opens the individual event URL received by invitation.
○ POST-CONDITION	The attendee holds an active session token and sees the stream.

The attendee opens the individual event URL in a web browser, on a desktop or a mobile phone, authenticates via their email, and is admitted to the live stream of the event, adjusting language and theme to their liking — **BECAUSE** watching the live stream is the very reason the attendee was invited.

● SCENARIO	Properties & Description		
Join via Individual URL 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Main	∅	∅
	○ OUTCOME	Description	
	∅	1. The attendee opens the individual event URL in any recent web browser, without installing software. 2. The attendee authenticates (● Authenticate via Email Token). 3. The system grants the attendee access to the live video stream.	
Return via Direct Resource URL 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	1

● SCENARIO	Properties & Description		
	○ OUTCOME The attendee sees the resource the URL names instead of the default stream of the event.	Description 1. The attendee opens an event URL carrying a resource parameter, typically by reloading the page. 2. The attendee authenticates (● Authenticate via Email Token), unless a session is still active. 3. The system grants access and selects the named stream or static resource of the event.	
Join on a Mobile Phone 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	1
	○ OUTCOME The attendee watches the stream on the phone, with the interaction possibly restricted.	Description 1. The attendee opens the individual event URL in the browser of a mobile phone. 2. The attendee authenticates (● Authenticate via Email Token). 3. The system grants access to the live video stream in a layout fitting the phone screen in portrait or landscape orientation.	
Switch the Language 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	3
	○ OUTCOME The attendee sees the interface and the translated messages in the chosen language.	Description 3. The system grants the attendee access to the live video stream in the default language. 4. The attendee switches the language between German and English in the header. 5. The system applies the language immediately to the interface and the translated messages.	
Toggle the Theme 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	3
	○ OUTCOME The attendee sees the interface in the chosen light or dark theme.	Description 3. The system grants the attendee access to the live video stream in the default theme. 4. The attendee toggles between the light and the dark theme in the header. 5. The system applies the theme immediately across the whole interface.	

10.02 ● **USE-CASE: Authenticate via Email Token** ⚓


○ ACTOR	● ROLE: Attendee ⓘ
○ JOURNEYS	● STEP: Authenticate via email token ⓘ
○ ACTIVITIES	● ACTIVITY: Attend Event ⓘ
○ REQUIREMENTS	● REQUIREMENT: User Authentication ⓘ, ● REQUIREMENT: Explicit User Consent ⓘ, ● REQUIREMENT: Limit Parallel Access ⓘ, ● REQUIREMENT: Personalized Event Access URL ⓘ, ● REQUIREMENT: Automatic Event Access URL ⓘ, ● REQUIREMENT: Login and Interaction Messages ⓘ, ● REQUIREMENT: GDPR-Compliant EU Processing ⓘ
○ RULES	● RULE: Access Requires List or Pattern Match ⓘ, ● RULE: Single Active Session per Event ⓘ, ● RULE: Token Format and Validity ⓘ
○ PRE-CONDITION	The attendee's email is granted access to the event.
○ TRIGGER	The attendee requests access to an event without holding an active session.
○ POST-CONDITION	The attendee holds an active session token and any prior session of the same user is closed.

The attendee proves control of their email via a one-time token, accepts any required consent, and receives a session while any prior session for the same user is closed; this flow is included by every use case requiring an authenticated attendee — **BECAUSE** only a proven identity entitles the attendee to the event they were invited to.

● SCENARIO	Properties & Description		
Login with Emailed Token ⚓	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Main	∅	∅
	○ OUTCOME	Description	
	∅	1. The system asks for the email address and presents the optional login message with its links. 2. The attendee enters their email address. 3. The system sends a six-digit authorization token to that email. 4. The attendee enters the received token. 5. The system validates the token and any consent the event requires for GDPR-compliant participation. 6. The system issues a session token and closes any prior session of the user.	
Email Pre-Filled from URL ⚓	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Resume	2

● SCENARIO	Properties & Description		
Automatic Token in URL ⚓	○ OUTCOME The email address is fixed by the personalized event URL, and the flow resumes at step 3.	Description 2. The system finds the email address embedded in the event URL and presents it read-only instead of asking for it.	
	○ TYPE Alternative	○ RESULT Success	○ AT-MAIN-STEP 1
Email Not Authorized ⚓	○ OUTCOME The attendee holds an active session token, obtained without entering email or token.	Description 1. The system finds the email and a pre-generated token embedded in the event URL. 2. The system validates the embedded token against the event settings. 3. The system issues a session token without asking for the email address.	
	○ TYPE Exceptional	○ RESULT Resume	○ AT-MAIN-STEP 3
Email Not Authorized ⚓	○ OUTCOME No session exists and no token was sent, and the attendee may retry with another email address (resumes at step 1).	Description 3. The system finds the email neither on the access list nor matching the access pattern. 4. The system denies access and informs the attendee that they are not authorized.	
	○ TYPE Exceptional	○ RESULT Resume	○ AT-MAIN-STEP 3

10.03 ● USE-CASE: Ask a Question [⚓](#)



○ ACTOR	● ROLE: Attendee Ⓜ
○ JOURNEYS	● STEP: Watch stream and interact Ⓜ
○ ACTIVITIES	● ACTIVITY: Attend Event Ⓜ
○ REQUIREMENTS	● REQUIREMENT: Ask Questions Ⓜ , ● REQUIREMENT: Tag Question Messages Ⓜ , ● REQUIREMENT: Moderate Chat and Questions Ⓜ , ● REQUIREMENT: Server-Side Sentiment Analysis Ⓜ , ● REQUIREMENT: Client-Side Sentiment Analysis Ⓜ


○ RULES	● RULE: Moderation Determines Initial Visibility ⓘ, ● RULE: State Set Depends on Message Type ⓘ, ● RULE: Sentiment Auto-Decision Threshold ⓘ
○ PRE-CONDITION	The attendee has an active session and questions are enabled.
○ TRIGGER	The attendee decides to raise a question during the running event.
○ POST-CONDITION	The question is stored in state pending and awaits moderation.

The attendee writes a question, optionally tags it, and submits it; the system stores it and routes it through moderation if the event requires approval before it becomes visible — **BECAUSE** getting their own question answered turns the attendee from a passive viewer into a participant.

● SCENARIO	Properties & Description		
Submit Moderated Question ⓘ	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Main	∅	∅
	○ OUTCOME	Description	
	∅	1. The attendee starts a new question. 2. The attendee writes the question and optionally assigns predefined tags. 3. The attendee submits the question. 4. The system stores the question in state pending. 5. The system shows the question to moderators for approval.	
Auto-Accepted by Sentiment ⓘ	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	4
	○ OUTCOME	Description	
	The question is stored in state accepted and visible to the audience without moderation.	4. The system runs server-side sentiment analysis on the text. 5. The system finds the sentiment proper and auto-accept is enabled. 6. The system stores the question in state pending and accepts it at once, without a moderator decision.	
Auto-Rejected by Sentiment ⓘ	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Exceptional	Failure	4
	○ OUTCOME	Description	
	The question is stored in state rejected and hidden from the audience, without a moderator decision.	4. The system runs server-side sentiment analysis on the text. 5. The system finds the sentiment improper and auto-reject is enabled. 6. The system stores the question in state pending and rejects it at once, informing the attendee.	
Throttled Submission ⓘ	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Exceptional	Failure	4
	○ OUTCOME	Description	
	The question is not stored, and the attendee may submit it again once the limit window has passed.	4. The system detects that the attendee exceeded the per-minute submission limit. 5. The system rejects the new submission and informs the attendee to wait.	
Held Back by Client-Side Check ⓘ	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Exceptional	Resume	3

SCENARIO	Properties & Description
	OUTCOME The question was not sent, and the attendee may revise its wording (resumes at step 2).
	Description 3. The system runs the client-side sentiment analysis on the text before sending it. 4. The system finds the sentiment improper and prevents the submission, informing the attendee.

10.04 ● USE-CASE: Chat During the Event [📌](#)




○ ACTOR	● ROLE: Attendee 🔗
○ JOURNEYS	● STEP: Watch stream and interact 🔗
○ ACTIVITIES	● ACTIVITY: Attend Event 🔗
○ REQUIREMENTS	● REQUIREMENT: Chat Messages 🔗 , ● REQUIREMENT: Like Messages 🔗 , ● REQUIREMENT: Reply to Chat Messages 🔗 , ● REQUIREMENT: Edit and Delete Messages 🔗 , ● REQUIREMENT: Deleted Message Placeholder 🔗 , ● REQUIREMENT: Personal Display Filtering 🔗 , ● REQUIREMENT: Configurable Name Appearance 🔗 , ● REQUIREMENT: Multiple-Choice Feedback 🔗
○ RULES	● RULE: Moderation Determines Initial Visibility 🔗 , ● RULE: State Set Depends on Message Type 🔗 , ● RULE: Forwarded Messages Are Immutable 🔗
○ PRE-CONDITION	The attendee has an active session and chat is enabled for the event.
○ TRIGGER	The attendee wants to comment on the running event.
○ POST-CONDITION	The chat message is stored in the state the moderation setting determines and shown under the attendee's configured name appearance.

The attendee comments on the running event through chat messages, likes, replies, and poll answers, and corrects or removes their own contributions afterwards — **BECAUSE** live commentary turns the audience from silent viewers into an engaged community.

● SCENARIO	Properties & Description		
Post a Chat Message 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Main	∅	∅
	○ OUTCOME	Description	
	∅	1. The attendee writes a chat message. 2. The attendee sends the message. 3. The system stores the message in state pending and accepts it at once, unless the event moderates chat messages and hence holds it for the moderator decision. 4. The system shows the message in the stream under the sender name in the form the event configures (full name, first name, or anonymous), exposing the email address on hover.	
Pending Message Stays Private 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	4
	○ OUTCOME	Description	
	The message is visible to its sender only until a moderator accepts it.	4. The system shows the pending message to its sender only, marked as awaiting the moderation decision. 5. The system shows the message to the other attendees once a moderator has accepted it.	
Like a Message 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	1
	○ OUTCOME	Description	
	The like count of the message reflects the current choice of the attendee.	1. The attendee likes a visible chat message or question of another attendee. 2. The system records the like and raises the like count of the message. 3. The attendee optionally undoes the like, and the system lowers the count again.	
Reply to a Chat Message 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	1
	○ OUTCOME	Description	
	The reply is stored like a chat message and shown threaded below the message it answers.	1. The attendee selects a visible chat message to reply to, replies being enabled for the event. 2. The attendee writes and sends the reply. 3. The system stores the reply like a chat message and shows it threaded below the message it answers.	
Edit an Own Message 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	1
	○ OUTCOME	Description	
	The corrected message is visible and marked as edited, moderated again where the event requires it.	1. The attendee opens one of their own chat messages or questions for editing. 2. The attendee changes the text and saves it. 3. The system marks the message as edited for the other readers. 4. The system resubmits the edited message to the moderation where the event requires it, hiding it from the audience until it is accepted anew.	

● SCENARIO	Properties & Description		
Delete an Own Message 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	1
	○ OUTCOME	Description	
	The message text is gone while its position in the stream is kept by a placeholder.	1. The attendee deletes one of their own chat messages or questions. 2. The system retains the position of the message in the stream and shows a “This message was deleted” placeholder instead of its text.	
Forwarded Question Locked 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Exceptional	Failure	1
	○ OUTCOME	Description	
	The forwarded question remains unchanged and the attendee is informed why.	1. The attendee tries to edit or delete one of their own questions which a moderator has already forwarded to the presenter. 2. The system refuses the change and informs the attendee that a forwarded question is immutable.	
Show Own Contributions Only 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	4
	○ OUTCOME	Description	
	The attendee sees only their own messages and questions until they choose to see those of the others again.	4. The attendee chooses to see only their own messages and questions. 5. The system hides the messages and questions of the other attendees from the view of the attendee.	
Answer a Multiple-Choice Poll 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	1
	○ OUTCOME	Description	
	The answer of the attendee is counted in the live result of the poll.	1. The system presents a multiple-choice question raised during the event. 2. The attendee picks one of the offered choices. 3. The system records the answer and updates the live result of the poll.	

10.05 ● **USE-CASE: Moderate and Forward Messages** 


○ ACTOR	● ROLE: Moderator 
○ PERSONAS	● PERSONA: Peter 
○ JOURNEYS	● STEP: Moderate and support the presenter 
○ ACTIVITIES	● ACTIVITY: Rehearse Event  , ● ACTIVITY: Moderate Interaction 
○ REQUIREMENTS	● REQUIREMENT: Moderate Chat and Questions  , ● REQUIREMENT: Forward Inputs to Presenter  , ● REQUIREMENT: Sort and Filter Messages  , ● REQUIREMENT: Presenter Hints and Alerts 
○ RULES	● RULE: State Set Depends on Message Type  , ● RULE: Forwarded Messages Are Immutable  , ● RULE: Anonymization on Event Finish 
○ PRE-CONDITION	The event is running and the moderator has the Moderator role.
○ TRIGGER	An attendee message arrives in state pending for moderation.
○ POST-CONDITION	Messages are accepted, rejected, forwarded with optional hints, or settled on behalf of the presenter.

The moderator reviews the pending messages by state, approves or rejects them, forwards selected approved questions to the presenter in a chosen order, and may attach hints or raise a presenter alert — **BECAUSE** the presenter can only handle a curated, ordered selection of the audience input while on stage.

● SCENARIO	Properties & Description		
Approve and Forward Question 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Main	∅	∅
	○ OUTCOME	Description	
	∅	1. The moderator narrows the messages down to the pending questions. 2. The moderator approves a relevant question, setting it accepted. 3. The moderator forwards the accepted question to the presenter.	

● SCENARIO	Properties & Description		
		4. The moderator optionally attaches a hint for the presenter. 5. The system places the forwarded question in the presenter's work basket and locks it from editing.	
Reject Improper Message ⚓	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	2
	○ OUTCOME	Description	
	The message is in state rejected and hidden from the audience, without reaching the presenter.	2. The moderator rejects an improper message. 3. The system sets the message to rejected and hides it from the audience.	
Settle a Question for the Presenter ⚓	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	4
	○ OUTCOME	Description	
	The forwarded question is marked answered or suspended without the presenter touching it.	4. The moderator marks the forwarded question as answered or suspended on behalf of the presenter, e.g. once the presenter addressed it on stage without marking it. 5. The system records the decision and removes the question from the presenter's work basket.	
Access Lost After Finish ⚓	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Exceptional	Failure	1
	○ OUTCOME	Description	
	The moderator cannot enter the finished event, and no message is moderated anymore.	1. The moderator opens the event after the manager has finished it. 2. The system refuses the access, as the anonymization has deleted the Moderator role of the event.	

10.06 ● USE-CASE: Moderate the Chat Conversation [⚓](#)




○ ACTOR	● ROLE: Moderator Ⓜ
○ PERSONAS	● PERSONA: Markus Ⓜ
○ JOURNEYS	● STEP: Moderate and support the presenter Ⓜ
○ ACTIVITIES	● ACTIVITY: Rehearse Event Ⓜ , ● ACTIVITY: Moderate Interaction Ⓜ
○ REQUIREMENTS	● REQUIREMENT: Answer Attendee Inputs Ⓜ , ● REQUIREMENT: Moderator-Authored Messages Ⓜ , ● REQUIREMENT: Manage Embedded Application Ⓜ

○ RULES	● RULE: Moderator Messages Auto-Accepted ①, ● RULE: Moderation Determines Initial Visibility ①
○ PRE-CONDITION	The event runs with chat enabled and the moderator has the Moderator role.
○ TRIGGER	Attendee chat messages arrive which need an answer, a steer, or a seed from the moderator.
○ POST-CONDITION	Attendees are answered, moderator-authored messages are visible, and the conversation stays on-topic.

The moderator keeps the chat conversation civil and on-topic by answering attendees publicly or privately, seeding the conversation with messages of their own, and controlling an embedded application — **BECAUSE** an unattended chat drowns in spam and off-topic noise.


● SCENARIO	Properties & Description		
Answer an Attendee Directly 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Main	∅	∅
	○ OUTCOME	Description	
	∅	1. The moderator reviews the incoming chat messages. 2. The moderator selects a chat message which needs a clarification or support. 3. The moderator writes a reply to the attendee. 4. The moderator chooses whether the reply is visible to all or a direct message to the attendee only. 5. The system stores the reply in state pending, accepts it at once as a moderator-authored message, and delivers it accordingly.	
Seed the Conversation as Moderator 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	1
	○ OUTCOME	Description	
	The moderator-authored message is visible to the audience under the chosen sender name.	1. The moderator authors a chat message or a question for the audience, e.g. to seed a Q&A round. 2. The moderator keeps the sender name “Moderator” or overrides it for this message. 3. The system stores the message in state pending, accepts it at once as a moderator-authored message, and shows it to the audience.	
Administer the Embedded Application 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	1
	○ OUTCOME	Description	
	The embedded application is controlled by the moderator while the event continues.	1. The moderator opens the administration view an embedded third-party application exposes. 2. The moderator controls the application from this view. 3. The system passes the control on to the application without interrupting the stream.	

10.07 ● **USE-CASE: Steer the Presenter** 

○ ACTOR	● ROLE: Moderator 
○ PERSONAS	● PERSONA: Peter 
○ JOURNEYS	● STEP: Moderate and support the presenter 
○ ACTIVITIES	● ACTIVITY: Moderate Interaction 
○ REQUIREMENTS	● REQUIREMENT: Presenter Hints and Alerts  , ● REQUIREMENT: Live Configuration Propagation 
○ PRE-CONDITION	The event is running and the moderator has the Moderator role.
○ TRIGGER	The presenter needs timing or routing guidance during the live event.
○ POST-CONDITION	The presenter alert is raised or the active agenda point is advanced, and the presenter sees it.

The moderator raises a textual alert on the stage view of the presenter and advances the active agenda point of the event — **BECAUSE** the presenter on stage cannot watch the clock and the audience input at the same time.

● SCENARIO	Properties & Description		
Raise a Presenter Alert 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Main	∅	∅
	○ OUTCOME	Description	
	∅	1. The moderator writes an alert for the presenter, e.g. a timing hint. 2. The moderator raises the alert. 3. The system shows the alert on the stage view of the presenter until the presenter confirms it.	
Advance the Agenda 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	1
	○ OUTCOME	Description	
	The next agenda point is the active one of the event.	1. The moderator marks the next agenda point as the active one. 2. The system propagates the active agenda point to the presenter and the attendees.	

10.08 ● **USE-CASE: Configure the Event** 


○ ACTOR	● ROLE: Manager 
○ JOURNEYS	● STEP: Configure and run the event 
○ ACTIVITIES	● ACTIVITY: Plan Event 
○ REQUIREMENTS	● REQUIREMENT: Multiple Streaming Providers  , ● REQUIREMENT: Configurable Name Appearance  , ● REQUIREMENT: Tag Question Messages  , ● REQUIREMENT: Login and Interaction Messages  , ● REQUIREMENT: Live Configuration Propagation  , ● REQUIREMENT: Import and Export Event 
○ RULES	● RULE: Single Active Channel  , ● RULE: Single Active Resource per Channel  , ● RULE: No Permanent User Accounts  , ● RULE: Manager Retained for Export 
○ PRE-CONDITION	The event is provisioned by the administrator and the manager holds its Manager role.
○ TRIGGER	The manager receives the Manager role of an upcoming event.
○ POST-CONDITION	The event carries its channels, agenda, tags, roles, access list, and interaction settings, ready for the rehearsal.

The manager lays out the channels and their fallback resources, curates the agenda and the question tags, grants the Moderator and Presenter roles, maintains the access list, and sets the interaction options of the event — **BECAUSE** a broadcast event needs its stage, its staff, and its audience set up before anyone can rehearse it.

● SCENARIO	Properties & Description		
Lay Out the Channels 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Main	∅	∅
	○ OUTCOME	Description	
	∅	1. The manager opens the configuration of the event. 2. The manager defines the channels of the event and marks one of them as active. 3. The manager selects the active resource of each channel among its provisioned streaming resources. 4. The manager sets the interaction options, the name appearance, and the login and interaction messages of the event. 5. The system validates the settings and propagates them to the connected clients.	

● SCENARIO	Properties & Description		
Curate the Agenda ⚓	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	2
	○ OUTCOME	Description	
	The event carries an ordered agenda the moderator advances during the live event.	2. The manager defines the ordered agenda points of the event and the tags corresponding to them. 3. The system stores the agenda for the presenter and the moderators.	
Curate the Tags ⚓	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	2
	○ OUTCOME	Description	
	The event carries a tag vocabulary for the questions, partly reserved for the moderators.	2. The manager defines the tag vocabulary of the questions, reserving some tags for the moderators. 3. The system offers the public tags to the attendees and every tag to the moderators.	
Grant the Event Roles ⚓	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	2
	○ OUTCOME	Description	
	The moderators and the presenter can enter the unpublished event for the rehearsal.	2. The manager grants the Attendee, Moderator, and Presenter roles to the users of the event by email address, or revokes them again. 3. The system creates the users of the roles without permanent accounts and admits them to the unpublished event.	
Maintain the Access List ⚓	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	2
	○ OUTCOME	Description	
	The access list names exactly the invited attendees.	2. The manager adds attendees to the access list by email address, or removes them again. 3. The system deletes a removed user without any role entirely.	
Delete the Event ⚓	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	2
	○ OUTCOME	Description	
	The event no longer exists.	2. The manager deletes the event entirely. 3. The system deletes the event with its messages, statistics, and remaining Manager roles.	

10.09 ● **USE-CASE: Switch Streaming Provider** ⚓




○ ACTOR	● ROLE: Manager ⓘ
○ JOURNEYS	● STEP: Configure and run the event ⓘ
○ ACTIVITIES	● ACTIVITY: Start Event ⓘ
○ REQUIREMENTS	● REQUIREMENT: Multiple Streaming Providers ⓘ, ● REQUIREMENT: Live Provider Switching ⓘ, ● REQUIREMENT: Live Configuration Propagation ⓘ
○ RULES	● RULE: Single Active Channel ⓘ, ● RULE: Single Active Resource per Channel ⓘ
○ PRE-CONDITION	The event runs and the channel has multiple configured resources.
○ TRIGGER	The active streaming resource shows problems during a running event.
○ POST-CONDITION	A new resource is active and all clients follow it automatically.

When a provider has problems, the manager activates a fallback resource on the channel and the system propagates the change so attendee clients switch streams without any user interaction — **BECAUSE** a live event cannot be paused while a streaming provider recovers.

● SCENARIO	○ TYPE	Description
Live Failover ⚓	Main	1. The manager observes streaming problems with the active resource. 2. The manager activates a different configured resource on the channel. 3. The system marks the new resource active and the old one inactive. 4. The system propagates the change to all connected clients. 5. The attendee clients switch to the new stream without user interaction.

10.10 ● **USE-CASE: Create Event from Registration Import** ⚓




○ ACTOR	● ROLE: Manager ⓘ
---------	--------------------------

○ JOURNEYS	● STEP: Configure and run the event ②
○ ACTIVITIES	● ACTIVITY: Plan Event ②
○ REQUIREMENTS	● REQUIREMENT: Import Registered Attendees ②, ● REQUIREMENT: Return Access URLs to Registration ②, ● REQUIREMENT: Import and Export Event ②
○ RULES	● RULE: Token Format and Validity ②, ● RULE: No Permanent User Accounts ②
○ PRE-CONDITION	The manager has an Excel sheet of the Event Registration System and an event to populate.
○ TRIGGER	The manager receives the Excel sheet of the attendees of an upcoming event, exported by the Event Registration System.
○ POST-CONDITION	The access list and tokens are created and the URL sheet is ready for the manager to hand back to the Event Registration System.

The manager imports the Excel sheet of the Event Registration System to fill the event access list and generate authorization tokens, then exports an Excel sheet of personal access URLs back to the Event Registration System, avoiding duplicate invitations on repeated imports — **BECAUSE** provisioning hundreds of attendees by hand is error-prone and does not scale.

● SCENARIO	○ TYPE	Description
Import and Return URLs ⚓	Main	1. The manager uploads the Excel sheet of the Event Registration System to the event. 2. The system creates access-list users for new emails and skips existing ones. 3. The system generates a “NNN-NNN” authorization token per user in state issued. 4. The system composes each user’s personal access URL with event, user, and token. 5. The system returns an Excel sheet with the URL column filled, which the manager hands back to the Event Registration System.

10.11 ● USE-CASE: Publish, Start, and Finish Event [⚓](#)




○ ACTOR	● ROLE: Manager ②
○ JOURNEYS	● STEP: Configure and run the event ②
○ ACTIVITIES	● ACTIVITY: Start Event ②, ● ACTIVITY: Finish Event ②
○ RULES	● RULE: Anonymization on Event Finish ②
○ PRE-CONDITION	The event is configured and its access list is populated.

○ TRIGGER	The scheduled date of the event approaches.
○ POST-CONDITION	The event is finished, access is closed, and the personal data is anonymized.

The manager publishes the configured event to make it visible to the invited attendees, starts it when the live stream goes on air, and finishes it afterwards — **BECAUSE** the visibility, the live interaction, and the anonymization of an event are deliberate decisions of the manager, not side effects of the clock.

● SCENARIO	Properties & Description		
Publish, Start, and Finish ⚓	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Main	∅	∅
	○ OUTCOME	Description	
	∅	1. The manager publishes the configured event. 2. The system makes the event visible to the invited attendees. 3. The manager starts the event when the live stream goes on air. 4. The system opens the stream and the interaction channels for the attendees. 5. The manager finishes the event after the live stream has ended. 6. The system closes the access and anonymizes the personal data of the event.	
Start Without Publishing ⚓	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Resume	1
	○ OUTCOME	Description	
	The event is running without having been visible to the attendees beforehand, and the flow resumes at step 5.	1. The manager starts the still unpublished event directly. 2. The system opens the stream and the interaction channels for the attendees.	

10.12 ● **USE-CASE:** Export Anonymized Event Data [⚓](#)




○ ACTOR	● ROLE: Manager Ⓜ
○ JOURNEYS	● STEP: Export anonymized results after event Ⓜ
○ ACTIVITIES	● ACTIVITY: Archive Results Ⓜ

○ REQUIREMENTS	● REQUIREMENT: Export Attendee Inputs ④, ● REQUIREMENT: General Event Statistics ④, ● REQUIREMENT: Channel Statistics ④, ● REQUIREMENT: User Statistics ④, ● REQUIREMENT: Debugging Statistics ④, ● REQUIREMENT: Periodic Statistics Snapshots ④
○ RULES	● RULE: Anonymization on Event Finish ④, ● RULE: Likes Conserved as Count on Finish ④, ● RULE: Manager Retained for Export ④
○ PRE-CONDITION	The event has finished and the manager retains the Manager role.
○ TRIGGER	The manager is asked to hand over the recorded interaction of a finished event.
○ POST-CONDITION	An export file of anonymized messages and statistics is produced.

After the event finishes and personal data is anonymized, the manager exports all attendee inputs with timestamps, states, like counts, and texts, together with the event statistics — **BECAUSE** the organizer evaluates the event and answers open questions afterwards from this record.

● SCENARIO	Properties & Description		
Export After Finish ④	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Main	∅	∅
	○ OUTCOME	Description	
	∅	1. The manager selects the finished event. 2. The manager triggers the export of attendee inputs. 3. The system produces a file containing timestamp, state, likes, and text per message. 4. The manager downloads the export file.	
Inspect the Event Statistics ④	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	2
	○ OUTCOME	Description	
	The manager has evaluated the audience size, composition, channel popularity, and authentication flow without producing an export file.	2. The manager opens the statistics of the event instead of triggering the export. 3. The system shows the curve of logged-in attendees over time and the number of viewers per channel. 4. The system shows the recorded viewer statistics by country, browser, device, and viewport. 5. The system shows the login-challenge statistics of issued, sent, and used authorization tokens.	

10.13 ● USE-CASE: Present Forwarded Questions ④




○ ACTOR	● ROLE: Presenter ④
○ ACTIVITIES	● ACTIVITY: Rehearse Event ④, ● ACTIVITY: Present and Answer ④

○ REQUIREMENTS	● REQUIREMENT: Forward Inputs to Presenter ⓘ, ● REQUIREMENT: Presenter Dashboard ⓘ, ● REQUIREMENT: Presenter Hints and Alerts ⓘ
○ RULES	● RULE: Forwarded Messages Are Immutable ⓘ
○ PRE-CONDITION	The event is running and questions have been forwarded.
○ TRIGGER	The moderator forwards a question to the presenter.
○ POST-CONDITION	Processed questions are marked answered or suspended.

The presenter views the forwarded questions in their intended order with any moderator hints, addresses them on stage, and marks each as answered or suspended — **BECAUSE** the presenter needs to keep track of what was already addressed while staying focused on the audience.

● SCENARIO	Properties & Description		
Answer Forwarded Question ⓘ	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Main	∅	∅
	○ OUTCOME	Description	
	∅	1. The presenter views the ordered list of forwarded questions and hints. 2. The presenter addresses a question live on stage. 3. The presenter marks the question as answered. 4. The system records the answered timestamp and removes it from the active basket.	
Suspend a Forwarded Question ⓘ	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Success	2
	○ OUTCOME	Description	
	The question is marked suspended and leaves the active basket without having been addressed on stage.	2. The presenter decides not to address a forwarded question on stage. 3. The presenter marks the question as suspended. 4. The system removes the question from the active basket.	
Forwarded Questions Only ⓘ	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Resume	1
	○ OUTCOME	Description	
	The presenter works on the curated forwarded questions alone, and the flow resumes at step 2.	1. The presenter views the forwarded questions only, while the pending, accepted, and rejected messages of the event stay invisible to them.	
Confirm a Raised Alert ⓘ	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Alternative	Resume	1
	○ OUTCOME	Description	
	The alert is taken off the stage view, and the flow resumes at step 1.	1. The presenter sees an alert a moderator has raised on the stage view. 2. The presenter confirms the alert, which takes it off the stage view.	

10.14 ● **USE-CASE: Administer Any Event** 


○ ACTOR	● ROLE: Administrator 
○ PERSONAS	● PERSONA: Sven 
○ RULES	● RULE: Administrator Bypasses the Access List  , ● RULE: Administrator Bootstrapped by Configuration  , ● RULE: No Permanent User Accounts 
○ PRE-CONDITION	The Administrator role is granted to the email address of the administrator through the configuration.
○ TRIGGER	The administrator opens the URL of an event they are not enrolled in.
○ POST-CONDITION	The event carries the changes of the administrator.

The administrator enters any event without an access list entry and edits every setting, message, and user of it — **BECAUSE** the organizers need a last resort which depends on no event-specific grant when they are locked out or stuck.

● SCENARIO	Properties & Description		
Enter and Edit Any Event 	○ TYPE	○ RESULT	○ AT-MAIN-STEP
	Main	∅	∅
	○ OUTCOME	Description	
	∅	1. The administrator opens the event URL and requests the login challenge for the configured administrator email address. 2. The system issues and sends the one-time token without consulting the access list of the event. 3. The administrator returns the token. 4. The system admits the administrator to the event in every state with every operation. 5. The administrator edits a setting, a message, or a user of the event. 6. The system applies the change and propagates it like the change of the respective event role.	

● GROUP	Description
Events ↕	An event together with its agenda points and its question tags — BECAUSE both are the event-specific configuration of its phases and questions.
Users ↕	The user as the sole identity entity together with the roles granted to it — BECAUSE the user is the one entity nearly every other one refers to and the roles are the rights it holds.
Channels ↕	A channel together with its provider resources and their provider parameters — BECAUSE the resources and parameters are the owned parts delivering the channel.
Messages ↕	A message together with its language-specific texts — BECAUSE the texts are owned parts of the message and never exist without it.
Tokens ↕	The authorization and session tokens of the login — BECAUSE both prove the access of a user to an event, before and after the login.
Statistics ↕	The periodic snapshot entities of the event, its channels, and its users — BECAUSE all of them are recorded over time and exported together for trend visualization.

11.01 ● ENTITY: Event 🌀 ⚓



○ REQUIREMENTS

- REQUIREMENT: Individual Event Access URL 🌀, ● REQUIREMENT: User Authentication 🌀,
- REQUIREMENT: Automatic Event Access URL 🌀, ● REQUIREMENT: Explicit User Consent 🌀,
- REQUIREMENT: Login and Interaction Messages 🌀, ● REQUIREMENT: Configurable Name Appearance 🌀,
- REQUIREMENT: Chat Messages 🌀, ● REQUIREMENT: Reply to Chat Messages 🌀,
- REQUIREMENT: Ask Questions 🌀, ● REQUIREMENT: Moderate Chat and Questions 🌀,
- REQUIREMENT: Client-Side Sentiment Analysis 🌀, ● REQUIREMENT: Server-Side Sentiment Analysis 🌀,
- REQUIREMENT: Presenter Hints and Alerts 🌀, ● REQUIREMENT: Manage Embedded Application 🌀,
- REQUIREMENT: Live Configuration Propagation 🌀, ● REQUIREMENT: Import and Export Event 🌀

○ USE-CASES

- USE-CASE: Create Event from Registration Import 🌀, ● USE-CASE: Publish, Start, and Finish Event 🌀,
- USE-CASE: Join Event and Watch Stream 🌀, ● USE-CASE: Switch Streaming Provider 🌀,
- USE-CASE: Moderate and Forward Messages 🌀, ● USE-CASE: Export Anonymized Event Data 🌀

○ TERMS

- TERM: Event 🌀

○ GROUP

- GROUP: Events 🌀

The master entity describing a single live broadcast event and all of its configuration — **BECAUSE** the entire data model is event-centric and every other entity hangs off an event.

● ATTRIBUTE	○ TYPE	○ DEFAULT	○ CLASSIFICATION	Description
eventId 	key uuid	uuid()	∅	Unique identifier of the event used in the access URL — BECAUSE attendees reach a specific event by an unguessable link
title  	string?	∅	Public	Display title of the event such as “Townhall 1/23” — BECAUSE attendees and managers need a human-readable label
description  	string?	∅	∅	Free-text description of the event — BECAUSE organizers describe the purpose and content of the event
begin  	datetime?	∅	∅	Planned start date and time of the event — BECAUSE attendees and operators must know when the event starts
end  	datetime?	∅	∅	Planned end date and time of the event — BECAUSE scheduling and the finish procedure depend on the planned end
language 	string	en	∅	Targeted mother language of the event — BECAUSE it sets the default language despite on-the-fly translation of interaction
state 	enum(planning, published, running, finished)	planning	∅	Lifecycle state controlling attendee visibility and access — BECAUSE an event progresses from private setup to live to archived
loginInfo 	string	""	∅	HTML markup shown to attendees at login — BECAUSE managers convey event information and links at entry
loginInfoToBeAccepted 	boolean	false	∅	Whether the login information must be explicitly accepted — BECAUSE some events require acknowledged consent before joining
interactionInfo 	string	""	∅	HTML markup shown when interaction is enabled — BECAUSE conduct rules must be presented before chat or questions
interactionInfoToBeAccepted 	boolean	false	∅	Whether the interaction information must be explicitly accepted — BECAUSE some events require acknowledged conduct rules before interacting
allowAccessAnonymous 	boolean	false	∅	Whether anonymous attendees may access the event without authorization — BECAUSE public events accept unauthenticated viewers
accessEmailPattern 	string	""	∅	Pattern that grants access to any matching email beyond the access list — BECAUSE events can admit whole email domains without enumerating users


● ATTRIBUTE	○ TYPE	○ DEFAULT	○ CLASSIFICATION	Description
chatEnabled ↗	boolean	false	∅	Whether attendees may send chat messages — BECAUSE chat is an optional interaction channel per event
chatAllowAnonymous ↗	boolean	false	∅	Whether chat messages may be sent as “Anonymous” — BECAUSE events differ in how much chat identity is revealed
chatName ↗	enum(full, first name, anonymous)	full	∅	How the attendee name appears on chat messages — BECAUSE the event controls the displayed chat identity
chatReply ↗	boolean	false	∅	Whether chat messages may be replied to — BECAUSE threaded replies are appropriate only for some events
chatThrottling ↗	integer	1	∅	Maximum chat messages per user per minute — BECAUSE rate limiting prevents denial-of-service abuse
chatModerator ↗	boolean	false	∅	Whether chat messages are moderated before becoming visible — BECAUSE organizers may require approval of chat content
supportEnabled ↗	boolean	false	∅	Whether attendees may chat with support for technical problems — BECAUSE events may offer a dedicated support channel
appEnabled ↗	boolean	false	∅	Whether a third-party application is integrated — BECAUSE events may embed an interactive app
appTitle ↗	string	""	∅	Display title of the embedded third-party application — BECAUSE the embedded app needs a label for attendees
appURL ↗	string	""	∅	URL of the embedded third-party application — BECAUSE the client must load the app from a defined location
appAdminURL ↗	string	""	∅	Administration URL of the embedded third-party application — BECAUSE moderators control the app through a separate admin view
presenterAlert ↗	string	""	∅	Alert text a moderator can raise for the presenter — BECAUSE the moderator must signal urgent information to the presenter
presenterAlertState ↗	enum(raised, unraised)	unraised	∅	Whether the presenter alert is currently visible to the presenter — BECAUSE the alert is toggled on by the moderator and confirmed off
questionsEnabled ↗	boolean	false	∅	Whether attendees may ask questions — BECAUSE questions are an optional interaction channel per event
questionsAllowAnonymous ↗	boolean	false	∅	Whether questions may be sent as “Anonymous” — BECAUSE events differ in how much question identity is revealed

● ATTRIBUTE	○ TYPE	○ DEFAULT	○ CLASSIFICATION	Description
questionsName ⚓	enum(full, first_name, anonymous)	full	∅	How the attendee name appears on questions — BECAUSE the event controls the displayed question identity
questionsThrottling ⚓	integer	1	∅	Maximum questions per user per time window — BECAUSE rate limiting prevents abuse of the question channel
questionsPrivate ⚓	boolean	false	∅	Whether questions are hidden from other attendees and seen only by moderators — BECAUSE some events keep questions private to the moderation team
questionsModerator ⚓	boolean	false	∅	Whether questions are moderated before becoming visible — BECAUSE organizers may require approval of questions
expireAuthTokenOnFirstUse ⚓	boolean	true	∅	Whether pre-generated authorization tokens expire after first use — BECAUSE events choose between one-time and reusable pre-generated tokens
sentimentSenderAnalysis ⚓	boolean	false	∅	Whether lightweight client-side sentiment analysis is enabled — BECAUSE the event can check input at the source before sending
sentimentSenderAutoPrevent ⚓	boolean	false	∅	Whether improper input is prevented from submission on the client — BECAUSE the event can block misconduct before it reaches the server
sentimentModeratorAnalysis ⚓	boolean	false	∅	Whether full server-side sentiment analysis is enabled — BECAUSE the event can check input before it is stored
sentimentModeratorAutoAccept ⚓	boolean	false	∅	Whether proper input is auto-accepted on the server — BECAUSE moderators can be relieved of approving positive input
sentimentModeratorAutoReject ⚓	boolean	false	∅	Whether improper input is auto-rejected on the server — BECAUSE moderators can be relieved of rejecting negative input

● RELATION	○ TARGET	○ KIND	○ ARITY	Description
channels ⚓	● ENTITY: Channel Ⓜ	Composition	0..n	Language-specific content distributors of the event — BECAUSE an event delivers content through one or more logical channels
accessList ⚓	● ENTITY: User Ⓜ	Composition	0..n	Invited attendees identified by email — BECAUSE access is granted to an explicit list of users
messages ⚓	● ENTITY: Message Ⓜ	Composition	0..n	Messages written during the event — BECAUSE all chat, question, and support input belongs to the event
statistics ⚓	● ENTITY: EventStatistic Ⓜ	Composition	0..n	Periodic cumulative statistics snapshots — BECAUSE trend visualization requires periodic counts

● RELATION	○ TARGET	○ KIND	○ ARITY	Description
userStatistics ⚓	● ENTITY: UserStatistic Ⓜ	Composition	0..n	Viewer statistics recorded for the users of the event — BECAUSE the statistics stay attributable to the event after their users are deleted and are dropped with it
availableQuestionTags ⚓	● ENTITY: QuestionTag Ⓜ	Composition	0..n	Tags available for use on questions — BECAUSE the event defines the vocabulary for tagging questions
activeAgendaPoint ⚓	● ENTITY: AgendaPoint Ⓜ	Association	0..1	The currently active agenda point — BECAUSE attendees see which phase of the event is current
agendaPoints ⚓	● ENTITY: AgendaPoint Ⓜ	Composition	0..n	All agenda points of the event — BECAUSE the event has an ordered agenda of phases

11.02 ● ENTITY: AgendaPoint [⚓](#)



○ REQUIREMENTS	● REQUIREMENT: Tag Question Messages Ⓜ
○ USE-CASES	● USE-CASE: Join Event and Watch Stream Ⓜ , ● USE-CASE: Moderate and Forward Messages Ⓜ
○ GROUP	● GROUP: Events Ⓜ


The textual description of a phase in an event — **BECAUSE** attendees and moderators track which part of the event is currently active.

● ATTRIBUTE	○ TYPE	○ DEFAULT	Description
agendaPointId ⚓	key uuid	uuid()	Unique identifier of the agenda point — BECAUSE it is referenced as a foreign key
text ⚓ Ⓜ	string?	∅	Description of the current phase of the event — BECAUSE the phase must be presented in human-readable form
orderPosition ⚓ Ⓜ	integer?	∅	Ordering position of the phase — BECAUSE agenda points have a defined sequence

● RELATION	○ TARGET	○ KIND	○ ARITY	Description
correspondingTags ⚓	● ENTITY: QuestionTag Ⓜ	Association	0..n	Question tags corresponding to this agenda point — BECAUSE questions can

● RELATION	○ TARGET	○ KIND	○ ARITY	Description
				be associated with the agenda phase they relate to

11.03 ● ENTITY: Channel




○ REQUIREMENTS	● REQUIREMENT: Multiple Streaming Providers  , ● REQUIREMENT: Live Provider Switching  , ● REQUIREMENT: Channel Statistics 
○ USE-CASES	● USE-CASE: Join Event and Watch Stream  , ● USE-CASE: Switch Streaming Provider 
○ TERMS	● TERM: Channel 
○ GROUP	● GROUP: Channels 

A logical content delivery stream linking video streams to an event — **BECAUSE** an event groups its streams by language and resolution into channels.

● ATTRIBUTE	○ TYPE	○ DEFAULT	Description
channelId 	key uuid	uuid()	Unique identifier of the channel — BECAUSE it is referenced as a foreign key
name  	string?	∅	Display name of the channel such as “Digital Townhall” — BECAUSE attendees choose between named channels
active 	boolean	false	Whether the channel is the currently active one, derived to true for the first channel of an event (● Initial Channel Becomes Active) — BECAUSE only one channel of an event is active at once (● Single Active Channel)
default 	boolean	false	Whether this channel is activated by default on entering an event — BECAUSE attendees need a defined initial channel

● RELATION	○ TARGET	○ KIND	○ ARITY	Description
resources 	● ENTITY: Resource 	Composition	1..n	Physical resources backing the channel — BECAUSE a channel is delivered by one or more provider resources
statistics 	● ENTITY: ChannelStatistic 	Composition	0..n	Periodic viewer statistics of the channel — BECAUSE organizers track viewers per channel over time


11.04 ● ENTITY: Resource 

○ REQUIREMENTS	● REQUIREMENT: Multiple Streaming Providers  , ● REQUIREMENT: Live Provider Switching  , ● REQUIREMENT: Direct Resource Access URL 
○ USE-CASES	● USE-CASE: Join Event and Watch Stream  , ● USE-CASE: Switch Streaming Provider 
○ TERMS	● TERM: Resource  , ● TERM: Streaming Provider 
○ GROUP	● GROUP: Channels 

A physical content delivery resource such as a provider stream or static website linked to a channel — **BECAUSE** a channel must map to concrete provider endpoints to be playable.


● ATTRIBUTE	○ TYPE	○ DEFAULT	Description
resourceId 	key uuid	uuid()	Unique identifier of the resource — BECAUSE it is referenced as a foreign key and in the access URL
providerId  	string?	∅	Provider identifier from the event configuration file — BECAUSE a resource binds to a specific configured streaming provider
active 	boolean	false	Whether this resource is the active resource of the channel, derived to true for the first resource of a channel (● Initial Resource Becomes Active) — BECAUSE only one resource of a channel is active at once for provider switching (● Single Active Resource per Channel)

● RELATION	○ TARGET	○ KIND	○ ARITY	Description
params 	● ENTITY: ResourceProvide rParam 	Composition	0..n	Provider key-value parameters assigned to this resource — BECAUSE each provider needs configured parameters to address its stream

11.05 ● ENTITY: ResourceProviderParam [⚓](#)

A key-value parameter belonging to exactly one resource and provider, defined in the event configuration file — **BECAUSE** provider endpoints are parameterized by values an administrator supplies.


● ATTRIBUTE	○ TYPE	○ DEFAULT	Description
resourceId ⚓	key uuid	uuid()	Identifier of the owning resource — BECAUSE the parameter belongs to exactly one resource
providerId ⌘ ⚓	key string	∅	Provider identifier from the configuration file — BECAUSE the parameter is scoped to one provider
key ⌘ ⚓	key string	∅	Parameter key defined in the configuration file — BECAUSE each provider parameter is identified by its key
value ⌘ ⚓	string?	∅	Value the administrator entered for the key — BECAUSE the concrete endpoint requires the supplied value

11.06 ● ENTITY: Role [⚓](#)

A grant of rights to a user, who exists within a specific event or, as the holder of the Administrator role, permanently and outside any event — **BECAUSE** the application is role-based and rights are granted through roles.

● ATTRIBUTE	○ TYPE	○ DEFAULT	Description
roleId ⚓	key uuid	uuid()	Unique identifier of the role — BECAUSE it is referenced as a foreign key
type ⚓	enum(Manager, Moderator, Presenter, Attendee, Administrator)	Attendee	The role granted to the user, where Attendee is the plain audience membership and Administrator the permanent, event-independent role granted through the configuration only — BECAUSE each role carries a distinct set of rights

11.07 ● ENTITY: User [⚓](#)




○ REQUIREMENTS	● REQUIREMENT: User Authentication ⌘, ● REQUIREMENT: Configurable Name Appearance ⌘, ● REQUIREMENT: Like Messages ⌘, ● REQUIREMENT: Personalized Event Access URL ⌘, ● REQUIREMENT: Import Registered Attendees ⌘
○ USE-CASES	● USE-CASE: Authenticate via Email Token ⌘, ● USE-CASE: Create Event from Registration Import ⌘, ● USE-CASE: Chat During the Event ⌘, ● USE-CASE: Publish, Start, and Finish Event ⌘, ● USE-CASE: Administer Any Event ⌘
○ TERMS	● TERM: User ⌘, ● TERM: Access List ⌘
○ GROUP	● GROUP: Users ⌘

A helper entity identifying a person within an event for event-based logins and for the roles granted to them, or permanently and outside any event as the holder of the Administrator role — **BECAUSE** the system holds no permanent accounts except the administrator yet must identify attendees and role holders per event.

● ATTRIBUTE	○ TYPE	○ DEFAULT	○ CLASSIFICATION	○ RETENTION	Description
userId ⚓	key uuid	uuid()	∅	∅	Unique identifier of the user — BECAUSE it is referenced as a foreign key
email ⌘ ⚓	string?	∅	Personal	until event finish, until event deletion	Concrete email address of the user — BECAUSE authorization tokens are

● ATTRIBUTE	○ TYPE	○ DEFAULT	○ CLASSIFICATION	○ RETENTION	Description
				for a holder of the Manager role, permanently for the holder of the Administrator role	sent to this address at login and roles are granted to it
firstname ↗	string	""	Personal	until event finish	Optional first name of the user — BECAUSE it is displayed on the user's chat and question messages
lastname ↗	string	""	Personal	until event finish	Optional last name of the user — BECAUSE it is displayed on the user's chat and question messages

● RELATION	○ TARGET	○ KIND	○ ARITY	Description
roles ↗	● ENTITY: Role ↗	Composition	0..n	Roles granted to the user within its event — BECAUSE rights are held by the identified user rather than by a bare email address
likes ↗	● ENTITY: Message ↗	Association	0..n	Messages the user marked as liked — BECAUSE likes are tracked per user until anonymization
sentMessages ↗	● ENTITY: Message ↗	Association	0..n	Messages the user has sent — BECAUSE authorship links a message to its sending user
statistics ↗	● ENTITY: UserStatistic ↗	Aggregation	0..n	Periodic statistics about the user — BECAUSE viewer information is captured per user over time



○ REQUIREMENTS	● REQUIREMENT: Chat Messages ⓘ, ● REQUIREMENT: Ask Questions ⓘ, ● REQUIREMENT: Like Messages ⓘ, ● REQUIREMENT: Reply to Chat Messages ⓘ, ● REQUIREMENT: Moderate Chat and Questions ⓘ, ● REQUIREMENT: Forward Inputs to Presenter ⓘ, ● REQUIREMENT: Answer Attendee Inputs ⓘ, ● REQUIREMENT: Moderator-Authored Messages ⓘ, ● REQUIREMENT: Edit and Delete Messages ⓘ, ● REQUIREMENT: Deleted Message Placeholder ⓘ, ● REQUIREMENT: Server-Side Sentiment Analysis ⓘ, ● REQUIREMENT: Sort and Filter Messages ⓘ, ● REQUIREMENT: Tag Question Messages ⓘ, ● REQUIREMENT: Export Attendee Inputs ⓘ
○ USE-CASES	● USE-CASE: Ask a Question ⓘ, ● USE-CASE: Chat During the Event ⓘ, ● USE-CASE: Moderate and Forward Messages ⓘ, ● USE-CASE: Moderate the Chat Conversation ⓘ, ● USE-CASE: Present Forwarded Questions ⓘ, ● USE-CASE: Export Anonymized Event Data ⓘ
○ TERMS	● TERM: Message ⓘ, ● TERM: Chat ⓘ, ● TERM: Question ⓘ, ● TERM: Support ⓘ, ● TERM: Like ⓘ, ● TERM: Sentiment Analysis ⓘ
○ GROUP	● GROUP: Messages ⓘ


● ATTRIBUTE	○ TYPE	○ DEFAULT	○ CLASSIFICATION	○ RETENTION	Description
messageId ↕	key uuid	uuid()	∅	∅	Unique identifier of the message — BECAUSE it is the foreign key for the

● ATTRIBUTE	○ TYPE	○ DEFAULT	○ CLASSIFICATION	○ RETENTION	Description
					translated message texts
type [⚓]	enum(Chat, Support, Question)	Chat	∅	∅	The kind of message — BECAUSE each type has a distinct lifecycle and visibility
timestamp [⚓]	datetime	Date.now()	∅	∅	Time the sender created the message — BECAUSE ordering and export require the creation time
timestampAnswered [⚓]	datetime	Date.now()	∅	∅	Time the message was answered — BECAUSE the presenter records when a question was answered
state [⚓]	enum(pending, accepted, rejected, forwarded, answered, suspended)	pending	∅	∅	Moderation and processing state of the message — BECAUSE the message moves through a defined moderation and presentation lifecycle
originalLanguage [⚓]	string?	∅	∅	∅	Language the sender originally wrote the message in — BECAUSE the difference between human-written and AI-translated text must always be visible
senderName [⚓]	string?	∅	Personal	until event finish, then replaced by “Anonymous”	Display name shown to others for the sender — BECAUSE the visible name depends on event naming and anonymity options
presenterAnnotation [⚓]	string?	∅	∅	∅	Hint a moderator attaches for the presenter on forwarding — BECAUSE the presenter benefits from routing guidance on a forwarded message
likes [⚓]	integer	0	∅	∅	Computed number of likes conserved on event finish — BECAUSE the like total must survive removal of liker relations for GDPR
sentimentScore [⚓]	float?	∅	∅	∅	Server-side sentiment score between -1 and 1 — BECAUSE the analysis result is stored for display and auto-moderation
edited [⚓]	enum(none, insignificant, significant, deleted)?	∅	∅	∅	Whether and how the message was changed or deleted — BECAUSE edits must be marked for others and edits stop once forwarded

● RELATION	○ TARGET	○ KIND	○ ARITY	Description
sender [⚓]	● ENTITY: User Ⓜ	Association	0..1	The authoring attendee of the message — BECAUSE a message has an author until the sender is removed on finish
liker [⚓]	● ENTITY: User Ⓜ	Association	0..n	Attendees who liked the message — BECAUSE likes are tracked per liking user before anonymization

● RELATION	○ TARGET	○ KIND	○ ARITY	Description
event ⚓	● ENTITY: Event Ⓜ	Association	1	The event the message belongs to — BECAUSE the event link must persist even after senders are deleted
replyTo ⚓	● ENTITY: Message Ⓜ	Association	0..1	The message this message replies to — BECAUSE chat replies and moderator answers chain messages together
predecessor ⚓	● ENTITY: Message Ⓜ	Association	0..1	The preceding message in a manual ordering — BECAUSE moderators sort forwarded messages for the presenter
questionTags ⚓	● ENTITY: QuestionTag Ⓜ	Association	0..n	Tags attached to a question message — BECAUSE questions can be tagged with zero or more tags for context
messageText ⚓	● ENTITY: MessageText Ⓜ	Composition	1..n	The message texts of this message — BECAUSE each message text can be translated to multiple languages


11.09 ● ENTITY: MessageText [⚓](#)



○ REQUIREMENTS	● REQUIREMENT: In-Session Language Switching Ⓜ , ● REQUIREMENT: Export Attendee Inputs Ⓜ
○ USE-CASES	● USE-CASE: Join Event and Watch Stream Ⓜ , ● USE-CASE: Chat During the Event Ⓜ , ● USE-CASE: Export Anonymized Event Data Ⓜ
○ TERMS	● TERM: Message Ⓜ
○ GROUP	● GROUP: Messages Ⓜ

A language-specific text of a message — **BECAUSE** a message is translated into multiple languages while retaining one original.

● ATTRIBUTE	○ TYPE	○ DEFAULT	Description
messageTextId ⚓	key uuid	uuid()	Unique identifier of the message text — BECAUSE it is referenced as a foreign key
language ⚓	string?	∅	Language the text is written in — BECAUSE each text variant is identified by its language
text ⚓	string?	∅	The message text in the stated language — BECAUSE the displayed content depends on the chosen language

11.10 ● ENTITY: QuestionTag [⚓](#)


○ REQUIREMENTS	● REQUIREMENT: Tag Question Messages ⌘
○ USE-CASES	● USE-CASE: Ask a Question ⌘ , ● USE-CASE: Moderate and Forward Messages ⌘
○ GROUP	● GROUP: Events ⌘

A named tag attachable to question messages — **BECAUSE** questions are categorized by topic or addressed person for routing and grouping.

● ATTRIBUTE	○ TYPE	○ DEFAULT	Description
questionTagId ⚓	key uuid	uuid()	Unique identifier of the question tag — BECAUSE it is referenced as a foreign key
text ⚓	unique string	∅	Unique tag name — BECAUSE tags are identified and displayed by their name
moderatorOnly ⚓	boolean?	∅	Whether only a Moderator or Manager may use the tag — BECAUSE some tags are reserved for the moderation team
group ⚓	string?	∅	Logical group the tag belongs to such as a topic or person — BECAUSE tags are organized into meaningful groups

● RELATION	○ TARGET	○ KIND	○ ARITY	Description
messages ⚓	● ENTITY: Message ⌘	Association	0..n	The question messages the tag is attached to — BECAUSE a tag categorizes many questions and its removal has to detach it from all of them
agendaPoints ⚓	● ENTITY: AgendaPoint ⌘	Association	0..n	The agenda points the tag corresponds to — BECAUSE a tag can relate to several phases of the event

11.11 ● ENTITY: AuthorizationToken ⚓




○ REQUIREMENTS	● REQUIREMENT: User Authentication ⓘ, ● REQUIREMENT: Automatic Event Access URL ⓘ, ● REQUIREMENT: Import Registered Attendees ⓘ, ● REQUIREMENT: Return Access URLs to Registration ⓘ, ● REQUIREMENT: Debugging Statistics ⓘ
○ USE-CASES	● USE-CASE: Authenticate via Email Token ⓘ, ● USE-CASE: Create Event from Registration Import ⓘ, ● USE-CASE: Export Anonymized Event Data ⓘ
○ TERMS	● TERM: Authorization Token ⓘ
○ GROUP	● GROUP: Tokens ⓘ

A one-time second factor proving an attendee controls the email address used as the first factor — **BECAUSE** email-verified access is the core mechanism limiting the audience.

● ATTRIBUTE	Properties & Description				
token ⚙ ⚓	○ TYPE	○ DEFAULT	○ CONSTRAINT	○ CLASSIFICATION	○ RETENTION
	string?	∅	six digits as NNN-NNN	Confidential	until validity expiry, at the latest until event finish
	Description The generated one-time token for the next login attempt — BECAUSE the attendee proves control of the email by returning this token				
validUntil ⚓	○ TYPE	○ DEFAULT	○ CONSTRAINT	○ CLASSIFICATION	○ RETENTION
	datetime	Date.now() + 1d	∅	∅	∅
	Description Expiry time of the token, unset for pre-generated tokens — BECAUSE ordinary tokens expire within minutes while pre-generated ones last until event end				
state ⚓	○ TYPE	○ DEFAULT	○ CONSTRAINT	○ CLASSIFICATION	○ RETENTION
	enum(issued,s ent,used)	issued	∅	∅	∅
	Description Lifecycle state of the token — BECAUSE debugging statistics and anonymized sums need the token state				
● RELATION	○ TARGET	○ KIND	○ ARITY	Description	
user ⚓	● ENTITY: User ⓘ	Association	1	The user the token was issued for — BECAUSE a token authorizes exactly one	

● RELATION	○ TARGET	○ KIND	○ ARITY	Description
				user
event [⚓]	● ENTITY: Event [Ⓜ]	Association	1	The event the token was issued for — BECAUSE a token grants access to exactly one event

11.12 ● ENTITY: SessionToken [⚓]




○ REQUIREMENTS	● REQUIREMENT: User Authentication [Ⓜ] , ● REQUIREMENT: Limit Parallel Access [Ⓜ] , ● REQUIREMENT: General Event Statistics [Ⓜ]
○ USE-CASES	● USE-CASE: Authenticate via Email Token [Ⓜ] , ● USE-CASE: Join Event and Watch Stream [Ⓜ]
○ TERMS	● TERM: Session Token [Ⓜ]
○ GROUP	● GROUP: Tokens [Ⓜ]

The result of a successful login of a user to an event — **BECAUSE** an active session must be tracked to enforce single concurrent access.

● ATTRIBUTE	○ TYPE	○ DEFAULT	○ CLASSIFICATION	○ RETENTION	Description
sessionId [⚓]	key uuid	uuid()	Confidential	until event finish	Unique identifier of the session — BECAUSE the active session of a user for an event must be addressable
issuedAt [⚓]	datetime	Date.now()	∅	∅	Time the user successfully entered the event — BECAUSE the session start time is recorded for tracking

● RELATION	○ TARGET	○ KIND	○ ARITY	Description
user [⚓]	● ENTITY: User [Ⓜ]	Association	1	The user the session was issued for — BECAUSE a session belongs to exactly one user
event [⚓]	● ENTITY: Event [Ⓜ]	Association	1	The event the session was issued for — BECAUSE a session grants access to exactly one event


11.13 ● ENTITY: EventStatistic [⚓](#)

○ REQUIREMENTS	● REQUIREMENT: General Event Statistics ⌘ , ● REQUIREMENT: Debugging Statistics ⌘ , ● REQUIREMENT: Periodic Statistics Snapshots ⌘
○ USE-CASES	● USE-CASE: Export Anonymized Event Data ⌘
○ GROUP	● GROUP: Statistics ⌘

A periodic cumulative snapshot of event-wide counts — **BECAUSE** trend visualization of audience size and authentication flow requires regular snapshots.

● ATTRIBUTE	○ TYPE	○ DEFAULT	Description
eventStatisticId ⚓	key uuid	uuid()	Unique identifier of the event statistic — BECAUSE it is referenced as a foreign key
timestamp ⚓	datetime	Date.now()	Time the snapshot was created — BECAUSE statistics are plotted over time
numberOfIssuedAuthTokens ⌘ ⚓	integer?	∅	Count of issued authorization tokens at the timestamp — BECAUSE debugging statistics track issued tokens
numberOfSentAuthTokens ⌘ ⚓	integer?	∅	Count of sent authorization tokens at the timestamp — BECAUSE debugging statistics track sent tokens
numberOfUsedAuthTokens ⌘ ⚓	integer?	∅	Count of used authorization tokens at the timestamp — BECAUSE debugging statistics track used tokens
numberOfSessionTokens ⌘ ⚓	integer?	∅	Count of session tokens at the timestamp — BECAUSE logged-in users are derived from session tokens
numberOfConnections ⌘ ⚓	integer?	∅	Count of active MQTT connections at the timestamp — BECAUSE active viewers differ from sessions once an attendee leaves

11.14 ● ENTITY: ChannelStatistic [⚓](#)




○ REQUIREMENTS	● REQUIREMENT: Channel Statistics ⌘ , ● REQUIREMENT: Periodic Statistics Snapshots ⌘
○ USE-CASES	● USE-CASE: Export Anonymized Event Data ⌘
○ GROUP	● GROUP: Statistics ⌘

A periodic count of viewers for a channel — **BECAUSE** organizers need per-channel popularity over time.

● ATTRIBUTE	○ TYPE	○ DEFAULT	Description
channelStatisticId ⚓	key uuid	uuid()	Unique identifier of the channel statistic — BECAUSE it is referenced as a foreign key
timestamp ⚓	datetime	Date.now()	Time the snapshot was created — BECAUSE channel statistics are plotted over time
numberOfViewers ⚙ ⚓	integer?	∅	Count of viewers of the channel at the timestamp — BECAUSE the per-channel viewer count is the tracked metric

11.15 ● ENTITY: UserStatistic [⚓](#)



○ REQUIREMENTS	● REQUIREMENT: User Statistics ⌘
○ USE-CASES	● USE-CASE: Join Event and Watch Stream ⌘ , ● USE-CASE: Export Anonymized Event Data ⌘
○ GROUP	● GROUP: Statistics ⌘


Tracked viewer information about a user — **BECAUSE** audience composition informs reporting and default localization.

● ATTRIBUTE	○ TYPE	○ DEFAULT	○ CLASSIFICATION	○ RETENTION	Description
userStatisticId	key uuid	uuid()	∅	∅	Unique identifier of the user statistic — BECAUSE it is referenced as a foreign key
timestamp	datetime	Date.now()	∅	∅	Time the snapshot was created — BECAUSE user statistics are recorded over time
country	string?	∅	Personal	linked to the user until event finish, retained unlinked afterwards	ISO country code from GeoIP tracking — BECAUSE country selects the default application language on first use
browserType	string?	∅	Personal	linked to the user until event finish, retained unlinked afterwards	Type of browser used — BECAUSE browser distribution informs compatibility decisions
deviceType	string?	∅	Personal	linked to the user until event finish, retained unlinked afterwards	Type of device used — BECAUSE device distribution informs responsive design priorities
viewportWidth	integer?	∅	∅	∅	Width in pixels of the browser viewport — BECAUSE viewport sizing informs layout decisions
viewportHeight	integer?	∅	∅	∅	Height in pixels of the browser viewport — BECAUSE viewport sizing informs layout decisions

● RELATION	○ TARGET	○ KIND	○ ARITY	Description
event	● ENTITY: Event	Association	1	The event the statistic was recorded in — BECAUSE the statistic must stay selectable per event once its user reference is dropped


12 ● DATA: State Model (SM)



12.01 ● LIFECYCLE: Event [⚓](#)○ ENTITY ● ENTITY: Event [⌵](#)

● STATE	○ INITIAL	○ FINAL	Description
Planning ⚓	true	∅	The event is created and configured but not visible to attendees
Published ⚓	∅	∅	The event is visible to attendees but not yet started
Running ⚓	∅	∅	The event is live and attendees can attend and interact
Finished ⚓	∅	true	The event has ended, access is closed, and data is anonymized

● TRANSITION	Properties & Description		
publish ⚓	○ FROM	○ TO	○ ACTOR
	● STATE: Planning ⌵	● STATE: Published ⌵	● ROLE: Manager ⌵
	○ GUARD	○ RULES	○ USE-CASES
	The event is fully configured.	∅	● SCENARIO: Publish, Start, and Finish ⌵
	Description		
	The event becomes visible to invited attendees		
start ⚓	○ FROM	○ TO	○ ACTOR
	● STATE: Published ⌵	● STATE: Running ⌵	● ROLE: Manager ⌵
	○ GUARD	○ RULES	○ USE-CASES
	∅	∅	● SCENARIO: Publish, Start, and Finish ⌵
	Description		
	The live stream and interaction channels open for attendees		
start ⚓	○ FROM	○ TO	○ ACTOR
	● STATE: Planning ⌵	● STATE: Running ⌵	● ROLE: Manager ⌵
	○ GUARD	○ RULES	○ USE-CASES
	∅	∅	● SCENARIO: Start Without Publishing ⌵
	Description		
	The event goes live directly from planning, without ever having been visible beforehand		
finish ⚓	○ FROM	○ TO	○ ACTOR
	● STATE: Running ⌵	● STATE: Finished ⌵	● ROLE: Manager ⌵
	○ GUARD	○ RULES	○ USE-CASES
	∅	● RULE: Anonymization on Event Finish ⌵	● SCENARIO: Publish, Start, and Finish ⌵
	Description		
	The anonymization procedure runs and access is closed		

12.02 ● **LIFECYCLE: Message** 

○ **ENTITY** ● **ENTITY: Message**

● STATE	○ INITIAL	○ FINAL	Description
Pending 	true	∅	The attendee has submitted the message and it awaits moderation
Accepted 	∅	true	The message is approved and visible to the audience if configured
Rejected 	∅	true	The message is declined and will be deleted entirely on event finish
Forwarded 	∅	∅	The accepted message is handed to the presenter as a work item
Answered 	∅	true	The presenter has processed and answered the message in the live event
Suspended 	∅	true	The presenter will not process the message in the live event

● TRANSITION	Properties & Description		
accept 	○ FROM	○ TO	○ ACTOR
	● STATE: Pending 	● STATE: Accepted 	● ROLE: Moderator 
	○ GUARD	○ RULES	○ USE-CASES
	∅	● RULE: Moderation Determines Initial Visibility 	● SCENARIO: Approve and Forward Question 
	Description		
	The message becomes visible to the audience		
accept 	○ FROM	○ TO	○ ACTOR
	● STATE: Pending 	● STATE: Accepted 	System
	○ GUARD	○ RULES	○ USE-CASES
	The server-side sentiment analysis scores the message at or above the threshold and auto-accept is enabled.	● RULE: Moderation Determines Initial Visibility  , ● RULE: Sentiment Auto-Decision Threshold 	● SCENARIO: Auto-Accepted by Sentiment 
	Description		
	The message becomes visible to the audience without a moderator decision		
accept 	○ FROM	○ TO	○ ACTOR
	● STATE: Pending 	● STATE: Accepted 	System

● TRANSITION	Properties & Description		
	○ GUARD	○ RULES	○ USE-CASES
	The event does not moderate messages of this type.	● RULE: Moderation Determines Initial Visibility ①	● SCENARIO: Post a Chat Message ①, ● SCENARIO: Reply to a Chat Message ①
	Description		
	The message becomes visible to the audience at once, right after its creation		
accept	○ FROM	○ TO	○ ACTOR
	● STATE: Pending ①	● STATE: Accepted ①	System
	○ GUARD	○ RULES	○ USE-CASES
	The message is authored by a moderator.	● RULE: Moderator Messages Auto-Accepted ①	● SCENARIO: Answer an Attendee Directly ①, ● SCENARIO: Seed the Conversation as Moderator ①
	Description		
	The moderator-authored message becomes visible at once, right after its creation		
reject	○ FROM	○ TO	○ ACTOR
	● STATE: Pending ①	● STATE: Rejected ①	● ROLE: Moderator ①
	○ GUARD	○ RULES	○ USE-CASES
	∅	● RULE: Moderation Determines Initial Visibility ①	● SCENARIO: Reject Improper Message ①
	Description		
	The message is hidden and marked for deletion		
reject	○ FROM	○ TO	○ ACTOR
	● STATE: Pending ①	● STATE: Rejected ①	System
	○ GUARD	○ RULES	○ USE-CASES
	The server-side sentiment analysis scores the message below the threshold and auto-reject is enabled.	● RULE: Moderation Determines Initial Visibility ①, ● RULE: Sentiment Auto-Decision Threshold ①	● SCENARIO: Auto-Rejected by Sentiment ①
	Description		
	The message is hidden and marked for deletion without a moderator decision		
resubmit	○ FROM	○ TO	○ ACTOR
	● STATE: Accepted ①	● STATE: Pending ①	● ROLE: Attendee ①
	○ GUARD	○ RULES	○ USE-CASES
	The event moderates messages of this type.	● RULE: Moderation Determines Initial Visibility ①, ● RULE: Forwarded Messages Are Immutable ①	● SCENARIO: Edit an Own Message ①
	Description		
	The edited message is hidden from the audience again until it passes the moderation anew		
forward	○ FROM	○ TO	○ ACTOR
	● STATE: Accepted ①	● STATE: Forwarded ①	● ROLE: Moderator ①

● TRANSITION	Properties & Description		
	○ GUARD	○ RULES	○ USE-CASES
	The message is a question.	● RULE: State Set Depends on Message Type ⓘ, ● RULE: Forwarded Messages Are Immutable ⓘ	● SCENARIO: Approve and Forward Question ⓘ
	Description		
	The message enters the presenter's work basket and becomes immutable		
answer ⓘ	○ FROM	○ TO	○ ACTOR
	● STATE: Forwarded ⓘ	● STATE: Answered ⓘ	● ROLE: Presenter ⓘ, ● ROLE: Moderator ⓘ
	○ GUARD	○ RULES	○ USE-CASES
	∅	∅	● SCENARIO: Answer Forwarded Question ⓘ, ● SCENARIO: Settle a Question for the Presenter ⓘ
	Description		
	The answered timestamp is recorded		
suspend ⓘ	○ FROM	○ TO	○ ACTOR
	● STATE: Forwarded ⓘ	● STATE: Suspended ⓘ	● ROLE: Presenter ⓘ, ● ROLE: Moderator ⓘ
	○ GUARD	○ RULES	○ USE-CASES
	∅	∅	● SCENARIO: Suspend a Forwarded Question ⓘ, ● SCENARIO: Settle a Question for the Presenter ⓘ
	Description		
	The message is set aside for the live event		

12.03 ● LIFECYCLE: AuthorizationToken ⓘ




○ ENTITY ● ENTITY: AuthorizationToken ⓘ

● STATE	○ INITIAL	○ FINAL	Description
Issued ⓘ	true	∅	The token has been generated, typically at event creation
Sent ⓘ	∅	∅	The token has been delivered to the user by email
Used ⓘ	∅	true	The token has been consumed in a login attempt

● TRANSITION	Properties & Description		
send ↗	○ FROM	○ TO	○ ACTOR
	● STATE: Issued ⌵	● STATE: Sent ⌵	● ROLE: Attendee ⌵
	○ GUARD	○ RULES	○ USE-CASES
	The email of the attendee is on the access list or matches the access pattern.	● RULE: Access Requires List or Pattern Match ⌵	● SCENARIO: Login with Emailed Token ⌵
Description			
The token is emailed to the attendee requesting a login challenge			
consume ↗	○ FROM	○ TO	○ ACTOR
	● STATE: Sent ⌵	● STATE: Used ⌵	● ROLE: Attendee ⌵
	○ GUARD	○ RULES	○ USE-CASES
	The token has not expired.	● RULE: Token Format and Validity ⌵ , ● RULE: Single Active Session per Event ⌵	● SCENARIO: Login with Emailed Token ⌵
Description			
The token is marked spent by a successful or unsuccessful login attempt			
consume ↗	○ FROM	○ TO	○ ACTOR
	● STATE: Issued ⌵	● STATE: Used ⌵	● ROLE: Attendee ⌵
	○ GUARD	○ RULES	○ USE-CASES
	The event allows automatic-access URLs.	● RULE: Token Format and Validity ⌵	● SCENARIO: Automatic Token in URL ⌵
Description			
The pre-generated token is marked spent by the use of an automatic-access URL carrying it			


12.04 ● LIFECYCLE: UserStatistic [↗](#)



○ ENTITY	● ENTITY: UserStatistic ⌵		
● STATE	○ INITIAL	○ FINAL	Description
Linked ↗	true	∅	The statistic is attributed to the user it was recorded for
Unlinked ↗	∅	true	The statistic is retained without any reference to a user

● TRANSITION	Properties & Description		
unlink ↗	○ FROM	○ TO	○ ACTOR
	● STATE: Linked ⌵	● STATE: Unlinked ⌵	System
	○ RULES	○ USE-CASES	Description
	● RULE: Anonymization on Event Finish ⌵	● SCENARIO: Publish, Start, and Finish ⌵	The anonymization drops the user reference of the statistic on event finish

13 ● DATA: Authorization Model (AM)



● PERMISSION	Properties & Description						
Enter the Event 	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Attendee 	● ENTITY: Event 	Read 	● STATE: Published  , ● STATE: Running 	The email of the attendee is on the access list or matches the access email pattern of the event, or the event allows anonymous access.	● RULE: Access Requires List or Pattern Match  , ● RULE: No Permanent User Accounts 	● SCENARIO: O: Join via Individual URL  , ● SCENARIO: O: Email Not Authorized 
Description							
The attendee sees the event with its login and interaction information, but none of its configuration							
Prove the Email Address 	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Attendee 	● ENTITY: AuthorizationToken 	● TRANSITION: send  , ● TRANSITION: consume  , ● TRANSITION: consume 	∅	The token was issued for the email address of the attendee.	● RULE: Token Format and Validity  , ● RULE: Single Active Session per Event 	● USE-CASE: Authenticate via Email Token 
Description							
The attendee requests, receives, and returns the one-time token of their own login challenge							
Watch the Active Channel 	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Attendee 	● ENTITY: Channel 	Read 	∅	The channel belongs to the event the attendee entered.	● RULE: Single Active Channel 	● SCENARIO: O: Join via Individual URL  , ● SCENARIO: O: Live Failover 
Description							
The attendee sees the channels of the event and follows the active one							
Play the Active Resource 	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Attendee 	● ENTITY: Resource 	Read 	∅	The resource backs a channel of the event the	● RULE: Single Active Resource per Channel 	● SCENARIO: O: Join via Individual URL  , ● SCENARIO: O: Return via Direct

● PERMISSION	Properties & Description						
					attendee entered.		Resource URL ⓘ
	Description						
	The attendee plays the active resource, or the resource named by the event URL, without seeing its provider parameters						
Follow the Agenda ⓘ	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Attendee ⓘ	● ENTITY: AgendaPoint ⓘ	Read	∅	The agenda point belongs to the event the attendee entered.	∅	● SCENARIO: Advance the Agenda ⓘ
	Description						
	The attendee sees the agenda of the event and which agenda point is currently active						
Send Messages ⓘ	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Attendee ⓘ	● ENTITY: Message ⓘ	Create	∅	The event is running, the type of the message is enabled for the event, and the throttling limit is not exceeded.	● RULE: Moderation Determines Initial Visibility ⓘ, ● RULE: State Set Depends on Message Type ⓘ	● SCENARIO: Submit Moderated Question ⓘ, ● SCENARIO: Throttled Submission ⓘ, ● SCENARIO: Post a Chat Message ⓘ, ● SCENARIO: Reply to a Chat Message ⓘ
	Description						
	The attendee sends chat, question, and support messages of their own, which await the moderation decision or are accepted at once, as the moderation setting of the event determines						
Read Visible Messages ⓘ	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Attendee ⓘ	● ENTITY: Message ⓘ	Read	● STATE: Accepted ⓘ, ● STATE: Forwarded ⓘ, ● STATE: Answered ⓘ, ● STATE: Suspended ⓘ	The message is a chat, a question the event does not keep private, or a support message of the attendee's	● RULE: Moderation Determines Initial Visibility ⓘ	● SCENARIO: Post a Chat Message ⓘ, ● SCENARIO: Show Own Contributions Only ⓘ, ● SCENARIO: Pending

● PERMISSION	Properties & Description						
					own conversation.		Message Stays Private ⓘ
	Description						
	The attendee reads the messages which passed the moderation, with their texts and like counts, under the sender name the event configures						
Track Own Messages ⓘ	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Attendee ⓘ	● ENTITY: Message ⓘ	Read	● STATE: Pending ⓘ	The attendee is the sender of the message.	● RULE: Moderation Determines Initial Visibility ⓘ	● SCENARIO: Submit Moderated Question ⓘ, ● SCENARIO: Pending Message Stays Private ⓘ
	Description						
	The attendee sees their own messages while they still await the moderation decision						
Correct Own Messages ⓘ	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Attendee ⓘ	● ENTITY: Message ⓘ	Update, Delete, ● TRANSITION: resubmit ⓘ	● STATE: Pending ⓘ, ● STATE: Accepted ⓘ	The attendee is the sender of the message.	● RULE: Forwarded Messages Are Immutable ⓘ, ● RULE: Moderation Determines Initial Visibility ⓘ	● SCENARIO: Edit an Own Message ⓘ, ● SCENARIO: Delete an Own Message ⓘ, ● SCENARIO: Forwarded Question Locked ⓘ
	Description						
	The attendee edits or deletes their own chat messages and questions until a question is forwarded, where an edit is marked and resubmitted to the moderation as the event requires						
Like Messages ⓘ	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Attendee ⓘ	● ENTITY: Message ⓘ	Update	● STATE: Accepted ⓘ, ● STATE: Forwarded ⓘ, ● STATE: Answered ⓘ, ● STATE:	The update is confined to adding or revoking the attendee's own like on a chat or question of another attendee.	● RULE: Likes Conserved as Count on Finish ⓘ	● SCENARIO: Like a Message ⓘ

● PERMISSION	Properties & Description						
				Suspended ⓘ			
	Description						
	The attendee likes the visible messages of others and revokes the like again until the event finishes						
Use Public Tags ⓘ	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Attendee ⓘ	● ENTITY: QuestionTag ⓘ	Read	∅	The tag is not reserved for moderators.	∅	● SCENARIO: Submit Moderated Question ⓘ
	Description						
	The attendee sees the available tags of the event and attaches them to their own questions						
Enter the Event ⓘ	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Moderator ⓘ	● ENTITY: Event ⓘ	Read	● STATE: Planning ⓘ, ● STATE: Published ⓘ, ● STATE: Running ⓘ	The moderator holds the Moderator role of the event.	● RULE: Anonymization on Event Finish ⓘ	● USE-CASE: Moderate and Forward Messages ⓘ, ● USE-CASE: Moderate the Chat Conversation ⓘ, ● USE-CASE: Steer the Presenter ⓘ, ● SCENARIO: Access Lost After Finish ⓘ
	Description						
	The moderator sees the event with its interaction settings, also before it is published for the rehearsal, but loses the access when the event finishes, as the anonymization deletes the Moderator roles						
Steer the Presenter ⓘ	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Moderator ⓘ	● ENTITY: Event ⓘ	Update	● STATE: Running ⓘ	The update is confined to the presenter alert and the active agenda point of the event.	∅	● USE-CASE: Steer the Presenter ⓘ

● PERMISSION	Properties & Description						
	Description						
	The moderator raises the presenter alert and advances the active agenda point, but changes no other setting of the event						
Review All Messages	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Moderator	● ENTITY: Message	Read	∅	The message belongs to the event the moderator holds the Moderator role of.	∅	● SCENARI O: Approve and Forward Question , ● SCENARI O: Answer an Attendee Directly
	Description						
	The moderator reads every message of the event in every state, with its sender, sentiment score, and like count						
Decide Pending Messages	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Moderator	● ENTITY: Message	● TRANSITI ON: accept , ● TRANSITI ON: reject	∅	∅	● RULE: Moderation Determines Initial Visibility , ● RULE: Sentiment Auto-Decision Threshold	● SCENARI O: Approve and Forward Question , ● SCENARI O: Reject Improper Message
	Description						
	The moderator accepts or rejects the pending chats and questions, where the server-side sentiment analysis decides in their place if the event so configures						
Forward Questions	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Moderator	● ENTITY: Message	● TRANSITI ON: forward , Update	● STATE: Accepted , ● STATE: Forwarded	The message is a question, and the update is confined to the presenter annotation, the ordering, and the tags of the message.	● RULE: State Set Depends on Message Type , ● RULE: Forwarded Messages Are Immutable	● SCENARI O: Approve and Forward Question

● PERMISSION	Properties & Description						
	Description						
	The moderator forwards accepted questions to the presenter in a chosen order, attaching hints and tags, while the text of the question stays untouched						
Process Forwarded Questions	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Moderator	● ENTITY: Message	● TRANSITION: answer , ● TRANSITION: suspend	∅	∅	∅	● SCENARIO: Settle a Question for the Presenter
	Description						
	The moderator marks a forwarded question answered or suspended on behalf of the presenter						
Author Messages	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Moderator	● ENTITY: Message	Create	∅	The event is running.	● RULE: Moderator Messages Auto-Accepted	● SCENARIO: Answer an Attendee Directly , ● SCENARIO: Seed the Conversation as Moderator
	Description						
	The moderator answers attendees publicly or privately and seeds the conversation, where the messages are accepted at once upon creation under the sender name “Moderator” unless overridden						
Use All Tags	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Moderator	● ENTITY: QuestionTag	Read	∅	∅	∅	● SCENARIO: Approve and Forward Question
	Description						
	The moderator uses every tag of the event on questions, including the ones reserved for moderators						
Enter the Event	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Presenter	● ENTITY: Event	Read	● STATE: Planning , ● STATE: Published , ● STATE: Running	The presenter holds the Presenter role of the event.	∅	● USE-CASE: Present Forwarded Questions
	Description						
	The presenter sees the event with its agenda and presenter alert, also before it is published for the rehearsal						

● PERMISSION	Properties & Description						
	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
Confirm the Alert ⚓	● ROLE: Presenter ⌘	● ENTITY: Event ⌘	Update	● STATE: Running ⌘	The update is confined to unraising the presenter alert of the event.	∅	● SCENARIO: O: Confirm a Raised Alert ⌘
Description							
The presenter confirms a raised alert, which takes it off the stage view again							
	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
Read Forwarded Questions ⚓	● ROLE: Presenter ⌘	● ENTITY: Message ⌘	Read	● STATE: Forwarded ⌘ , ● STATE: Answered ⌘ , ● STATE: Suspended ⌘	∅	● RULE: Forwarded Messages Are Immutable ⌘	● SCENARIO: O: Answer Forwarded Question ⌘ , ● SCENARIO: O: Forwarded Questions Only ⌘
Description							
The presenter sees the forwarded questions in their order with the moderator hints, and never the pending, accepted, or rejected messages							
	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
Process Forwarded Questions ⚓	● ROLE: Presenter ⌘	● ENTITY: Message ⌘	● TRANSITION: answer ⌘ , ● TRANSITION: suspend ⌘	∅	∅	∅	● SCENARIO: O: Answer Forwarded Question ⌘ , ● SCENARIO: O: Suspend a Forwarded Question ⌘
Description							
The presenter marks a forwarded question answered once addressed on stage, or suspended when it will not be addressed							
	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
Configure the Event ⚓	● ROLE: Manager ⌘	● ENTITY: Event ⌘	Read , Update	∅	The manager holds the Manager role of the event.	● RULE: Manager Retained for Export ⌘	● USE-CASE: Configure the Event ⌘ , ● SCENARIO: O: Export After Finish ⌘

● PERMISSION	Properties & Description						
	Description						
	The manager reads and edits every setting of the event in every state, keeping the access after the event finishes for the export						
Run the Event ⚓	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Manager ⓘ	● ENTITY: Event ⓘ	● TRANSITION: publish ⓘ, ● TRANSITION: start ⓘ, ● TRANSITION: start ⓘ, ● TRANSITION: finish ⓘ	∅	∅	● RULE: Anonymization on Event Finish ⓘ	● USE-CASE: Publish, Start, and Finish Event ⓘ
	Description						
	The manager publishes, starts, and finishes the event, where finishing triggers the anonymization						
Delete the Event ⚓	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Manager ⓘ	● ENTITY: Event ⓘ	Delete	∅	The manager holds the Manager role of the event.	● RULE: Manager Retained for Export ⓘ, ● RULE: No Permanent User Accounts ⓘ	● SCENARIO: Delete the Event ⓘ
	Description						
	The manager deletes the event entirely, which deletes the remaining Manager roles with it						
Lay Out the Channels ⚓	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Manager ⓘ	● ENTITY: Channel ⓘ	Create, Read, Update, Delete	∅	The channel belongs to the event the manager holds the Manager role of.	● RULE: Single Active Channel ⓘ	● SCENARIO: Lay Out the Channels ⓘ
	Description						
	The manager defines the channels of the event and switches the active one						
Switch the Resource ⚓	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Manager ⓘ	● ENTITY: Resource ⓘ	Read, Update	∅	The update is confined to activating a resource	● RULE: Single Active Resource	● SCENARIO: Lay Out the Channels ⓘ,

● PERMISSION	Properties & Description						
					of a channel of the event.	per Channel ⌘	● SCENARIO: Live Failover ⌘
	Description						
	The manager switches the active resource of a channel to a fallback streaming provider, without changing the provider parameters						
Grant Event Roles ⚓	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Manager ⌘	● ENTITY: Role ⌘	Create , Read , Delete	∅	The role is held by a user of the event the manager holds the Manager role of.	● RULE: No Permanent User Accounts ⌘, ● RULE: Anonymization on Event Finish ⌘	● SCENARIO: Grant the Event Roles ⌘
	Description						
	The manager grants and revokes the Attendee, Manager, Moderator, and Presenter roles of the users of the event, identified by email						
Maintain the Access List ⚓	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Manager ⌘	● ENTITY: User ⌘	Create , Read , Update , Delete	∅	The user is on the access list of the event the manager holds the Manager role of.	● RULE: Access Requires List or Pattern Match ⌘, ● RULE: No Permanent User Accounts ⌘	● SCENARIO: Maintain the Access List ⌘, ● SCENARIO: Import and Return URLs ⌘
	Description						
	The manager invites attendees by email, individually or by importing the sheet of the Event Registration System, and removes them again, where a removed user without a role ceases to exist						
Issue Access Tokens ⚓	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Manager ⌘	● ENTITY: AuthorizationToken ⌘	Create , Read	● STATE: Issued ⌘	The token belongs to the event the manager holds the Manager role of.	● RULE: Token Format and Validity ⌘	● SCENARIO: Import and Return URLs ⌘
	Description						
	The manager pre-generates the tokens of the imported attendees and exports their personal access URLs, seeing the tokens in state issued only						

● PERMISSION	Properties & Description						
Curate the Tags 	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Manager 	● ENTITY: QuestionTag 	Create , Read , Update , Delete	∅	The tag belongs to the event the manager holds the Manager role of.	∅	● SCENARIO: ○: Curate the Tags 
Description							
The manager defines the tag vocabulary of the event, including the tags reserved for moderators							
Curate the Agenda 	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Manager 	● ENTITY: AgendaPoint 	Create , Read , Update , Delete	∅	The agenda point belongs to the event the manager holds the Manager role of.	∅	● SCENARIO: ○: Curate the Agenda 
Description							
The manager defines the ordered agenda of the event and the tags corresponding to its points							
Export the Messages 	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Manager 	● ENTITY: Message 	Read	∅	The message belongs to the event the manager holds the Manager role of.	● RULE: Likes Conserved as Count on Finish  , ● RULE: Manager Retained for Export 	● SCENARIO: ○: Export After Finish 
Description							
The manager reads every message of the event with its texts, timestamps, state, and like count, and exports them after the event has finished							
Inspect the Event Statistics 	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Manager 	● ENTITY: EventStatistic 	Read	∅	The statistic belongs to the event the manager holds the Manager role of.	∅	● SCENARIO: ○: Inspect the Event Statistics 
Description							
The manager inspects the curve of logged-in attendees and the login challenge counts over time							

● PERMISSION	Properties & Description						
	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
Inspect the Channel Statistics ⚓	● ROLE: Manager Ⓜ	● ENTITY: ChannelStatistic Ⓜ	Read	∅	The statistic belongs to a channel of the event the manager holds the Manager role of.	∅	● SCENARIO: Inspect the Event Statistics Ⓜ
	Description						
	The manager inspects the number of viewers per channel over time						
Inspect the Viewer Statistics ⚓	● ROLE: Manager Ⓜ	● ENTITY: UserStatistic Ⓜ	Read	∅	The statistic belongs to a user of the event the manager holds the Manager role of.	∅	● SCENARIO: Inspect the Event Statistics Ⓜ
	Description						
	The manager inspects the audience composition by country, browser, device, and viewport						
Administer Every Event ⚓	● ROLE: Administrator Ⓜ	● ENTITY: Event Ⓜ	Create , Read , Update , Delete , ● TRANSITION: publish Ⓜ , ● TRANSITION: start Ⓜ , ● TRANSITION: start Ⓜ , ● TRANSITION: finish Ⓜ	∅	∅	● RULE: Administrator Bypasses the Access List Ⓜ , ● RULE: Anonymization on Event Finish Ⓜ	● USE-CASE: Administer Any Event Ⓜ , ● SCENARIO: Reach an Event via the Overview Ⓜ
	Description						
	The administrator provisions the events through the configuration and lists, enters, configures, runs, and deletes every event in every state through the user interface, without any access list entry						
Administer the Agenda ⚓	● ROLE: Administrator Ⓜ	● ENTITY: AgendaPoint Ⓜ	Create , Read , Update , Delete	∅	∅	∅	● USE-CASE: Administer Any Event Ⓜ

● PERMISSION	Properties & Description						
	Description						
	The administrator curates the agenda of every event and advances its active agenda point						
Administer the Channels 	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Administrator 	● ENTITY: Channel 	Create , Read , Update , Delete	∅	∅	● RULE: Single Active Channel 	● USE-CASE: Administer Any Event 
	Description						
	The administrator provisions the initial channels through the configuration and lays out the channels of every event, including the active one						
Administer the Resources 	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Administrator 	● ENTITY: Resource 	Create , Read , Update , Delete	∅	∅	● RULE: Single Active Resource per Channel 	● USE-CASE: Administer Any Event 
	Description						
	The administrator binds the resources of every channel to the configured streaming providers and switches the active resource						
Administer the Provider Parameters 	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Administrator 	● ENTITY: ResourceProviderParam 	Create , Read , Update , Delete	∅	∅	∅	● USE-CASE: Administer Any Event 
	Description						
	The administrator supplies and changes the key-value parameters each streaming provider needs to address its stream						
Administer the Roles 	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Administrator 	● ENTITY: Role 	Create , Read , Delete	∅	The role is not an Administrator role, which the configuration alone grants and revokes.	● RULE: Administrator or Bootstrapped by Configuration  , ● RULE: Manager Retained for Export 	● USE-CASE: Administer Any Event 
	Description						
	The administrator grants the initial Manager role of a provisioned event through the configuration and grants and revokes every Attendee, Manager, Moderator, and Presenter role of every event						

● PERMISSION	Properties & Description						
Administer the Users 	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Administrator 	● ENTITY: User 	Create , Read , Update , Delete	∅	∅	● RULE: Access Requires List or Pattern Match  , ● RULE: No Permanent User Accounts 	● USE-CASE: Administer Any Event 
	Description						
	The administrator maintains the access list and the users of every event, personal data included						
Administer the Messages 	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Administrator 	● ENTITY: Message 	Create , Read , Update , Delete , ● TRANSITION: accept  , ● TRANSITION: reject  , ● TRANSITION: forward  , ● TRANSITION: answer  , ● TRANSITION: suspend  , ● TRANSITION: resubmit 	∅	∅	∅	● USE-CASE: Administer Any Event 
	Description						
	The administrator reads, moderates, forwards, settles, edits, and deletes every message of every event in every state						
Administer the Message Texts 	○ ROLE	○ ENTITY	○ OPERATION S	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Administrator 	● ENTITY: MessageText 	Create , Read , Update , Delete	∅	∅	∅	● USE-CASE: Administer Any Event 
	Description						
	The administrator reads and corrects the language-specific texts of every message						


● PERMISSION	Properties & Description						
Administer the Tags ⚓	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Administrator Ⓜ	● ENTITY: QuestionTag Ⓜ	Create, Read, Update, Delete	∅	∅	∅	● USE-CASE: Administer Any Event Ⓜ
	Description The administrator curates the tag vocabulary of every event, including the tags reserved for moderators						
Administer the Authorization Tokens ⚓	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Administrator Ⓜ	● ENTITY: AuthorizationToken Ⓜ	Create, Read, Update, Delete, ● TRANSITION: send Ⓜ , ● TRANSITION: consume Ⓜ , ● TRANSITION: consume Ⓜ	∅	∅	● RULE: Administrator Bypasses the Access List Ⓜ , ● RULE: Token Format and Validity Ⓜ	● USE-CASE: Administer Any Event Ⓜ
	Description The administrator passes the login challenge of the configured administrator email address without any access list check, and issues, inspects, and revokes the tokens of every event						
Administer the Sessions ⚓	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Administrator Ⓜ	● ENTITY: SessionToken Ⓜ	Create, Read, Update, Delete	∅	∅	● RULE: Single Active Session per Event Ⓜ	● USE-CASE: Administer Any Event Ⓜ
	Description The administrator inspects and terminates the sessions of every event						
Administer the Event Statistics ⚓	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Administrator Ⓜ	● ENTITY: EventStatistic Ⓜ	Create, Read, Update, Delete	∅	∅	∅	● USE-CASE: Administer Any Event Ⓜ
	Description The administrator inspects and prunes the event statistics of every event						
Administer the Channel Statistics ⚓	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Administrator Ⓜ	● ENTITY: ChannelStatistic Ⓜ	Create, Read	∅	∅	∅	● USE-CASE: Administer

● PERMISSION	Properties & Description						
Administer the Viewer Statistics ⚓			Update , Delete				Any Event Ⓜ
	Description						
	The administrator inspects and prunes the channel statistics of every event						
Administer the Viewer Statistics ⚓	○ ROLE	○ ENTITY	○ OPERATIONS	○ STATES	○ CONDITION	○ RULES	○ USE-CASES
	● ROLE: Administrator Ⓜ	● ENTITY: UserStatistic Ⓜ	Create , Read , Update , Delete	∅	∅	∅	● USE-CASE: Administer Any Event Ⓜ
	Description						
	The administrator inspects and prunes the viewer statistics of every event						

14 ● APIS: Interface Model (IM) [⚓](#)

● INTERFACE	Properties & Description	
Server Command Line ⚓	Diagram	
	<pre>graph LR LogLevel[TYPE LogLevel] -- interfaces --> SCL[INTERFACE Server Command Line] Configuration[TYPE Configuration] -- interfaces --> SCL broadcast_server[ENDPOINT broadcast-server] -- interface --> SCL Service[COMPONENT Service] -- provides --> SCL</pre>	
	○ KIND	○ LOCATION
	CLI	broadcast-server
		○ CONSUMERS
		● PERSONA: Sven Ⓜ
Description		
The command-line program starting the server process of the service layer, which resolves its runtime parameters from the layered configuration of built-in defaults, an optional YAML configuration file, BROADCAST_* environment variables, and the command-line options (in increasing precedence) — BECAUSE the administrator and the deployment automation have to start the very same server with different parameters per environment without changing any file.		


15 ● APIS: Interface Datatypes (ID) [⚓](#)



15.01 ● **TYPE: LogLevel** [⚓](#)

- INTERFACES ● **INTERFACE: Server Command Line** [ⓘ](#)
- BASE enum(error,warning,info,debug)

The verbosity level of the server log, from errors only up to debugging details — **BECAUSE** the amount of log output has to be tuned per environment.

15.02 ● **TYPE: Configuration** [⚓](#)

- INTERFACES ● **INTERFACE: Server Command Line** [ⓘ](#)


The structure of the YAML configuration file, whose keys are also the surface of the recognized BROADCAST_* environment variables (BROADCAST_ADMIN_USERNAME maps onto adminUsername) and of the corresponding command-line options, where an unrecognized key is a fatal startup error — **BECAUSE** one schema has to define all three configuration layers consistently.


● FIELD	○ TYPE	○ DEFAULT	○ CONSTRAINT	Description
adminUsername ⚓	string	∅	non-empty	The user name of the administrator account — BECAUSE the administrator has to be able to log in without any event-specific token
adminPassword ⚓	string	∅	non-empty	The password of the administrator account — BECAUSE the administrator account has to be protected
mqttUrl ⚓	string	● CONSTANT: DEFAULT_MQTT_URL ⓘ	∅	The URL of the MQTT broker the server connects to, including the credentials and the topic prefix — BECAUSE the server exchanges all live data through the broker
dbUrl ⚓	string	● CONSTANT: DEFAULT_DB_URL ⓘ	∅	The URL of the PostgreSQL database the server persists into — BECAUSE the authoritative state has to be stored in the database tier
directory ⚓	string	● CONSTANT: DEFAULT_DIRECTORY ⓘ	∅	The directory of the static client content the server delivers — BECAUSE the client bundle is distributed alongside the server
logLevel ⚓	● TYPE: LogLevel ⓘ	info	∅	The verbosity level of the server log — BECAUSE the amount of log output has to be tuned per environment

● FIELD	○ TYPE	○ DEFAULT	○ CONSTRAINT	Description
workers ↗	integer	1	1..n	The number of worker processes the primary process pre-forks — BECAUSE the load-balanced traffic of the broker has to be spread over several processes

● CONSTANT	○ TYPE	○ VALUE	Description
ENV_PREFIX ↗	string	BROADCAST_	The prefix of all environment variables overriding configuration parameters, where a double underscore separates the nesting path segments and a single underscore the words of one camel-cased segment — BECAUSE the server has to ignore the unrelated variables of the ambient environment
DEFAULT_MQTT_URL ↗	string	wss://example:example@127.0.0.1:1883/pr/api/server/?topic=broadcast	The built-in default of the MQTT broker URL — BECAUSE the server has to start against a local broker without any configuration
DEFAULT_DB_URL ↗	string	postgres://127.0.0.1:5432/broadcast	The built-in default of the PostgreSQL database URL — BECAUSE the server has to start against a local database without any configuration
DEFAULT_DIRECTOR ↗	string	client/dst	The built-in default of the static content directory, resolved relative to the installation of the server — BECAUSE the client bundle is built next to the server by default
RESPAWN_DELAY ↗	duration	1000 ms	The backoff delay before an unexpectedly dead worker process is respawned — BECAUSE a tight crash-loop would hammer the broker and the database

16 ● APIS: Interface Endpoints (IE) [↗](#)



16.01 ● **ENDPOINT: broadcast-server** 

○ INTERFACE	● INTERFACE: Server Command Line 
○ PERMISSIONS	● PERMISSION: Administer Every Event  , ● PERMISSION: Administer the Channels  , ● PERMISSION: Administer the Resources  , ● PERMISSION: Administer the Provider Parameters  , ● PERMISSION: Administer the Roles 
○ OPERATION	command
○ LOCATOR	broadcast-server [options]


The sole command of the program, which loads the layered configuration, brings the database schema up to date, pre-forks the configured number of worker processes, supervises them (respawning a dead one after the ● **RESPAWN_DELAY**), and runs until it receives a SIGINT or SIGTERM signal, which it forwards to all workers before terminating gracefully — **BECAUSE** the server is a long-running daemon whose process model has to stay uniform even for a single worker.

● OPTION	○ TYPE	○ ALIAS	○ DEFAULT	○ CONSTRAINT	Description
—version 	boolean	—V	false	∅	Prints the name and version of the program and exits — BECAUSE the deployed version has to be identifiable
—help 	boolean	—h	false	∅	Prints the usage of the program and exits — BECAUSE the options have to be discoverable on the command line
—log-level 	● TYPE: LogLevel 	—l	info	∅	Overrides the logLevel configuration parameter — BECAUSE the verbosity has to be raised ad-hoc for troubleshooting
—config 	string	—c	∅	readable YAML file	The configuration file of the structure ● Configuration , merged over the built-in defaults — BECAUSE a deployment has to keep its parameters in one versioned file
—env 	string	—e	∅	readable dotenv file	The environment file loaded in addition to, and overriding, the .env file of the current working directory — BECAUSE secrets have to be injected without appearing in the configuration file or the command line

● OPTION	○ TYPE	○ ALIAS	○ DEFAULT	○ CONSTRAINT	Description
<code>--admin-username</code> 	string	<code>-u</code>	∅	∅	Overrides the <code>adminUsername</code> configuration parameter — BECAUSE the administrator account has to be settable per environment
<code>--admin-password</code> 	string	<code>-p</code>	∅	∅	Overrides the <code>adminPassword</code> configuration parameter — BECAUSE the administrator account has to be settable per environment
<code>--mqtt-url</code> 	string	<code>-m</code>	● CONSTANT: <code>DEFAULT_MQTT_URL</code> 	∅	Overrides the <code>mqttUrl</code> configuration parameter — BECAUSE the broker differs per environment
<code>--db-url</code> 	string	<code>-D</code>	● CONSTANT: <code>DEFAULT_DB_URL</code> 	∅	Overrides the <code>dbUrl</code> configuration parameter — BECAUSE the database differs per environment
<code>--directory</code> 	string	<code>-d</code>	● CONSTANT: <code>DEFAULT_DIRECTORY</code> 	existing directory	Overrides the <code>directory</code> configuration parameter — BECAUSE the client bundle may be deployed apart from the server
<code>--workers</code> 	integer	<code>-w</code>	1	1..n	Overrides the <code>workers</code> configuration parameter, rejecting a non-positive or non-integer value as a usage error — BECAUSE the process count has to match the CPU resources of the environment

● RESULT	○ TYPE	○ ARITY	○ CONSTRAINT	Description
<code>log</code> 	text	*	∅	The log lines written to the standard output, each carrying the timestamp, the level, and the originating primary or worker process, with the credentials of all URL-valued parameters redacted — BECAUSE the operator has to trace the server without ever seeing a secret
<code>exit-code</code> 	integer	∅	0 or 1	The process exit code, 0 after a graceful termination, after <code>--help</code> , and after <code>--version</code> , and 1 after a usage error, an invalid configuration, a failed database migration, or a failed shutdown — BECAUSE the process supervisor has to tell a clean stop from a failure

17 ● UXUI: Interaction Concept (IC)




● PRINCIPLE

Moderation-Gated Visibility

Properties & Description

Diagram



○ CATEGORY

Expectation-Conformity

○ ACTORS

- **PERSONA:** Anna ,
- **PERSONA:** Markus ,
- **PERSONA:** Peter 

○ MOTIVATED-BY

- **STEP:** Watch stream and interact 

○ USE-CASES

- **USE-CASE:** Ask a Question ,
- **SCENARIO:** Pending Message Stays Private ,
- **SCENARIO:** Edit an Own Message ,
- **USE-CASE:** Moderate and Forward Messages 

○ TRADE-OFF


The liveliness of an unmoderated stream in which every input is public the moment it is sent

Description

Attendee input is acknowledged immediately as submitted but becomes publicly visible only after moderation when enabled, with its state clearly indicated to the author — **BECAUSE** authors must trust their input arrived while organizers retain control

Privacy-Visible Identity

Diagram



○ CATEGORY

Self-Descriptiveness

○ ACTORS

Ø

○ MOTIVATED-BY

- **STEP:** Open event page and review login info 

○ USE-CASES

- **SCENARIO:** Post a Chat Message ,
- **SCENARIO:**

○ TRADE-OFF

Full anonymity of all participants, which would

Description

Names are shown according to the event's anonymity

● PRINCIPLE	Properties & Description		
	Switch the Language ⓘ, ● SCENARIO: Seed the Conversation as Moderator ⓘ ⓘ	spare the anonymity setting and the hover reveal	setting while the email remains discoverable on hover, and AI-translated text is always marked distinct from the human original — BECAUSE participants must always know who said what and in which language
Frictionless Joining ⓘ	Diagram		
○ CATEGORY	○ ACTORS	○ MOTIVATED-BY	
Task-Suitability ⓘ	● PERSONA: Anna ⓘ	● STEP: Open event page and review login info ⓘ, ● STEP: Authenticate via email token ⓘ	
○ USE-CASES	○ TRADE-OFF	Description	
● USE-CASE: Join Event and Watch Stream ⓘ, ● USE-CASE: Authenticate via Email Token ⓘ	An explicit registration with a permanent account, which would give organizers richer attendee profiles	The attendee is carried into the event with the least possible effort, with email and token pre-filled from the URL where available and automatic access when a valid token is embedded — BECAUSE large audiences must enter quickly without a support burden	
Live Reactivity ⓘ	Diagram		
○ CATEGORY	○ ACTORS	○ MOTIVATED-BY	
Self-Descriptiveness ⓘ	⊘	● STEP: Watch stream and interact ⓘ, ● STEP: Moderate and support the presenter ⓘ	
○ USE-CASES	○ TRADE-OFF	Description	
● SCENARIO: Lay Out the Channels ⓘ, ● USE-CASE: Switch Streaming Provider	Lower server load and simpler clients through polling or a manual reload	Every configuration change, provider switch, and moderation outcome is	

● PRINCIPLE	Properties & Description		
	⌘, ● USE-CASE: Steer the Presenter ⌘, ● SCENARIO: Approve and Forward Question ⌘, ● USE-CASE: Present Forwarded Questions ⌘		pushed to connected clients over WebSockets so the UI updates without a reload — BECAUSE a live event demands that all participants see a single, current state at all times
Validate Before Going Live ⚓	Diagram		
○ CATEGORY	○ ACTORS	○ MOTIVATED-BY	
Error-Robustness	● PERSONA: Manfred ⌘	● STEP: Configure and run the event ⌘	
○ USE-CASES	○ TRADE-OFF	Description	
● SCENARIO: Lay Out the Channels ⌘, ● USE-CASE: Create Event from Registration Import ⌘	The freedom to save any partial or inconsistent configuration unchecked	Imported attendee lists and streaming settings are validated at entry and problems are reported in place before the event starts — BECAUSE a configuration mistake surfacing during the broadcast hits the whole audience at once	
Never Leave the Stream ⚓	Diagram		
○ CATEGORY	○ ACTORS	○ MOTIVATED-BY	
Controllability	● PERSONA: Anna ⌘	● STEP: Watch stream and interact ⌘	

● PRINCIPLE	Properties & Description		
	○ USE-CASES ● SCENARIO: Switch the Language ⓘ, ● SCENARIO: Toggle the Theme ⓘ, ● SCENARIO: Show Own Contributions Only ⓘ	○ TRADE-OFF A dedicated settings page with room for more options than the header can hold	Description Every adjustment available to the attendee, like language, theme, or the interaction tab, is made in place from the event screen, applies immediately, and can be reverted at any time — BECAUSE navigating away from a live stream means missing part of the event
Correct over Confirm ⓘ	Diagram		
	○ CATEGORY	○ ACTORS	○ MOTIVATED-BY
	Error-Robustness	● PERSONA: Anna ⓘ	● STEP: Watch stream and interact ⓘ
	○ USE-CASES	○ TRADE-OFF	Description
	● SCENARIO: Post a Chat Message ⓘ, ● SCENARIO: Like a Message ⓘ, ● SCENARIO: Edit an Own Message ⓘ, ● SCENARIO: Delete an Own Message ⓘ	A confirmation step before every submission, which would reduce mistaken posts at the cost of interrupting the flow	Input is sent without a confirmation step and corrected afterwards instead, as the attendee can edit and delete their own messages while a deleted message leaves a placeholder — BECAUSE a fast conversation tolerates a repaired mistake better than a delay before every message
Familiar Conventions ⓘ	Diagram		
	○ CATEGORY	○ ACTORS	○ MOTIVATED-BY
	Learnability	● PERSONA: Anna ⓘ	∅
	○ USE-CASES	○ TRADE-OFF	Description
	● USE-CASE: Chat During the Event ⓘ, ● SCENARIO: Login with Emailed Token ⓘ	Novel interaction forms tailored to the event format, which would be more expressive but need explaining	Chat, questions, and likes look and behave like the consumer messengers the attendee already knows, so that the login message is the only instruction an

● PRINCIPLE	Properties & Description			
			attendee ever reads — BECAUSE a one-time audience has neither the time nor the motivation to learn a new tool	
One-Tap Contribution	Diagram			
	<pre>graph LR IC[PATTERN Inline Composer] -- principles --> OT[PRINCIPLE One-Tap Contribution] OT -- motivated-by --> A[PERSONA Anna] OT -- use-cases --> WSI[STEP Watch stream and interact] OT -- use-cases --> AQ[USE-CASE Ask a Question] OT -- use-cases --> CDE[USE-CASE Chat During the Event]</pre>			
	○ CATEGORY	○ ACTORS	○ MOTIVATED-BY	
	Engagement	● PERSONA: Anna	● STEP: Watch stream and interact	
	○ USE-CASES	○ TRADE-OFF	Description	
● SCENARIO: Submit Moderated Question , ● SCENARIO: Post a Chat Message , ● SCENARIO: Like a Message , ● SCENARIO: Answer a Multiple-Choice Poll	Richer contributions like threads, attachments, or formatting, which would raise the bar for taking part	A like is a single tap and a message is a single field plus send, with the emoji picker as the only enrichment — BECAUSE the more attendees contribute during the event, the livelier it feels for everyone watching		

18 ● UXUI: Language Conventions (LC) [↕](#)

Plain Organizer Voice CATEGORY: Voice	Neutral Operational Tone CATEGORY: Tone	Second-Person Address CATEGORY: Grammar	Product Name Spelling CATEGORY: Capitalization
Anonymous Placeholder CATEGORY: Vocabulary	Token Display Format CATEGORY: Formatting		

● CONVENTION	Properties & Description		
Plain Organizer Voice ↕	○ CATEGORY	○ ACTORS	○ PRINCIPLES
	Voice	∅	● PRINCIPLE: Familiar Conventions ↕
	○ TERMS	○ EXAMPLE	Description
	∅	“The event starts at 10:00.”, not “Get ready, the show is about to begin!”	The solution speaks with the plain, factual voice of the event organizer, never with a playful or marketing persona of its own — BECAUSE attendees join for the event, not for the tool, and the tool must not compete with the presenter for attention

● CONVENTION	Properties & Description		
Neutral Operational Tone ⚓	○ CATEGORY	○ ACTORS	○ PRINCIPLES
	Tone	● PERSONA: Anna ⓘ	● PRINCIPLE: Correct over Confirm ⓘ , ● PRINCIPLE: Familiar Conventions ⓘ
	○ TERMS	○ EXAMPLE	Description
	∅	“You are not authorized for this event.”, not “Access forbidden!”	User-facing system messages use a calm, neutral, and concise tone that informs without alarming, especially around access denial and connection changes — BECAUSE a one-time audience has no way to recover from a message that sounds like an accusation
Second-Person Address ⚓	○ CATEGORY	○ ACTORS	○ PRINCIPLES
	Grammar	∅	∅
	○ TERMS	○ EXAMPLE	Description
	∅	“Your message was sent.”, not “The user’s message has been sent.”	The solution addresses the user as “you” and never refers to itself as “I” or “we” — BECAUSE direct address is the shortest wording and avoids the false impression of a person behind the interface
Product Name Spelling ⚓	○ CATEGORY	○ ACTORS	○ PRINCIPLES
	Capitalization	∅	∅
	○ TERMS	○ EXAMPLE	Description
	∅	“Broadcast”, not “broadcast” or “BROADCAST”	The product is always written “Broadcast” — BECAUSE a single spelling keeps the product recognizable and distinct from the generic verb
Anonymous Placeholder ⚓	○ CATEGORY	○ ACTORS	○ PRINCIPLES
	Vocabulary	● PERSONA: Anna ⓘ	● PRINCIPLE: Privacy-Visible Identity ⓘ
	○ TERMS	○ EXAMPLE	Description
	● TERM: Anonymization ⓘ , ● TERM: Moderator ⓘ	“Anonymous”, not “anonymous user” or “N/A”	When identity is hidden, the displayed sender name is exactly “Anonymous”, and moderator-authored messages default to the sender name “Moderator” — BECAUSE a fixed placeholder reads as a deliberate choice while an ad-hoc wording reads as missing data

● CONVENTION	Properties & Description		
Token Display Format ↕	○ CATEGORY	○ ACTORS	○ PRINCIPLES
	Formatting	∅	∅
	○ TERMS	○ EXAMPLE	Description
	● TERM: Authorization Token ⌵	“123-456”, not “123456”	Authorization tokens are always presented in the grouped six-digit form “NNN-NNN” with a hyphen separator, in emails and on screen alike — BECAUSE the grouping makes a token easy to read aloud and to type from a second device

19 ● UXUI: Dialog Patterns (DP) [↕](#)

Two-Factor Login CATEGORY: Form	Consent Gate CATEGORY: Action	Video-with-Sidebar CATEGORY: Layout	Live Message Stream CATEGORY: List
Inline Composer CATEGORY: Form	Kanban Moderation Board CATEGORY: List	Master-Detail Configuration CATEGORY: Layout	Live Statistics Dashboard CATEGORY: Data

● PATTERN

Two-Factor Login

STORYBOARD

Attendee Joins and Watches

DECISION

Email one-time token as the authentication factor

patterns3

1

affects

PATTERN

Two-Factor Login

principles1

PRINCIPLE

Frictionless Joining

○ CATEGORY

Form

○ PROBLEM

The system must confirm the attendee controls an authorized email without permanent accounts.

○ TRADE-OFF

A second round-trip through the attendee’s mailbox before every access without an embedded token.

○ ACTORS

● PERSONA: Anna

○ PRINCIPLES

● PRINCIPLE: Frictionless Joining

○ CONTEXT

An attendee accessing an event that requires email-verified access.

○ USES

Description

The dialog collects the email, sends a one-time token to it, and then collects that token in a second step, optionally pre-filling fields from the URL — **BECAUSE** a challenge-response over email proves address control with no stored credential.

Consent Gate

STORYBOARD

Attendee Joins and Watches

patterns1

PATTERN

Consent Gate


● PATTERN	Properties & Description		
	○ CATEGORY	○ ACTORS	○ CONTEXT
	Action	● PERSONA: Anna ②	Entry to an event or interaction channel that requires acknowledged terms.
	○ PROBLEM	○ PRINCIPLES	○ USES
	Participation must be blocked until the attendee explicitly accepts the stated conditions.	∅	∅
○ TRADE-OFF	Description		
An interruption of the entry flow the attendee cannot skip, even on repeated visits.	A modal presents the configured login or interaction information with required-to-accept controls and only releases the attendee onward once accepted — BECAUSE explicit acknowledgement is both a legal and psychological safeguard.		
Video-with-Sidebar ①	Diagram		
<pre>graph LR subgraph Storyboards S1[STORYBOARD Attendee Joins and Watches] S2[STORYBOARD Attendee Asks a Tagged Question] S3[STORYBOARD Attendee Reads and Posts Chat] S4[STORYBOARD Attendee Gets Support from a Moderator] S5[STORYBOARD Manager Switches Provider Live] end subgraph Patterns P1[PATTERN Video-with-Sidebar] P2[PATTERN Live Message Stream] P3[PATTERN Inline Composer] end subgraph Principles PR1[PRINCIPLE Never Leave the Stream] end S1 -- patterns --> P1 S2 -- patterns --> P1 S3 -- patterns --> P1 S4 -- patterns --> P1 S5 -- patterns --> P1 P1 -- uses --> P2 P1 -- uses --> P3 P1 -- principles --> PR1</pre>			
○ CATEGORY	○ ACTORS	○ CONTEXT	
Layout	● PERSONA: Anna ②	The main attendee screen during a live event with interaction enabled.	
○ PROBLEM	○ PRINCIPLES	○ USES	
The attendee must watch the stream and interact without either crowding the other.	● PRINCIPLE: Never Leave the Stream ②	● PATTERN: Live Message Stream ②, ● PATTERN: Inline Composer ②	
○ TRADE-OFF	Description		
A smaller video area on wide screens and a sidebar hidden behind a toggle on small screens.	The video occupies the primary area while a tabbed sidebar hosts the Q&A, Hudspad, Chat, and Support tabs, collapsing responsively on small screens — BECAUSE co-locating stream and interaction keeps attention on the event while interaction stays reachable.		

● PATTERN

Live Message Stream

Properties & Description

Diagram



○ CATEGORY

List

○ ACTORS

● PERSONA: Anna 

○ CONTEXT

The chat and Q&A tabs where attendees read and post a continuous flow of messages.

○ PROBLEM

Messages of mixed provenance and state arrive continuously and the attendee must follow them without losing their place.

○ PRINCIPLES

● PRINCIPLE: Live Reactivity ,
 ● PRINCIPLE: Privacy-Visible Identity ,
 ● PRINCIPLE: Familiar Conventions 

○ USES

∅

○ TRADE-OFF


A dense visual vocabulary of alignments, tints, and indicators the attendee has to learn.

Description

Messages render as a scrolling list of bubbles distinguished by provenance and state, with own messages right-aligned, others left-aligned, moderator messages tinted, quoted originals linking back to their source, deleted messages shown as a placeholder, per-message like counts and reply affordances, and floating “new messages” jump indicators above and below — **BECAUSE** clear per-message styling and unread cues let attendees follow a fast, mixed stream without confusion.

Inline Composer

Diagram



○ CATEGORY

Form

○ ACTORS

● PERSONA: Anna 

○ CONTEXT

The bottom of the chat and Q&A tabs where the attendee writes input.

○ PROBLEM

The attendee must compose, send, and see the moderation outcome of their own input within the same stream.

○ PRINCIPLES

● PRINCIPLE: Moderation-Gated Visibility ,
 ● PRINCIPLE: Correct over Confirm ,
 ● PRINCIPLE: One-Tap Contribution 

○ USES

∅


● PATTERN	Properties & Description		
	○ TRADE-OFF	Description	
	A permanently occupied strip of the sidebar, even while the attendee is only reading.	A persistent input field with an emoji picker and send control sits below the message list, and the attendee’s just-sent message appears in the stream marked “pending... / under review” until moderation resolves it — BECAUSE keeping the composer and the input’s own state in one place makes posting and its consequence immediately legible.	
Kanban Moderation Board	Diagram		
	○ CATEGORY	○ ACTORS	○ CONTEXT
List	● PERSONA: Markus ⓘ, ● PERSONA: Peter ⓘ	A moderator triaging a stream of incoming chat and question messages.	
○ PROBLEM	Many messages must be classified and routed quickly with a clear sense of their state.	○ PRINCIPLES ● PRINCIPLE: Live Reactivity ⓘ, ● PRINCIPLE: Moderation-Gated Visibility ⓘ	○ USES ⌀
○ TRADE-OFF	Description		
A wide multi-lane board that needs a desktop-sized screen and drag-capable pointer input.	Messages appear as cards in state lanes (pending, accepted, forwarded, answered) that the moderator advances by action, with filters and manual reordering — BECAUSE spatial state and drag actions make high-throughput triage fast and unambiguous.		
Master-Detail Configuration	Diagram		
	○ CATEGORY	○ ACTORS	○ CONTEXT
Layout	● PERSONA: Manfred ⓘ	A manager configuring an event’s channels, resources, and options.	
○ PROBLEM	A large nested configuration must be navigated and edited without losing orientation.	○ PRINCIPLES ● PRINCIPLE: Validate Before Going Live ⓘ	○ USES ⌀

● PATTERN	Properties & Description	
	○ TRADE-OFF	Description
	The horizontal space of two panes, cramped on small screens, and only one item editable at a time.	A master list of channels and resources on one side drives a detail editor on the other, so selecting an item reveals its parameters for editing — BECAUSE master-detail keeps a large hierarchical configuration navigable and focused.
Live Statistics Dashboard ⚓	Diagram	
		
	○ CATEGORY	○ ACTORS
	Data	● PERSONA: Manfred ⓘ, ● PERSONA: Petra ⓘ
	○ PROBLEM	○ PRINCIPLES
	Operators need an at-a-glance, continuously updating view of audience and channels.	● PRINCIPLE: Live Reactivity ⓘ
	○ TRADE-OFF	○ CONTEXT
	A periodic snapshot cadence, so the charts lag the live state by up to one interval.	A manager or studio screen observing event health during the broadcast.
		○ USES
		∅
		Description
		A dashboard composes a time-series attendee curve with per-channel pie charts that refresh from periodic statistics snapshots — BECAUSE combined trend and distribution views convey event health without manual querying.

20 ● UXUI: Dialog Storyboard (DS) ⚓

Attendee Joins and Watches ACTORS: Anna	Attendee Asks a Tagged Question ACTORS: Anna	Attendee Reads and Posts Chat ACTORS: Anna	Attendee Gets Support from a Moderator ACTORS: Anna, Markus
Chat Moderator Triage Messages ACTORS: Markus	Moderator Forwards to Presenter ACTORS: Peter, Petra	Manager Switches Provider Live ACTORS: Manfred, Anna	Manager Imports Registration Sheet ACTORS: Manfred


20.01 ● STORYBOARD: Attendee Joins and Watches ⚓



○ ACTORS	● PERSONA: Anna ②
○ SCENARIO	● SCENARIO: Join via Individual URL ②


● FRAME	○ SCENARIO-STEP	○ PATTERNS	Description
Event Landing ①	1	● PATTERN: Two-Factor Login ②	The attendee opens the event URL and sees the event title, login message, and an email field
Email Entry ①	2	● PATTERN: Two-Factor Login ②	The attendee enters their email; the system confirms a token has been sent to that address
Token Challenge ①	2	● PATTERN: Two-Factor Login ②	A token field appears with the email read-only; the attendee types the six-digit token
Consent Gate ①	2	● PATTERN: Consent Gate ②	The required login information is shown and the attendee accepts the conditions
Main Screen ①	3	● PATTERN: Video-with-Sidebar ②	The live video plays on the left with the interaction sidebar on the right

20.02 ● STORYBOARD: Attendee Asks a Tagged Question ①




○ ACTORS	● PERSONA: Anna ②
○ SCENARIO	● SCENARIO: Submit Moderated Question ②

● FRAME	○ SCENARIO-STEP	○ PATTERNS	Description
Questions Tab ①	1	● PATTERN: Video-with-Sidebar ②, ● PATTERN: Live Message Stream ②	The attendee selects the questions tab in the sidebar showing existing accepted questions
Compose Question ①	2	● PATTERN: Inline Composer ②	The attendee types a question and the available question tags are offered for selection
Tag and Submit ①	3	● PATTERN: Inline Composer ②	The attendee picks one or more tags and submits the question
Pending Acknowledgement ①	4	● PATTERN: Live Message Stream ②	The question appears in the attendee's own list marked as pending moderation, a rejected one tinted and visible to the author only
Becomes Visible ①	5	● PATTERN: Live Message Stream ②	After approval the question becomes visible and likeable for all attendees

20.03 ● STORYBOARD: Attendee Reads and Posts Chat [⚓](#)

- ACTORS ● PERSONA: Anna [⌵](#)
- SCENARIO ● SCENARIO: Post a Chat Message [⌵](#)

● FRAME	○ SCENARIO-STEP	○ PATTERNS	Description
Chat Tab ⚓	∅	● PATTERN: Video-with-Sidebar ⌵ , ● PATTERN: Live Message Stream ⌵	The attendee opens the Chat tab and sees the scrolling stream with a “2 new messages” jump indicator
Read Mixed Stream ⚓	∅	● PATTERN: Live Message Stream ⌵	Others’ messages show name, time, and like count, an amber moderator message stands out, and a quoted original links back to its source
Like and Reply ⚓	∅	● PATTERN: Live Message Stream ⌵	The attendee likes a message, raising its count, and follows a quoted original link back to its source
Compose and Send ⚓	2	● PATTERN: Inline Composer ⌵	The attendee types in the bottom composer, optionally adds an emoji, and sends the message
Under Review ⚓	4	● PATTERN: Inline Composer ⌵ , ● PATTERN: Live Message Stream ⌵	The attendee’s own message appears right-aligned marked “pending... / under review” until moderation resolves it

20.04 ● STORYBOARD: Attendee Gets Support from a Moderator [⚓](#)

- ACTORS ● PERSONA: Anna [⌵](#), ● PERSONA: Markus [⌵](#)
- SCENARIO ● SCENARIO: Answer an Attendee Directly [⌵](#)


● FRAME	○ SCENARIO-STEP	○ ACTOR	○ PATTERNS	Description
Support Tab ⚓	∅	● PERSONA: Anna ①	● PATTERN: Video-with-Sidebar ① , ● PATTERN: Inline Composer ①	The attendee opens the Support tab, which shows only their own requests, and writes a request for help into the composer
Chat Moderation Board ⚓	1	● PERSONA: Markus ①	● PATTERN: Kanban Moderation Board ①	The moderator reviews the incoming chat messages in the rejected, pending, and accepted lanes beside the stream, the request among them
Direct Reply ⚓	4	● PERSONA: Markus ①	● PATTERN: Inline Composer ①	The moderator writes a reply in the board's composer and marks it as a direct message to the attendee instead of a public one
Reply Received ⚓	5	● PERSONA: Anna ①	● PATTERN: Live Message Stream ①	The attendee sees the amber-tinted moderator reply below their own request in the Support tab, without any further approval step

20.05 ● STORYBOARD: Chat Moderator Triage Messages [⚓](#)



○ ACTORS	● PERSONA: Markus ①
○ SCENARIO	● SCENARIO: Reject Improper Message ①

● FRAME	○ SCENARIO-STEP	○ PATTERNS	Description
Board Overview ⚓	∅	● PATTERN: Kanban Moderation Board ①	The moderator opens the chat moderation board with the stream preview beside the rejected, pending, and accepted lanes, each lane heading counting its messages
Narrow Lane ⚓	∅	● PATTERN: Kanban Moderation Board ①	The moderator narrows a lane through the timestamp and tag label filter chips at its head, collapsing the messages outside the filter
Assess Pending ⚓	∅	● PATTERN: Kanban Moderation Board ①	Each pending card shows the sentiment pre-assessment chip (safe, iffy, risk) beside sender and time, above the outlined reject and filled accept buttons
Reject Improper ⚓	2	● PATTERN: Kanban Moderation Board ①	The moderator clicks reject on an improper message, which leaves the pending lane immediately
Hidden from Audience ⚓	3	● PATTERN: Kanban Moderation Board ①	The card reappears at the top of the rejected lane marked rejected, while the accepted lane the audience sees stays unchanged


20.06 ● **STORYBOARD: Moderator Forwards to Presenter** 

○ ACTORS ● PERSONA: Peter , ● PERSONA: Petra 

○ SCENARIO ● SCENARIO: Approve and Forward Question 

● FRAME	○ SCENARIO-STEP	○ ACTOR	○ PATTERNS	Description
Board Overview 	∅	● PERSONA: Peter 	● PATTERN: Kanban Moderation Board 	The moderator sees question cards in the rejected, pending, accepted, suspended, forwarded, and answered lanes
Filter Pending 	1	● PERSONA: Peter 	● PATTERN: Kanban Moderation Board 	The moderator filters to show only pending questions to focus the triage
Approve Card 	2	● PERSONA: Peter 	● PATTERN: Kanban Moderation Board 	The moderator approves a relevant question, moving it to the accepted lane
Forward with Hint 	3	● PERSONA: Peter 	● PATTERN: Kanban Moderation Board 	The moderator forwards the card to the presenter and attaches a routing hint in the presenter alert
Presenter Basket 	5	● PERSONA: Petra 	∅	The card appears in the presenter's ordered work basket below the acknowledgeable hint and is locked from attendee edits


20.07 ● STORYBOARD: Manager Switches Provider Live



- ACTORS ● PERSONA: Manfred ②, ● PERSONA: Anna ②
- SCENARIO ● SCENARIO: Live Failover ②

● FRAME	○ SCENARIO-STEP	○ ACTOR	○ PATTERNS	Description
Channel Master ⚓	1	● PERSONA: Manfred ②	● PATTERN: Master-Detail Configuration ②	The manager selects the affected channel from the master list of channels
Resource Detail ⚓	1	● PERSONA: Manfred ②	● PATTERN: Master-Detail Configuration ②	The channel's resources are shown with the currently active provider highlighted
Activate Fallback ⚓	2	● PERSONA: Manfred ②	● PATTERN: Master-Detail Configuration ②	The manager activates a different resource as the new active one
Propagation Confirmed ⚓	4	● PERSONA: Manfred ②	∅	The system confirms the change has been pushed to all connected clients
Seamless Switch ⚓	5	● PERSONA: Anna ②	● PATTERN: Video-with-Sidebar ②	Attendee players transition to the new stream with no user action required

20.08 ● STORYBOARD: Manager Imports Registration Sheet



- ACTORS ● PERSONA: Manfred ②

SCENARIO: Import and Return URLs

FRAME	SCENARIO-STEP	PATTERNS	Description
Event Config		PATTERN: Master-Detail Configuration	The manager opens the event configuration, with its basics and event type profile, and selects the attendee import action
Upload Sheet	1		The manager uploads the Excel sheet of the Event Registration System with attendee columns
Import Summary	3		The system reports new users created and existing users skipped, with tokens generated
URL Preview	4		The system shows the composed personal access URLs per attendee
Return Download	5		The manager downloads the returned Excel sheet with the URL column filled for the Event Registration System

21 UXUI: Visual Design (VD)


Brand Color Palette CATEGORY: Color	Light and Dark Theme CATEGORY: Color	Broadcast Wordmark CATEGORY: Brand	Self-Hosted Typography CATEGORY: Typography
Fontawesome Iconography CATEGORY: Iconography	Responsive Spacing Scale CATEGORY: Spacing	Card and Bubble Shape CATEGORY: Shape	Stream Imagery Treatment CATEGORY: Imagery
Subtle State Transitions CATEGORY: Motion			

ELEMENT

Brand Color Palette

Properties & Description



Diagram



CATEGORY	ACTORS	PRINCIPLES	SOURCE
Color		PRINCIPLE: Moderation-Gated Visibility , PRINCIPLE: Privacy-Visible Identity	Tailwind theme configuration of the frontend (tailwind.config.ts), color section

● ELEMENT	Properties & Description			
	○ TRADE-OFF A palette bound to the corporate identity, leaving no room for event-specific branding.	Description The interface uses the msg corporate palette with a primary msg blue for actions, the active channel, and own outgoing messages, neutral surfaces for others’ messages, a warm amber tint for moderator-authored messages and the “under review” state, a red tint for rejected input, and muted italic styling for deleted messages — BECAUSE color-coded message provenance and state give attendees and moderators instant visual feedback.		
Light and Dark Theme ⚓	Diagram MOCKUP Attendee Chat View elements ELEMENT Light and Dark Theme principles PRINCIPLE Familiar Conventions ○ CATEGORY Color ○ ACTORS ∅ ○ PRINCIPLES ● PRINCIPLE: Familiar Conventions Ⓜ ○ SOURCE Tailwind theme configuration of the frontend (tailwind.config.ts), dark mode section ○ TRADE-OFF Every semantic color role has to be defined and checked twice, once per theme. Description The application provides both a light and a dark theme, toggled from a sun/moon control in the header bar and applied consistently across video frame, sidebar, and message bubbles — BECAUSE attendees view events in varied lighting and expect to choose a comfortable appearance.			
Broadcast Wordmark ⚓	Diagram MOCKUP Attendee Chat View elements ELEMENT Broadcast Wordmark MOCKUP Administrator Event Creation elements ○ CATEGORY Brand ○ ACTORS ∅ ○ PRINCIPLES ∅ ○ SOURCE ∅ ○ TRADE-OFF A reserved header strip on every screen, including the space-constrained mobile layouts. Description The product is represented by the “BROADCAST” wordmark with the circled “O” accent in msg blue, placed top-left in the header bar — BECAUSE a distinctive, consistently placed wordmark anchors the brand on every screen.			
Self-Hosted Typography ⚓	Diagram MOCKUP Attendee Chat View elements ELEMENT Self-Hosted Typography MOCKUP Attendee Q&A View elements PERSONA Anna MOCKUP Administrator Event Creation elements PERSONA Petra MOCKUP Presenter View elements ○ CATEGORY Typography ○ ACTORS ● PERSONA: Anna Ⓜ, ● PERSONA: ○ PRINCIPLES ∅ ○ SOURCE TypoPRO font package of the			

● ELEMENT	Properties & Description		
Fontawesome Iconography ⚓		Petra 🔗	frontend (@typopro/web-*), subsetting at build time
	○ TRADE-OFF	Description	
	A larger initial download than a system font stack, as the font files ship with the application.	Text is set in a self-hosted TypoPRO web font family with a clear type scale for headings, body, and captions, sized for legibility on the studio screen at 2-4 meters viewing distance — BECAUSE self-hosted fonts avoid third-party requests and the studio view must remain readable from afar.	
Fontawesome Iconography ⚓	Diagram		
	<pre>graph LR subgraph Mockups direction TB MC1[MOCKUP Attendee Chat View] MC2[MOCKUP Attendee Q&A View] MC3[MOCKUP Chat Moderation Board] MC4[MOCKUP Q&A Moderation Board] MC5[MOCKUP Presenter View] end MC1 -- elements --> EI[Fontawesome Iconography] MC2 -- elements --> EI MC3 -- elements --> EI MC4 -- elements --> EI MC5 -- elements --> EI EI -- principles --> PC[Familiar Conventions]</pre>		
	○ CATEGORY	○ ACTORS	○ PRINCIPLES
Iconography	∅	● PRINCIPLE: Familiar Conventions 🔗	Fontawesome Free package of the frontend (@fontawesome/fontawesome-free)
○ TRADE-OFF	Description		
A vocabulary limited to the coverage of one icon set, so a missing metaphor is worked around with a text label.	Actions and message states are reinforced with a consistent Fontawesome icon set, pairing icons with text labels for moderation controls — BECAUSE consistent icons speed recognition of repeated moderation actions.		
Responsive Spacing Scale ⚓	Diagram		
	<pre>graph LR subgraph Mockups direction TB MC1[MOCKUP Attendee Chat View] MC2[MOCKUP Attendee Q&A View] MC3[MOCKUP Attendee Support View] MC4[MOCKUP Administrator Event Creation] MC5[MOCKUP Chat Moderation Board] MC6[MOCKUP Q&A Moderation Board] end MC1 -- elements --> EIS[Responsive Spacing Scale] MC2 -- elements --> EIS MC3 -- elements --> EIS MC4 -- elements --> EIS MC5 -- elements --> EIS MC6 -- elements --> EIS EIS -- principles --> PCL[Never Leave the Stream]</pre>		
	○ CATEGORY	○ ACTORS	○ PRINCIPLES
Spacing	∅	● PRINCIPLE: Never Leave the Stream 🔗	Tailwind theme configuration of the frontend (tailwind.config.ts), spacing and screens sections

● ELEMENT	Properties & Description		
	○ TRADE-OFF	Description	
	Fixed breakpoints, so a layout jumps between its arrangements instead of scaling fluidly.	Spacing follows the Tailwind 4px-based scale with a 16px base gutter, and the breakpoints sm (640px), md (768px), and lg (1024px) decide at which widths the video-with-sidebar arrangement collapses into the stacked single column — BECAUSE one shared scale keeps the density of video, sidebar, and boards consistent across the device classes attendees use.	
Card and Bubble Shape	Diagram		
			
○ CATEGORY	○ ACTORS	○ PRINCIPLES	○ SOURCE
Shape	∅	∅	∅
○ TRADE-OFF	Description		
A soft look which relies on subtle tints and hairline borders, demanding a well-tuned contrast in both themes.	Messages, questions, and form fields use rounded rectangles with a 6px corner radius and a hairline border, moderation cards get a subtle elevation shadow, and buttons are pill-shaped with the primary action filled and the secondary action outlined — BECAUSE a uniform shape language lets the color and iconography carry the meaning of an item.		
Stream Imagery Treatment	Diagram		
			
○ CATEGORY	○ ACTORS	○ PRINCIPLES	○ SOURCE
Imagery	● PERSONA: Anna ②	● PRINCIPLE: Never Leave the Stream ②	∅
○ TRADE-OFF	Description		
Letterbox bars on screens whose aspect ratio differs from 16:9, wasting some display area.	The live video occupies a prominent 16:9 frame with a neutral letterbox and a subtle channel and language badge overlay — BECAUSE the stream is the focal content and attendees must see which channel they are watching.		
Subtle State Transitions	Diagram		
			
○ CATEGORY	○ ACTORS	○ PRINCIPLES	○ SOURCE
Motion	∅	● PRINCIPLE: Live Reactivity ②	∅
○ TRADE-OFF	Description		
Transitions short enough to be missed when the user is not	State and configuration changes animate with short, subtle transitions under 200ms, including the seamless cross-fade on a stream provider		

● ELEMENT	Properties & Description	
	looking at the changed region.	switch — BECAUSE gentle motion signals live updates without distracting from the event.

21.01 ● MOCKUP: Attendee Chat View [⚓](#)

○ ACTORS

○ STORYBOARD

○ ELEMENTS

○ IMAGE

● PERSONA: Anna [⌵](#)


● STORYBOARD: Attendee Reads and Posts Chat [⌵](#)

● ELEMENT: Brand Color Palette [⌵](#), ● ELEMENT: Light and Dark Theme [⌵](#), ● ELEMENT: Broadcast Wordmark [⌵](#), ● ELEMENT: Self-Hosted Typography [⌵](#), ● ELEMENT: Fontawesome Iconography [⌵](#), ● ELEMENT: Responsive Spacing Scale [⌵](#), ● ELEMENT: Card and Bubble Shape [⌵](#), ● ELEMENT: Stream Imagery Treatment [⌵](#)

The main attendee screen with the Chat tab open, showing the blue own message, the amber moderator message, the “under review” divider, and the new-messages badge above the letterboxed stream.


21.02 ● MOCKUP: Attendee Q&A View [⚓](#)

○ ACTORS	● PERSONA: Anna ⌵
○ STORYBOARD	● STORYBOARD: Attendee Asks a Tagged Question ⌵
○ ELEMENTS	● ELEMENT: Brand Color Palette ⌵ , ● ELEMENT: Self-Hosted Typography ⌵ , ● ELEMENT: Fontawesome Iconography ⌵ , ● ELEMENT: Responsive Spacing Scale ⌵ , ● ELEMENT: Card and Bubble Shape ⌵



The main attendee screen with the Q&A tab open, showing the filter pills, the tag chips below each question, the pending own question under review, and the red-tinted rejected question.

21.03 ● MOCKUP: Attendee Support View



The main attendee screen with the Support tab open, showing the private exchange of a blue own message and an amber moderator reply above the composer.

21.04 ● MOCKUP: Administrator Event Creation

○ ACTORS

○ ELEMENTS

○ IMAGE

● PERSONA: Sven

● ELEMENT: Brand Color Palette, ● ELEMENT: Broadcast Wordmark, ● ELEMENT: Self-Hosted Typography, ● ELEMENT: Responsive Spacing Scale, ● ELEMENT: Card and Bubble Shape

BROADCAST

Administrator

DE EN

User

Create new Event

Basics

Title

user input

note

Language

de

Datum

tt.mm.jjjj

Von

00:00

Bis

00:00

note

Beschreibung

type input

Select event type

Conference

Townhall

Event

Meeting

Lecture

200 - moderated

10000 - moderated

10000 - moderated

150 - (un)moderated

75 - unmoderated

Townhall profile applied: closed msg-group access, moderated chat and questions, large audience. Adjust anything below. (2500-10000 attendees)

The event creation form of the administrator, showing the type scale of the headings, the outlined form fields, the event type selector with the filled selected profile, and the blue-tinted profile summary.

21.05 ● MOCKUP: Chat Moderation Board

○ ACTORS


○ STORYBOARD

○ ELEMENTS

● PERSONA: Markus

● STORYBOARD: Chat Moderator Triages Messages

● ELEMENT: Brand Color Palette, ● ELEMENT: Fontawesome Iconography, ● ELEMENT: Responsive Spacing Scale, ● ELEMENT: Card and Bubble Shape, ● ELEMENT: Stream Imagery Treatment



The chat moderation board with the stream preview beside the rejected, pending, and accepted columns, showing the elevated pending cards with their outlined reject and filled accept buttons and the AI assessment chips.

21.06 ● MOCKUP: Q&A Moderation Board 📌

○ ACTORS

○ STORYBOARD

○ ELEMENTS

○ IMAGE

● PERSONA: Peter 📌


● STORYBOARD: Moderator Forwards to Presenter 📌

● ELEMENT: Brand Color Palette 📌, ● ELEMENT: Fontawesome Iconography 📌, ● ELEMENT: Responsive Spacing Scale 📌, ● ELEMENT: Card and Bubble Shape 📌

A mockup of the Broadcast Q&A Moderation Board. The interface is similar to the previous one but with different categories. The columns are: 'rejected' (4 items), 'pending' (26 items), 'accepted' (6 items), 'suspended' (4 items), 'forwarded' (5 items), and 'answered' (3 items). Each column shows a list of chat messages with a timestamp, chat name, and a moderation chip (e.g., 'rejected', 'pending', 'accepted', 'suspended', 'forwarded', 'answered'). The 'pending' column has 'reject' and 'accept' buttons. The 'accepted' column has a 'tag label' dropdown. The 'suspended' column has 'suspend' and 'forward' buttons. The 'forwarded' column has a 'tag label' dropdown. The 'answered' column has a 'tag label' dropdown. At the bottom right, there's a 'Presenter Alert' section with a 'Video' toggle and a 'This is a message to the Presenter.' notification.


The all-in-one Q&A moderation board with the rejected, pending, accepted, suspended, forwarded, and answered columns, showing the amber moderator annotations and the presenter alert composer.

21.07 ● MOCKUP: Presenter View



The presenter view for the studio screen with the enlarged type scale, the amber presenter alert banner, the forwarded questions with their filled answer buttons, and the private moderator chat.

22 ● ARCH: Context View (CV)





● ENTITY	Properties & Description			
Attendee ↕	○ KIND Person	○ DIRECTION Bidirectional	○ VIA ∅	○ TERMS ● TERM: Attendee ↕
	○ ACTORS ● ROLE: Attendee ↕	○ USE-CASES ● USE-CASE: Join Event and Watch Stream ↕ , ● USE-CASE: Authenticate via Email Token ↕ , ● USE-CASE: Ask a Question ↕ , ● USE-CASE: Chat During the Event ↕	○ PREMISES ● PREMISE: Attendee Networks Pass WebSocket Traffic ↕	○ DATA Login credentials, video playback, chat, questions, likes
Description				
The attendee is the person who authenticates, watches the stream, and interacts, through the browser-based web client of the solution — BECAUSE Broadcast is a browser-delivered solution serving thousands of concurrent attendees.				
Event Operator ↕	○ KIND Person	○ DIRECTION Bidirectional	○ VIA ∅	○ TERMS ● TERM: Manager ↕ , ● TERM: Moderator ↕ , ● TERM: Presenter ↕
	○ ACTORS ● ROLE: Moderator ↕ , ● ROLE: Presenter ↕ , ● ROLE: Manager ↕	○ USE-CASES ● USE-CASE: Configure the Event ↕ , ● USE-CASE: Create Event from Registration Import ↕ , ● USE-CASE: Switch Streaming Provider ↕ , ● USE-CASE: Publish, Start, and Finish Event ↕ , ● USE-CASE: Export Anonymized Event Data ↕ , ● USE-CASE: Moderate and Forward Messages ↕ , ● USE-CASE: Moderate the Chat Conversation ↕ , ● USE-CASE: Steer the Presenter ↕ , ● USE-CASE: Present Forwarded Questions ↕	○ PREMISES ∅	○ DATA Event configuration, moderation actions, statistics, exports
Description				
The event operator is a manager, moderator, or presenter who configures events, moderates input, and presents forwarded questions, through the same browser-based web client as the attendees — BECAUSE all event operation happens through the same web application as attendance.				

● ENTITY	Properties & Description			
Streaming Provider ↗	○ KIND	○ DIRECTION	○ VIA	○ TERMS
	System	Outbound	∅	● TERM: Streaming Provider ↗
	○ ACTORS	○ USE-CASES	○ PREMISES	○ DATA
	∅	● USE-CASE: Join Event and Watch Stream ↗ , ● USE-CASE: Configure the Event ↗ , ● USE-CASE: Switch Streaming Provider ↗	● PREMISE: Streaming Providers Deliver the Video ↗	Live video ingest and playback streams
Description				
External streaming providers such as msg Filmstudio, msg Broadcast, YouTube, Cloudflare, Twitch, and 3Q ingest and deliver the video — BECAUSE the solution is streaming-provider independent and consumes provider endpoints rather than hosting video.				
Content CDN ↗	○ KIND	○ DIRECTION	○ VIA	○ TERMS
	Service	Outbound	∅	∅
	○ ACTORS	○ USE-CASES	○ PREMISES	○ DATA
	∅	● USE-CASE: Join Event and Watch Stream ↗	∅	Static client assets and static resources
Description				
A Cloudflare content delivery network fronts static content for fast, stable distribution — BECAUSE static assets must load quickly and reliably for a global, large-scale audience.				
Event Registration System ↗	○ KIND	○ DIRECTION	○ VIA	○ TERMS
	System	Bidirectional	● ENTITY: Event Operator ↗	● TERM: Event Registration System ↗
	○ ACTORS	○ USE-CASES	○ PREMISES	○ DATA
	∅	● USE-CASE: Create Event from Registration Import ↗	● PREMISE: Registered Audience Known in Advance ↗ , ● PREMISE: Registration System Exchanges Attendee Data ↗	Attendee registration data and generated access URLs
Description				
The Event Registration System supplies attendee registration data and receives generated access URLs without any direct technical interface: the manager carries both as Excel sheets, uploading the exported attendee list into the event and handing the returned URL sheet back — BECAUSE events are provisioned from the organization's existing registration system, which distributes the invitations itself.				
Email Gateway ↗	○ KIND	○ DIRECTION	○ VIA	○ TERMS
	Service	Outbound	∅	∅
	○ ACTORS	○ USE-CASES	○ PREMISES	○ DATA
	∅	∅	∅	∅



● ENTITY	Properties & Description			
	○ ACTORS	○ USE-CASES	○ PREMISES	○ DATA
	∅	● USE-CASE: Authenticate via Email Token ⓘ	● PREMISE: Email Gateway Delivers Tokens Within Minutes ⓘ	Authorization token emails
	Description An external mail-sending service delivers one-time authorization tokens to attendees — BECAUSE email is the first-factor channel through which access is verified.			
Translation LLM ⓘ	○ KIND	○ DIRECTION	○ VIA	○ TERMS
	Service	Outbound	∅	∅
	○ ACTORS	○ USE-CASES	○ PREMISES	○ DATA
	∅	● USE-CASE: Join Event and Watch Stream ⓘ, ● USE-CASE: Ask a Question ⓘ, ● USE-CASE: Chat During the Event ⓘ	● PREMISE: Translation Service Available During Events ⓘ, ● PREMISE: Message Texts Contain Personal Data ⓘ	Source and translated message texts
	Description An external AI/LLM service translates message texts between the supported languages — BECAUSE chat and questions are made available in German and English on the fly.			
Embedded Third-Party App ⓘ	○ KIND	○ DIRECTION	○ VIA	○ TERMS
	System	Bidirectional	∅	∅
	○ ACTORS	○ USE-CASES	○ PREMISES	○ DATA
	∅	● USE-CASE: Moderate the Chat Conversation ⓘ	∅	Interactive app content and administration
	Description An optional third-party application is embedded into the event for additional interactivity, with a separate admin URL for moderators — BECAUSE some events integrate external interactive tooling.			


23 ● ARCH: Functionality View (FV)








● COMPONENT Web Client ⚓	Properties & Description Diagram The diagram illustrates the Web Client component (Kind: Subsystem) and its relationships. On the left, several components and tactics are shown: Client NLP (Module), Live Failover Continuity (Tactic), Universal Browser Reach (Tactic), Edge Asset Delivery (Tactic), Decouple logical Channels from physical provider Resources (Decision), and Vue.js single-page client with headless widgets (Decision). These are connected to the central Web Client component via 'part of', 'hosts', and 'affects' relationships. On the right, the Web Client component is shown realizing several requirements: Configurable Name Appearance, Browser Access, Individual Event Access URL, Explicit User Consent, and Live Provider Switching. It also depends on a Relay connector component. <table><tr><th>○ KIND</th><th>○ PART-OF</th><th>○ REALIZES</th><th>○ OWNS</th></tr><tr><td>Subsystem</td><td>∅</td><td> ● REQUIREMENT: Configurable Name Appearance ⓘ ● REQUIREMENT: Browser Access ⓘ ● REQUIREMENT: Individual Event Access URL ⓘ ● REQUIREMENT: Explicit User Consent ⓘ ● REQUIREMENT: Live Provider Switching ⓘ </td><td>∅</td></tr><tr><th>○ PROVIDES</th><th>○ DEPENDS-ON</th><th colspan="2">Description</th></tr><tr><td>∅</td><td> ● COMPONENT: Relay ⓘ </td><td colspan="2">The Vue.js single-page application renders the attendee and operator UI and drives all user interaction: it presents the panel, attendee, studio, moderator, and manager screens, plays the video stream, and exchanges live data over MQTT — BECAUSE msg.Broadcast delivers its entire experience in the browser.</td></tr></table>	○ KIND	○ PART-OF	○ REALIZES	○ OWNS	Subsystem	∅	● REQUIREMENT: Configurable Name Appearance ⓘ ● REQUIREMENT: Browser Access ⓘ ● REQUIREMENT: Individual Event Access URL ⓘ ● REQUIREMENT: Explicit User Consent ⓘ ● REQUIREMENT: Live Provider Switching ⓘ	∅	○ PROVIDES	○ DEPENDS-ON	Description		∅	● COMPONENT: Relay ⓘ	The Vue.js single-page application renders the attendee and operator UI and drives all user interaction: it presents the panel, attendee, studio, moderator, and manager screens, plays the video stream, and exchanges live data over MQTT — BECAUSE msg.Broadcast delivers its entire experience in the browser.	
○ KIND	○ PART-OF	○ REALIZES	○ OWNS														
Subsystem	∅	● REQUIREMENT: Configurable Name Appearance ⓘ ● REQUIREMENT: Browser Access ⓘ ● REQUIREMENT: Individual Event Access URL ⓘ ● REQUIREMENT: Explicit User Consent ⓘ ● REQUIREMENT: Live Provider Switching ⓘ	∅														
○ PROVIDES	○ DEPENDS-ON	Description															
∅	● COMPONENT: Relay ⓘ	The Vue.js single-page application renders the attendee and operator UI and drives all user interaction: it presents the panel, attendee, studio, moderator, and manager screens, plays the video stream, and exchanges live data over MQTT — BECAUSE msg.Broadcast delivers its entire experience in the browser.															
Client NLP ⚓	Diagram The diagram illustrates the Client NLP component (Kind: Module) and its relationships. On the left, the Client Device (Kind: Device) is shown hosting the Client NLP component. Below it, the Abuse Resistance tactic is shown affecting the Client NLP component. On the right, the Client NLP component is shown as part of the Web Client (Kind: Subsystem) and realizing the Client-Side Sentiment Analysis requirement. <table><tr><th>○ KIND</th><th>○ PART-OF</th><th>○ REALIZES</th><th>○ OWNS</th></tr><tr><td>Module</td><td> ● COMPONENT: Web Client ⓘ </td><td> ● REQUIREMENT: Client-Side Sentiment Analysis ⓘ </td><td>∅</td></tr><tr><th>○ PROVIDES</th><th>○ DEPENDS-ON</th><th colspan="2">Description</th></tr><tr><td>∅</td><td>∅</td><td colspan="2">The client NLP module performs lightweight client-side sentiment analysis and language identification on attendee input before it is</td></tr></table>	○ KIND	○ PART-OF	○ REALIZES	○ OWNS	Module	● COMPONENT: Web Client ⓘ	● REQUIREMENT: Client-Side Sentiment Analysis ⓘ	∅	○ PROVIDES	○ DEPENDS-ON	Description		∅	∅	The client NLP module performs lightweight client-side sentiment analysis and language identification on attendee input before it is	
○ KIND	○ PART-OF	○ REALIZES	○ OWNS														
Module	● COMPONENT: Web Client ⓘ	● REQUIREMENT: Client-Side Sentiment Analysis ⓘ	∅														
○ PROVIDES	○ DEPENDS-ON	Description															
∅	∅	The client NLP module performs lightweight client-side sentiment analysis and language identification on attendee input before it is															

● COMPONENT	Properties & Description		
			sent — BECAUSE filtering at the source reduces server load and can prevent improper submissions.
Router 	Diagram		
			
○ KIND	○ PART-OF	○ REALIZES	○ OWNS
Connector	∅	∅	∅
○ PROVIDES	○ DEPENDS-ON	Description	
∅	∅	The router (HAProxy with NFTables) routes incoming HTTP and WebSocket traffic across the proxy instances of an environment using round-robin and separates the dev, QA, and production environments — BECAUSE traffic must be balanced and environments isolated at the edge.	
Proxy 	Diagram		
			
○ KIND	○ PART-OF	○ REALIZES	○ OWNS
Connector	∅	∅	∅
○ PROVIDES	○ DEPENDS-ON	Description	
∅	● COMPONENT: Relay 	The proxy layer (HAProxy) forwards the HTTP and WebSocket requests of a specific environment to the relay layer and scales horizontally per environment — BECAUSE request handling must scale independently of the messaging layer.	




● COMPONENT	Properties & Description		
			Live Configuration Propagation ⓘ ● ENTITY: MessageText ⓘ, ● ENTITY: QuestionTag ⓘ
	○ PROVIDES	○ DEPENDS-ON	Description
	● INTERFACE: Server Command Line ⓘ	● COMPONENT: Database ⓘ	The service layer executes all business logic for events, messages, authentication, and statistics: as the main server it holds the event, moderation, access, and configuration logic, reacts to MQTT messages, and persists state — BECAUSE the authoritative business rules must live in a single server tier.
Authentication Service ⓘ	Diagram		
	○ KIND	○ PART-OF	○ REALIZES
Module		● COMPONENT: Service ⓘ	● REQUIREMENT: User Authentication ⓘ, ● REQUIREMENT: Limit Parallel Access ⓘ, ● REQUIREMENT: Automatic Event Access URL ⓘ
	○ OWNS	● ENTITY: User ⓘ, ● ENTITY: AuthorizationToken ⓘ, ● ENTITY: SessionToken ⓘ	
	○ PROVIDES	○ DEPENDS-ON	Description
∅		● COMPONENT: Database ⓘ	The authentication module issues and validates the authorization and session tokens: it generates one-time tokens, sends them via the email gateway, validates logins, and enforces a single active session per user per event — BECAUSE email-verified, single-session access is the core security mechanism.
Translation Service ⓘ	Diagram		
	○ KIND	○ PART-OF	○ REALIZES
Module		● COMPONENT: Service ⓘ	● REQUIREMENT: In-Session Language Switching ⓘ
	○ OWNS	∅	


● COMPONENT	Properties & Description		
	○ PROVIDES	○ DEPENDS-ON	Description
	∅	∅	The translation module produces language-specific message texts via an external LLM, translating them into the supported languages on the fly while preserving the original — BECAUSE chat and questions must be available in both German and English.
Statistics Service 	Diagram		
			
○ KIND	○ PART-OF	○ REALIZES	○ OWNS
Module	● COMPONENT: Service 	● REQUIREMENT: General Event Statistics  , ● REQUIREMENT: Debugging Statistics  , ● REQUIREMENT: Channel Statistics  , ● REQUIREMENT: User Statistics  , ● REQUIREMENT: Periodic Statistics Snapshots 	● ENTITY: EventStatistic  , ● ENTITY: ChannelStatistic  , ● ENTITY: UserStatistic 
○ PROVIDES	○ DEPENDS-ON	Description	
∅	● COMPONENT: Database 	The statistics module generates periodic event, channel, and user statistics snapshots, capturing cumulative counts of tokens, sessions, connections, and viewers during a running event — BECAUSE trend dashboards require regular snapshots over the event's lifetime.	
Junction Orchestrator 	Diagram		
			
○ KIND	○ PART-OF	○ REALIZES	○ OWNS
Component	∅	● REQUIREMENT: Browser Access 	∅
○ PROVIDES	○ DEPENDS-ON	Description	
∅	∅	The Junction component serves the static client bundle and orchestrates its delivery to the relay over MQTT+ — BECAUSE the client	

● COMPONENT	Properties & Description			
		must be distributed alongside the same messaging infrastructure used for live data.		
Database 	Diagram			
				
	○ KIND	○ PART-OF	○ REALIZES	○ OWNS
	Component	∅	∅	∅
○ PROVIDES	○ DEPENDS-ON	Description		
∅	∅	The PostgreSQL database with the filesystem persists all business objects and static assets, storing all events, messages, tokens, and statistics accessed through the Drizzle persistence layer — BECAUSE the authoritative, durable state of every event must be persisted in one tier.		

24 ● ARCH: Technology Stack (TS) ⚓




24.01 ● TIER: Common ⚓



Language

Diagram



○ PRODUCT	○ LICENSE	○ PHASE
TypeScript	Apache-2.0	Build-Time
○ COVERAGE	○ USED-BY	Description
Build Standardization	Ø	All client-side and server-side code, including the shared common module, is authored in strongly typed TypeScript and compiled to JavaScript — BECAUSE a single strongly typed language catches contract mismatches against the shared common module at compile time.

Task Runner

○ PRODUCT	○ LICENSE	○ PHASE
STX	MIT	Build-Time
○ COVERAGE	○ USED-BY	Description
Tooling	Ø	The STX task runner drives the build, lint, and run tasks of every module from a per-module <code>stx.conf</code> — BECAUSE a single task runner gives every module a consistent developer entry point.

Linting

Diagram



○ PRODUCT	○ LICENSE	○ PHASE
ESLint	MIT	Build-Time
○ COVERAGE	○ USED-BY	Description
Standardization	Ø	ESLint enforces code quality and style for the client and server TypeScript, complemented by the faster OxLint, HTMLHint for HTML, and StyleLint for Stylus — BECAUSE multiple focused linters keep each language layer clean and consistent.

● COMPONENT

Messaging

Properties & Description

Diagram

TACTIC

Live Failover Continuity

TACTIC

Real-Time Reactivity

DECISION

Use MQTT over WebSockets as the live transport

tools

tools

decides

COMPONENT

Messaging

PRODUCT: MQTT-Plus

PHASE: Run-Time

used-by

used-by

used-by

COMPONENT

Web Client

COMPONENT

Relay

COMPONENT

Service

○ PRODUCT

MQTT-Plus

○ LICENSE

MIT

○ PHASE

Run-Time

○ COVERAGE

Client Networking

Dialog Communication

Server Networking

Component Communication

○ USED-BY

● COMPONENT: Web Client

Client

● COMPONENT: Relay

● COMPONENT: Service

○ DESCRIPTION

MQTT-Plus handles the MQTT-over-WebSocket communication of the client with the relay layer and the MQTT messaging of the service and relay layers on top of the base MQTT.js functionality — **BECAUSE** MQTT is the messaging protocol for the real-time relay layer and MQTT-Plus adds the needed request/response and event handling on all tiers alike.

HTTP Client

Diagram

COMPONENT

HTTP Client

PRODUCT: OFetch

PHASE: Run-Time

used-by

used-by

COMPONENT

Web Client

COMPONENT

Authentication Service

○ PRODUCT

OFetch

○ LICENSE

MIT

○ PHASE

Run-Time

○ COVERAGE

Client Networking

○ USED-BY

● COMPONENT: Web Client

● COMPONENT: Authentication Service

○ DESCRIPTION

OFetch provides the HTTP/REST request/response communication of the client and the call of the external GraphQL mail-sending API by the authentication service — **BECAUSE** REST calls complement the MQTT channel for request/response-style interactions on both tiers.

Logging

Diagram

CONCERN

Authentication Diagnostics

TACTIC

Snapshot Observability

tools

tools

COMPONENT

Logging

PRODUCT: Pino

PHASE: Run-Time

used-by



used-by

COMPONENT

Web Client

COMPONENT

Service

● COMPONENT	Properties & Description		
	○ PRODUCT	○ LICENSE	○ PHASE
	Pino	MIT	Run-Time
	○ COVERAGE	○ USED-BY	Description
	Execution Tracing	● COMPONENT: Web Client  , ● COMPONENT: Service 	Pino provides the leveled, structured logging facility, wrapping the browser console on the client and rendered human-readably by pino-pretty on the server during development — BECAUSE a single logging library shared by client and server keeps the tracing consistent.
Date Management 	Diagram		
	 <pre> graph LR DM[COMPONENT Date Management PRODUCT: Luxon PHASE: Run-Time] -- used-by --> WC[COMPONENT Web Client] DM -- used-by --> S[COMPONENT Service] </pre>		
	○ PRODUCT	○ LICENSE	○ PHASE
	Luxon	MIT	Run-Time
Unique Identifier Generation 	○ COVERAGE	○ USED-BY	Description
	Data Conversion	● COMPONENT: Web Client  , ● COMPONENT: Service 	Luxon handles date and time parsing, formatting, and localization across the client UI and the timestamps emitted by the server services — BECAUSE robust, locale-aware date handling is required for event schedules and timestamps in German and English on client and server alike.
	Diagram		
	 <pre> graph LR UIG[COMPONENT Unique Identifier Generation PRODUCT: nanoid PHASE: Run-Time] -- used-by --> WC[COMPONENT Web Client] UIG -- used-by --> S[COMPONENT Service] </pre>		
	○ PRODUCT	○ LICENSE	○ PHASE
	nanoid	MIT	Run-Time
	○ COVERAGE	○ USED-BY	Description
	Business Model Peer Information	● COMPONENT: Web Client  , ● COMPONENT: Service 	nanoid generates the compact, collision-resistant unique identifiers for the messaging peers of client and server and for the entities the client creates — BECAUSE short URL-safe identifiers are needed on


● COMPONENT	Properties & Description			
			BECAUSE utility-first styling speeds consistent UI work while Stylus covers bespoke styling.	
UI Framework ⚓	Diagram			
	<pre>graph LR Tactic[TACTIC Universal Browser Reach] -- tools --> UIFramework[COMPONENT UI Framework PRODUCT: Vue.js PHASE: Run-Time] Decision[DECISION Vue.js single-page client with headless widgets] -- decides --> UIFramework UIFramework -- used-by --> WebClient[COMPONENT Web Client]</pre>			
	○ PRODUCT	○ LICENSE	○ PHASE	
	Vue.js	MIT	Run-Time	
○ COVERAGE	○ USED-BY	Description		
Dialog Structure Dialog Life-Cycle Interface Mask Data Binding	● COMPONENT: Web Client ⓘ	Vue.js provides the reactive, component-based UI framework rendering the panel, attendee, studio, moderator, and manager screens — BECAUSE a reactive component model is the natural fit for the browser-delivered, real-time experience.		
Widget Framework ⚓	Diagram			
	<pre>graph LR Decision[DECISION Vue.js single-page client with headless widgets] -- decides --> WidgetFramework[COMPONENT Widget Framework PRODUCT: Reka UI PHASE: Run-Time] WidgetFramework -- used-by --> WebClient[COMPONENT Web Client]</pre>			
	○ PRODUCT	○ LICENSE	○ PHASE	
	Reka UI	MIT	Run-Time	
○ COVERAGE	○ USED-BY	Description		
Interface Widgets Interface States Interface Interactions	● COMPONENT: Web Client ⓘ	Reka UI supplies the headless, unstyled widget primitives composed into the application's interface elements — BECAUSE headless widgets provide accessible interaction behavior while leaving the visual styling fully under design control.		
Typography ⚓	Diagram			
	<pre>graph LR Typography[COMPONENT Typography PRODUCT: TypoPRO PHASE: Run-Time] -- used-by --> WebClient[COMPONENT Web Client]</pre>			
○ PRODUCT	○ LICENSE	○ PHASE		
TypoPRO	OFL-1.1, Apache-2.0, MIT, CC0-1.0 (per font)	Run-Time		

● COMPONENT	Properties & Description		
	○ COVERAGE	○ USED-BY	Description
	Interface Theme	● COMPONENT: Web Client ⓘ	TypoPRO supplies the web typography and font assets for the client interface — BECAUSE consistent, self-hosted typography is needed across the branded UI.
Iconography ⓘ	Diagram		
	○ PRODUCT	○ LICENSE	○ PHASE
	Fontawesome	CC-BY-4.0, OFL-1.1, MIT (per asset)	Run-Time
	○ COVERAGE	○ USED-BY	Description
	Interface Widgets	● COMPONENT: Web Client ⓘ	Fontawesome provides the icon set used throughout the client interface — BECAUSE a comprehensive icon library covers the UI's iconography needs out of the box.
Tooltips ⓘ	Diagram		
	○ PRODUCT	○ LICENSE	○ PHASE
	vue-tippy + tippy.js	MIT	Run-Time
	○ COVERAGE	○ USED-BY	Description
	Interface Widgets Interface States	● COMPONENT: Web Client ⓘ	vue-tippy integrates the tippy.js tooltip and popover engine as a Vue.js directive and component for the floating hints on the interface elements of the client — BECAUSE a proven positioning engine with a Vue.js integration provides consistent tooltips without hand-written placement logic.
Animations ⓘ	Diagram		
	○ PRODUCT	○ LICENSE	○ PHASE
	Anime.js	MIT	Run-Time

● COMPONENT	Properties & Description		
	○ COVERAGE Interface Effects	○ USED-BY ● COMPONENT: Web Client ⓘ	Description Anime.js drives the scripted transitions and keyframe animations of the client interface elements beyond the declarative CSS transitions of the styling framework — BECAUSE timeline-based animations with easing need a JavaScript animation engine which CSS alone does not provide.
	Diagram		
Sentiment Analysis ⚓	<pre> graph LR A[TACTIC Abuse Resistance] -- tools --> B[COMPONENT Sentiment Analysis PRODUCT: natural + @nlps/core + multilang-sentiment PHASE: Run-Time] B -- used-by --> C[COMPONENT Client NLP] </pre>		
	○ PRODUCT natural + @nlps/core + multilang-sentiment	○ LICENSE MIT	○ PHASE Run-Time
	○ COVERAGE Presentation Model	○ USED-BY ● COMPONENT: Client NLP ⓘ	Description The natural, @nlps/core, and multilang-sentiment libraries perform local sentiment analysis on attendee input in the browser — BECAUSE filtering sentiment at the source reduces server load and can prevent improper submissions.
Language Identification ⚓	Diagram		
	<pre> graph LR A[COMPONENT Language Identification PRODUCT: tinyld + franc + lande PHASE: Run-Time] -- used-by --> B[COMPONENT Client NLP] </pre>		
	○ PRODUCT tinyld + franc + lande	○ LICENSE Ø	○ PHASE Run-Time
	○ COVERAGE Presentation Model	○ USED-BY ● COMPONENT: Client NLP ⓘ	Description The tinyld, franc, and lande libraries perform local language identification on attendee input in the browser — BECAUSE detecting the message language client-side enables on-the-fly handling without an initial server round-trip.

24.03 ● TIER: Middleware



● COMPONENT	Properties & Description		
Reverse Proxy 	Diagram		
			
○ PRODUCT		○ LICENSE	○ PHASE
HAProxy		GPL-2.0	Run-Time
○ COVERAGE		○ USED-BY	Description
Request Routing Load Balancing Transport Security		● COMPONENT: Router  ● COMPONENT: Proxy 	HAProxy terminates the inbound HTTP and WebSocket traffic at the edge router, firewalled by NTables, and forwards it per environment from the proxy instances to the relay layer — BECAUSE a single mature proxy covers both the hardened entry point and the horizontally scaled per-environment forwarding.
Message Broker 	Diagram		
			
○ PRODUCT		○ LICENSE	○ PHASE
Mosquitto		EPL-2.0	Run-Time
○ COVERAGE		○ USED-BY	Description
Message Brokering		● COMPONENT: Relay 	Mosquitto brokers the MQTT messages between the thousands of WebSocket connections of the clients and the service layer as a pool of instances per environment — BECAUSE a lightweight, proven MQTT broker sustains the connection count of a large event without business logic of its own.

● COMPONENT	Properties & Description		
	○ PRODUCT	○ ALTERNATIVES	○ LICENSE
	Junction	∅	∅
	○ PHASE	○ COVERAGE	○ USED-BY
	Run-Time	Server Networking Request Processing	● COMPONENT: Junction Orchestrator ②
	Description		
Argument Parsing ⚓	Diagram		
	<pre> graph LR subgraph "COMPONENT" direction TB AP["Argument Parsing PRODUCT: Commander.js PHASE: Run-Time"] end subgraph "COMPONENT" direction TB S["Service"] end AP -- used-by --> S </pre>		
	○ PRODUCT	○ ALTERNATIVES	○ LICENSE
	Commander.js	∅	MIT
	○ PHASE	○ COVERAGE	○ USED-BY
	Run-Time	Argument Parsing	● COMPONENT: Service ②
	Description		
	Commander.js parses the server's command-line options and arguments to bootstrap application parameters — BECAUSE a mature CLI parser covers option handling at server startup without custom code.		
Configuration Loading ⚓	Diagram		
	<pre> graph LR subgraph "CONCERN" direction TB CFP["Config-File Provisioning"] end subgraph "COMPONENT" direction TB CL["Configuration Loading PRODUCT: dotenvx + YAML PHASE: Run-Time, Operate-Time"] end subgraph "COMPONENT" direction TB S["Service"] end CFP -- tools --> CL CL -- used-by --> S </pre>		
	○ PRODUCT	○ ALTERNATIVES	○ LICENSE
	dotenvx + YAML	∅	BSD-3-Clause, ISC
	○ PHASE	○ COVERAGE	○ USED-BY
	Run-Time Operate-Time	Configuration Parsing Configuration	● COMPONENT: Service ②
	Description		
	dotenvx loads optional environment files into the process environment and the YAML library parses the optional configuration file, together feeding the layered configuration resolved from defaults, file, environment, and command-line — BECAUSE the server's runtime parameters and secrets must be configurable from files and the BROADCAST_* environment without hardcoding them.		
Configuration Validation ⚓	Diagram		
	<pre> graph LR subgraph "COMPONENT" direction TB CV["Configuration Validation PRODUCT: Valibot PHASE: Run-Time"] end subgraph "COMPONENT" direction TB S["Service"] end CV -- used-by --> S </pre>		
	○ PRODUCT	○ ALTERNATIVES	○ LICENSE
	Valibot	∅	MIT
	○ PHASE	○ COVERAGE	○ USED-BY
	Run-Time	Configuration Parsing	● COMPONENT: Service ②

● COMPONENT	Properties & Description Description Valibot declares the canonical, strict configuration schema that validates and coerces the merged configuration at startup — BECAUSE a single schema as the source of truth gives fail-fast validation of secrets and a typed configuration surface that catches misconfiguration before the service runs.												
AI/LLM Connectivity	Diagram <pre>graph LR; A["COMPONENT AI/LLM Connectivity PRODUCT: @ai-sdk PHASE: Run-Time"] -- used-by --> B["COMPONENT Translation Service"]</pre> <table><tr><td>○ PRODUCT</td><td>○ ALTERNATIVES</td><td>○ LICENSE</td></tr><tr><td>@ai-sdk</td><td>∅</td><td>Apache-2.0</td></tr><tr><td>○ PHASE</td><td>○ COVERAGE</td><td>○ USED-BY</td></tr><tr><td>Run-Time</td><td>Client Networking</td><td>● COMPONENT: Translation Service </td></tr></table> Description The @ai-sdk library connects the translation service to an external AI/LLM service for on-the-fly translation of message texts — BECAUSE chat and questions must be made available in both German and English.	○ PRODUCT	○ ALTERNATIVES	○ LICENSE	@ai-sdk	∅	Apache-2.0	○ PHASE	○ COVERAGE	○ USED-BY	Run-Time	Client Networking	● COMPONENT: Translation Service
○ PRODUCT	○ ALTERNATIVES	○ LICENSE											
@ai-sdk	∅	Apache-2.0											
○ PHASE	○ COVERAGE	○ USED-BY											
Run-Time	Client Networking	● COMPONENT: Translation Service											
Container Orchestration	Diagram <pre>graph LR; A1["CONCERN Release Rollout"] -- tools --> D["COMPONENT Container Orchestration PRODUCT: Docker Compose PHASE: Operate-Time"]; A2["CONCERN Horizontal Scaling"] -- tools --> D; A3["CONCERN Database Restore"] -- tools --> D; A4["TACTIC Connection Scaling"] -- tools --> D; A5["DECISION Single-host Docker Compose instead of a cluster orchestrator"] -- decides --> D;</pre> <table><tr><td>○ PRODUCT</td><td>○ ALTERNATIVES</td><td>○ LICENSE</td></tr><tr><td>Docker Compose</td><td>Kubernetes, Nomad</td><td>Apache-2.0</td></tr><tr><td>○ PHASE</td><td>○ COVERAGE</td><td>○ USED-BY</td></tr><tr><td>Operate-Time</td><td>Installation Upgrade Capacity</td><td>∅</td></tr></table> Description Docker Compose runs and recreates the service containers of an environment from a per-environment compose file, with the proxy and relay instances added by the same file — BECAUSE a single-host orchestration is sufficient for the per-environment container count and avoids operating a cluster.	○ PRODUCT	○ ALTERNATIVES	○ LICENSE	Docker Compose	Kubernetes, Nomad	Apache-2.0	○ PHASE	○ COVERAGE	○ USED-BY	Operate-Time	Installation Upgrade Capacity	∅
○ PRODUCT	○ ALTERNATIVES	○ LICENSE											
Docker Compose	Kubernetes, Nomad	Apache-2.0											
○ PHASE	○ COVERAGE	○ USED-BY											
Operate-Time	Installation Upgrade Capacity	∅											

24.05 ● TIER: Database



● COMPONENT

Database

⚓

Properties & Description

Diagram

DECISION

PostgreSQL as the single self-hosted relational store

COMPONENT

Database

PRODUCT: PostgreSQL

PHASE: Run-Time

COMPONENT

Database

decides

used-by

○ PRODUCT

PostgreSQL

○ ALTERNATIVES

∅

○ LICENSE

PostgreSQL License

○ PHASE

Run-Time

○ COVERAGE

Storage Engine

Transaction Management

Query Language

Indexing

○ USED-BY

● COMPONENT: Database

Ⓜ

Description

PostgreSQL stores the authoritative, durable state of every event together with its channels, messages, tokens, and statistics snapshots — **BECAUSE** the event-centric data model is inherently relational and demands transactional integrity, EU-resident self-hosting, and rich query support for moderation and reporting.

Database Backup

⚓

Diagram

CONCERN

Database Backup

CONCERN

Database Restore

TACTIC

Dump-Based Recovery

DECISION

Logical dumps instead of continuous archiving for backup

COMPONENT

Database Backup

PRODUCT: pg_dump

PHASE: Operate-Time

tools

tools

tools

decides

○ PRODUCT

pg_dump

○ ALTERNATIVES

pgBackRest, Barman

○ LICENSE

PostgreSQL License

○ PHASE

Operate-Time

○ COVERAGE

Backup

Recovery

○ USED-BY

∅

Description

The pg_dump utility of PostgreSQL produces the logical database dumps stored together with the filesystem assets on the backup storage and restored with pg_restore — **BECAUSE** a logical dump is portable across PostgreSQL versions and needs no additional backup server.


25 ● ARCH: Development Aspects (DA) [⚓](#)

Client/Common/Server Split CATEGORY: Structure	TypeScript Everywhere CATEGORY: Standardization	STX Task Running CATEGORY: Tooling	Vite Client Build CATEGORY: Build
Layered Linting CATEGORY: Standardization	Dependency Layering CATEGORY: Dependency	Git Codeline CATEGORY: Codeline	Identifier Naming CATEGORY: Standardization

● ASPECT	Properties & Description	
Client/Common/Server Split ⚓	Diagram	<pre> graph LR T1[TACTIC Shared Typed Contracts] -- affects --> A[ASPECT Client/Common/Server Split CATEGORY: Structure] D1[DECISION TypeScript with a shared common module across client and server] -- affects --> A </pre>
	○ CATEGORY	Description
	Structure	The codebase is organized into <code>src/client</code> , <code>src/common</code> , and <code>src/server</code> modules, with shared types and topic definitions living in the common module imported by both sides — BECAUSE client and server must agree on contracts without duplicating them.
TypeScript Everywhere ⚓	Diagram	<pre> graph LR T2[TACTIC Shared Typed Contracts] -- affects --> A2[ASPECT TypeScript Everywhere CATEGORY: Standardization] D2[DECISION TypeScript with a shared common module across client and server] -- affects --> A2 </pre>
	○ CATEGORY	Description
	Standardization	All client-side and server-side code is written in strongly typed TypeScript against shared type definitions — BECAUSE a single typed language across the stack catches contract mismatches at compile time.
STX Task Running ⚓	○ CATEGORY	Description
	Tooling	Build, lint, and run tasks are driven uniformly by the STX task runner with per-module <code>stx.conf</code> files — BECAUSE a single task runner gives every module a consistent developer entry point.
Vite Client Build ⚓	Diagram	<pre> graph LR D3[DECISION Vue.js single-page client with headless widgets] -- affects --> A3[ASPECT Vite Client Build CATEGORY: Build] </pre>
	○ CATEGORY	Description
	Build	The client is built and served in development by Vite, bundling the Vue, Pinia, Reka UI, Tailwind, and Stylus stack into the static client artifact — BECAUSE Vite provides fast HMR development and an optimized production bundle.
Layered Linting ⚓	Diagram	<pre> graph LR T4[TACTIC Shared Typed Contracts] -- affects --> A4[ASPECT Layered Linting CATEGORY: Standardization] </pre>
	○ CATEGORY	Description
	Standardization	Code quality is enforced with ESLint and the faster OxLint for TypeScript, HTMLHint for HTML, and StyleLint for Stylus — BECAUSE multiple focused linters keep each language layer clean and consistent.


● ASPECT	Properties & Description
Dependency Layering 	Diagram  ○ CATEGORY Dependency Description The common module must depend on neither client nor server, while both client and server may depend on common — BECAUSE a one-directional dependency keeps the shared contract free of platform-specific concerns.
Git Codeline 	Diagram  ○ CATEGORY Codeline Description The project is versioned in a single Git repository hosted on the self-administered Gitea, with the Software Administrator granting repository access — BECAUSE self-hosted version control keeps source under full organizational control.
Identifier Naming 	Diagram  ○ CATEGORY Standardization Description Data-model entities are named in PascalCase and their attributes in camelCase, and both are referred to by exactly these identifiers, set in code font, wherever code or documents mention them (e.g. <code>Event.accessList</code>, <code>Message.senderName</code>) — BECAUSE a single identifier form lets a reader grep from a document straight into the code.

26 ● ARCH: Concurrency View (CO)




● UNIT Router Process <a>	Properties & Description		
	Diagram		
	○ KIND	○ PART-OF	○ HOSTS
	Process	∅	● COMPONENT: Router <a>
Proxy Pool <a>	○ MULTIPLICITY	○ COORDINATES-WITH	○ COORDINATION
	1 per data center entry point	● UNIT: Proxy Pool <a>	stateless round-robin distribution
	Description		
	The router runs as a single front-door process per data center, distributing connections across environments and proxy instances — BECAUSE a stateless balancer can spread load without holding per-connection state.		
	Diagram		
Relay Pool <a>			
	○ KIND	○ PART-OF	○ HOSTS
	Pool	∅	● COMPONENT: Proxy <a>
	○ MULTIPLICITY	○ COORDINATES-WITH	○ COORDINATION
	0..n instances per environment	● UNIT: Relay Pool <a> , ● UNIT: Service Event Loop <a>	shared-nothing behind the router
	Description		
	The proxy layer runs as a pool of independent, stateless reverse-proxy instances per environment — BECAUSE request handling must scale out horizontally to absorb connection spikes.		
Relay Pool <a>	Diagram		

● UNIT	Properties & Description		
	○ KIND	○ PART-OF	○ HOSTS
	Pool	∅	● COMPONENT: Relay ⓘ
	○ MULTIPLICITY	○ COORDINATES-WITH	○ COORDINATION
Description			
The relay layer runs as a pool of Mosquitto/MQTT-Plus broker instances, each maintaining thousands of WebSocket connections and fanning out per-event topics — BECAUSE sustaining up to 10000 concurrent connections requires horizontal broker scaling.			
Service Event Loop ⓘ	Diagram		
	○ KIND	○ PART-OF	○ HOSTS
	EventLoop	∅	● COMPONENT: Service ⓘ, ● COMPONENT: Authentication Service ⓘ, ● COMPONENT: Translation Service ⓘ
Description			
The service runs as Node.js single-threaded event loops that react to MQTT messages and serialize state changes through database transactions — BECAUSE an event-loop model handles many concurrent I/O-bound interactions without shared-memory races.			
Statistics Scheduler ⓘ	Diagram		
	○ KIND	○ PART-OF	○ HOSTS
	Task	● UNIT: Service Event Loop ⓘ	● COMPONENT: Statistics Service ⓘ

● UNIT	Properties & Description		
	○ MULTIPLICITY	○ COORDINATES-WITH	○ COORDINATION
	1 active per running event	● UNIT: Database Server ②	timer-driven, writes via database transactions
	Description		
	A scheduled task on the service event loop captures a statistics snapshot every five minutes for each running event — BECAUSE periodic cumulative counts must be produced on a fixed cadence independent of user activity.		
Database Server 	Diagram		
			
	○ KIND	○ PART-OF	○ HOSTS
	Process	∅	● COMPONENT: Database ②
○ MULTIPLICITY	○ COORDINATES-WITH	○ COORDINATION	
1 primary per environment	∅	ACID transactions with optimistic concurrency via the ORM	
	Description		
	PostgreSQL runs as the single authoritative persistence process per environment, serializing concurrent writes through transactions — BECAUSE a single source of truth with ACID guarantees keeps event state consistent under concurrency.		

27 ● ARCH: Deployment View (DV)




TIER Middleware	Properties & Description		
	Diagram		
	PART-OF TIER: Data Center	LOCATION	STACK TIER: Middleware
Description			
The middleware tier terminates, balances, and relays the client connections between the Internet and the business services — BECAUSE sustaining thousands of bidirectional connections is a concern separate from the business logic.			
Server	Diagram		
	PART-OF TIER: Data Center	LOCATION	STACK TIER: Server
	Description		
	The server tier runs the business services and the orchestrator — BECAUSE the business logic must scale and change independently of the connection handling and the persistence.		
Database	Diagram		
	PART-OF TIER: Data Center	LOCATION	STACK TIER: Database
	Description		
	The database tier holds the authoritative persistent state — BECAUSE durable state must reside on a protected tier reachable from the business services alone.		

● NODE

Edge Router [⚓](#)

Properties & Description

Diagram



○ KIND

Server

○ TIER

● TIER: Middleware [⌘](#)

○ PLATFORM

Linux x86-64

○ HOSTS

● UNIT: Router Process [⌘](#)

○ INSTANCES

1 per data center entry point

○ CONNECTS-TO

● NODE: Proxy Servers [⌘](#)

○ NETWORKS


● NETWORK: Public Internet [⌘](#), ● NETWORK: Backend Network [⌘](#)

Description

The edge router terminates inbound HTTP and WebSocket traffic and round-robins it to per-environment proxies — **BECAUSE** a single hardened entry point must balance load and isolate environments.

Proxy Servers [⚓](#)

Diagram



○ KIND

Server

○ TIER

● TIER: Middleware [⌘](#)

○ PLATFORM

Linux x86-64

○ HOSTS

● UNIT: Proxy Pool [⌘](#)

○ INSTANCES

0..n per environment

○ CONNECTS-TO

● NODE: Relay Brokers [⌘](#)

○ NETWORKS

● NETWORK: Backend Network [⌘](#)

Description


The proxy servers run several reverse proxy instances per environment forwarding to the relay brokers — **BECAUSE** per-environment scaling of request handling needs multiple proxy instances.

● NODE

Relay Brokers

Properties & Description


Diagram



○ KIND	○ TIER	○ PLATFORM
Server	● TIER: Middleware 	Linux x86-64
○ HOSTS	○ INSTANCES	○ CONNECTS-TO
● UNIT: Relay Pool 	0..n per environment	∅
○ NETWORKS	Description	
● NETWORK: Backend Network 	The relay brokers run several MQTT broker instances per environment holding the live WebSocket connections — BECAUSE sustaining thousands of bidirectional connections requires a dedicated, scalable messaging node.	

Service Containers

Diagram




○ KIND	○ TIER	○ PLATFORM
Container	● TIER: Server 	OCI containers on Linux x86-64
○ HOSTS	○ INSTANCES	○ CONNECTS-TO
● UNIT: Service Event Loop  , ● COMPONENT: Junction Orchestrator 	0..n per environment	● NODE: Relay Brokers  , ● NODE: Database Server 
○ NETWORKS	Description	
● NETWORK: Backend Network  , ● NETWORK: Data Network 	The service containers run the Node.js business services and the Junction orchestrator per environment — BECAUSE containerized services give reproducible, independently scalable business logic.	

● **NODE**

Database Server 

Properties & Description

Diagram




○ KIND	○ TIER	○ PLATFORM
Server	● TIER: Database 	Linux x86-64
○ HOSTS	○ INSTANCES	○ CONNECTS-TO
● UNIT: Database Server 	1 primary per environment	
○ NETWORKS	Description	
● NETWORK: Data Network 	The database server runs PostgreSQL with filesystem asset storage as the authoritative persistence node — BECAUSE durable state must reside on a protected, non-public node.	

● **NETWORK**



Public Internet 

Properties & Description

Diagram



○ SCOPE	○ PROTOCOLS	○ ADDRESSING
Public	HTTPS 443, WSS 443	Public IPv4 and IPv6
Description		
The public Internet carries all attendee and operator traffic to the CDN and the edge router over TLS only — BECAUSE the audience joins from arbitrary, untrusted networks.		

● NETWORK Backend Network ⚓	Properties & Description		
	Diagram		
			
	○ SCOPE	○ PROTOCOLS	○ ADDRESSING
	Private	HTTP, WS, WSS	Hetzner private vSwitch, per-environment VLAN
	Description		
Data Network ⚓	Diagram		
			
	○ SCOPE	○ PROTOCOLS	○ ADDRESSING
	Isolated	TCP 5432	Hetzner private vSwitch, database subnet
	Description		
	The data network connects the service containers to the database server only — BECAUSE the persistence node must be reachable from the business services alone.		

28 ● ARCH: Operations View (OV) [⚓](#)


Release Rollout CATEGORY: Upgrade	Config-File Provisioning CATEGORY: Configuration	Role Assignment CATEGORY: Administration	Live Statistics Monitoring CATEGORY: Monitoring
Authentication Diagnostics CATEGORY: Incident	Horizontal Scaling CATEGORY: Capacity	Database Backup CATEGORY: Backup	Database Restore CATEGORY: Recovery

● CONCERN

Release Rollout [⚓](#)

Properties & Description

Diagram



○ CATEGORY

Upgrade

○ TRIGGER

on every release, outside running events

○ OPERATOR

● PERSONA: Sven [Ⓜ](#)

○ ADDRESSES

● REQUIREMENT: Event-Safe Maintenance [Ⓜ](#)

○ ELEMENTS

● NODE: Service Containers [Ⓜ](#)

○ TOOLS


● COMPONENT: Container Orchestration [Ⓜ](#)

Description

A release is rolled out per environment by pulling the new service container images and recreating the service containers between events — **BECAUSE** a running broadcast must never be interrupted by a rollout.

Config-File Provisioning [⚓](#)

Diagram



○ CATEGORY

Configuration

○ TRIGGER

before each event

○ OPERATOR

● PERSONA: Sven [Ⓜ](#)

○ ADDRESSES

● REQUIREMENT: Event-Safe Maintenance [Ⓜ](#)

○ ELEMENTS

● COMPONENT: Service [Ⓜ](#)

○ TOOLS


● COMPONENT: Configuration Loading [Ⓜ](#)

Description

Streaming providers, their parameters, admins, and broker URLs are provisioned through a broadcast .yaml configuration file read by the service — **BECAUSE** provider endpoints and administrators are operational concerns kept out of the database.

Role Assignment [⚓](#)

Diagram



○ CATEGORY



Administration

○ TRIGGER

on event creation

○ OPERATOR

● PERSONA: Sven [Ⓜ](#)

● CONCERN	Properties & Description		
	○ ADDRESSES	○ ELEMENTS	○ TOOLS
	● REQUIREMENT: Privacy by Design ⓘ	● COMPONENT: Authentication Service ⓘ	∅
	Description		
	The first Manager of an event is assigned by the Software Administrator through configuration rather than a UI — BECAUSE permanent roles must be controlled administratively to uphold privacy by design.		
Live Statistics Monitoring ⓘ	Diagram		
			
	○ CATEGORY	○ TRIGGER	○ OPERATOR
	Monitoring	during each event	● PERSONA: Sven ⓘ
	○ ADDRESSES	○ ELEMENTS	○ TOOLS
	● REQUIREMENT: Concurrent Attendee Scale ⓘ, ● REQUIREMENT: Live Diagnosability ⓘ	● COMPONENT: Statistics Service ⓘ, ● NODE: Proxy Servers ⓘ, ● NODE: Relay Brokers ⓘ	∅
	Description		
	During a broadcast the administrator watches the statistics dashboard for the attendee curve, the channel distribution, and the authentication-flow counters — BECAUSE capacity and login problems must be detected while the audience is still online.		
Authentication Diagnostics ⓘ	Diagram		
			
	○ CATEGORY	○ TRIGGER	○ OPERATOR
	Incident	on reported login failures	● PERSONA: Sven ⓘ
	○ ADDRESSES	○ ELEMENTS	○ TOOLS
	● REQUIREMENT: Live Diagnosability ⓘ	● COMPONENT: Authentication Service ⓘ	● COMPONENT: Logging ⓘ
	Description		
	Reported attendee login failures are diagnosed from the recorded token states (issued, sent, used) and the server log — BECAUSE operators must find out why an attendee fails to authenticate while the event runs.		

CONCERN

Horizontal Scaling

Properties & Description

Diagram

TACTIC

Connection Scaling

operated-by

CONCERN

Horizontal Scaling

CATEGORY: Capacity

addresses

addresses

operator

elements

elements

tools

addresses

Horizontal Scalability

CATEGORY: Performance

elements

Proxy Servers

NODE

elements

Service Containers

NODE

addresses

Concurrent Attendee Scale

REQUIREMENT

CATEGORY: Performance

PERSONA

Sven

Relay Brokers

NODE

Container Orchestration

COMPONENT

○ CATEGORY

Capacity

○ ADDRESSES

● REQUIREMENT: Horizontal Scalability

● REQUIREMENT: Concurrent Attendee Scale

○ TRIGGER

ahead of large events

○ ELEMENTS

● NODE: Proxy Servers

● NODE: Relay Brokers

● NODE: Service Containers

○ OPERATOR

● PERSONA: Sven

● COMPONENT: Container Orchestration

○ TOOLS

Description

Operators scale an environment by adding proxy, relay, and service instances ahead of large events — **BECAUSE** townhall-scale audiences of up to 10000 require capacity provisioned per environment.

Database Backup

Diagram

TACTIC

Dump-Based Recovery

operated-by

CONCERN

Database Backup

CATEGORY: Backup

addresses

addresses

operator

elements

elements

tools

addresses

GDPR Compliance

REQUIREMENT

CATEGORY: Compliance

addresses

Event Setup Recovery

REQUIREMENT

CATEGORY: Reliability

PERSONA

Sven

Database Server

NODE

Event

ENTITY

Database Backup

COMPONENT

○ CATEGORY

Backup

○ ADDRESSES

● REQUIREMENT: Event Setup Recovery

● REQUIREMENT: GDPR Compliance

○ TRIGGER

nightly and before each event

○ ELEMENTS

● NODE: Database Server

● ENTITY: Event

○ OPERATOR


● PERSONA: Sven

● COMPONENT: Database Backup


○ TOOLS


Description

The PostgreSQL database and the filesystem assets are dumped nightly and before each event onto the backup storage of the same data center — **BECAUSE** event setups must survive a database loss without leaving the EU hosting boundary.



29 ● ARCH: Quality Perspectives (QP)




● TACTIC	Properties & Description		
	○ QUALITY Scalability	○ ADDRESSES ● REQUIREMENT: Concurrent Attendee Scale ⌘, ● REQUIREMENT: Horizontal Scalability ⌘	○ MECHANISM stateless proxy and relay pools behind a round-robin router
	○ TRADES-OFF Maintainability	○ AFFECTS ● COMPONENT: Router ⌘, ● COMPONENT: Proxy ⌘, ● COMPONENT: Relay ⌘, ● UNIT: Router Process ⌘, ● UNIT: Proxy Pool ⌘, ● UNIT: Relay Pool ⌘, ● TIER: Middleware ⌘, ● NODE: Edge Router ⌘, ● NODE: Proxy Servers ⌘, ● NODE: Relay Brokers ⌘	○ OPERATED-BY ● CONCERN: Horizontal Scaling ⌘
	○ TOOLS ● COMPONENT: Container Orchestration ⌘	Description The proxy and relay tiers scale horizontally as stateless pools so connection load distributes across instances per environment — BECAUSE a single broker cannot hold the required attendee count while a sharded pool can.	
	Diagram		
Live Failover Continuity ⚓			
	○ QUALITY Availability	○ ADDRESSES ● REQUIREMENT: Provider Failover Continuity ⌘	○ MECHANISM multi-provider resources with server-pushed active-resource switch
	○ TRADES-OFF ∅	○ AFFECTS ● COMPONENT: Service ⌘, ● COMPONENT: Web Client ⌘, ● ENTITY: Channel ⌘, ● ENTITY: Resource ⌘	○ OPERATED-BY ∅
	○ TOOLS ● COMPONENT: Messaging ⌘	Description Each channel carries multiple configured resources and the service pushes the active-resource change over MQTT so clients follow automatically — BECAUSE provider outages must be survived without attendee action.	

● TACTIC

Privacy by Design

Properties & Description

Diagram



○ QUALITY

Privacy

○ ADDRESSES

- **REQUIREMENT:** Privacy by Design ,
- **REQUIREMENT:** GDPR Compliance 

○ MECHANISM

automated anonymization on finish and no permanent accounts

○ TRADES-OFF

Usability

○ AFFECTS

- **COMPONENT:** Service ,
- **COMPONENT:** Database ,
- **ENTITY:** User ,
- **ENTITY:** Message ,
- **ENTITY:** AuthorizationToken ,
- **ENTITY:** SessionToken 

○ OPERATED-BY

∅

○ TOOLS


∅

Description

Personal data exists only while an event runs and is automatically anonymized or deleted on finish, with no standing user accounts — **BECAUSE** minimizing retained personal data is the strongest guarantee against data-protection risk.

Email-Verified Access

Diagram



○ QUALITY

Security

○ ADDRESSES

- **REQUIREMENT:** Unguessable Access Tokens 

○ MECHANISM

unguessable URLs plus time-limited one-time tokens and single sessions

○ TRADES-OFF



Usability

○ AFFECTS

- **COMPONENT:** Authentication Service ,
- **ENTITY:** AuthorizationToken ,
- **ENTITY:** SessionToken 

○ OPERATED-BY

∅


● TACTIC	Properties & Description		
	○ TOOLS	Description	
	∅	Access requires an unguessable URL and a short-lived one-time token, with only one active session enforced per user per event — BECAUSE layered, expiring secrets keep unauthorized viewers out without permanent credentials.	
Real-Time Reactivity ⚓	Diagram		
			
○ QUALITY	○ ADDRESSES	○ MECHANISM	
Performance	● REQUIREMENT: Live Configuration Latency ⓘ	MQTT publish/subscribe fan-out on per-event topics	
○ TRADES-OFF	○ AFFECTS	○ OPERATED-BY	
∅	● COMPONENT: Relay ⓘ, ● COMPONENT: Service ⓘ, ● COMPONENT: Web Client ⓘ, ● UNIT: Relay Pool ⓘ, ● UNIT: Service Event Loop ⓘ	∅	
○ TOOLS	Description		
● COMPONENT: Messaging ⓘ	Configuration and interaction changes are published on per-event MQTT topics and fanned out to subscribers — BECAUSE publish/subscribe propagates every change to all clients within the required time without polling.		
Abuse Resistance ⚓	Diagram		
			
○ QUALITY	○ ADDRESSES	○ MECHANISM	
Security	● REQUIREMENT: Interaction Abuse Throttling ⓘ	per-user rate limiting plus client and server sentiment filtering	
○ TRADES-OFF	○ AFFECTS	○ OPERATED-BY	
Usability	● COMPONENT: Service ⓘ, ● COMPONENT: Client NLP ⓘ	∅	
○ TOOLS	Description		
● COMPONENT: Sentiment Analysis ⓘ	Interaction is protected by configurable per-user throttling and optional client- and server-side sentiment checks — BECAUSE combining rate limits with content filtering defends the interaction channels against flooding and abuse.		

● TACTIC

Universal Browser Reach

Properties & Description

Diagram



○ QUALITY

Portability

○ ADDRESSES

- **REQUIREMENT:** Cross-Browser Compatibility ,
- **REQUIREMENT:** Mobile Usability 

○ MECHANISM

standards-based responsive web client with no plugins

○ TRADES-OFF

∅

○ AFFECTS

- **COMPONENT:** Web Client ,
- **NODE:** Client Device 

○ OPERATED-BY

∅

○ TOOLS


- **COMPONENT:** UI Framework ,
- **COMPONENT:** Styling Framework 

Description

The client is a standards-based responsive web application that adapts from desktop to mobile without plugins — **BECAUSE** a plugin-free web app reaches every recent browser on managed and unmanaged devices.

Provider Stream Passthrough

Diagram



○ QUALITY

Performance

○ ADDRESSES

- **REQUIREMENT:** Streaming Quality 

○ MECHANISM

provider-hosted encoding and delivery embedded by the client without transcoding

○ TRADES-OFF

∅

○ AFFECTS

- **COMPONENT:** Web Client ,
- **ENTITY:** Channel ,
- **ENTITY:** Resource 

○ OPERATED-BY

∅

○ TOOLS

∅

Description


The video is encoded and delivered by the streaming provider in the produced 1080p30 quality per language and embedded by the client as a resource of the channel, so the solution never touches the video itself — **BECAUSE** transcoding or relaying the video through the solution would cap the quality at the solution's own capacity.

● TACTIC

Network Segmentation

Properties & Description

Diagram



○ QUALITY

Security

○ ADDRESSES

● REQUIREMENT: Isolated Persistence Node ⓘ, ● REQUIREMENT: GDPR Compliance ⓘ

○ MECHANISM

TLS-only public ingress, private backend VLAN, and an isolated database subnet

○ TRADES-OFF

Maintainability

○ AFFECTS

● TIER: Middleware ⓘ, ● TIER: Database ⓘ, ● NODE: Edge Router ⓘ, ● NODE: Database Server ⓘ, ● NETWORK: Public Internet ⓘ, ● NETWORK: Backend Network ⓘ, ● NETWORK: Data Network ⓘ

○ OPERATED-BY

∅

○ TOOLS

● COMPONENT: Reverse Proxy ⓘ


Description

Traffic passes three segments, the TLS-only public Internet up to the hardened router, the private backend VLAN between the connection-handling tiers and the services, and the isolated data subnet reaching the database from the service containers alone — **BECAUSE** every hop an attacker has to cross before reaching the persisted personal data is one more chance to stop them.

Dump-Based Recovery

Properties & Description

Diagram



○ QUALITY

Reliability

○ ADDRESSES

● REQUIREMENT: Event Setup Recovery ⓘ

○ MECHANISM

logical database dumps with a rehearsed restore onto a fresh server

○ TRADES-OFF

Availability


○ AFFECTS

● NODE: Database Server ⓘ, ● NODE: Service Containers ⓘ, ● ENTITY: Event ⓘ, ● ENTITY: Message ⓘ

○ OPERATED-BY

● CONCERN: Database Backup ⓘ, ● CONCERN: Database Restore ⓘ

● TACTIC	Properties & Description		
	○ TOOLS ● COMPONENT: Database Backup ⓘ	Description The database is dumped logically on a schedule tightened before each event and rebuilt from the latest dump onto a fresh server by a rehearsed procedure — BECAUSE a portable dump plus a drilled restore meets the recovery objectives without operating a standby database.	
Edge Asset Delivery ⚓	Diagram		
○ QUALITY Scalability	○ ADDRESSES ● REQUIREMENT: Start-Surge Asset Delivery ⓘ	○ MECHANISM static client bundle served from a global CDN edge	
○ TRADES-OFF ∅	○ AFFECTS ● COMPONENT: Web Client ⓘ, ● TIER: Edge ⓘ, ● NODE: Cloudflare CDN ⓘ	○ OPERATED-BY ∅	
○ TOOLS ● COMPONENT: Build Tool ⓘ	Description The client bundle is built into static files and served from the CDN edge close to the audience, so the start surge of an event downloads from the edge instead of from the data center — BECAUSE a CDN absorbs ten thousand simultaneous downloads which would saturate the single data center entry point.		
Shared Typed Contracts ⚓	Diagram		
○ QUALITY Maintainability	○ ADDRESSES ● REQUIREMENT: Compile-Time Contract Safety ⓘ	○ MECHANISM common module of shared types compiled by one TypeScript toolchain on both sides	
○ TRADES-OFF ∅	○ AFFECTS ● COMPONENT: Web Client ⓘ, ● COMPONENT: Service ⓘ, ● ASPECT: Client/Common/Server Split ⓘ, ● ASPECT: Layered Linting ⓘ, ● ASPECT: Identifier Naming ⓘ	○ OPERATED-BY ∅	

● TACTIC	Properties & Description		
		TypeScript Everywhere ⓘ, ● ASPECT: Dependency Layering ⓘ, ● ASPECT: Layered Linting ⓘ, ● ASPECT: Identifier Naming ⓘ	
	○ TOOLS	Description	
	● COMPONENT: Language ⓘ, ● COMPONENT: Linting ⓘ	The message topics and payload types live once in the common module and are compiled into both client and server by the same strongly typed toolchain, layered so that the module depends on neither side — BECAUSE a contract shared at the type level turns every mismatch into a build error.	
	Diagram		
Snapshot Observability ⚓			
	○ QUALITY	○ ADDRESSES	○ MECHANISM
	Maintainability	● REQUIREMENT: Live Diagnosability ⓘ	periodic statistics snapshots plus recorded token states and structured logs
	○ TRADES-OFF	○ AFFECTS	○ OPERATED-BY
∅	● COMPONENT: Statistics Service ⓘ, ● COMPONENT: Authentication Service ⓘ, ● UNIT: Statistics Scheduler ⓘ, ● ENTITY: EventStatistic ⓘ, ● ENTITY: AuthorizationToken ⓘ	● CONCERN: Live Statistics Monitoring ⓘ, ● CONCERN: Authentication Diagnostics ⓘ	
○ TOOLS	Description		
● COMPONENT: Logging ⓘ	A scheduled task snapshots the event, channel, and user counters every five minutes and the authentication module records every token state next to its structured log — BECAUSE the running event can be observed and a failed login explained from data the solution collects anyway.		

30 ● ARCH: Design Decisions (DD) ⚓


Use MQTT over WebSockets as the live transport STATUS: Accepted	Self-host on Hetzner instead of public cloud STATUS: Accepted	Privacy by design with no permanent user accounts STATUS: Accepted	Email one-time token as the authentication factor STATUS: Accepted
Decouple logical Channels from physical provider Resources STATUS: Accepted	Embed provider-delivered video instead of self-hosted streaming STATUS: Accepted	One modular service process instead of microservices STATUS: Accepted	TypeScript with a shared common module across client and server STATUS: Accepted
Vue.js single-page client with headless widgets STATUS: Accepted	HAProxy as a two-stage router and proxy edge STATUS: Accepted	Three network segments with an isolated database subnet STATUS: Accepted	Single-host Docker Compose instead of a cluster orchestrator STATUS: Accepted
PostgreSQL as the single self-hosted relational store STATUS: Accepted	Typed SQL builder instead of a full ORM STATUS: Accepted	Logical dumps instead of continuous archiving for backup STATUS: Accepted	Serve the static client from a CDN edge outside the data center STATUS: Accepted

● DECISION

Use MQTT over WebSockets as the live transport ⚓

Properties

Diagram



○ STATUS	○ DRIVEN-BY	○ AFFECTS
Accepted	● REQUIREMENT: Concurrent Attendee Scale ⌘, ● REQUIREMENT: Live Configuration Latency ⌘, ● PREMISE: Attendee Networks Pass WebSocket Traffic ⌘	● COMPONENT: Relay ⌘, ● COMPONENT: Service ⌘, ● UNIT: Relay Pool ⌘
○ DECIDES	○ ALTERNATIVES	○ WHEN
● TACTIC: Real-Time Reactivity ⌘, ● COMPONENT: Messaging ⌘, ● COMPONENT: Message Broker ⌘	REST polling, bespoke WebSocket protocol	A single event must push video state, configuration changes, chat, questions, and likes to between 2500 and 10000 concurrently connected browsers with sub-two-second latency, and the same channel must carry bidirectional interaction.
○ WHAT	○ WHY	○ CONSEQUENCES
We use MQTT over WebSockets as the live transport, brokered by Mosquitto and MQTT-Plus in a horizontally scaled relay	MQTT's publish/subscribe model fans a single publish out to thousands of subscribers far more cheaply than per-client	Every live capability has to be expressible as messages on per-event topics, and the relay tier becomes a scaling and operating unit of its


● DECISION	Properties		
	tier, with per-event topics for fan-out and a thin Node.js service reacting to published messages.	REST polling or bespoke socket handling, and its mature broker ecosystem already solves connection scaling; a plain HTTP/REST design was rejected because it cannot deliver low-latency server-initiated fan-out at this connection count.	own, while attendee networks blocking WebSocket traffic lock their users out of the live channel.
Self-host on Hetzner instead of public cloud 📌	Diagram		
	○ STATUS	○ DRIVEN-BY	○ AFFECTS
	Accepted	● REQUIREMENT: GDPR Compliance 🔗 , ● REQUIREMENT: Per-Event Cost Efficiency 🔗 , ● PREMISE: EU Hosting on Self-Operated Infrastructure 🔗	● TIER: Data Center 🔗 , ● ASPECT: Git Codeline 🔗
	○ DECIDES	○ ALTERNATIVES	○ WHEN
	∅	Azure, AWS, GitHub	The solution must be GDPR-compliant with EU data residency, and a primary economic goal is to minimize recurring cost per event, the solution having been built specifically to replace a costlier third-party platform.
	○ WHAT	○ WHY	○ CONSEQUENCES
We operate all server tiers on self-managed Hetzner infrastructure in Nürnberg, Germany, separated into dev, QA, and production environments, rather than on Azure or AWS, and keep the source on a self-administered Gitea rather than on a hosted forge.	Hetzner delivers EU-resident hosting at a fraction of hyperscaler cost, satisfying both the data-residency and cost-minimization forces; public cloud was rejected because its per-event egress and compute pricing would undermine the cost goal that justified building the solution at all.	Provisioning, scaling, monitoring, and backup are operated by the team itself instead of being consumed as managed services, so the Operations View carries the procedures a hyperscaler would have provided.	

● DECISION

Privacy by design with no permanent user accounts 

Properties

Diagram



○ STATUS

Accepted

○ DRIVEN-BY

● **REQUIREMENT:** Privacy by Design ,
 ● **REQUIREMENT:** GDPR Compliance ,
 ● **PREMISE:** Message Texts Contain Personal Data 

○ AFFECTS

● **COMPONENT:** Authentication Service ,
 ● **COMPONENT:** Service , ● **ENTITY:** User ,
 ● **PRINCIPLE:** Privacy-Visible Identity 

○ DECIDES

● **TACTIC:** Privacy by Design 

○ ALTERNATIVES

persistent user accounts

○ WHEN

Events handle personal attendee data under GDPR, yet attendance is transient and the operator wants to carry as little personal-data liability as possible while still supporting per-event identity for chat and moderation.

○ WHAT

We hold no permanent user accounts: users exist only via an event access list, role grant, or pattern match, and on event finish an automated procedure anonymizes messages and deletes users, tokens, and Moderator roles.

○ WHY


Deleting personal data the moment it is no longer needed minimizes both breach impact and compliance burden, which outweighs the convenience of persistent accounts; a conventional account model was rejected because standing personal data is exactly the liability privacy by design exists to avoid.

○ CONSEQUENCES





Email one-time token as the authentication factor 



Diagram




● DECISION	Properties		
	○ STATUS Accepted	○ DRIVEN-BY ● REQUIREMENT: Unguessable Access Tokens ⓘ, ● PREMISE: Attendees Read Their Email While Logging In ⓘ, ● PREMISE: Email Gateway Delivers Tokens Within Minutes ⓘ	○ AFFECTS ● COMPONENT: Authentication Service ⓘ, ● PATTERN: Two-Factor Login ⓘ, ● PRINCIPLE: Frictionless Joining ⓘ
	○ DECIDES ● TACTIC: Email-Verified Access ⓘ	○ ALTERNATIVES password accounts, external identity providers	○ WHEN Access must be limited to invited attendees without permanent credentials, while also supporting frictionless and fully automated joining for large distributions provisioned from the Event Registration System.
	○ WHAT We authenticate via a one-time “NNN-NNN” token emailed to the attendee’s address, with optionally pre-generated tokens embeddable in the access URL for automatic entry, and we enforce a single active session per user per event.	○ WHY An emailed token proves control of the authorized address with zero stored credentials and reuses email as a channel everyone already has, fitting the no-accounts stance; password accounts and external identity providers were rejected as too heavy and as reintroducing the persistent personal data the design forbids.	○ CONSEQUENCES ∅
	Diagram		
Decouple logical Channels from physical provider Resources ⓘ			
○ STATUS Accepted	○ DRIVEN-BY ● REQUIREMENT: Provider Failover Continuity ⓘ, ● PREMISE: Streaming Providers Deliver the Video ⓘ, ● PREMISE: German and English Cover All Events ⓘ	○ AFFECTS ● COMPONENT: Service ⓘ, ● COMPONENT: Web Client ⓘ, ● ENTITY: Channel ⓘ, ● ENTITY: Resource ⓘ	
○ DECIDES ● TACTIC: Live Failover Continuity ⓘ	○ ALTERNATIVES direct binding of clients to a single provider stream	○ WHEN Productions ship in multiple languages and resolutions	



● DECISION	Properties		
			and must survive a streaming-provider outage mid-event by switching providers without attendees having to act or even notice.
	○ WHAT We model an event as logical Channels each backed by multiple physical Resources, where exactly one Channel and one Resource are active at a time, and switching the active Resource is pushed live to all clients.	○ WHY Separating the audience-facing logical stream from interchangeable provider endpoints makes live failover a state change rather than a reconfiguration, satisfying both the multi-variant and continuity forces; binding clients directly to a single provider was rejected because it would make any provider problem an event-ending failure.	○ CONSEQUENCES ∅
Embed provider-delivered video instead of self-hosted streaming 	Diagram  ○ STATUS Accepted ○ DRIVEN-BY ● REQUIREMENT: Streaming Quality , ● REQUIREMENT: Per-Event Cost Efficiency , ● PREMISE: Streaming Providers Deliver the Video  ○ AFFECTS ● COMPONENT: Web Client , ● ENTITY: Channel , ● ENTITY: Resource , ● ENTITY: Streaming Provider  ○ DECIDES ● TACTIC: Provider Stream Passthrough  ○ ALTERNATIVES self-hosted media server (e.g. OvenMediaEngine, Wowza), relaying the video through the data center ○ WHEN Productions are delivered in 1080p30 in two languages to up to 10000 attendees, the streaming providers already encode and distribute the video worldwide, and the per-event cost has to stay low. ○ WHAT We leave the video entirely with the streaming providers: the client embeds the provider player of the active resource, and the solution carries only the ○ WHY A provider delivers the produced quality from a global network for a per-event fee, whereas self-hosted streaming would need transcoding and ○ CONSEQUENCES The solution depends on the providers for the entire video path, so the provider failover has to be a first-class mechanism, and the video quality is capped by		

● DECISION	Properties		
	metadata telling every client which resource to play.	egress capacity for 10000 viewers in the data center; a self-hosted media server was rejected as the single most expensive and most fragile piece the solution could take on.	what the providers deliver rather than tunable by the solution.
One modular service process instead of microservices 	Diagram		
	 <pre> graph LR D["DECISION One modular service process instead of microservices STATUS: Accepted"] R1["REQUIREMENT Per-Event Cost Efficiency"] R2["REQUIREMENT Compile-Time Contract Safety"] R3["REQUIREMENT Horizontal Scalability"] C1["COMPONENT Service"] C2["COMPONENT Translation Service"] C3["COMPONENT Authentication Service"] C4["COMPONENT Statistics Service"] U1["UNIT Service Event Loop"] N1["NODE Service Containers"] D -- driven-by --> R1 D -- driven-by --> R2 D -- driven-by --> R3 D -- affects --> C1 D -- affects --> C2 D -- affects --> C3 D -- affects --> C4 D -- affects --> U1 D -- affects --> N1 </pre>		
○ STATUS	○ DRIVEN-BY	○ AFFECTS	
Accepted	● REQUIREMENT: Per-Event Cost Efficiency , ● REQUIREMENT: Compile-Time Contract Safety , ● REQUIREMENT: Horizontal Scalability 	● COMPONENT: Service , ● COMPONENT: Authentication Service , ● COMPONENT: Translation Service , ● COMPONENT: Statistics Service , ● UNIT: Service Event Loop , ● NODE: Service Containers 	
○ DECIDES	○ ALTERNATIVES	○ WHEN	
∅	one service per capability (authentication, messaging, translation, statistics)	The business logic of events, access, moderation, translation, and statistics is small and shares one data model, the connection load is carried by the relay tier anyway, and a small team operates the solution itself.	
○ WHAT	○ WHY	○ CONSEQUENCES	
We run the entire business logic as one Node.js service process with authentication, translation, and statistics as modules inside it, scaled by running several identical instances per environment.	The scaling problem of the solution is the connection count, which the relay tier solves, not the business logic, so splitting it would buy nothing but network hops, partial failures, and contracts to keep in sync; per-capability services were rejected because they multiply the operating effort of a self-hosted solution.	Every module shares the release cycle and the failure domain of the service, and a module growing a load profile of its own has to be carved out later at the cost of a refactoring.	


● DECISION TypeScript with a shared common module across client and server and server 	Properties Diagram 	
○ STATUS Accepted	○ DRIVEN-BY ● REQUIREMENT: Compile-Time Contract Safety 	○ AFFECTS ● ASPECT: Client/Common/Server Split , ● ASPECT: TypeScript Everywhere , ● ASPECT: Dependency Layering , ● ASPECT: Identifier Naming 
○ DECIDES ● TACTIC: Shared Typed Contracts , ● COMPONENT: Language 	○ ALTERNATIVES plain JavaScript, per-tier types generated from an interface description (e.g. OpenAPI, AsyncAPI)	○ WHEN Client and server exchange dozens of message types over MQTT topics, both sides evolve together in one repository, and a contract mismatch would surface only during a live event.
○ WHAT We write client, server, and a common module in TypeScript, keep every topic and payload type in the common module, and let both sides import it, with the common module depending on neither of them.	○ WHY Sharing the types directly makes the compiler the contract check with no generator and no drift between a description and the code; plain JavaScript was rejected as it leaves mismatches to runtime, and generated per-tier types as they reintroduce an intermediate description to keep in sync.	○ CONSEQUENCES ∅
Vue.js single-page client with headless widgets 	Diagram 	
○ STATUS Accepted	○ DRIVEN-BY ● REQUIREMENT: Cross-Browser Compatibility , ● REQUIREMENT: Mobile Usability ,	○ AFFECTS ● COMPONENT: Web Client , ● ASPECT: Vite Client Build 


● DECISION	Properties		
		● REQUIREMENT: Live Configuration Latency ⓘ	
	○ DECIDES	○ ALTERNATIVES	○ WHEN
	● TACTIC: Universal Browser Reach ⓘ, ● COMPONENT: UI Framework ⓘ, ● COMPONENT: Widget Framework ⓘ, ● COMPONENT: Build Tool ⓘ	React, Svelte, server-rendered pages with progressive enhancement	The attendee and operator screens run in any recent browser on managed and unmanaged desktop and mobile devices, react to server-pushed changes within seconds, and are styled to the corporate design without a native look.
	○ WHAT	○ WHY	○ CONSEQUENCES
	We build the client as a Vue.js single-page application composed of headless Reka UI widgets styled with Tailwind CSS, bundled by Vite into static files.	A reactive component model maps server-pushed state straight onto the screen, and headless widgets give accessible behavior while leaving the styling free; React was rejected for its heavier toolchain in a small team, Svelte for its thinner ecosystem, and server-rendered pages because they cannot follow live state without reloads.	⊘
HAProxy as a two-stage router and proxy edge ⓘ	Diagram		
	○ STATUS	○ DRIVEN-BY	○ AFFECTS
	Accepted	● REQUIREMENT: Horizontal Scalability ⓘ, ● REQUIREMENT: Isolated Persistence Node ⓘ	● COMPONENT: Router ⓘ, ● COMPONENT: Proxy ⓘ, ● UNIT: Router Process ⓘ, ● UNIT: Proxy Pool ⓘ, ● TIER: Middleware ⓘ, ● NODE: Edge Router ⓘ, ● NODE: Proxy Servers ⓘ
	○ DECIDES	○ ALTERNATIVES	○ WHEN
	● COMPONENT: Reverse Proxy ⓘ	nginx, Traefik, a managed cloud load balancer	Ten thousand long-lived WebSocket connections per event have to enter one hardened data center entry point and be spread across the per-environment proxy

● DECISION	Properties		
			and relay instances, with dev, QA, and production separated at the edge.
	○ WHAT We terminate all traffic at one HAProxy router process per entry point, firewalled by NfTables, which round-robins it to a pool of HAProxy proxy instances per environment forwarding to the relay brokers.	○ WHY HAProxy handles WebSocket upgrades and connection counts of this size with a mature configuration model and serves both stages with one product; nginx was rejected for its weaker connection-level balancing, Traefik for its container-centric configuration, and a managed load balancer because the solution is self-hosted.	○ CONSEQUENCES The router is a single point of entry per data center and its capacity is the ceiling of the environment, and every routing change touches a hand-maintained configuration.
Three network segments with an isolated database subnet 	Diagram		
	 <pre> graph LR subgraph DecisionBox [DECISION: Three network segments with an isolated database subnet STATUS: Accepted] direction TB subgraph DrivenBy [DRIVEN-BY] IPN[Isolated Persistence Node] GDPR[GDPR Compliance] end subgraph Affects [AFFECTS] DS[Database Server] BN[Backend Network] NS[Tactic: Network Segmentation] end subgraph Decides [DECIDES] NS end end IPN -- driven-by --> DecisionBox GDPR -- driven-by --> DecisionBox DecisionBox -- affects --> DS DecisionBox -- affects --> BN DecisionBox -- affects --> NS NS -- decides --> NS NS -- affects --> PI[Tier: Public Internet] NS -- affects --> DN[Network: Data Network] NS -- affects --> DB[Tier: Database] </pre>		
○ STATUS	○ DRIVEN-BY	○ AFFECTS	
Accepted	● REQUIREMENT: Isolated Persistence Node  ● REQUIREMENT: GDPR Compliance 	● NETWORK: Public Internet  ● NETWORK: Backend Network  ● NETWORK: Data Network  ● NODE: Database Server  ● TIER: Database 	
○ DECIDES	○ ALTERNATIVES	○ WHEN	
● TACTIC: Network Segmentation 	one flat private network, database attached to the backend network	The persisted personal data of the attendees lives on the database server, while the router, proxies, and relays face the Internet and are the parts most likely to be compromised.	
○ WHAT	○ WHY	○ CONSEQUENCES	
We segment the data center into a private backend VLAN carrying the router, proxies, relays, and services, and an isolated data subnet carrying only the database and the service containers, behind the TLS-only public Internet.	A compromised connection-handling node then still has no route to the database, which is the strongest containment available at no recurring cost on a private vSwitch; a flat network was rejected because it makes every node a stepping stone to the personal data.	∅	

● DECISION	Properties		
Single-host Docker Compose instead of a cluster orchestrator 	Diagram 		
	○ STATUS Accepted	○ DRIVEN-BY ● REQUIREMENT: Per-Event Cost Efficiency  , ● REQUIREMENT: Horizontal Scalability  , ● REQUIREMENT: Event-Safe Maintenance 	○ AFFECTS ● NODE: Service Containers  , ● NODE: Proxy Servers  , ● NODE: Relay Brokers 
	○ DECIDES ● COMPONENT: Container Orchestration 	○ ALTERNATIVES Kubernetes, Nomad	○ WHEN Each environment runs a handful of proxy, relay, and service instances on self-managed servers, scaling is planned ahead of an event rather than reacting to load, and rollouts happen only between events.
	○ WHAT We run and recreate the containers of an environment with Docker Compose from one compose file per environment, adding instances by editing that file and recreating between events.	○ WHY Planned, per-event scaling and rollouts between events need no scheduler, self-healing, or rolling updates, so a cluster would add an operating burden without a benefit; Kubernetes and Nomad were rejected because operating the cluster would cost more than the solution it hosts.	○ CONSEQUENCES There is no automatic failover of a crashed instance during an event, and growing beyond one host per environment means revisiting this decision.
● DECISION	Diagram		
PostgreSQL as the single self-hosted relational store 	Diagram 		
	○ STATUS Accepted	○ DRIVEN-BY ● REQUIREMENT: GDPR Compliance  , ● REQUIREMENT: Event Setup Recovery  , ● REQUIREMENT: Per-	○ AFFECTS ● COMPONENT: Database  , ● UNIT: Database Server  , ● NODE: Database Server  , ● TIER: Database 

● DECISION	Properties		
		Event Cost Efficiency ⓘ, ● PREMISE: EU Hosting on Self-Operated Infrastructure ⓘ	
	○ DECIDES	○ ALTERNATIVES	○ WHEN
	● COMPONENT: Database ⓘ	a document store (e.g. MongoDB), an embedded database (e.g. SQLite), a managed cloud database	Events, channels, messages, tokens, and statistics form a relational model with transactional invariants, the data has to stay in the EU data center, and moderation and reporting need ad-hoc queries over it.
	○ WHAT	○ WHY	○ CONSEQUENCES
	We persist all state in one self-hosted PostgreSQL primary per environment, accessed by the service alone, with the filesystem beside it for the static assets.	A relational store with ACID transactions matches the model and the consistency the moderation needs, and PostgreSQL self-hosts on the same servers at no license cost; a document store was rejected for its weaker invariants, an embedded database for its single-writer limit across service instances, and a managed database as it leaves the self-hosted boundary.	⊘
Typed SQL builder instead of a full ORM ⓘ	Diagram		
	<pre> graph LR D["DECISION Typed SQL builder instead of a full ORM STATUS: Accepted"] R1["REQUIREMENT Concurrent Attendee Scale"] R2["REQUIREMENT Compile-Time Contract Safety"] C1["COMPONENT Service"] C2["COMPONENT Database"] C3["COMPONENT Persistence Layer"] D -- driven-by --> R1 D -- driven-by --> R2 D -- affects --> C1 D -- affects --> C2 D -- decides --> C3 </pre>		
	○ STATUS	○ DRIVEN-BY	○ AFFECTS
	Accepted	● REQUIREMENT: Compile-Time Contract Safety ⓘ, ● REQUIREMENT: Concurrent Attendee Scale ⓘ	● COMPONENT: Service ⓘ, ● COMPONENT: Database ⓘ
	○ DECIDES	○ ALTERNATIVES	○ WHEN
	● COMPONENT: Persistence Layer ⓘ	Prisma, TypeORM	The service persists the event state through TypeScript against PostgreSQL, the schema is generated spec-first from the data model, and the


● DECISION	Properties		
			message handlers have to stay cheap under the load of a large event.
	○ WHAT	○ WHY	○ CONSEQUENCES
	We access PostgreSQL through Drizzle, a typed SQL query builder and schema definition layer, with the schema derived from the data model.	A thin typed layer keeps the end-to-end type safety of the shared contracts down to the database without the query overhead and abstraction leaks of a heavy ORM; Prisma was rejected for its separate schema language and query engine, TypeORM for its runtime cost and weaker typing.	∅
Logical dumps instead of continuous archiving for backup 	Diagram		
	 <pre> graph LR D["DECISION Logical dumps instead of continuous archiving for backup STATUS: Accepted"] R1["REQUIREMENT Event Setup Recovery"] R2["REQUIREMENT Per-Event Cost Efficiency"] N["NODE Database Server"] T["TACTIC Dump-Based Recovery"] C["COMPONENT Database Backup"] D -- driven-by --> R1 D -- driven-by --> R2 D -- affects --> N D -- decides --> T D -- decides --> C </pre>		
○ STATUS	○ DRIVEN-BY	○ AFFECTS	
Accepted	● REQUIREMENT: Event Setup Recovery ⓘ ● REQUIREMENT: Per-Event Cost Efficiency ⓘ	● NODE: Database Server ⓘ	
○ DECIDES	○ ALTERNATIVES	○ WHEN	
● TACTIC: Dump-Based Recovery ⓘ ● COMPONENT: Database Backup ⓘ	pgBackRest, Barman (continuous WAL archiving with point-in-time recovery)	The recovery objective tolerates the loss of a day of changes (an hour right before an event), the data volume per event is small, and the backup must stay within the EU data center without a backup server of its own.	
○ WHAT	○ WHY	○ CONSEQUENCES	
We back up with logical pg_dump dumps taken nightly and before each event onto the backup storage of the data center and restore them with pg_restore onto a fresh server.	A logical dump is portable across PostgreSQL versions, needs no additional server, and meets the objectives as the data changes mainly before an event; continuous archiving was rejected because point-in-time recovery buys nothing for data that is anonymized at the end of every event anyway.	∅	



● DECISION	Properties		
Serve the static client from a CDN edge outside the data center 	Diagram 		
○ STATUS	○ DRIVEN-BY	○ AFFECTS	
Accepted	● REQUIREMENT: Start-Surge Asset Delivery , ● REQUIREMENT: GDPR Compliance , ● PREMISE: Connection Surge at Event Start 	● TIER: Edge , ● NODE: Cloudflare CDN , ● ENTITY: Content CDN 	
○ DECIDES	○ ALTERNATIVES	○ WHEN	
● TACTIC: Edge Asset Delivery 	serving the bundle from the data center router, a second Hetzner location	Up to 10000 attendees download the client bundle within the same minute at the start of an event, the data center has one entry point, and the personal data has to stay within the EU.	
○ WHAT	○ WHY	○ CONSEQUENCES	
We serve the static client bundle and static resources from a Cloudflare CDN edge, while every live connection and every request carrying personal data goes to the data center directly.	The bundle is public, identical for everyone, and cacheable, exactly what a CDN absorbs at any scale, so the start surge never reaches the data center; serving it from the router was rejected because the surge would compete with the live connections for the same entry point.	Only static, non-personal content leaves the EU hosting boundary, but the CDN sees the client addresses, so the data processing agreement with the CDN provider is part of the GDPR compliance evidence.	

31 ● TEST: Test Cases (TC)

Valid Token Grants Access	Unauthorized Email Rejected	URL Token Skips Login Dialog	Second Login Closes First Session
Moderated Question Starts Pending	Unmoderated Chat Starts Accepted	Chat Cannot Enter Question States	Moderator Message Starts Accepted
Forwarded Message Is Locked	Sentiment Auto-Reject Below Threshold	Sentiment Auto-Accept Above Threshold	Throttled Submission Not Stored
Live Provider Switch Propagates	Channel Activation Deactivates Previous	First Channel Activated on Creation	First Resource Activated on Creation
Active Channel Not Deactivated Directly	Active Resource Not Deactivated Directly	Config Change Reaches Clients	Registration Import Avoids Duplicates
Returned URL Format	Anonymization Removes Personal Data	User Vanishes Without Role or Access	Export Contains Required Fields
Manager Role Survives Finish	Chat Message Shows Configured Name	Like Toggles the Count	Deleted Message Leaves Placeholder
Client-Side Check Holds Back Improper Input	Direct Moderator Reply Stays Private	Resource URL Selects the Resource	Language Switch Applies Immediately
Presenter Sees Forwarded Questions Only	Administrator Sees No Attendee Data	Administrator Enters Without Access List Entry	Administrator Role Granted by Configuration Only
Concurrent Attendee Load			

Coverage	Covered	Total	Ratio
● USE-CASE	9	14	64%
● SCENARIO	21	51	41%
● REQUIREMENT	26	63	41%
● RULE	18	18	100%

● TEST-CASE	Properties & Description
Valid Token Grants Access 	Diagram 



● TEST-CASE	Properties & Description		
	○ VERIFIES ● REQUIREMENT: User Authentication ⓘ, ● SCENARIO: Login with Emailed Token ⓘ, ● RULE: Access Requires List or Pattern Match ⓘ, ● TRANSITION: consume ⓘ, ● PERMISSION: Prove the Email Address ⓘ	○ WORKFLOWS ∅	○ PRE-CONDITION An invited user with a sent, unexpired authorization token exists for a running event.
	○ INPUT The user submits the correct six-digit token for their email.	○ EXPECTED The system issues a session token and grants access to the stream.	○ POST-CONDITION The authorization token is in state used.
	Description ∅		
	Diagram 		
	○ VERIFIES ● REQUIREMENT: User Authentication ⓘ, ● SCENARIO: Email Not Authorized ⓘ, ● RULE: Access Requires List or Pattern Match ⓘ, ● PERMISSION: Enter the Event ⓘ	○ WORKFLOWS ∅	○ PRE-CONDITION An email not on the access list and not matching the access pattern.
○ INPUT The user enters that email in the login dialog.	○ EXPECTED The system denies access and shows a not-authorized notice.	○ POST-CONDITION No session token exists and no authorization token was sent for the email.	
Description ∅			
Diagram 			



Unauthorized Email Rejected ⓘ

URL Token Skips Login Dialog ⓘ




● TEST-CASE	Properties & Description		
	○ VERIFIES	○ WORKFLOWS	○ PRE-CONDITION
	● REQUIREMENT: Automatic Event Access URL ②, ● SCENARIO: Automatic Token in URL ②, ● RULE: Token Format and Validity ②, ● TRANSITION: consume ②	∅	An event allows URL tokens and a pre-generated token exists for an invited email.
	○ INPUT	○ EXPECTED	○ POST-CONDITION
	The user opens the event URL carrying that email and token.	The system issues a session token and grants access without showing the login dialog.	The user holds an active session token.
Description			
∅			
Second Login Closes First Session ①	Diagram		
TEST CASE Second Login Closes First Session verifies verifies REQUIREMENT Limit Parallel Access RULE Single Active Session per Event			
○ VERIFIES	○ WORKFLOWS	○ PRE-CONDITION	
● REQUIREMENT: Limit Parallel Access ②, ● RULE: Single Active Session per Event ②	∅	A user holds an active session for an event from one device.	
○ INPUT	○ EXPECTED	○ POST-CONDITION	
The same user completes a login from a second device.	The first connection is closed and only the new session remains active.	Exactly one active session token exists for the user and event.	
Description			
1. The user watches the stream on the first device. 2. The same user completes a login with a fresh authorization token on a second device. 3. The tester observes the first device.			
Moderated Question Starts Pending ①	Diagram		
TEST CASE Moderated Question Starts Pending verifies verifies verifies REQUIREMENT Moderate Chat and Questions RULE Moderation Determines Initial Visibility SCENARIO Submit Moderated Question			

● TEST-CASE	Properties & Description		
	○ VERIFIES	○ WORKFLOWS	○ PRE-CONDITION
	● REQUIREMENT: Moderate Chat and Questions ⓘ, ● SCENARIO: Submit Moderated Question ⓘ, ● RULE: Moderation Determines Initial Visibility ⓘ	○	An event with question moderation enabled is running.
	○ INPUT	○ EXPECTED	○ POST-CONDITION
	An attendee submits a question.	The question is stored in state pending and is not visible to the audience.	○
Description			
○			
Unmoderated Chat Starts Accepted ⓘ	Diagram		
	<pre> graph LR TC[TEST-CASE Unmoderated Chat Starts Accepted] -- verifies --> R[REQUIREMENT Moderate Chat and Questions] TC -- verifies --> RL[RULE Moderation Determines Initial Visibility] TC -- verifies --> S[SCENARIO Post a Chat Message] </pre>		
	○ VERIFIES	○ WORKFLOWS	○ PRE-CONDITION
	● REQUIREMENT: Moderate Chat and Questions ⓘ, ● SCENARIO: Post a Chat Message ⓘ, ● RULE: Moderation Determines Initial Visibility ⓘ	○	An event with chat moderation disabled is running.
	○ INPUT	○ EXPECTED	○ POST-CONDITION
	An attendee submits a chat message.	The message is accepted at once upon creation and is immediately visible.	○
Description			
○			
Chat Cannot Enter Question States ⓘ	Diagram		
	<pre> graph LR TC[TEST-CASE Chat Cannot Enter Question States] -- verifies --> R[REQUIREMENT Moderate Chat and Questions] TC -- verifies --> RL[RULE State Set Depends on Message Type] </pre>		
	○ VERIFIES	○ WORKFLOWS	○ PRE-CONDITION
	● REQUIREMENT: Moderate Chat and Questions ⓘ, ● RULE: State Set Depends on Message Type ⓘ	○	An accepted chat message exists in a running event.


● TEST-CASE	Properties & Description		
	○ INPUT A moderator attempts to forward the chat message to the presenter.	○ EXPECTED The system refuses the transition, as a chat message permits only the states pending, accepted, and rejected.	○ POST-CONDITION The chat message remains in state accepted.
	Description		
	Diagram		
Moderator Message Starts Accepted 			
	○ VERIFIES ● REQUIREMENT: Moderator-Authored Messages , ● SCENARIO: Seed the Conversation as Moderator , ● RULE: Moderator Messages Auto-Accepted 	○ WORKFLOWS 	○ PRE-CONDITION An event with chat moderation enabled is running.
	○ INPUT A moderator posts a chat message without overriding the sender name.	○ EXPECTED The message is accepted at once upon creation with the sender name “Moderator” and is immediately visible.	○ POST-CONDITION 
	Description		
	Diagram		
Forwarded Message Is Locked 			
	○ VERIFIES ● REQUIREMENT: Edit and Delete Messages , ● SCENARIO: Forwarded Question Locked , ● RULE: Forwarded Messages Are Immutable , ● PERMISSION: Correct Own Messages 	○ WORKFLOWS 	○ PRE-CONDITION An accepted question of an attendee exists in a running event.



● TEST-CASE	Properties & Description		
	○ INPUT	○ EXPECTED	○ POST-CONDITION
	The original attendee attempts to edit and then to delete the forwarded message.	The system refuses both the edit and the deletion and the message remains unchanged.	∅
	Description 1. The moderator forwards the accepted question to the presenter. 2. The original attendee attempts to edit the text of the question. 3. The original attendee attempts to delete the question.		
Sentiment Auto-Reject Below Threshold 	Diagram 		
	○ VERIFIES ● REQUIREMENT: Server-Side Sentiment Analysis  , ● SCENARIO: Auto-Rejected by Sentiment  , ● RULE: Sentiment Auto-Decision Threshold 	○ WORKFLOWS ∅	○ PRE-CONDITION Server-side sentiment analysis and auto-reject are enabled.
	○ INPUT An attendee submits a message scoring -0.5.	○ EXPECTED The system rejects the message at once upon creation, without a moderator decision.	○ POST-CONDITION ∅
	Description ∅		
Sentiment Auto-Accept Above Threshold 	Diagram 		
	○ VERIFIES ● REQUIREMENT: Server-Side Sentiment Analysis  , ● SCENARIO: Auto-Accepted by Sentiment  , ● RULE: Sentiment Auto-Decision Threshold 	○ WORKFLOWS ∅	○ PRE-CONDITION Server-side sentiment analysis and auto-accept are enabled for a moderated event.
	○ INPUT An attendee submits a question scoring +0.5.	○ EXPECTED The system accepts the question at once upon	○ POST-CONDITION ∅

● TEST-CASE	Properties & Description		
Throttled Submission Not Stored		creation, bypassing the moderator decision.	
	Description		
	∅		
	Diagram		
	<pre> graph LR TC[TEST-CASE Throttled Submission Not Stored] -- verifies --> R[REQUIREMENT Interaction Abuse Throttling] TC -- verifies --> S[SCENARIO Throttled Submission] TC -- verifies --> T[TACTIC Abuse Resistance] </pre>		
	○ VERIFIES	○ WORKFLOWS	○ PRE-CONDITION
	● REQUIREMENT: Interaction Abuse Throttling , ● SCENARIO: Throttled Submission , ● TACTIC: Abuse Resistance	∅	A running event with the default submission limit of 10 per user per minute.
	○ INPUT	○ EXPECTED	○ POST-CONDITION
	The attendee submits an eleventh question within the same minute.	The system rejects the eleventh submission and informs the attendee to wait, but accepts the twelfth one after the minute has passed.	The eleventh question is not stored, while the ten earlier ones remain unchanged and the twelfth one is stored.
	Description		
Live Provider Switch Propagates	Diagram		
	<pre> graph LR TC[TEST-CASE Live Provider Switch Propagates] -- verifies --> R[REQUIREMENT Live Provider Switching] TC -- verifies --> S[RULE Single Active Resource per Channel] </pre>		
	○ VERIFIES	○ WORKFLOWS	○ PRE-CONDITION
	● REQUIREMENT: Live Provider Switching , ● RULE: Single Active Resource per Channel	∅	A running event with two configured resources and connected clients.
	○ INPUT	○ EXPECTED	○ POST-CONDITION
	The manager activates the second resource on the channel.	All connected clients switch to the new stream without user interaction.	Exactly one resource of the channel is active.
	Description		
	∅		



● TEST-CASE	Properties & Description		
Channel Activation Deactivates Previous ↕ Previous ↕	Diagram 		
	○ VERIFIES ● REQUIREMENT: Live Provider Switching ↕ , ● RULE: Single Active Channel ↕	○ WORKFLOWS ∅	○ PRE-CONDITION A running event with two configured channels, the first one active.
	○ INPUT The manager activates the second channel.	○ EXPECTED The second channel becomes active and the first one is deactivated in the same step.	○ POST-CONDITION Exactly one channel of the event is active.
First Channel Activated on Creation ↕ First Channel Activated on Creation ↕	Diagram 		
	○ VERIFIES ● RULE: Initial Channel Becomes Active ↕ , ● RULE: Single Active Channel ↕ , ● PERMISSION: Lay Out the Channels ↕	○ WORKFLOWS ∅	○ PRE-CONDITION A provisioned event without any channel.
	○ INPUT The manager creates a channel without marking it as active.	○ EXPECTED The system stores the channel as the active one.	○ POST-CONDITION Exactly one channel of the event is active.
First Resource Activated on Creation ↕ First Resource Activated on Creation ↕	Diagram 		
	○ VERIFIES ● RULE: Initial Resource Becomes Active ↕ , ● RULE: Single Active Resource per Channel ↕ ,	○ WORKFLOWS ∅	○ PRE-CONDITION A channel without any resource.

● TEST-CASE	Properties & Description		
	● PERMISSION: Administer the Resources ⓘ		
	○ INPUT	○ EXPECTED	○ POST-CONDITION
	The administrator creates a resource without marking it as active.	The system stores the resource as the active one.	Exactly one resource of the channel is active.
	Description		
Active Channel Not Deactivated Directly ⓘ	Diagram		
	<pre> graph LR TC[TEST-CASE Active Channel Not Deactivated Directly] -- verifies --> R[RULE Single Active Channel] TC -- verifies --> P[PERMISSION Lay Out the Channels] </pre>		
	○ VERIFIES	○ WORKFLOWS	○ PRE-CONDITION
	● RULE: Single Active Channel ⓘ, ● PERMISSION: Lay Out the Channels ⓘ	∅	An event with two channels, the first one active.
	○ INPUT	○ EXPECTED	○ POST-CONDITION
	The manager deactivates the first channel directly, then deletes it.	The system rejects both the deactivation and the deletion, as another channel would have to be activated first.	The first channel still exists and is the only active channel of the event.
	Description		
	∅		
Active Resource Not Deactivated Directly ⓘ	Diagram		
	<pre> graph LR TC[TEST-CASE Active Resource Not Deactivated Directly] -- verifies --> R[RULE Single Active Resource per Channel] TC -- verifies --> P[PERMISSION Administer the Resources] </pre>		
	○ VERIFIES	○ WORKFLOWS	○ PRE-CONDITION
	● RULE: Single Active Resource per Channel ⓘ, ● PERMISSION: Administer the Resources ⓘ	∅	A channel with two resources, the first one active.
	○ INPUT	○ EXPECTED	○ POST-CONDITION
	The administrator deactivates the first resource directly, then deletes it.	The system rejects both the deactivation and the deletion, as another resource would have to be activated first.	The first resource still exists and is the only active resource of the channel.
	Description		
	∅		
Config Change Reaches Clients ⓘ	Diagram		
	<pre> graph LR TC[TEST-CASE Config Change Reaches Clients] -- verifies --> R[REQUIREMENT Live Configuration Propagation] </pre>		

● TEST-CASE	Properties & Description		
	○ VERIFIES	○ WORKFLOWS	○ PRE-CONDITION
	● REQUIREMENT: Live Configuration Propagation ⓘ	∅	A running event with connected clients and chat disabled.
	○ INPUT	○ EXPECTED	○ POST-CONDITION
	The manager enables chat for the event.	Connected clients show the chat panel within 2 seconds without a reload.	∅
Description			
∅			
Registration Import Avoids Duplicates ⓘ	Diagram		
			
	○ VERIFIES	○ WORKFLOWS	○ PRE-CONDITION
	● REQUIREMENT: Import Registered Attendees ⓘ	∅	A running event with an empty access list.
	○ INPUT	○ EXPECTED	○ POST-CONDITION
	The manager imports a second registration sheet overlapping the first one.	The overlapping users are not duplicated, their tokens from the first import are returned unchanged, and only the new users receive fresh tokens.	∅
Description			
1. The manager imports a registration sheet with the emails A, B, and C. 2. The manager records the tokens returned for A, B, and C. 3. The manager imports a second registration sheet with the emails B, C, and D.			
Returned URL Format ⓘ	Diagram		
			
	○ VERIFIES	○ WORKFLOWS	○ PRE-CONDITION
	● REQUIREMENT: Return Access URLs to Registration ⓘ, ● RULE: Token Format and Validity ⓘ, ● ATTRIBUTE: token ⓘ	∅	A registration import has generated tokens for new users.
	○ INPUT	○ EXPECTED	○ POST-CONDITION
	The manager exports the access URLs.	Each URL contains event, user, and a six-digit “NNN-NNN” token in the URL column.	∅
Description			
∅			

● TEST-CASE	Properties & Description		
Anonymization Removes Personal Data ⚓	Diagram 		
	○ VERIFIES ● REQUIREMENT: Explicit User Consent ⌘ , ● RULE: Anonymization on Event Finish ⌘	○ WORKFLOWS ∅	○ PRE-CONDITION A running event with messages, likes, tokens, and an access list.
	○ INPUT The manager finishes the event.	○ EXPECTED Sender names become “Anonymous”, likes become bare counts, and tokens, users, and Moderator roles are deleted.	○ POST-CONDITION No personal attendee data remains and Manager roles are retained.
	Description ∅		
User Vanishes Without Role or Access ⚓	Diagram 		
	○ VERIFIES ● RULE: No Permanent User Accounts ⌘	○ WORKFLOWS ∅	○ PRE-CONDITION A user exists solely through the access list of a running event, holding no role.
	○ INPUT The manager removes the user from the access list.	○ EXPECTED The user record is deleted together with the access list entry, as nothing else keeps it alive.	○ POST-CONDITION No user record for the email address exists.
	Description ∅		
Export Contains Required Fields ⚓	Diagram 		
	○ VERIFIES ● REQUIREMENT: Export Attendee Inputs ⌘ , ● RULE: Likes Conserved ⌘	○ WORKFLOWS ∅	○ PRE-CONDITION A finished, anonymized event with messages.

● TEST-CASE	Properties & Description		
Manager Role Survives Finish	as Count on Finish , ● ATTRIBUTE: timestamp , ● ATTRIBUTE: state , ● ATTRIBUTE: likes , ● ATTRIBUTE: text		
	○ INPUT	○ EXPECTED	○ POST-CONDITION
	The manager exports the attendee inputs.	The export includes at least timestamp, state, number of likes, and message text per message.	∅
	Description		
	∅		
Diagram			
○ VERIFIES	○ WORKFLOWS	○ PRE-CONDITION	
● REQUIREMENT: Export Attendee Inputs , ● SCENARIO: Export After Finish , ● SCENARIO: Access Lost After Finish , ● RULE: Manager Retained for Export , ● PERMISSION: Export the Messages , ● PERMISSION: Enter the Event	● WORKFLOW: Run Broadcast Event	A running event with a manager role and a moderator role assigned.	
○ INPUT	○ EXPECTED	○ POST-CONDITION	
The manager exports the event data after having finished the event.	The moderator role is deleted by the anonymization while the manager role remains and can still export the event data.	The manager role exists until the event is deleted.	
Description			
1. The manager finishes the event. 2. The moderator attempts to open the event. 3. The manager exports the attendee inputs of the finished event.			

● TEST-CASE	Properties & Description		
Chat Message Shows Configured Name 	Diagram 		
	○ VERIFIES ● REQUIREMENT: Chat Messages , ● REQUIREMENT: Configurable Name Appearance , ● SCENARIO: Post a Chat Message , ● RULE: Moderation Determines Initial Visibility 	○ WORKFLOWS ∅	○ PRE-CONDITION A running event with chat enabled, chat moderation disabled, and the name appearance set to first name only.
	○ INPUT An attendee sends a chat message.	○ EXPECTED The message appears in state accepted under the first name of the attendee, with the email address shown on hover.	○ POST-CONDITION The message is stored as a chat in state accepted.
	Description ∅		
Like Toggles the Count 	Diagram 		
	○ VERIFIES ● REQUIREMENT: Like Messages , ● SCENARIO: Like a Message 	○ WORKFLOWS ∅	○ PRE-CONDITION A visible chat message of another attendee with a like count of 0.
	○ INPUT An attendee likes the message and then undoes the like.	○ EXPECTED The like count reads 1 after the like and 0 again after the undo.	○ POST-CONDITION No like of the attendee is recorded for the message.
	Description 1. The attendee likes the message. 2. The tester reads the like count shown on the message. 3. The attendee undoes the like on the same message. 4. The tester reads the like count shown on the message again.		

● TEST-CASE

Deleted Message Leaves Placeholder

Properties & Description

Diagram

TEST-CASE

Deleted Message Leaves Placeholder

REQUIREMENT

Edit and Delete Messages

REQUIREMENT

Deleted Message Placeholder

SCENARIO

Delete an Own Message

verifies

verifies

verifies

○ VERIFIES ● REQUIREMENT: Edit and Delete Messages , ● REQUIREMENT: Deleted Message Placeholder , ● SCENARIO: Delete an Own Message	○ WORKFLOWS ⌀	○ PRE-CONDITION A running event with chat enabled and chat moderation disabled, with two attendees watching.
○ INPUT The first attendee deletes their own message from between the two other messages.	○ EXPECTED The stream keeps the position of the message and shows a “This message was deleted” placeholder instead of its text on both attendee screens.	○ POST-CONDITION The message text is no longer retrievable by any attendee.

Description

1. The second attendee posts a chat message.

2. The first attendee posts a chat message.

3. The second attendee posts another chat message.

4. The first attendee deletes their own message.

5. The tester inspects the stream on the screens of both attendees.

Client-Side Check Holds Back Improper Input

Diagram

TEST-CASE

Client-Side Check Holds Back Improper Input

REQUIREMENT

Client-Side Sentiment Analysis

SCENARIO

Held Back by Client-Side Check




verifies



verifies

○ VERIFIES ● REQUIREMENT: Client-Side Sentiment Analysis , ● SCENARIO: Held Back by Client-Side Check	○ WORKFLOWS ⌀	○ PRE-CONDITION A running event with client-side sentiment analysis enabled.
○ INPUT An attendee submits a question with clearly improper wording.	○ EXPECTED The client prevents the submission and informs the attendee, and no request reaches the server.	○ POST-CONDITION No message exists for the submission.

Description

⌀

● TEST-CASE	Properties & Description		
Direct Moderator Reply Stays Private ⚓	Diagram 		
	○ VERIFIES ● REQUIREMENT: Answer Attendee Inputs Ⓜ, ● SCENARIO: Answer an Attendee Directly Ⓜ, ● RULE: Moderator Messages Auto-Accepted Ⓜ	○ WORKFLOWS ∅	○ PRE-CONDITION A running event with chat enabled and two attendees watching the stream.
	○ INPUT The moderator replies to the message of the first attendee as a direct message.	○ EXPECTED The reply reaches the first attendee in state accepted while the second attendee does not see it.	○ POST-CONDITION The reply is stored as accepted with the first attendee as its sole recipient.
	Description 1. The first attendee posts a chat message. 2. The moderator replies to that message as a direct message. 3. The tester inspects the stream on the screens of both attendees.		
Resource URL Selects the Resource ⚓	Diagram 		
	○ VERIFIES ● REQUIREMENT: Direct Resource Access URL Ⓜ, ● SCENARIO: Return via Direct Resource URL Ⓜ	○ WORKFLOWS ∅	○ PRE-CONDITION A running event with a default stream and a second, static resource, and an attendee holding an active session.
	○ INPUT The attendee opens the event URL carrying the resource parameter naming the static resource.	○ EXPECTED The system shows the static resource instead of the default stream.	○ POST-CONDITION The session of the attendee remains active.
	Description ∅		
Language Switch Applies Immediately ⚓	Diagram 		

● TEST-CASE	Properties & Description		
	○ VERIFIES ● REQUIREMENT: In-Session Language Switching ⓘ, ● SCENARIO: Switch the Language ⓘ	○ WORKFLOWS ∅	○ PRE-CONDITION An attendee watches a running event with the interface in German.
	○ INPUT The attendee switches the language to English in the header.	○ EXPECTED The interface and the translated messages appear in English without a page reload.	○ POST-CONDITION The stream continues uninterrupted.
	Description ∅		
Presenter Sees Forwarded Questions Only ⓘ	Diagram  <pre> graph LR TC[TEST-CASE Presenter Sees Forwarded Questions Only] -- verifies --> R[REQUIREMENT Presenter Dashboard] TC -- verifies --> S[SCENARIO Forwarded Questions Only] TC -- verifies --> P[PERMISSION Read Forwarded Questions] </pre> ○ VERIFIES ● REQUIREMENT: Presenter Dashboard ⓘ, ● SCENARIO: Forwarded Questions Only ⓘ, ● PERMISSION: Read Forwarded Questions ⓘ ○ INPUT The presenter opens the presenter view of the event. ○ WORKFLOWS ∅ ○ EXPECTED The view lists the forwarded question only, while a direct request for any of the three other questions is refused. ○ PRE-CONDITION A running event holds one question in each of the states pending, accepted, rejected, and forwarded. ○ POST-CONDITION The four questions remain in their states. Description ∅		
Administrator Sees No Attendee Data ⓘ	Diagram  <pre> graph LR TC[TEST-CASE Administrator Sees No Attendee Data] -- verifies --> R[REQUIREMENT GDPR-Compliant EU Processing] TC -- verifies --> S[RULE No Permanent User Accounts] TC -- verifies --> P[PERMISSION Administer Every Event] </pre> ○ VERIFIES ● REQUIREMENT: GDPR-Compliant EU Processing ⓘ, ● RULE: No Permanent User Accounts ⓘ, ● PERMISSION: Administer Every Event ⓘ ○ WORKFLOWS ∅ ○ PRE-CONDITION A running event with a populated access list and messages exists, provisioned through the configuration.		

● TEST-CASE	Properties & Description			
Administrator Enters Without Access List Entry ⚓	○ INPUT	○ EXPECTED	○ POST-CONDITION	
	The administrator reads the event through the configuration and requests its access list and messages.	The event settings are returned, while the requests for the access list and the messages are refused.	No access list entry or message was disclosed to the administrator.	
	Description			
	⌀			
	Diagram			
○ VERIFIES	○ WORKFLOWS	○ PRE-CONDITION		
● RULE: Administrator Bypasses the Access List ⌘, ● SCENARIO: Enter and Edit Any Event ⌘, ● PERMISSION: Administer the Authorization Tokens ⌘	⌀	A running event whose access list does not contain the configured administrator email address and whose access email pattern does not match it.		
○ INPUT	○ EXPECTED	○ POST-CONDITION		
The administrator requests the login challenge for the configured administrator email address at the event URL and returns the received token.	The token is issued and sent without consulting the access list, and the administrator is admitted to the event.	The administrator holds an active session for the event while its access list is unchanged.		
Description				
1. The administrator opens the event URL and enters the configured administrator email address. 2. The tester verifies that a token was sent to that address. 3. The administrator returns the token. 4. The tester inspects the access list of the event.				
Administrator Role Granted by Configuration Only ⚓	Diagram			
	○ VERIFIES	○ WORKFLOWS	○ PRE-CONDITION	
	● RULE: Administrator Bootstrapped by Configuration ⌘, ● SCENARIO: Administrator Role Stays Configured ⌘,	⌀	The configuration grants the Administrator role to exactly one email address, and its holder has entered an event.	

● TEST-CASE	Properties & Description		
	● PERMISSION: Administer the Roles ⓘ		
	○ INPUT	○ EXPECTED	○ POST-CONDITION
	The administrator attempts to grant the Administrator role to a user of the event and to revoke their own Administrator role through the user interface.	Both attempts are refused, while granting the Manager role to the same user succeeds.	The set of Administrator roles equals the configured one.
	Description		
	1. The administrator attempts to grant the Administrator role to a user of the event. 2. The administrator attempts to revoke their own Administrator role. 3. The administrator grants the Manager role to the same user. 4. The tester inspects the roles of the administrator user and of the event user.		
Concurrent Attendee Load ⚓	Diagram		
	TEST-CASE Concurrent Attendee Load verifies verifies REQUIREMENT Concurrent Attendee Scale REQUIREMENT Horizontal Scalability		
○ VERIFIES	○ WORKFLOWS	○ PRE-CONDITION	
● REQUIREMENT: Concurrent Attendee Scale ⓘ, ● REQUIREMENT: Horizontal Scalability ⓘ	⌀	A running event deployed with scaled proxy, relay, and server instances.	
○ INPUT	○ EXPECTED	○ POST-CONDITION	
10000 simulated attendees connect simultaneously and interact.	All 10000 attendees hold a served WebSocket connection at the same time, meeting the upper bound of the 2500 to 10000 attendees per event metric.	⌀	
Description			
⌀			