

CSC3320 System Level Programming

Lab Assignment 8 - Post-Lab

Ramey Serdah

Due at 11:59 pm on Friday, March 12, 2021

Purpose: Learn how to use debugger in **gdb** to debug a program in Unix.

Part 1:

You are given a C program “q1.c” as below. But since there are no enough comments in the program, it is hard to find out the feature of the function **foo**. So let us trace the execution of the program and find out what **foo** does. Please follow the steps below and answer the questions accordingly.

```
#include <stdio.h>

int foo(int num)
{
    int rev_num = 0;
    while (num > 0)
    {
        rev_num = rev_num*10 + num%10;
        num = num/10;
    }
    return rev_num;
}

/* Driver program to test foo */
int main()
{
    int num = 1125;
    printf("Result is %d", foo(num));
    return 0;
}
```

1) Compile “q1.c” with **-g** option so that we can debug the executable using **gdb**. `$gcc -o q1 -g q1.c`

2) Launch **gdb** for “q1”.

```
$gdb q1
```

3) List the source code of “q1.c” from line 1.

```
(gdb)list 1
```

4) Set a breakpoint at the line of statement “while (num > 0)”.

Question: Write your command.

break 7

1

4) Run the program until the first breakpoint.

Question: Write your command.

run

5) Use **display** to show the value of rev_num and num at each time when program stops.

(gdb) display rev_num

(gdb) display num

6) Run the while loop step by step using command **n** multiple times. (gdb) n

Question: check the value of rev_num and num after each iteration and fill in the table below.

	1 st iteration	2 nd iteration	3 rd iteration	4 th iteration
num	1125	112	11	1
rev_num	5	52	521	5211

7) When the program terminates, quit **gdb** using command **q**.

(gdb) q

8) Question: Now can you tell what the function foo does?

The function foo reverses a number.

Part 2:

You are given a C program “q2.c” as below. This program is used to calculate the average word length for a sentence (a string in a single line):

Enter a sentence: It was deja vu all over again.

Average word length: 3.4

For simplicity, the program considers a punctuation mark to be part of the word to which it is attached. And it displays the average word length to one decimal place.

```
#include <stdio.h>

int main() {

    int letters;
    int words;
    char character;

    printf("Enter a Sentence: ");

    while((character=getchar()) != '\n'){
        if(character != ' '){
            if(!space){
                words++;
                space=1;
            }
            letters++;
        }else
            space = 0;
    }

    printf("Average word length : %.1f", letters/words);

    return 0;
}
```

However, there are multiple errors in the given C program. Please correct compiler errors and use **gdb** to debug the program and find out the errors.

Question: *Please write down the line numbers containing the errors and show how to correct them.*

(Note: you do not need to write down the commands you issued in **gdb**.)

```
5    int letters = 0; //Initialize letters
6    int space = 0; //Initialize space
7    int words = 0; //Need to initialize words or else it has random value
11   while((character=getchar()) != '\n') //Need the single quotes for \n
28   printf("\nAverage word length : %.1f", (float)letters/words); //Cast to
float so it does not do integer division
```

Submission:

- Please follow the instructions below step by step, and then write a report by answering the questions and upload the report (named as **Lab8_FirstNameLastName.pdf or Lab8_FirstNameLastName.doc**) to Google Classroom, under the rubric Lab 8 Out-of-lab Assignment. • Please add the lab assignment NUMBER and your NAME at the top of your file sheet.