LINE ORIENTED FLIGHT TRAINING LOFT FFSQ 4.2 INITIAL / TRANSITION / UPGRADE

B747 - 400

FULL FLIGHT SIMULATOR

LESSON GUIDE

KSFO
SAN FRANCISCO, CALIFORNIA

TO

KLAX
LOS ANGELES, CALFORNIA

TO

PHNL
HONOLULU, HAWAI'I

01 December 2021

REVISION HIGHLIGHTS

Passenger Operations Information

INTRODUCTION

Line Orientated Flight Training (LOFT) is training method used to give crewmembers the opportunity to practice line operations in a realistic environment and to improve total crew performance. LOFT is “non-jeopardy” training (i.e., there is no passing or failing grade based on LOFT performance). If the LOFT instructor identifies crewmember performance deficiencies, additional training or instruction will be provided. This training or instruction shall be in a form most appropriate to correct the specific performance deficiency, including additional LOFT. Before the crewmember may enter line operations, the performance deficiencies will be corrected, and the instructor will document the training as satisfactorily completed. The “non-jeopardy” concept allows crewmembers to use their full resources and creativity. At the end of a LOFT session and after debriefing, the instructor certifies that the training has been completed.

A simulator training session used to facilitate the transition from flight simulation to operational flying by integrating technical knowledge, flying skills, procedural knowledge and CRM/TEM into the operation environment. The Session allows the crew to practice those technical skills presented in previous training in a real-world line environment. It must contain at least two typical flight segments of the Company’s routes. One flight segment will contain strictly normal operating procedures, while the other will include training in abnormal and emergency operations.

The objective of the qualification LOFT is to meet the requirements of initial qualification within part 121, appendix H, and will be conducted in a simulator approved under part 121, appendix H.

The Qualification LOFT requires a complete crew complement (2 crewmembers). The crewmember who is qualifying should be scheduled with other crewmembers that are fully line qualified. In any case, the crewmembers will be TASK familiar with their assigned position but need not be LINE familiar. The use of substitutes is highly discouraged.

Repositioning should not be used. System non-normals which are contained in the Lesson Guide should not be pre-briefed as crews benefit from the decisions made, right or wrong for each abnormal given. The instructor should not instruct or interrupt the LOFT except in extreme and unusual circumstances. Completion of the LOFT ends with a thorough debriefing.

Scheduled briefing and simulator times are as follows: (Hr + Min)

Pre-Briefing Times

2+00

De-Briefing Times

1+00

Simulator Times

4+00

OBJECTIVE

Facilitate the transition from flight simulation to operational flying by integrating technical knowledge, flying skills, procedural knowledge and CRM/TEM into the operation environment.

TRAINING MATERIALS

- Flight Crew Operations Manual
- Flight Operations Manual
- Quick Reference Handbook
- Glare-shield Checklist
- Normal/Non-Normal Communications Card
- EFB
- Operational Flight Plan
- Weather and NOTAMs
- Weight & Balance

REVISIONS

The FFS lesson guide for LOFT is listed in the Training Section on GlobalNet. The lesson guide is a read only file. Only the most recent lesson guide, as indicated by a creation date as well as a date on each page of the lesson guide, is listed on GlobalNet.

The master lesson guide file is maintained by the training department and any changes to this file must be approved by the Fleet Captain or designee.

Suggestions or comments regarding the Recurrent Training lesson guide contents are welcome and should be sent to:

FOTM@AtlasAir.com
RLOFT747@AtlasAir.com

LOFT ELEMENTS

- Normal crew station preflight
- Normal Engine Starts
- Area departure and arrival procedure
- Non Normal Procedure
- Oceanic and Remote Continental Airspace
- Enroute Diversion
- Engine Failure Driftdown
- Normal ILS Approach
- Non-ILS Approach
- Passenger Operations

GENERAL

- Operational Flight Plans (OFPs), Weather (Wx), Notams, Weight & Balance (W&B), Flight Deck Performance (FDP)*, Takeoff and Landing Report (TLR), and Pre Departure Clearance (PDC) will be provided by the instructor and used by the crew for each leg of the LOFT.
- All flows, duties, procedures will be in compliance with the FCOM.
- If the crew pairing consists of CA/CA, each CA is required to perform his/her LOFT leg from the left seat.
- If the crew pairing is FO/FO, crewmembers will switch seat positions prior to the start of the second leg.
- Landing assessments shall be completed prior to each landing using the FDP or TLR printouts provided in the Support Material.
- When the crew requests the departure ATIS the instructor will provide it in the form of a ACARs ATIS printout, provided in the support material. The instructor may use the simulator audio weather reporting function.
- The PDC will be provided to the crew after the OFP has been programmed into the FMC.
- RVR, Visibility and Ceiling must be set as indicated in the guidance provided.

CRM/TEM CONSIDERATIONS

PREFLIGHT

- Crew coordination and communications while addressing:
  - DDG Items.
  - Runway and / or departure changes.
- Take-off brief.
- Cabin Crew Briefing.
- All operational items should be verbalized clearly and understood by all crewmembers.
- Some items to be considered include.
  - The need for a take-off alternate.
  - EFP.
  - Discuss the use of autopilot after take-off as a company requirement for RNAV Departure.
  - Cabin Crew Coordination during Non-Normal situations.

ENGINE START

- Maintain communications with ground personal and maintenance.
- The malfunction should be recognized promptly and conflicting ideas resolved.
- Application of good crew coordination while executing the appropriate checklist(s) during non-normal start.
- Cause of malfunction should be determined, DDG consulted and implications discussed and resolved.

TAXI

- Verify “Cabin secure for pushback” has been received from the Cabin Crew.
- Verbally confirm both PF and PM both heard and understood taxi clearance correctly.
- If there is a discrepancy or if one crewmember fails to understand the clearance, clarification / restatement shall be requested to insure agreement.
- If in doubt STOP the aircraft to confirm instructions and regain situational awareness.
- Extra vigilance is required during the low visibility taxi to comply with hold short lines, hold bars and the threat of runway incursion.

TAKEOFF

- Verify “CABIN READY” is received on the call panel display or from the Cabin Crew prior to taking the active runway.
- Proper runway verification and takeoff procedures.

CLIMB AND CRUISE

- Clearly verbalize specific changes to the FMS/CDU, verify changes prior to executing and then monitor the aircraft and modes of automation.
- Verify required chimes and announcements to the Cabin Crew are completed.

AIRWORK

- Malfunctions should be recognized promptly.
- Checklists prioritized and called for clearly with good time management.
- Any conflicting ideas resolved by both crewmembers.
- During non-normal’s, one crewmember will be assigned the task of flying the airplane.
- Determine and plan the aircraft configurations for the non-normal, add time if necessary.
- Crews should discuss performance issues (Threats) referencing the FDP or TLR for specific runways and autobrake consideration.
- Crews should communicate with Cabin Crew for non-normal coordination and Cabin preparation.
- Time permitting Crews should confer with Dispatch for flight coordination.

ENGINE FAILURE

- Establishing priorities and time management.
  - Aircraft control and navigation.
  - Use of autopilot.
  - ATC communications.
  - Cabin Crew communications.
  - Contingency Procedure.
  - Prioritizing completion of checklists.
- Crews will identify and verbalize any reduction in or loss of personal situational awareness.
- Anticipate, recognize and recover as a countermeasure.
- Allow sufficient time for programming tasks, limit programming at critical times.
- PF sets priorities to avoid overloading the PM.
- Crews should explain the problem in plain English to the Cabin Crew utilizing the TEST Checklist.

APPROACH AND LANDING

- Establish priorities, planning, and sequencing during non-normal.
  - Aircraft control and navigation.
  - Maintain Situational awareness and terrain avoidance.
  - Use of automation to reduce workload.
- Plan and brief automation modes and configurations to use during the approach.
- Carefully monitor the automation associated with the coupled approach and autoland; verbalize any loss of system components.
- Manage tasks and situational demands by prioritizing crew duties. PF sets priorities to avoid overloading the PM during manual flight.
- Managing modes of automation during approaches is critical. Anticipate FMA modes, recognize if automation is correctly responding and recover when necessary.
- Anticipate potential missed approach and brief “bottom lines” and back up plans.
- Monitor centerline alignment and autobrake status.
- Closely monitor ground speed during the roll out and make appropriate call outs at 80 kts and when slowing for runway exit.

- Clear and concise communication with Crewmembers, Cabin Crew and Passengers is critical to a successful outcome.
- Crews should discuss performance issues (Threats) referencing the FDP or TLR for specific runways and autobrake consideration.
- Crews should give the required notifications to the Cabin Crew during decent.
- After landing flows and checklist should be completed when clear of all active runways.

MISSED APPROACH

- During MAP tasks and responsibilities must be clearly verbalized to eliminate any confusion during the critical phase of flight.
- Effective use of automation will greatly enhance the go-around maneuver and increase situational awareness.
- Manage time critical tasks and situational demands by prioritizing crew activities.
- Time permitting advise the Cabin Crew of the missed approach and intentions
- Time permitting give a brief announcement to the Passengers.

TAXI-IN AND PARK

- Verbally confirm both PF and PM both heard and understood taxi clearance correctly.
- If there is a discrepancy or if one crewmember fails to understand the clearance, clarification / restatement shall be requested prior to proper execution of instructions.
- If in doubt STOP the aircraft to confirm instructions and regain situational awareness.

DEBRIEFING AND ANALYSIS

- Facilitate openly and evaluate the crew's successes and mistakes.
- Discuss the monitoring and challenging that took place during the flight and how it helped to avoid or correct errors.
- Was an open tone established that encouraged crewmember participation during critical phases of the flight?
- Discuss what they learned from their mistakes / successes, what they would take to the "Line".

LESSON SUMMARY

Part 1

- The first leg of the LOFT begins in San Francisco, California (KSFO) with destination Los Angeles, California (KLAX)
- Passenger Operations
- Normal Preflight
- Normal Engine Starts
- Normal Takeoff
- Departure Procedure
- LNAV and VNAV
- RVSM
- Arrival Procedure
- Normal Approach and Landing

Part 2

- The second leg of the LOFT begins in Los Angeles, California (KLAX) with destination Honolulu, Hawai'i (KSFO)
- Begin with engines running and in takeoff position
- Passenger Operations
- Normal Takeoff
- Departure Procedure
- LNAV and VNAV
- Oceanic and Remote Continental Airspace Procedures
- RVSM
- Non Normal Procedure (Engine Fail at Cruise Altitude)
- Diversion to Enroute Alternate
- Non-Normal Cabin Crew Coordination
- Arrival Procedure
- Normal Approach and Landing

BRIEFING ITEMS

- Review LOFT
  - Normal Preflight Preparation
  - Review Flight Paperwork
- RVSM
  - Prior to Entering
  - Level Off and Level Change Procedures
- Review Oceanic and Remote Continental Airspace Procedures
  - Use FCOM SP Chapter for review
  - Flight Planning and Contingency procedures
  - Preflight
  - Prior to entry
  - After Oceanic entry
  - Approaching Waypoints
  - Overhead Waypoints
  - 10-minutes after waypoint passage
  - Mid point
  - Coast in
- Non Radar Vs. Radar Environments
  - Position Reports
  - SLOP
- Application of CRM/TEM skills, proactive planning and setting bottom lines during normal and non-normal procedures
- Passenger Operations
  - Review FOM Chapter 15 for specifics
  - Review Normal/Non-Normal Communications Card