OFP DATA

ORIGIN: SAN FRANCISCO INTL (KSFO)
DESTINATION: LOS ANGELES INTL (KLAX)
FLIGHT NUMBER: GTI 400
ROUTE: SUSEY EBAYE AVE
RUNWAY: 10L
DEPARTURE: SAHEY_ SUSEY TRANSITION
TAKEOFF ALT: KOAK

	-400 / -8		-400/ -8
OFP TOW	278.0/ 338.0	**OFP ZFW**	200.0/260.0
RAMP FUEL	78.0	**TAXI FUEL (INFO ONLY)**	0.9
RESERVE	9.9	**COST INDEX**	44
FLT LEVEL	370	**DDG**	NONE
FF	X.X	**DIST**	303
ENROUTE WIND.	000/000		

LOAD SHEET DATA KILOS

	-400 / -8		
ZFW	200.0/260.0	**CG**	21%
TOGW	278.0/338.0		

WEATHER

San Francisco International Information *"Alpha" XXxxz, Wind 190/10G25, Visibility ¼ sm FG, sky condition Overcast 001, Temperature 06, Dew Point 06, Altimeter 29.92, Departing Runways 10L, RVR 10L 500/500/500. On initial contact advise you have information Alpha*

CLEARANCE

Clearance*, Cleared to Los Angeles International airport, SAHEY__Departure, SUSEY Transition, EBAYE, AVE then as filed. Climb VIA the SID expect FL370 one zero minutes after departure, squawk 1747. Expect Runway 10L for departure.*

TLR EXCERPT

---------SPECIAL ENG FAIL TAKEOFF PROCEDURES ---------

RWY	CLB VIA	REACHING	OR	TURN	FRA	HOLD
19L	V2	RWY END	D0.9 SFO	LT OAK	1013	STD
19R	V2	RWY END	D0.8 SFO	LT OAK	1013	STD
28L		D1.8 SFO	D0.7 IGWQ	RT H305	1100	
28R		D2.3 SFO	D1.1 IGWQ	RT H305	1100	

KSFO	CF680C2B1F	
FLT NO	RLS NO	TIME
400	1	1951Z
WIND KTS	OAT C	QNH
190/15	6	29.92

GRWT	278.0	VREF30 154
FUEL	78.0	
ZFW	200.0	

REMARKS
ENG ANTI ICE ON

KSFO	10L	11670
MTOW	278.0	SMRGN 2184
FLAPS	10	PACKS ON
ATM	50C	V1 140
THR	D-TO-2	VR 148
N1	92.3	V2 157
CG	21.0	TRIM 6.2

RT H120 ACCEL 1000

AOC END

KSFO	CF680C2B5F	
FLT NO	RLS NO	TIME
400	1	1951Z
WIND KTS	OAT C	QNH
190/15	6	29.92

GRWT	278.0	VREF30 155
FUEL	78.0	
ZFW	200.0	

REMARKS
ENG ANTI ICE ON

KSFO	10L	11670
MTOW	278.0	SMRGN 2184
FLAPS	10	PACKS ON
ATM	50C	V1 140
THR	D-TO-2	VR 148
N1	93.1	V2 157
CG	21.0	TRIM 6.2

RT H120 ACCEL 1000

AOC END

KSFO	GENX-2B67	
FLT NO	RLS NO	TIME
400	1	1951Z
WIND KTS	OAT C	QNH
190/15	6	29.92

GRWT	338.0	VREF30 158
FUEL	78.0	
ZFW	260.0	

REMARKS
ENG ANTI ICE ON

KSFO	10L	11870
MTOW	338.0	SMRGN 675
FLAPS	20	PACKS ON
ATM	48C	V1 147
THR	D-TO-2	VR 152
N1	82.6	V2 160
CG	21.0	TRIM 7.9

RT H120 ACCEL 1000

AOC END

KSFO	CF680C2B1F	
FLT NO	RLS NO	TIME
400	1	1951Z
WIND KTS	OAT C	QNH
190/15	6	29.92
GRWT	278.0	VREF30 155
FUEL	78.0	
ZFW	200.0	

REMARKS
ENG ANTI ICE ON

KSFO	10R	11381
MTOW	278.0	SMRGN 2743
FLAPS	10	PACKS ON
ATM	50C	V1 141
THR	D-TO-2	VR 149
N1	92.3	V2 158
CG	21.0	TRIM 6.2

RT H120 ACCEL 1000

AOC END

KSFO	CF680C2B5F	
FLT NO	RLS NO	TIME
400	1	1951Z
WIND KTS	OAT C	QNH
190/15	6	29.92
GRWT	278.0	VREF30 156
FUEL	78.0	
ZFW	200.0	

REMARKS
ENG ANTI ICE ON

KSFO	10R	11381
MTOW	278.0	SMRGN 2743
FLAPS	10	PACKS ON
ATM	50C	V1 141
THR	D-TO-2	VR 149
N1	93.1	V2 158
CG	21.0	TRIM 6.2

RT H120 ACCEL 1000

AOC END

KSFO	GENX-2B67	
FLT NO	RLS NO	TIME
400	1	1951Z
WIND KTS	OAT C	QNH
190/15	6	29.92
GRWT	338.0	VREF30 158
FUEL	78.0	
ZFW	260.0	

REMARKS
ENG ANTI ICE ON

KSFO	10R	11381
MTOW	338.0	SMRGN 700
FLAPS	20	PACKS ON
ATM	48C	V1 145
THR	D-TO-2	VR 152
N1	82.6	V2 160
CG	21.0	TRIM 7.9

RT H120 ACCEL 1000

AOC END

PCWU LLWS USE ONLY

```
KSFO          CF680C2B1F
FLT NO    RLS NO    TIME
400          1     1951Z
WIND KTS  OAT C      QNH
 190/15    +15     29.92
-----------------------
GRWT 300.0    VREF30 157
FUEL 60.0
ZFW  240.0

REMARKS
LLWS ADVISORY

KSFO 28R           11870
MTOW  300.0   SMRGN 4559
FLAPS 20        PACKS ON
ATM   --          V1 155
THR   TO          VR 155
N1    108.4       V2 173
CG    21.0      TRIM 6.0

SPECIAL       ACCEL 1000

KSFO 28R          SPECIAL
REACHING D2.3 SFO OR D1.1
IGWQ RT H305
```

```
KSFO          CF680C2B5F
FLT NO    RLS NO    TIME
400          1     1951Z
WIND KTS  OAT C      QNH
 190/15    +23     29.92
-----------------------
GRWT 300.0    VREF30 157
FUEL 60.0
ZFW  240.0

REMARKS
LLWS ADVISORY

KSFO 28R           11870
MTOW  241.5   SMRGN 4559
FLAPS 20        PACKS ON
ATM   --          V1 155
THR   TO          VR 155
N1    108.4       V2 173
CG    21.0      TRIM 6.0

SPECIAL       ACCEL 1000

KSFO 28R          SPECIAL
REACHING D2.3 SFO OR D1.1
IGWQ RT H305
```

```
KSFO           GENX-2B67
FLT NO    RLS NO    TIME
400          1     1951Z
WIND KTS  OAT C      QNH
190/15    +23     29.92
-----------------------
GRWT 338.0    VREF30 158
FUEL 78.0
ZFW  260.0

REMARKS
LLWS ADVISORY

KSFO 28R           11870
MTOW  338.0   SMRGN 1850
FLAPS 20        PACKS ON
ATM   --          V1 168
THR   TO          VR 173
N1    99.3        V2 183
CG    21.0      TRIM 7.9

SPECIAL       ACCEL 1000

KSFO 28R          SPECIAL
REACHING D2.3 SFO OR D1.1
IWGQ RT H305
```

WINDSHEAR PERFORMANCE

Selecting **LLWS ADVISORY** to YES in ACARS results in:

- TO Thrust, No Assumed
- Flaps 20

and utilizes the improved climb method to increase V-speeds to the maximum permitted for a given weight.

Note: *If a low gross weight/aft CG condition exists, ensure that TO-2 is selected.*