

Comment	Description	Designator	Footprint	LibRef	Quantity
EC200miniDB	EICUT.com	*1	PCBComponent_1	EC200miniDB	1
	Bipolar ceramic capacitor SMD	C1, C2	CAP 1206/3216	Cap_Multi_SMD_100nF_1206	2
100n	Bipolar ceramic capacitor SMD	C3, C4, C5, C8, C11, C12, C15, C16, C17, C18, C26, C27, C28, C29	CAP 1206/3216	Cap_Multi_SMD_100nF_1206	14
22p	Bipolar ceramic capacitor SMD	C6, C7	CAP 1206/3216	Cap_Multi_SMD_100nF_1206	2
10u	Tantalum Capacitor,TAJ Series-SMD	C9, C10, C13, C14	SMT_C_Tantalum_B	Cap_Tantalum	4
2n	Bipolar ceramic capacitor SMD	C19, C20	CAP 1206/3216	Cap_Multi_SMD_100nF_1206	2
1uF, 50V	Bipolar ceramic capacitor SMD	C21, C22, C23, C24, C25, C30, C31	CAP 1206/3216	Cap_Multi_1u_50_1206	7
Yellow, 1206	LED	D1, D5, D6, D7	LED 1206/3216 YELLOW	Semi_LED_Yellow_1206	4
1N5819	Schottky Rectifiers	D2, D3, D4	430X270D	Semi_Diod_Sch_1N5819_SMD	3
2A	Short circiut protection	F1, F3	1206_F	Other_Elec_Fuse_SMD	2
180°C, 10'A	Thermal Fuse	F2	PIN-W2/E2.8	Other_Elec_Fuse_Thermal	1
10x2	Male Box Header, 20 pins	GLCD1	BOX-HDR-10X2-2.54mm-S	Con_IDC_10x2	1
4Pin	4Pin Power Connector	I1, sensors1	645004114822	Con_Power_4_PC_V	2
RJ45, mini	RJ45 Mini With two LEDs	J1	RJ45_MINI	Con_PC_RJ45_MINI	1
7x2	Header, dual row, 14 pin	KeyPad1	HDR_THT_7x2M_2.54mm	Con_MPH_7x2_V_THT_2.54	1
100nH	Inductor	L1	IND1206	Ind_SMD_1206	1
6Pin	6Pin Power Connector	Light1, Motor1	645006114822	Con_Power_6_PC_V	2
5V	Magnetic Transducer Buzzer	LS1	BZ_SJ	Other_Elec_Buzzer	1
LM2596	DC to DC Buck converter 1.23V-30V 3A	MS1, MS2	LM2596_modsen	ModSen_LM2596	2
Value?	LED	ON1	LED 1206/3216 GREEN	Semi_LED_SMD	1
10K	Multi Turn	P1	Multi turn 01	Res_Multi	1
2Pin	Power Connector 2Pin	Power1	Phoenix_2PIN_RA_P5.08mm	Con_Power_2	1
NPN	NPN General purpose Transistor	Q1, Q2	SOT23_N	Semi_BJT_BC817	2
NPN	NPN Power transistor	Q3, Q4, Q5	TO-220 AB	Semi_BJT_TIP41C	3
Value?	Resistor	R1, R2, R5, R6	RES 1206 (3216X08L)	Res_SMD_0805, Res_SMD_1206	4
4.7K	Resistor	R3, R7, R8, R18, R21, R23	RES 1206 (3216X08L)	Res_SMD_1206	6
47K	Resistor	R4, R9, R12, R19, R20, R22	RES 1206 (3216X08L)	Res_SMD_1206	6
1.8K	Resistor	R10, R15, R16, R17	RES 1206 (3216X08L)	Res_SMD_1206	4
10K	Resistor	R11, R26, R27, R28, R29, R30, R31	RES 1206 (3216X08L)	Res_SMD_1206	7
1K	Resistor	R13	RES 1206 (3216X08L)	Res_SMD_1206	1
5.6K	Resistor	R14	RES 1206 (3216X08L)	Res_SMD_1206	1
0	Resistor	R24, R25	RES 1206 (3216X08L)	Res_SMD_1206	2
100	Resistor	R32, R33	RES 1206 (3216X08L)	Res_SMD_1206	2
Value	Resistor	R34, R35, R36, R37, R38	RES 1206 (3216X08L)	Res_SMD_1206	5
PB	SMT Tactile Switch	Reset1, S1, S2, S3, S4, S5	SW_PB_SMD_2PIN_SPST_6X3X2	SW_PushButton_2_SMD	6
6	Header, single row, 6 pin	SD1	HDR_THT_6F_2.54mm	Con_FPH_6x1_V_THT_2.54	1
4	Header, single row, 4 pin	SIM1	HDR_THT_4F_2.54mm	Con_FPH_4x1_V_THT_2.54	1
ATMEGA64A-AU	AVR AVR® ATmega Microcontroller IC 8-Bit 16MHz 64KB (32K x 16) FLASH 64-TQFP (14x14)	U1	QFP80P1600X1600X120-64N	ATMEGA64A-AU	1
MAX3232	RS-232 Interface IC 3.0V to 5.5V, Low-Power, up to 1Mbps, True RS-232 Transceivers Using Four 0.1uF External Capacitors	U2	NSO16_M	IC_Converter_MAX3232CSE	1
ULN2003	Seven darlington array drivers	U3	SO16_M	IC_Driver_ULN2003	1
UART	UART Connector	UART1	MOLEX KK 0022272041	Con_UART	1
5x2	Male Box Header, 10 pins	usbasp1	BOX-HDR-5X2-2.54mm-S	Con_IDC_5x2	1
8M	Crystal Oscillator	Y1	XTAL Small	Other_Elec_Xtal_THT	1