

Develop code that declares, initializes, and uses primitives, arrays, enums, and objects as static, instance, and local variables. Also, use legal identifiers for variable names.

Variable Identifiers

Variable names must be legal Java identifiers:

- Keywords and reserved words may not be used.
- It must start with a letter, dollar sign (\$), or underscore (_).
- Subsequent characters may be letters, dollar signs, underscores, or digits.
- It is case sensitive. For example, `mymodel` and `MyModel` are different identifiers.

The following are not legal variable names:

```
My Variable           // Contains a space
9pins                 // Begins with a digit
a+c                   // The plus sign is not an alphanumeric character
testing1-2-3          // The hyphen is not an alphanumeric character
O'Reilly              // Apostrophe is not an alphanumeric character
OReilly_&Associates    // ampersand is not an alphanumeric character
```

Keywords: `abstract` `assert` `boolean` `break` `byte` `case` `catch` `char` `class` `const` `continue` `default` `do` `double` `else` `enum` `extends` `false` `final` `finally` `float` `for` `goto` `if` `implements` `import` `instanceof` `int` `interface` `long` `native` `new` `null` `package` `private` `protected` `public` `return` `short` `static` `strictfp` `super` `switch` `synchronized` `this` `throw` `throws` `transient` `true` `try` `void` `volatile` `while`

The `goto` keyword is not used.

The `const` is also not used.

The `assert` is a new keyword added with Java 1.4

The `enum` is a new keyword added with Java 5.0



SCDJWS 1.4
Quiz



ICAD
Study Guide



Magnet
Mocker

SCWCD 1.4
Study Guide

SCBCD 1.3
Study Guide

SCDJWS 1.4
Study Guide

IBM Test 287
Study Guide