

CRUD commands

Create deployment

`kubectl create deployment [name]`

Edit deployment

`kubectl edit deployment [name]`

Delete deployment

`kubectl delete deployment [name]`

Status of different K8s components

`kubectl get nodes | pod | services | replicaset | deployment`

Debugging pods

Log to console

`kubectl logs [pod name]`

Debugging pods

Log to console

Get Interactive Terminal

Get info about pod

```
kubectl logs [pod name]
```

```
kubectl exec -it [pod name] -- bin/bash
```

```
kubectl describe pod [pod name]
```

Use configuration file for CRUD

Apply a configuration file

Delete with configuration file

```
kubectl apply -f [file name]
```

```
kubectl delete -f [file name]
```

```
tinker@DJ9HWM2Y9M ~ % kubectl get po -A
```

NAMESPACE	NAME	READY	STATUS	RESTARTS	AGE
kube-system	coredns-668d6bf9bc-k5xzk	1/1	Running	0	14m
kube-system	etcd-minikube	1/1	Running	0	14m
kube-system	kube-apiserver-minikube	1/1	Running	0	14m
kube-system	kube-controller-manager-minikube	1/1	Running	0	14m
kube-system	kube-proxy-lnf5s	1/1	Running	0	14m
kube-system	kube-scheduler-minikube	1/1	Running	0	14m
kube-system	storage-provisioner	1/1	Running	1 (13m ago)	14m

Layers of Abstraction



Deployment manages a ..



ReplicaSet manages a ..



Pod is an abstraction of ..



Container

Deployment manage Pods