



# WebAPI Cheatsheet

Get started with WebAPI including authentication calls, basic commands, and more.

## HTTP Verbs

<b>GET</b>	Read
<b>POST</b>	Create
<b>PUT</b>	Replace
<b>PATCH</b>	Modify
<b>DELETE</b>	Delete

## IHttpActionResult

200	<b>Ok</b>
302	<b>Redirect</b>
400	<b>BadRequest</b>
401	<b>Unauthorized</b>
404	<b>NotFound</b>
409	<b>Conflict</b>
500	<b>Exception</b>

## Find Me At

www.IAmTimCorey.com



Tim Corey

## Sign Up For An Account

To create a new account through the API, you will need to do the following:

**Default API Path:** </api/account/register>

**Call Type:** POST

**Body** (*raw application/json*):

```
{
  "Email": "youremail@test.com",
  "Password": "TestPwd123?",
  "ConfirmPassword": "TestPwd123?"
}
```

## Get Token (Log In)

To log into your account and get the token to be used on all future calls, perform the following call:

**Default API Path:** </token>

**Call Type:** GET

**Body** (*x-www-form-urlencoded*):

```
{
  grant_type: password
  username: youremail@test.com
  password: TestPwd123?
}
```

## Making an Authorized Call

Once you have your token, to call an API endpoint that requires authorization, make the following additions to whatever call you make:

### Headers

```
{
  Authorization: "Bearer <token>"
}
```

## Endpoint Attributes

To modify an endpoint in some way, you can include one or more of the following attributes:

### [Authorize]

Everyone who calls this endpoint must include the bearer token. You can also limit authorization like so: **[Authorize (Roles = "Employees")]**

### [HttpGet]

Specifies the type of HTTP verb required to connect to this endpoint. Other verb can be used as well (HttpPost, HttpPut, etc.)

### [Route("api/Test/MyRoute")]

Specifies route used to connect to this endpoint. This overrides the default. Especially useful for deeper paths or method overloading.