

Concordia University
Department of Computer Science and Software
Engineering

SOEN 331 - S and U
Introduction to Formal Methods
for Software Engineering

Assignment 2 - Solutions
The Object-Z specification language

Team 19 - Section U

| | | |
|-----------------------|---------------------|---------------------|
| Samuel Boaknin | Ryan Leyland | Saleha Tariq |
|-----------------------|---------------------|---------------------|

40009692

40015165

40006997

Meng Susana Ung

40099729

Due Date: March 11, 2021

1 Contact management

1.1 State

1.2 Class Contacts

| |
|---|
| <i>Contacts</i> |
| $\uparrow (MakeNewContact, AddNumber, SearchForNumber, DeleteNumber)$ |
| $numbers : \mathbb{P}PhoneNumberType$ $recorded : PhoneNumberType \leftrightarrow NameType$ |
| $numbers = dom\ recorded$ |
| <i>INIT</i> |
| $recorded = \emptyset$ |
| <i>MakeNewContactOK</i> |
| $\Delta(recorded)$ $number? : PhoneNumberType$ $name? : NameType$ |
| $number? \notin numbers$ $name? \notin ran\ recorded$ $recorded' = recorded \cup \{number? \mapsto name?\}$ |
| <i>AddNumberOK</i> |
| $\Delta(recorded)$ $number? : PhoneNumberType$ |
| $number? \notin numbers$ $name? \in ran\ recorded$ $recorded' = recorded \cup \{number? \mapsto name?\}$ |
| <i>SearchForNumberOK</i> |
| $\exists Contacts$ $name? : NameType$ $numbers! : \mathbb{P} number$ |
| $numbers! = \{n : number \mid recorded(n) = name?\}$ |
| <i>DeleteNumberOK</i> |
| $\Delta(recorded)$ $number? : PhoneNumberType$ |
| $number? \in numbers$ $recorded' = \{number?\} \triangleleft recorded$ |
| ... |

Contacts/cont.

...

NameUnknown

name? : *NameType*

response! : *Message*

name? \notin *ran recorded*

response! = '*Name unknown*'

NumberUnknown

number? : *PhoneNumberType*

response! : *Message*

number? \notin *dom recorded*

response! = '*Number unknown*'

NameExists

name? : *NameType*

response! : *Message*

name? \in *ran recorded*

response! = '*Name already exists*'

NumberExists

number? : *PhoneNumberType*

response! : *Message*

number? \in *dom recorded*

response! = '*Number already exists*'

ContactsEmpty

response! : *Message*

count = 0

response! = '*Contacts is empty*'

Success

response! : *Message*

response! = '*Success*'

$MakeNewContact \hat{=} (MakeNewContactOK \wedge Success) \oplus (NameExists \vee NumberExists)$

$AddNumber \hat{=} (AddNumberOK \wedge Success) \oplus (NameUnknown \vee NumberExists)$

$SearchForNumber \hat{=} (SearchForNumberOK \wedge Success) \oplus (NameUnknown \vee ContactsEmpty)$

$DeleteNumber \hat{=} (DeleteNumberOK \wedge Success) \oplus (NumberUnknown \vee ContactsEmpty)$

1.3 Class Contacts2