

Concordia University
Department of Computer Science and Software
Engineering
SOEN 331 - S and U
Introduction to Formal Methods
for Software Engineering

Assignment 4 - Solutions
Temporal Logic
Team 19 - Section U

Samuel Boaknin
40009692

Ryan Leyland
40015165

Saleha Tariq
40006997








Meng Susana Ung
40099729


Date: April 19, 2021

Contents

1	Question 1	3
2	Question 2	5

1 Question 1






There exists three model's whereby the program terminates, given by the following expressions:

$\langle (a \wedge c \wedge e), e, e, e, g \rangle$


$\langle (a \wedge d), y, y, y, (x \wedge y), w \rangle$

$\langle c, \emptyset, \emptyset, \emptyset, g \rangle$


2 Question 2




If ϕ is an invariant, then ψ is true in some moment in time.




If ϕ is an invariant, then from $i + 1$ onwards, ψ could become an invariant.



If ϕ is true at i and ψ is true at $i + 1$, then τ can become an invariant anywhere on the path.



If ψ is true at i and χ is true at $i + 1$, then τ is also true at $i + 1$.



If χ is true at i and ω is true at $i + 1$, then from $i + 2$ onwards, ϕ is true until ψ becomes true.

(6)

(7)

(8)