

Concordia University
Department of Computer Science and Software
Engineering

SOEN 331 - S and U
Introduction to Formal Methods
for Software Engineering

Assignment 2 - Solutions
The Object-Z specification language
Team 19 - Section U

Samuel Boaknin	Ryan Leyland	Saleha Tariq
-----------------------	---------------------	---------------------

40009692

40015165

40006997

Meng Susana Ung


40099729

Due Date: March 11, 2021

1 Contact management

1.1 State

1. This is our diagram for the state of the system:



2. The formal definition of *numbers* is as follows:

$$numbers : \mathbb{P} \text{ PhoneNumberType}$$

3. The relation *recorded* must indeed be captured by a function. A function, by definition, enforces that each element of a source set (that is, the set in the domain) is mapped to exactly one element of a target set (a set of elements in the range). Part of the requirements for the system is that people may not share phone numbers. By making *recorded* a function, and setting the *numbers* set as a subset of the domain, the requirement of a phone number being associated to a single person is trivially met. If this is not done, an additional series of specifications must be defined such that this requirement is observed *at best*, and at worst, there is a severe risk of failing to meet the defined requirements. Thus, it is at least convenient, if not necessary that *recorded* is a function where *numbers* is a subset of the domain.

4. The domain of *recorded* is *numbers*, and its codomain is *NameType*.
5. The function *recorded* is a partial function, because partial functions, by definition, do not map all elements in the domain to an element in the co-domain. Specifically, *recorded* doesn't relate every element of *PhoneNumberType* to *NameType*.
6. The function *recorded* will not be either injective, surjective, or bijective. It cannot be injective because an injective function, by definition, is a function where one element in the domain is mapped to at most one element in the co-domain, but *recorded* allows for multiple phone numbers to be associated with one person, so multiple parts of the domain could be associated with an element of the co-domain. It cannot be surjective as a surjective function, by definition, is a function where each element in the co-domain has at least one element in the domain mapped to it. In *recorded*, there are elements contained in the co-domain of *recorded* that are not in the range of *recorded* therefore there exists elements in the codomain which are not mapped to by any element of the domain. It cannot be bijective because a bijective function is both injective and surjective and it has already been proven that this function is neither. Therefore, *recorded* must be a general function because every element in the domain is mapped to one element of the co-domain, but more than one element of the domain can be mapped to the same element of the co-domain.
7. The formal definition of *recorded* is as follows:

$$\textit{recorded} : \textit{PhoneNumberType} \rightarrow \textit{NameType}$$

1.2 Class Contacts

Contacts

$\uparrow (MakeNewContact, AddNumber, SearchForNumber, DeleteNumber)$

$numbers : \mathbb{P} PhoneNumberType$
 $recorded : PhoneNumberType \leftrightarrow NameType$

$numbers = dom\ recorded$

INIT

$recorded = \emptyset$

MakeNewContactOK

$\Delta(recorded)$
 $number? : PhoneNumberType$
 $name? : NameType$

$number? \notin numbers$
 $name? \notin ran\ recorded$
 $recorded' = recorded \cup \{number? \mapsto name?\}$

AddNumberOK

$\Delta(recorded)$
 $number? : PhoneNumberType$
 $name? : NameType$

$number? \notin numbers$
 $name? \in ran\ recorded$
 $recorded' = recorded \cup \{number? \mapsto name?\}$

SearchForNumberOK

$\exists Contacts$
 $name? : NameType$
 $numberset! : \mathbb{P} numbers$

$name? \in ran\ recorded$
 $numberset! = \{n : numbers \mid recorded(n) = name?\}$

DeleteNumberOK

$\Delta(recorded)$
 $number? : PhoneNumberType$

$number? \in numbers$
 $recorded' = \{number?\} \triangleleft recorded$

...

Contacts/cont.

...

NameUnknown

name? : *NameType*

response! : *Message*

name? \notin *ran recorded*

response! = '*Name unknown*'

NumberUnknown

number? : *PhoneNumberType*

response! : *Message*

number? \notin *dom recorded*

response! = '*Number unknown*'

NameExists

name? : *NameType*

response! : *Message*

name? \in *ran recorded*

response! = '*Name already exists*'

NumberExists

number? : *PhoneNumberType*

response! : *Message*

number? \in *dom recorded*

response! = '*Number already exists*'

Success

response! : *Message*

response! = '*Success*'

$MakeNewContact \hat{=} (MakeNewContactOK \wedge Success) \oplus (NameExists \vee NumberExists)$

$AddNumber \hat{=} (AddNumberOK \wedge Success) \oplus (NameUnknown \vee NumberExists)$

$SearchForNumber \hat{=} (SearchForNumberOK \wedge Success) \oplus (NameUnknown)$

$DeleteNumber \hat{=} (DeleteNumberOK \wedge Success) \oplus (NumberUnknown)$

1.3 Class Contacts2

Contacts2

$\uparrow (MakeNewContact, AddNumber, SearchForNumber, DeleteNumber, SearchForPerson)$

Contacts

SearchForPersonOK

$\exists Contacts2$

$number? : PhoneNumberType$

$name! : NameType$

$number? \in numbers$

$name! = recorded(number?)$

$SearchForPerson \hat{=} (SearchForPersonOK \wedge Success) \oplus (NumberUnknown)$