

Image_Captioning

1. from show, attend and tell [4]:

1. Extract a 14x14 Feature Map from CNN.
2. Image: $H \times W \times 3$ -CNN-> Features, $v: L \times D$, $L = W \times H$, this Feature vector becomes an input to become an RNN's first hidden state h_0 . The RNN outputs a distribution over L possible locations, a_1 . These are the locations of these grids in the feature vector $L \times D$. a_1 is multiplied with the feature map to get a weighted features $z_1 = \sum_{i=1}^L a_i v_i$ (v_i are the features inside each grid locations that come as the output of the feature map) which will become input together with y_1 (first word) or the start token (SOS) in the next RNN time step.
3. h_1 which is the the next hidden step of the next time step in the RNN, gives us a_2 and d_1 , a distribution over vocabulary that tells us what is the predicted word. a_2 is again multiplied with the feature map to give us a new weighted representation of the image feature map z_2 . And d_1 could be the input y_2 , or when we're training we're training we could use the second word of the caption to be input y_2 to the next step of the RNN, so z_2 and y_2 are the inputs to hidden state to the next step in the RNN. This generates a_3 and d_2 . d_2 is the distribution over the vocabulary which tells us what is the word, a_3 tells us which part of the image to focus on. This is repeated again and again, and the caption is generated.
4. In soft attention the a_1 the weight vector, is a softmax vector, and we use it as weights to multiply with each of grid locations in v . This gives us a soft attention or the feature map of the entire image.
5. In hard attention we only choose a winning entry and only use that grid location as an input to the next time step. Hard since we're not using a soft distribution of the weights across all parts of the image.

2. CLIP

1. Motivation:
 1. Rather than training models with fixed set of predetermined object categories (in image classification) that limits their flexibility. Can we train a vision model to work "zero-shot"?
 2. Prior works in NLP have shown that learning from descriptions rather than fixed labels can be very data efficient. For example VirTex demonstrated data efficiency of captioning. ConVIRT showed data efficiency of contrastive training.
 3. Scale: NLP systems have benefited tremendously from scale. GPT-3 showed zero-shot transfer scale benefits.
2. CLIP learns from text-image pairs that are already publicly available on the internet using self-supervised learning, contrastive methods, self-training approaches, and generative modeling.

References

1. Paper: An End-to-End Trainable Neural Network for Image-based Sequence Recognition and Its Application to Scene Text Recognition - Baoguang Shi et al
2. Convolutional Image Captioning, Jyoti Aneja, Aditya Deshpande, Alexander G. Schwig.
3. Karpathy et al, Deep visual-semantic alignments for generating image description, CVPR 2015.
4. Xu et al, Show attend and tell: Neural Image Caption generation with Visual Attention, ICML 2015.
5. CLIP