

Formale Semantik

05. Prädikatenlogik

Roland Schäfer

Institut für Germanistische Sprachwissenschaft
Friedrich-Schiller-Universität Jena

Achtung: Folien in Überarbeitung. Englische Teile sind noch von 2007!
Stets aktuelle Fassungen: <https://github.com/rsling/VL-Semantik>

1 Why predicate calculus?

2 The construction of PC

- Atoms and syntax
- Semantics
- More rules

3 Laws of PC

- Negation and distribution
- Movement
- Some in-class practice

4 Natural deduction in PC

- Quantifier elimination
- An example

Why predicate calculus?

- properties/relations vs. individuals

- properties/relations vs. individuals
- *Martin is an expert on inversion and Martin is a good climber.*

- properties/relations vs. individuals
- *Martin is an expert on inversion and Martin is a good climber.*
- ...becomes $E \wedge C$

- properties/relations vs. individuals
- *Martin is an expert on inversion and Martin is a good climber.*
- ...becomes $E \wedge C$
- compositionality restricted to level of connected propositional atoms

Some desirable deductions

- important generalizations about all and some individuals (which have property P)

Some desirable deductions

- important generalizations about all and some individuals (which have property P)
- ' $\text{all } P \rightarrow \text{some } P$ '

Some desirable deductions

- important generalizations about all and some individuals (which have property P)
- ' $\text{all } P \rightarrow \text{some } P$ '
- ' $\text{Martin } P \rightarrow \text{some } P$ '

The construction of PC

- individual variables: $x, y, z, x_1, x_2 \dots$

- individual **variables**: $x, y, z, x_1, x_2 \dots$
- individual **constants**: a, b, c, \dots

- individual **variables**: $x, y, z, x_1, x_2 \dots$
- individual **constants**: a, b, c, \dots
- variables and constants: **terms**

- individual **variables**: $x, y, z, x_1, x_2 \dots$
- individual **constants**: a, b, c, \dots
- variables and constants: **terms**
- **predicate symbols** (taking individual symbols or tuples of them): A, B, C, \dots

- individual **variables**: $x, y, z, x_1, x_2 \dots$
- individual **constants**: a, b, c, \dots
- variables and constants: **terms**
- **predicate symbols** (taking individual symbols or tuples of them): A, B, C, \dots
- **quantifiers**: existential \exists (or \vee) and universal \forall (or \wedge)

- individual **variables**: $x, y, z, x_1, x_2 \dots$
- individual **constants**: a, b, c, \dots
- variables and constants: **terms**
- **predicate symbols** (taking individual symbols or tuples of them): A, B, C, \dots
- **quantifiers**: existential \exists (or \vee) and universal \forall (or \wedge)
- plus the connectives of SL

- for an n -ary predicate P and terms $t_1 \dots t_n$,
 $P(t_1 \dots t_n)$ or $Pt_1 \dots t_n$ is a wff.

Some syntax

- for an n -ary predicate P and terms $t_1 \dots t_n$,
 $P(t_1 \dots t_n)$ or $Pt_1 \dots t_n$ is a wff.
- possible prefix, function (bracket) and infix notation:
 Pxy , $P(x, y)$, xPy

Some syntax

- for an n -ary predicate P and terms $t_1 \dots t_n$,
 $P(t_1 \dots t_n)$ or $Pt_1 \dots t_n$ is a wff.
- possible prefix, function (bracket) and infix notation:
 Pxy , $P(x, y)$, xPy
- syntax for connectives from SL

Some syntax

- for an n -ary predicate P and terms $t_1 \dots t_n$,
 $P(t_1 \dots t_n)$ or $Pt_1 \dots t_n$ is a wff.
- possible prefix, function (bracket) and infix notation:
 Pxy , $P(x, y)$, xPy
- syntax for connectives from SL
- for any wff ϕ and any variable x , $(\exists x)\phi$ and $(\forall x)\phi$ are wff's

Semantic for individual constants

- denote individuals

Semantic for individual constants

- denote individuals
- a model \mathcal{M} contains a set of individuals D

Semantic for individual constants

- denote individuals
- a model \mathcal{M} contains a set of individuals D
- the valuation function V (or F): from constants to individuals in D

Semantic for individual constants

- denote individuals
- a model \mathcal{M} contains a set of individuals D
- the valuation function V (or F): from constants to individuals in D
- for some \mathcal{M}_1 : $D = \{Martin, Kilroy, Scully\}$

Semantic for individual constants

- denote individuals
- a model \mathcal{M} contains a set of individuals D
- the valuation function V (or F): from constants to individuals in D
- for some \mathcal{M}_1 : $D = \{Martin, Kilroy, Scully\}$
- $V_{\mathcal{M}_1}(m) = Martin$

Semantic for individual constants

- denote individuals
- a model \mathcal{M} contains a set of individuals D
- the valuation function V (or F): from constants to individuals in D
- for some \mathcal{M}_1 : $D = \{Martin, Kilroy, Scully\}$
- $V_{\mathcal{M}_1}(m) = Martin$
- $V_{\mathcal{M}_1}(k) = Kilroy, V_{\mathcal{M}_1}(s) = Scully$

- denote relations (sets of n -tuples)

Semantics for predicate symbols

- denote relations (sets of n-tuples)
- $\llbracket P \rrbracket^{\mathcal{M}_1} = \{Martin, Kilroy\}$ or $V_{\mathcal{M}_1}(P) = \{Martin, Kilroy\}$

- denote relations (sets of n-tuples)
- $\llbracket P \rrbracket^{\mathcal{M}_1} = \{Martin, Kilroy\}$ or $V_{\mathcal{M}_1}(P) = \{Martin, Kilroy\}$
- $V_{\mathcal{M}_1}(Q) = \{\langle Martin, Kilroy \rangle, \langle Martin, Scully \rangle, \langle Kilroy, Kilroy \rangle, \langle Scully, Scully \rangle\}$

Semantics for predicate symbols

- denote relations (sets of n-tuples)
- $\llbracket P \rrbracket^{\mathcal{M}_1} = \{\text{Martin}, \text{Kilroy}\}$ or $V_{\mathcal{M}_1}(P) = \{\text{Martin}, \text{Kilroy}\}$
- $V_{\mathcal{M}_1}(Q) = \{\langle \text{Martin}, \text{Kilroy} \rangle, \langle \text{Martin}, \text{Scully} \rangle, \langle \text{Kilroy}, \text{Kilroy} \rangle, \langle \text{Scully}, \text{Scully} \rangle\}$
- s.t. $\llbracket P(m) \rrbracket^{\mathcal{M}_1} = \llbracket P \rrbracket^{\mathcal{M}_1}(\llbracket m \rrbracket^{\mathcal{M}_1}) = 1$ iff $\llbracket m \rrbracket^{\mathcal{M}_1} \in \llbracket P \rrbracket^{\mathcal{M}_1}$

- **connectives**: 'apply to' formulas (semantically truth-valued), semantics as in SL

- **connectives**: 'apply to' formulas (semantically truth-valued), semantics as in SL
- $(\forall x)\phi = 1$ iff ϕ is true for every $d \in D$
assigned to every occurrence of x in ϕ

- **connectives**: 'apply to' formulas (semantically truth-valued), semantics as in SL
- $(\forall x)\phi = 1$ iff ϕ is true for every $d \in D$
assigned to every occurrence of x in ϕ
- $(\exists x)\phi = 1$ iff ϕ is true for at least one $d \in D$
assigned to every occurrence of x in ϕ

- **connectives**: 'apply to' formulas (semantically truth-valued), semantics as in SL
- $(\forall x)\phi = 1$ iff ϕ is true for every $d \in D$
assigned to every occurrence of x in ϕ
- $(\exists x)\phi = 1$ iff ϕ is true for at least one $d \in D$
assigned to every occurrence of x in ϕ
- algorithmic instruction to check wff's containing Q's

- **connectives**: 'apply to' formulas (semantically truth-valued), semantics as in SL
- $(\forall x)\phi = 1$ iff ϕ is true for every $d \in D$
assigned to every occurrence of x in ϕ
- $(\exists x)\phi = 1$ iff ϕ is true for at least one $d \in D$
assigned to every occurrence of x in ϕ
- algorithmic instruction to check wff's containing Q's
- check outside-in (unambiguous scoping)

- universal quantifiers can be swapped:

$$(\forall \mathbf{x})(\forall \mathbf{y})\phi \Leftrightarrow (\forall \mathbf{y})(\forall \mathbf{x})\phi$$

- universal quantifiers can be swapped:

$$(\forall x)(\forall y)\phi \Leftrightarrow (\forall y)(\forall x)\phi$$

- same for existential quantifiers:

$$(\exists x)(\exists y)\phi \Leftrightarrow (\exists y)(\exists x)\phi$$

Dependencies

- universal quantifiers can be swapped:

$$(\forall x)(\forall y)\phi \Leftrightarrow (\forall y)(\forall x)\phi$$

- same for existential quantifiers:

$$(\exists x)(\exists y)\phi \Leftrightarrow (\exists y)(\exists x)\phi$$

- whereas: $(\exists x)(\forall y)\phi \Rightarrow (\forall y)(\exists x)\phi$

- universal quantifiers can be swapped:

$$(\forall x)(\forall y)\phi \Leftrightarrow (\forall y)(\forall x)\phi$$

- same for existential quantifiers:

$$(\exists x)(\exists y)\phi \Leftrightarrow (\exists y)(\exists x)\phi$$

- whereas: $(\exists x)(\forall y)\phi \Rightarrow (\forall y)(\exists x)\phi$

- example in \mathcal{M}_1 :

$$\triangleright \underline{\underline{\llbracket (\forall x)(\exists y)Qxy \rrbracket^{\mathcal{M}_1}}} = 1$$

- universal quantifiers can be swapped:

$$(\forall x)(\forall y)\phi \Leftrightarrow (\forall y)(\forall x)\phi$$

- same for existential quantifiers:

$$(\exists x)(\exists y)\phi \Leftrightarrow (\exists y)(\exists x)\phi$$

- whereas: $(\exists x)(\forall y)\phi \Rightarrow (\forall y)(\exists x)\phi$

- example in \mathcal{M}_1 :

- ▶ $\llbracket (\forall x)(\exists y)Qxy \rrbracket^{\mathcal{M}_1} = 1$

- ▶ but: $\llbracket (\exists y)(\forall x)Qxy \rrbracket^{\mathcal{M}_1} = 0$

- universal quantifiers can be swapped:
 $(\forall x)(\forall y)\phi \Leftrightarrow (\forall y)(\forall x)\phi$
- same for existential quantifiers:
 $(\exists x)(\exists y)\phi \Leftrightarrow (\exists y)(\exists x)\phi$
- whereas: $(\exists x)(\forall y)\phi \Rightarrow (\forall y)(\exists x)\phi$
- example in \mathcal{M}_1 :
 - ▶ $\llbracket (\forall x)(\exists y)Qxy \rrbracket^{\mathcal{M}_1} = 1$
 - ▶ but: $\llbracket (\exists y)(\forall x)Qxy \rrbracket^{\mathcal{M}_1} = 0$
 - ▶ direct consequence of algorithmic definition

- universal quantifiers can be swapped:
 $(\forall x)(\forall y)\phi \Leftrightarrow (\forall y)(\forall x)\phi$
- same for existential quantifiers:
 $(\exists x)(\exists y)\phi \Leftrightarrow (\exists y)(\exists x)\phi$
- whereas: $(\exists x)(\forall y)\phi \Rightarrow (\forall y)(\exists x)\phi$
- example in \mathcal{M}_1 :
 - ▶ $\llbracket (\forall x)(\exists y)Qxy \rrbracket^{\mathcal{M}_1} = 1$
 - ▶ but: $\llbracket (\exists y)(\forall x)Qxy \rrbracket^{\mathcal{M}_1} = 0$
 - ▶ direct consequence of algorithmic definition
 - ▶ if $\exists\forall$ is true, $\forall\exists$ follows

Hints on quantifiers

- domain of quantifiers: D (universe of discourse)

Hints on quantifiers

- domain of quantifiers: D (universe of discourse)
- $\forall x$ checks for truth of some predication for all individuals

Hints on quantifiers

- domain of quantifiers: D (universe of discourse)
- $\forall x$ checks for truth of some predication for all individuals
- $\exists x(Px \wedge \neg Px)$ is a contradiction

Hints on quantifiers

- domain of quantifiers: D (universe of discourse)
- $\forall x$ checks for truth of some predication for all individuals
- $\exists x(Px \wedge \neg Px)$ is a contradiction
- $\forall x(Wx \wedge \neg Wx)$ is a contradicton,
 $\forall x$ 'checks' for an empty set by def.

Hints on quantifiers

- domain of quantifiers: D (universe of discourse)
- $\forall x$ checks for truth of some predication for all individuals
- $\exists x(Px \wedge \neg Px)$ is a contradiction
- $\forall x(Wx \wedge \neg Wx)$ is a contradiction,
 $\forall x$ 'checks' for an empty set by def.
- standard form of NL quantification:
 $\forall x(Wx \rightarrow Bx)$ 'All women are beautiful.'

Hints on quantifiers

- domain of quantifiers: D (universe of discourse)
- $\forall x$ checks for truth of some predication for all individuals
- $\exists x(Px \wedge \neg Px)$ is a contradiction
- $\forall x(Wx \wedge \neg Wx)$ is a contradiction,
 $\forall x$ 'checks' for an empty set by def.
- standard form of NL quantification:
 $\forall x(Wx \rightarrow Bx)$ 'All women are beautiful.'
- standard form of NL existential quantification:
 $\exists x(Wx \wedge Bx)$ 'Some woman is beautiful.'

- by def., functors take formulas, not terms:

- by def., functors take formulas, not terms:
 - ▶ $\neg Wm$ 'Mary doesn't weep.'

- by def., functors take formulas, not terms:
 - ▶ $\neg Wm$ 'Mary doesn't weep.'
 - ▶ $(\exists x)(Gx \wedge Wx)$ 'Some girl weeps.'

- by def., functors take formulas, not terms:
 - ▶ $\neg Wm$ 'Mary doesn't weep.'
 - ▶ $(\exists x)(Gx \wedge Wx)$ 'Some girl weeps.'
 - ▶ * $W\neg x$

- by def., functors take formulas, not terms:
 - ▶ $\neg Wm$ 'Mary doesn't weep.'
 - ▶ $(\exists x)(Gx \wedge Wx)$ 'Some girl weeps.'
 - ▶ * $W\neg x$
 - ▶ * $(\exists\neg x)(Gx)$

- by def., functors take formulas, not terms:
 - ▶ $\neg Wm$ 'Mary doesn't weep.'
 - ▶ $(\exists x)(Gx \wedge Wx)$ 'Some girl weeps.'
 - ▶ * $W\neg x$
 - ▶ * $(\exists\neg x)(Gx)$
- quantifiers take variables, not constants:

- by def., functors take formulas, not terms:
 - ▶ $\neg Wm$ 'Mary doesn't weep.'
 - ▶ $(\exists x)(Gx \wedge Wx)$ 'Some girl weeps.'
 - ▶ * $W\neg x$
 - ▶ * $(\exists \neg x)(Gx)$
- quantifiers take variables, not constants:
 - ▶ $(\forall x)(Ox \rightarrow Wx)$ 'All ozelots are wildcats.'

- by def., functors take formulas, not terms:
 - ▶ $\neg Wm$ 'Mary doesn't weep.'
 - ▶ $(\exists x)(Gx \wedge Wx)$ 'Some girl weeps.'
 - ▶ * $W\neg x$
 - ▶ * $(\exists \neg x)(Gx)$
- quantifiers take variables, not constants:
 - ▶ $(\forall x)(Ox \rightarrow Wx)$ 'All ozelots are wildcats.'
 - ▶ * $(\forall o)(Wo)$

- by def., functors take formulas, not terms:
 - ▶ $\neg Wm$ 'Mary doesn't weep.'
 - ▶ $(\exists x)(Gx \wedge Wx)$ 'Some girl weeps.'
 - ▶ * $W\neg x$
 - ▶ * $(\exists \neg x)(Gx)$
- quantifiers take variables, not constants:
 - ▶ $(\forall x)(Ox \rightarrow Wx)$ 'All ozelots are wildcats.'
 - ▶ * $(\forall o)(Wo)$
- \neg negates the wff, not the q:
 - * $(\neg \forall x)Px$ but $\neg(\forall x)Px$

- quantifiers **bind** variables

Scope

- quantifiers **bind** variables
- free variables (constants) are unbound

Scope

- quantifiers **bind** variables
- free variables (constants) are unbound
- **no double binding** * $(\forall x \exists x)Px$

Scope

- quantifiers **bind** variables
- free variables (constants) are unbound
- **no double binding** * $(\forall x \exists x)Px$
- **Q scope**: only the first wff to its right:

- quantifiers **bind** variables
- free variables (constants) are unbound
- **no double binding** * $(\forall x \exists x) Px$
- **Q scope**: only the first wff to its right:
 - ▶ $(\forall x) Px$ $\vee Qx$

- quantifiers **bind** variables
- free variables (constants) are unbound
- **no double binding** * $(\forall x \exists x) Px$
- **Q scope**: only the first wff to its right:
 - ▶ $(\forall x) Px \vee Qx$
 - ▶ $\underline{(\forall x)(Px \vee Qx)} = \underline{(\forall x)Px} \vee \underline{(\forall x)Qx}$

- quantifiers **bind** variables
- free variables (constants) are unbound
- **no double binding** * $(\forall x \exists x) Px$
- **Q scope**: only the first wff to its right:
 - ▶ $(\forall x) Px \vee Qx$
 - ▶ $(\forall x)(Px \vee Qx) = (\forall x) Px \vee (\forall x) Qx$
 - ▶ $(\exists x) Px \rightarrow (\forall y)(Qy \wedge Ry)$

- quantifiers **bind** variables
- free variables (constants) are unbound
- **no double binding** * $(\forall x \exists x) Px$
- **Q scope**: only the first wff to its right:
 - ▶ $(\forall x) Px \vee Qx$
 - ▶ $\overline{(\forall x)(Px \vee Qx)} = \overline{(\forall x)Px} \vee \overline{(\forall x)Qx}$
 - ▶ $\overline{(\exists x)Px} \rightarrow \overline{(\forall y)(Qy \wedge Ry)}$
 - ▶ $\overline{(\exists x)Px} \wedge Qx$ (second x is a unbound)

- quantifiers **bind** variables
- free variables (constants) are unbound
- **no double binding** * $(\forall x \exists x) Px$
- **Q scope**: only the first wff to its right:
 - ▶ $(\forall x) Px \vee Qx$
 - ▶ $(\forall x)(Px \vee Qx) = (\forall x) Px \vee (\forall x) Qx$
 - ▶ $(\exists x) Px \rightarrow (\forall y)(Qy \wedge Ry)$
 - ▶ $(\exists x) Px \wedge Qx$ (second x is a unbound)
- **no double-naming**

Laws of PC

- \exists and \forall 'or' and 'and' over the universe of discourse (hence: \vee and \wedge)

- \exists and \forall 'or' and 'and' over the universe of discourse (hence: \vee and \wedge)
- $(\forall x)Px \Leftrightarrow Px_1 \wedge Px_2 \wedge \dots \wedge Px_n$ for all x_n assigned to $d_n \in D$

Universal \vee and \wedge

- \exists and \forall ‘or’ and ‘and’ over the universe of discourse (hence: \vee and \wedge)
- $(\forall x)Px \Leftrightarrow Px_1 \wedge Px_2 \wedge \dots \wedge Px_n$ for all x_n assigned to $d_n \in D$
- $(\exists x)Px \Leftrightarrow Px_1 \vee Px_2 \vee \dots \vee Px_n$ for all x_n assigned to $d_n \in D$

- \exists and \forall ‘or’ and ‘and’ over the universe of discourse (hence: \vee and \wedge)
- $(\forall x)Px \Leftrightarrow Px_1 \wedge Px_2 \wedge \dots \wedge Px_n$ for all x_n assigned to $d_n \in D$
- $(\exists x)Px \Leftrightarrow Px_1 \vee Px_2 \vee \dots \vee Px_n$ for all x_n assigned to $d_n \in D$
- hence: $\neg(\forall x)Px \Leftrightarrow \neg(Px_1 \wedge Px_2 \wedge \dots \wedge Px_n)$

- \exists and \forall ‘or’ and ‘and’ over the universe of discourse (hence: \vee and \wedge)
- $(\forall x)Px \Leftrightarrow Px_1 \wedge Px_2 \wedge \dots \wedge Px_n$ for all x_n assigned to $d_n \in D$
- $(\exists x)Px \Leftrightarrow Px_1 \vee Px_2 \vee \dots \vee Px_n$ for all x_n assigned to $d_n \in D$
- hence: $\neg(\forall x)Px \Leftrightarrow \neg(Px_1 \wedge Px_2 \wedge \dots \wedge Px_n)$
- with DeM: $\overline{Px_1 \wedge Px_2 \wedge \dots \wedge Px_n}$

Universal \forall and \wedge

- \exists and \forall 'or' and 'and' over the universe of discourse (hence: \vee and \wedge)
- $(\forall x)Px \Leftrightarrow Px_1 \wedge Px_2 \wedge \dots \wedge Px_n$ for all x_n assigned to $d_n \in D$
- $(\exists x)Px \Leftrightarrow Px_1 \vee Px_2 \vee \dots \vee Px_n$ for all x_n assigned to $d_n \in D$
- hence: $\neg(\forall x)Px \Leftrightarrow \neg(Px_1 \wedge Px_2 \wedge \dots \wedge Px_n)$
- with DeM: $\overline{Px_1 \wedge Px_2 \wedge \dots \wedge Px_n}$
- $\Leftrightarrow \overline{Px_1} \vee \overline{Px_2} \vee \dots \vee \overline{Px_n}$

Universal \forall and \wedge

- \exists and \forall ‘or’ and ‘and’ over the universe of discourse (hence: \vee and \wedge)
- $(\forall x)Px \Leftrightarrow Px_1 \wedge Px_2 \wedge \dots \wedge Px_n$ for all x_n assigned to $d_n \in D$
- $(\exists x)Px \Leftrightarrow Px_1 \vee Px_2 \vee \dots \vee Px_n$ for all x_n assigned to $d_n \in D$
- hence: $\neg(\forall x)Px \Leftrightarrow \neg(Px_1 \wedge Px_2 \wedge \dots \wedge Px_n)$
- with DeM: $\overline{Px_1 \wedge Px_2 \wedge \dots \wedge Px_n}$
- $\Leftrightarrow \overline{Px_1} \vee \overline{Px_2} \vee \dots \vee \overline{Px_n}$
- $\Leftrightarrow (\exists x)\neg Px$

Quantifier negation (QN)

- $\neg(\forall x)Px \Leftrightarrow (\exists x)\neg Px$

Quantifier negation (QN)

- $\neg(\forall x)Px \Leftrightarrow (\exists x)\neg Px$
- $\neg(\exists x)Px \Leftrightarrow (\forall x)\neg Px$

Quantifier negation (QN)

- $\neg(\forall x)Px \Leftrightarrow (\exists x)\neg Px$
- $\neg(\exists x)Px \Leftrightarrow (\forall x)\neg Px$
- $\neg(\forall x)\neg Px \Leftrightarrow (\exists x)Px$

Quantifier negation (QN)

- $\neg(\forall x)Px \Leftrightarrow (\exists x)\neg Px$
- $\neg(\exists x)Px \Leftrightarrow (\forall x)\neg Px$
- $\neg(\forall x)\neg Px \Leftrightarrow (\exists x)Px$
- $\neg(\exists x)\neg Px \Leftrightarrow (\forall x)Px$

The distribution laws

- the conjunction of universally quantified formulas:

$$\underline{(\forall x)(Px \wedge Qx)} \Leftrightarrow \underline{(\forall x)Px} \wedge \underline{(\forall x)Qx}$$

The distribution laws

- the conjunction of universally quantified formulas:

$$\underline{(\forall x)(Px \wedge Qx)} \Leftrightarrow \underline{(\forall x)Px} \wedge \underline{(\forall x)Qx}$$

- the disjunction of existentially quantified formulas:

$$\underline{(\exists x)(Px \vee Qx)} \Leftrightarrow \underline{(\exists x)Px} \vee \underline{(\exists x)Qx}$$

The distribution laws

- the conjunction of universally quantified formulas:

$$\underline{(\forall x)(Px \wedge Qx)} \Leftrightarrow \underline{(\forall x)Px} \wedge \underline{(\forall x)Qx}$$

- the disjunction of existentially quantified formulas:

$$\underline{(\exists x)(Px \vee Qx)} \Leftrightarrow \underline{(\exists x)Px} \vee \underline{(\exists x)Qx}$$

- not v.v.: $(\forall x)Px \vee (\forall x)Qx \Rightarrow (\forall x)(Px \vee Qx)$

The distribution laws

- the conjunction of universally quantified formulas:

$$\underline{(\forall x)(Px \wedge Qx)} \Leftrightarrow \underline{(\forall x)Px} \wedge \underline{(\forall x)Qx}$$

- the disjunction of existentially quantified formulas:

$$\underline{(\exists x)(Px \vee Qx)} \Leftrightarrow \underline{(\exists x)Px} \vee \underline{(\exists x)Qx}$$

- not v.v.: $(\forall x)Px \vee (\forall x)Qx \Rightarrow (\forall x)(Px \vee Qx)$
- why?

Quantifier movement (QM)

- desirable format: **prefix + matrix**

Quantifier movement (QM)

- desirable format: **prefix + matrix**
- Movement Laws for antecedents of conditionals:

$$(\exists x)Px \rightarrow \phi \Leftrightarrow (\forall x)(Px \rightarrow \phi)$$

$$(\forall x)Px \rightarrow \phi \Leftrightarrow (\exists x)(Px \rightarrow \phi)$$

Quantifier movement (QM)

- desirable format: **prefix + matrix**
- Movement Laws for antecedents of conditionals:
 $(\exists x)Px \rightarrow \phi \Leftrightarrow (\forall x)(Px \rightarrow \phi)$
 $(\forall x)Px \rightarrow \phi \Leftrightarrow (\exists x)(Px \rightarrow \phi)$
- Movement Laws for Q's in disjunction, conjunction, and the consequent of conditionals: **Just move them to the prefix!**

Quantifier movement (QM)

- desirable format: **prefix + matrix**
- Movement Laws for antecedents of conditionals:
 $(\exists x)Px \rightarrow \phi \Leftrightarrow (\forall x)(Px \rightarrow \phi)$
 $(\forall x)Px \rightarrow \phi \Leftrightarrow (\exists x)(Px \rightarrow \phi)$
- Movement Laws for Q's in disjunction, conjunction, and the consequent of conditionals: **Just move them to the prefix!**
- condition: **x must not be free in ϕ .**

Quantifier movement (QM)

- desirable format: **prefix + matrix**
- Movement Laws for antecedents of conditionals:
 $(\exists x)Px \rightarrow \phi \Leftrightarrow (\forall x)(Px \rightarrow \phi)$
 $(\forall x)Px \rightarrow \phi \Leftrightarrow (\exists x)(Px \rightarrow \phi)$
- Movement Laws for Q's in disjunction, conjunction, and the consequent of conditionals: **Just move them to the prefix!**
- condition: **x must not be free in ϕ .**
- i.e.: Watch your variables!

Let's formalize:

- *Paul Kalkbrenner is a musician and signed on bpitchcontrol.*

Let's formalize:

- *Paul Kalkbrenner is a musician and signed on bpitchcontrol.*
- *Herr S. installed RedHat and not every Linux distribution is easy to install.*

Let's formalize:

- *Paul Kalkbrenner is a musician and signed on bpitchcontrol.*
- *Herr S. installed RedHat and not every Linux distribution is easy to install.*
- *All talkmasters are human and Harald Schmidt is a talkmaster.*

Let's formalize:

- *Paul Kalkbrenner is a musician and signed on bpitchcontrol.*
- *Herr S. installed RedHat and not every Linux distribution is easy to install.*
- *All talkmasters are human and Harald Schmidt is a talkmaster.*
- *Some talkmasters are not musicians.*

Let's formalize:

- *Paul Kalkbrenner is a musician and signed on bpitchcontrol.*
- *Herr S. installed RedHat and not every Linux distribution is easy to install.*
- *All talkmasters are human and Harald Schmidt is a talkmaster.*
- *Some talkmasters are not musicians.*
- *Heiko Laux owns Kanzleramt records and does not like any Gigolo artist.*

Let's formalize:

- *Paul Kalkbrenner is a musician and signed on bpitchcontrol.*
- *Herr S. installed RedHat and not every Linux distribution is easy to install.*
- *All talkmasters are human and Harald Schmidt is a talkmaster.*
- *Some talkmasters are not musicians.*
- *Heiko Laux owns Kanzleramt records and does not like any Gigolo artist.*
- *Some humans are neither talkmasters nor do they own Kanzleramt records.*

Natural deduction in PC

Universal instantiation ($- \forall$) and generalization ($+ \forall$)

- $(\forall x)Px \rightarrow Pa$

Universal instantiation ($-\forall$) and generalization ($+\forall$)

- $(\forall x)Px \rightarrow Pa$
- always applies

Universal instantiation ($-\forall$) and generalization ($+\forall$)

- $(\forall x)Px \rightarrow Pa$
- always applies

Universal instantiation ($- \forall$) and generalization ($+ \forall$)

- $(\forall x)Px \rightarrow Pa$
- always applies
- can use any variable/constant

Universal instantiation ($- \forall$) and generalization ($+ \forall$)

- $(\forall x)Px \rightarrow Pa$
- always applies
- can use any variable/constant
- $Pa \rightarrow (\forall x)Px$

Universal instantiation ($-\forall$) and generalization ($+\forall$)

- $(\forall x)Px \rightarrow Pa$
- always applies
- can use any variable/constant
- $Pa \rightarrow (\forall x)Px$
- iff Pa was instantiated by $-\forall$

Existential generalization ($+\exists$) and instantiation ($-\exists$)

- $Pa \rightarrow (\exists x)Px$ for any individual constant a

Existential generalization ($+\exists$) and instantiation ($-\exists$)

- $Pa \rightarrow (\exists x)Px$ for any individual constant a
- always applies

Existential generalization ($+\exists$) and instantiation ($-\exists$)

- $Pa \rightarrow (\exists x)Px$ for any individual constant a
- always applies
- $(\exists x)Px \rightarrow Pa$ for some indiv. const.

Existential generalization ($+\exists$) and instantiation ($-\exists$)

- $Pa \rightarrow (\exists x)Px$ for any individual constant a
- always applies
- $(\exists x)Px \rightarrow Pa$ for some indiv. const.
- always applies (there is a minimal individual for $\exists x$)

Existential generalization ($+\exists$) and instantiation ($-\exists$)

- $Pa \rightarrow (\exists x)Px$ for any individual constant a
- always applies
- $(\exists x)Px \rightarrow Pa$ for some indiv. const.
- always applies (there is a minimal individual for $\exists x$)
- for some $(\exists x)Px$ and $(\exists x)Qx$ the minimal individual might be different

Existential generalization ($+\exists$) and instantiation ($-\exists$)

- $Pa \rightarrow (\exists x)Px$ for any individual constant a
- always applies
- $(\exists x)Px \rightarrow Pa$ for some indiv. const.
- always applies (there is a minimal individual for $\exists x$)
- for some $(\exists x)Px$ and $(\exists x)Qx$ the minimal individual might be different
- hence: **When you apply EI, always use fresh constants!**

One sample task

- (1) Herr Keydana drives a Golf. (2) Anything that drives a golf is human or a complex program simulating an artificial neural net. (3) There are no programs s.a.a.n.n. which are complex enough to drive a Golf.

One sample task

- (1) Herr Keydana drives a Golf. (2) Anything that drives a golf is human or a complex program simulating an artificial neural net. (3) There are no programs s.a.a.n.n. which are complex enough to drive a Golf.
- Formalize and prove: At least one human exists.

One sample task

- (1) Herr Keydana drives a Golf. (2) Anything that drives a golf is human or a complex program simulating an artificial neural net. (3) There are no programs s.a.a.n.n. which are complex enough to drive a Golf.
- Formalize and prove: *At least one human exists.*
- (1) *Dk*

One sample task

- (1) Herr Keydana drives a Golf. (2) Anything that drives a golf is human or a complex program simulating an artificial neural net. (3) There are no programs s.a.a.n.n. which are complex enough to drive a Golf.
- Formalize and prove: **At least one human exists.**
- (1) Dk
- (2) $(\forall x)(Dx \rightarrow Hx \vee Px)$

One sample task

- (1) Herr Keydana drives a Golf. (2) Anything that drives a golf is human or a complex program simulating an artificial neural net. (3) There are no programs s.a.a.n.n. which are complex enough to drive a Golf.
- Formalize and prove: **At least one human exists.**
- (1) Dk
- (2) $(\forall x)(Dx \rightarrow Hx \vee Px)$
- (3) $\neg(\exists x)(Px \wedge Dx)$

One sample task

- (1) Herr Keydana drives a Golf. (2) Anything that drives a golf is human or a complex program simulating an artificial neural net. (3) There are no programs s.a.a.n.n. which are complex enough to drive a Golf.
- Formalize and prove: **At least one human exists.**
- (1) Dk
- (2) $(\forall x)(Dx \rightarrow Hx \vee Px)$
- (3) $\neg(\exists x)(Px \wedge Dx)$
- $(\exists x)Hx$

The proof

(1)	Dk	
(2)	$(\forall x)(Dx \rightarrow Hx \vee Px)$	
(3)	$\neg(\exists x)(Px \wedge Dx)$	
<hr/>		
(4)	$(\forall x)\neg(Px \wedge Dx)$	3,QN
(5)	$(\forall x)(\neg Px \vee \neg Dx)$	4,DeM
(6)	$(\forall x)(Dx \rightarrow \neg Px)$	5,Comm,Impl
(7)	$Dk \rightarrow \neg Pk$	6, $\neg\forall(1)$
(8)	$\neg Pk$	1,7,MP
(9)	$Dk \rightarrow Hk \vee Pk$	2, $\neg\forall(1)$
(10)	$Hk \vee Pk$	1,9,MP
(11)	Hk	8,10,DS
\therefore	$(\exists x)Hx$	10, $+\exists$

Kontakt

Prof. Dr. Roland Schäfer
Institut für Germanistische Sprachwissenschaft
Friedrich-Schiller-Universität Jena
Fürstengraben 30
07743 Jena

<https://rolandschaefer.net>
roland.schaefer@uni-jena.de

Creative Commons BY-SA-3.0-DE

Dieses Werk ist unter einer Creative Commons Lizenz vom Typ *Namensnennung - Weitergabe unter gleichen Bedingungen 3.0 Deutschland* zugänglich. Um eine Kopie dieser Lizenz einzusehen, konsultieren Sie

<http://creativecommons.org/licenses/by-sa/3.0/de/> oder wenden Sie sich brieflich an Creative Commons, Postfach 1866, Mountain View, California, 94042, USA.