

# Tips for Writing Python Scripts

## Transcript

Copyright © 2006 ESRI

All rights reserved.

The information contained in this document is the exclusive property of ESRI. This work is protected under United States copyright law and other international copyright treaties and conventions. No part of this work may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or by any information storage or retrieval system, except as expressly permitted in writing by ESRI. All requests should be sent to Attention: Contracts and Legal Services Manager, ESRI, 380 New York Street, Redlands, CA 92373-8100, USA.

The information contained in this document is subject to change without notice.

@esri.com, 3D Analyst, ADF, AML, ARC/INFO, ArcAtlas, ArcCAD, ArcCatalog, ArcCOGO, ArcData, ArcDoc, ArcEdit, ArcEditor, ArcEurope, ArcExplorer, ArcExpress, ArcFM, ArcGIS, ArcGlobe, ArcGrid, ArcIMS, ArcInfo Librarian, ArcInfo, ArcInfo-Professional GIS, ArcInfo-The World's GIS, ArcLocation, ArcLogistics, ArcMap, ArcNetwork, ArcNews, ArcObjects, ArcOpen, ArcPad, ArcPlot, ArcPress, ArcQuest, ArcReader, ArcScan, ArcScene, ArcSchool, ArcSDE, ArcSdl, ArcStorm, ArcSurvey, ArcTIN, ArcToolbox, ArcTools, ArcUSA, ArcUser, ArcView, ArcVoyager, ArcWatch, ArcWeb, ArcWorld, Atlas GIS, AtlasWare, Avenue, BusinessMAP, Database Integrator, DBI Kit, ESRI, ESRI-Team GIS, ESRI-The GIS Company, ESRI-The GIS People, FormEdit, Geographic Design System, Geography Matters, Geography Network, GIS by ESRI, GIS Day, GIS for Everyone, GISData Server, InsiteMAP, JTX, MapBeans, MapCafé, MapObjects, ModelBuilder, MOLE, NetEngine, PC ARC/INFO, PC ARCPLOT, PC ARCSHELL, PC DATA CONVERSION, PC STARTER KIT, PC TABLES, PC ARCEDIT, PC NETWORK, PC OVERLAY, PLTS, Rent-a-Tech, RouteMAP, SDE, SML, Spatial Database Engine, StreetEditor, StreetMap, TABLES, the ARC/INFO logo, the ArcCAD logo, the ArcCAD WorkBench logo, the ArcCOGO logo, the ArcData logo, the ArcData Online logo, the ArcEdit logo, the ArcExplorer logo, the ArcExpress logo, the ArcFM logo, the ArcFM Viewer logo, the ArcGIS logo, the ArcGrid logo, the ArcIMS logo, the ArcInfo logo, the ArcLogistics Route logo, the ArcNetwork logo, the ArcPad logo, the ArcPlot logo, the ArcPress for ArcView logo, the ArcPress logo, the ArcScan logo, the ArcScene logo, the ArcSDE CAD Client logo, the ArcSDE logo, the ArcStorm logo, the ArcTIN logo, the ArcTools logo, the ArcView 3D Analyst logo, the ArcView Business Analyst logo, the ArcView Data Publisher logo, the ArcView GIS logo, the ArcView Image Analysis logo, the ArcView Internet Map Server logo, the ArcView logo, the ArcView Network Analyst logo, the ArcView Spatial Analyst logo, the ArcView StreetMap 2000 logo, the ArcView StreetMap logo, the ArcView Tracking Analyst logo, the Atlas GIS logo, the Avenue logo, the BusinessMAP logo, the Data Automation Kit logo, the ESRI ArcAtlas Data logo, the ESRI ArcEurope Data logo, the ESRI ArcScene Data logo, the ESRI ArcUSA Data logo, the ESRI ArcWorld Data logo, the ESRI Digital Chart of the World Data logo, the ESRI globe logo, the ESRI Press logo, the Geography Network logo, the MapCafé logo, the MapObjects Internet Map Server logo, the MapObjects logo, the MOLE logo, the NetEngine logo, the PC ARC/INFO logo, the Production Line Tool Set logo, the RouteMAP IMS logo, the RouteMAP logo, the SDE logo, The World's Leading Desktop GIS, Water Writes, www.esri.com, www.geographynetwork.com, www.gisday.com, and Your Personal Geographic Information System are trademarks, registered trademarks, or service marks of ESRI in the United States, the European Community, or certain other jurisdictions.

Other companies and products mentioned herein are trademarks or registered trademarks of their respective trademark owners.

Hello, I'm Jeff Bigos, an instructor with the ESRI Educational Services group here in Redlands, California. I teach our *Introduction to Geoprocessing Scripts Using Python* course. Today I want to highlight five topics that can be useful to you when writing your geoprocessing scripts with Python. This discussion is for anyone who has an interest in writing geoprocessing scripts with Python.

Our first topic is deleting variables that hold an insert or an update cursor. When using an update cursor, or an insert cursor within our scripts to calculate values within a table or a feature class, it is a good practice to delete the variable that created the cursor. For example, if we wanted to update a name field on a rivers feature class within a script, we can use an update cursor. To establish that update cursor, we might set a variable in our script called *cur* and set it equal to `gp.UpdateCursor`. From there, we might put the update operation in a WHILE loop to calculate the values for us. When we are done with updating the values within our feature class, it is a good practice to delete the *cur* variable. To do that, Python has a statement called *del*. This statement allows us to delete variables from memory that we have used within our script. Make sure the *del* statement is in all lowercase letters, and if you're writing your script from within Python Win, that *del* statement should show up in blue. Within our script we would see *del cur*. This removes the lock on the feature class that Python needed to update the field on the input feature class.

The second topic is a `ValidateTableName` method. This is a method on the geoprocessor that will return a proper table name based on name restrictions within the output workspace. We can use this in our scripts to verify a user-defined input table name. If we wrote a script that requires a user to type in the name of an output feature class, there's a chance that they could use a character that is invalid with the output workspace. This method has two parameters.

- The first is the table name. This could be a new table or a feature class that you want to generate within your script and put into a database.
- The second parameter is a workspace. This is the workspace, or folder, that you are validating your table with. For example, if a user tries to name an output feature class *test\** we could validate the user input with the workspace and verify whether we could use *test\** as a feature class name. In this case, the asterisk is invalid for the database we're working with, so the `ValidateTableName` method will turn the asterisk into an underscore. Our result will be the name *test\_*.

Our third topic is the Windows Scheduler. With the Windows Scheduler, you can set up your Python scripts to run at various times as a scheduled task. On most Windows operating systems, the Windows Scheduler can be found in the following location: Start > Programs > Accessories > System Tools > Scheduled Tasks. Then choose the option for Add Scheduled Task. This will take you into the Schedule Task Wizard, where you can specify what script to run and when.

Our fourth topic is the Make Feature Layer tool. In ArcToolbox, in the Data Management Tools toolbox, there is a toolset called Layers and Table Views. In this toolset you will find these Select Layer by Location and Select Layer by Attribute tools. If you look at the Help for these tools, the first parameter you have to supply is a feature layer, and not a feature class. To help you run these tools within a Python script, there is a tool called Make Feature Layer. This tool is also found in the Layers and Table Views toolset. This tool will take an input feature class and create a layer from it. The output of the Make Feature Layer tool can then be used as input to the Select by Location and Select Layer by Attributes tools. In addition, there is a tool in there called Make Table View. The output of the Make Table View tool can be used as input to the Select Layer by Attribute tool as well.

Finally, the Get Count tool. This tool is a personal favorite of mine to use within Python scripts. This tool will return how many records are within a table or how many features are within a feature class. It's a simple yet powerful tool.

To review our topics, if you're using an update or an insert cursor to update values within a feature class or a table, it is a good practice to delete the variable, holding onto that cursor when you're finished. The ValidateTableName method will validate the name of a table with a workspace. Use the Windows Scheduler to run your scripts at specific dates and times. The Make Feature Layer tool will create a feature layer from a feature class that you can use with other tools. And finally, the Get Count tool will tell you the number of records in a table, or features in a feature class.

For further resources, check out our instructor-led course *Introduction to Writing Geoprocessing Scripts Using Python*. Thank you for tuning into this session of our ESRI Instructional Series podcast. Stay tuned for future broadcasts.