

CS60021: Scalable Data Mining

Sourangshu Bhattacharya


In this Lecture:

- Outline:
 - What is Big Data?
 - Issues with Big Data
 - What is Hadoop ?
 - What is Map Reduce ?
 - Example Map Reduce program.

Motivation: Google Example

- 20+ billion web pages x 20KB = 400+ TB
- 1 computer reads 30-35 MB/sec from disk
 - ~4 months to read the data
- ~ 400 hard drives to store the data
- Takes even more to **do something useful with the data!**
- **Today, a standard architecture for such problems is emerging:**
 - Cluster of commodity Linux nodes
 - Commodity network (ethernet) to connect them

Cluster Architecture



Large-scale Computing

- Large-scale computing for data mining problems on commodity hardware
- Challenges:
 - How do you distribute computation?
 - How can we make it easy to write distributed programs?
 - Machines fail:
 - One server may stay up 3 years (1,000 days)
 - If you have 1,000 servers, expect to loose 1/day
 - People estimated Google had ~1M machines in 2011
 - 1,000 machines fail every day!

Big Data Challenges

- Scalability: processing should scale with increase in data.
- Fault Tolerance: function in presence of hardware failure
- Cost Effective: should run on commodity hardware
- Ease of use: programmers do not write additional code for communication, fault tolerance, etc.
- Flexibility: able to process unstructured data
- **Solution: Map Reduce !**

Idea and Solution

- **Issue:** Copying data over a network takes time
- **Idea:**
 - Bring computation close to the data
 - Store files multiple times for reliability
- **Map-reduce** addresses these problems
 - Elegant way to work with big data
 - **Storage Infrastructure – File system**
 - Google: GFS. Hadoop: HDFS
 - **Programming model**
 - Map-Reduce

What is Hadoop ?

- A scalable fault-tolerant distributed system for data storage and processing.
- Core Hadoop:
 - Hadoop Distributed File System (HDFS)
 - Hadoop YARN: Job Scheduling and Cluster Resource Management
 - Hadoop Map Reduce: Framework for distributed data processing.
- Open Source system with large community support.
<https://hadoop.apache.org/>

What is Map Reduce ?

- Method for distributing a task across multiple servers.
- Proposed by Dean and Ghemawat, 2004.
- Consists of two developer created phases:
 - Map
 - Reduce
- In between Map and Reduce is the Shuffle and Sort phase.
- User is responsible for casting the problem into map – reduce framework.
- Multiple map-reduce jobs can be “chained”.

Programming Model: MapReduce

Warm-up task:

- We have a huge text document
- Count the number of times each distinct word appears in the file
- **Sample application:**
 - Analyze web server logs to find popular URLs

Task: Word Count

Case 1:

- File too large for memory, but all <word, count> pairs fit in memory

Case 2:

- Count occurrences of words:
 - `words(doc.txt) | sort | uniq -c`
 - where `words` takes a file and outputs the words in it, one per a line
- Case 2 captures the essence of **MapReduce**
 - Great thing is that it is naturally parallelizable

MapReduce: Overview


- Sequentially read a lot of data
- **Map:**
 - Extract something you care about
- **Group by key:** Sort and Shuffle
- **Reduce:**
 - Aggregate, summarize, filter or transform
- Write the result

Outline stays the same, **Map** and **Reduce** change to fit the problem

More Specifically

- **Input:** a set of key-value pairs
- Programmer specifies two methods:
 - **Map(k, v)** $\rightarrow \langle k', v' \rangle^*$
 - Takes a key-value pair and outputs a set of key-value pairs
 - E.g., key is the filename, value is a single line in the file
 - There is one Map call for every (k, v) pair
 - **Reduce($k', \langle v' \rangle^*$)** $\rightarrow \langle k', v'' \rangle^*$
 - **All values v' with same key k' are reduced together and processed in v' order**
 - There is one Reduce function call per unique key k'

MapReduce: Word Counting



Word Count Using MapReduce

map(key, value):

```
// key: document name; value: text of the
document
for each word w in value:
    emit(w, 1)
```

reduce(key, values):

```
// key: a word; value: an iterator over
counts
    result = 0
    for each count v in values:
        result += v
    emit(key, result)
```

HADOOP

Map Phase

- User writes the mapper method.
- Input is an unstructured record:
 - E.g. A row of RDBMS table,
 - A line of a text file, etc
- Output is a set of records of the form: <key, value>
 - Both key and value can be anything, e.g. text, number, etc.
 - E.g. for row of RDBMS table: <column id, value>
 - Line of text file: <word, count>


Shuffle/Sort phase

- Shuffle phase ensures that all the mapper output records with the same key value, goes to the same reducer.
- Sort ensures that among the records received at each reducer, records with same key arrives together.

Reduce phase


- Reducer is a user defined function which processes mapper output records with some of the keys output by mapper.
- Input is of the form <key, value>
 - All records having same key arrive together.
- Output is a set of records of the form <key, value>
 - Key is not important

Parallel picture




Example

Word Count: Count the total no. of occurrences of each word



Map Reduce - Example



What was the max/min temperature for the last century ?

Hadoop Map Reduce

☐ Provides:

- ☐ Automatic parallelization and Distribution
- ☐ Fault Tolerance
- ☐ Methods for interfacing with HDFS for colocation of computation and storage of output.
- ☐ Status and Monitoring tools
- ☐ API in Java
- ☐ Ability to define the mapper and reducer in many languages through Hadoop streaming.

HDFS

What's HDFS


- HDFS is a distributed file system that is fault tolerant, scalable and extremely easy to expand.
- HDFS is the primary distributed storage for Hadoop applications.
- HDFS provides interfaces for applications to move themselves closer to data.
- HDFS is designed to 'just work', however a working knowledge helps in diagnostics and improvements.

Components of HDFS

There are two (*and a half*) types of machines in a HDFS cluster

- NameNode :- is the heart of an HDFS filesystem, it maintains and manages the file system metadata. E.g; what blocks make up a file, and on which datanodes those blocks are stored.
- DataNode :- where HDFS stores the actual data, there are usually quite a few of these.

HDFS Architecture




HDFS

- Design Assumptions
 - Hardware failure is the norm.
 - Streaming data access.
 - Write once, read many times.
 - High throughput, not low latency.
 - Large files.
- Characteristics:
 - Performs best with modest number of large files
 - Optimized for streaming reads
 - Layer on top of native file system.

HDFS

- Data is organized into file and directories.
- Files are divided into blocks and distributed to nodes.
- Block placement is known at the time of read
 - Computation moved to same node.
- Replication is used for:
 - Speed
 - Fault tolerance
 - Self healing.

HDFS Architecture



NameNode Metadata

- **Meta-data in Memory**
 - The entire metadata is in main memory
 - No demand paging of meta-data
- **Types of Metadata**
 - List of files
 - List of Blocks for each file
 - List of DataNodes for each block
 - File attributes, e.g creation time, replication factor
- **A Transaction Log**
 - Records file creations, file deletions. etc

DataNode

- **A Block Server**
 - Stores data in the local file system (e.g. ext3)
 - Stores meta-data of a block (e.g. CRC)
 - Serves data and meta-data to Clients
- **Block Report**
 - Periodically sends a report of all existing blocks to the NameNode
- **Facilitates Pipelining of Data**
 - Forwards data to other specified DataNodes

HDFS – User Commands (dfs)

List directory contents

```
hdfs dfs -ls  
hdfs dfs -ls /  
hdfs dfs -ls -R /var
```

Display the disk space used by files

```
hdfs dfs -du /hbase/data/hbase/namespace/  
hdfs dfs -du -h /hbase/data/hbase/namespace/  
hdfs dfs -du -s /hbase/data/hbase/namespace/
```

HDFS – User Commands (dfs)

Copy data to HDFS

```
hdfs dfs -mkdir tdata
hdfs dfs -ls
hdfs dfs -copyFromLocal tutorials/data/geneva.csv tdata
hdfs dfs -ls -R
```

Copy the file back to local filesystem

```
cd tutorials/data/
hdfs dfs -copyToLocal tdata/geneva.csv geneva.csv.hdfs
md5sum geneva.csv geneva.csv.hdfs
```

HDFS – User Commands (acls)

List acl for a file

```
hdfs dfs -getfacl tdata/geneva.csv
```


List the file statistics – (%r – replication factor)

```
hdfs dfs -stat "%r" tdata/geneva.csv
```

Write to hdfs reading from stdin


```
echo "blah blah blah" | hdfs dfs -put - tdataset/tfile.txt  
hdfs dfs -ls -R  
hdfs dfs -cat tdataset/tfile.txt
```

HDFS read client



Source: Hadoop: The Definitive Guide

HDFS write Client



Source: Hadoop: The Definitive Guide

Block Placement

- **Current Strategy**
 - One replica on local node
 - Second replica on a remote rack
 - Third replica on same remote rack
 - Additional replicas are randomly placed
- **Clients read from nearest replica**
- **Would like to make this policy pluggable**

NameNode Failure

- **A single point of failure**
- **Transaction Log stored in multiple directories**
 - A directory on the local file system
 - A directory on a remote file system (NFS/CIFS)

Data Pipelining

- Client retrieves a **list of DataNodes** on which to place replicas of a block
- Client writes block to the first DataNode
- The first DataNode forwards the data to the next DataNode in the Pipeline
- Usually, when all replicas are written, the Client moves on to write the next block in file

Conclusion:

- We have seen:
 - The structure of HDFS.
 - The shell commands.
 - The architecture of HDFS system.
 - Internal functioning of HDFS.


MAPREDUCE INTERNALS

Hadoop Map Reduce

- Provides:
 - Automatic parallelization and Distribution
 - Fault Tolerance
 - Methods for interfacing with HDFS for colocation of computation and storage of output.
 - Status and Monitoring tools
 - API in Java
 - Ability to define the mapper and reducer in many languages through Hadoop streaming.

Hadoop(v2)

MR job



Wordcount program

```
import java.io.IOException;
import java.util.StringTokenizer;

import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.Path;
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapreduce.Job;
import org.apache.hadoop.mapreduce.Mapper;
import org.apache.hadoop.mapreduce.Reducer;
import org.apache.hadoop.mapreduce.lib.input.FileInputFormat;
import org.apache.hadoop.mapreduce.lib.output.FileOutputFormat;
```

Wordcount program - Main

```
public class WordCount {  
  
    public static void main(String[] args) throws Exception {  
  
        Configuration conf = new Configuration();  
  
        Job job = Job.getInstance(conf, "word count");  
        job.setJarByClass(WordCount.class);  
        job.setMapperClass(TokenizerMapper.class);  
        job.setCombinerClass(IntSumReducer.class);  
        job.setReducerClass(IntSumReducer.class);  
        job.setOutputKeyClass(Text.class);  
        job.setOutputValueClass(IntWritable.class);  
  
        FileInputFormat.addInputPath(job, new Path(args[0]));  
        FileOutputFormat.setOutputPath(job, new Path(args[1]));  
        System.exit(job.waitForCompletion(true) ? 0 : 1);  
    }  
}
```

Wordcount program - Mapper

```
public static class TokenizerMapper extends Mapper<Object, Text, Text,
IntWritable>{
private final static IntWritable one = new IntWritable(1);
private Text word = new Text();

public void map(Object key, Text value, Context context )
throws IOException, InterruptedException {
    StringTokenizer itr = new StringTokenizer(value.toString());
    while (itr.hasMoreTokens()) {
        word.set(itr.nextToken()); context.write(word, one);
    }
}
}
```

Wordcount program - Reducer

```
public static class IntSumReducer extends
Reducer<Text,IntWritable,Text,IntWritable> {
private IntWritable result = new IntWritable();

public void reduce(Text key, Iterable<IntWritable> values, Context context
)
throws IOException, InterruptedException {
    int sum = 0;
    for (IntWritable val : values) {
        sum += val.get();
    }
    result.set(sum);
    context.write(key, result);
}
}
```


Wordcount program - running

```
export JAVA_HOME=[ Java home directory ]
```


```
bin/hadoop com.sun.tools.javac.Main WordCount.java
```

```
jar cf wc.jar WordCount*.class
```

```
bin/hadoop jar wc.jar WordCount [Input path] [Output path]
```

Hadoop(v2)

MR job



Wordcount in python

Mapper.py

```
#!/usr/bin/env python

import sys

# input comes from STDIN (standard input)
for line in sys.stdin:
    # remove leading and trailing whitespace
    line = line.strip()
    # split the line into words
    words = line.split()
    # increase counters
    for word in words:
        # write the results to STDOUT (standard output);
        # what we output here will be the input for the
        # Reduce step, i.e. the input for reducer.py
        #
        # tab-delimited; the trivial word count is 1
        print '%s\t%s' % (word, 1)
```

Wordcount in python

```
#!/usr/bin/env python
```

```
from operator import itemgetter
import sys
```

```
# maps words to their counts
word2count = {}
```

```
# input comes from STDIN
```

```
for line in sys.stdin:
    # remove leading and trailing whitespace
    line = line.strip()
```

```
    # parse the input we got from mapper.py
```

```
    word, count = line.split('\t', 1)
```

```
    # convert count (currently a string) to int
```

```
    try:
```

```
        count = int(count)
```

```
        word2count[word] = word2count.get(word, 0) + count
```

```
    except ValueError:
```

```
        # count was not a number, so silently
```

```
        # ignore/discard this line
```

```
    pass
```

```
# sort the words lexicographically;
```

```
#
```

```
# this step is NOT required, we just do it so that our
```

```
# final output will look more like the official Hadoop
```

```
# word count examples
```

```
sorted_word2count = sorted(word2count.items(), key=itemgetter(0))
```

```
# write the results to STDOUT (standard output)
```

```
for word, count in sorted_word2count:
```

```
    print '%s\t%s' % (word, count)
```

Reducer.py

Execution code

```
bin/hadoop dfs -ls
```

```
bin/hadoop dfs -copyFromLocal example example
```


```
bin/hadoop jar contrib/streaming/hadoop-0.19.2-streaming.jar -file  
wordcount-py.example/mapper.py -mapper wordcount-  
py.example/mapper.py -file wordcount-py.example/reducer.py -reducer  
wordcount-py.example/reducer.py -input example -output java-output
```

```
bin/hadoop dfs -cat java-output/part-00000
```


```
bin/hadoop dfs -copyToLocal java-output/part-00000 java-output-local
```

Hadoop(v2)


MR job




Map Reduce Data Flow




Data: Stream of keys and values



Hadoop MR Data Flow



Shuffle and sort




Source: Hadoop: The Definitive Guide

Data Flow

- **Input and final output are stored on a distributed file system (FS):**
 - Scheduler tries to schedule map tasks “close” to physical storage location of input data
- **Intermediate results are stored on local FS of Map workers.**
- **Output of Reduce workers are stored on a distributed file system.**
- **Output is often input to another MapReduce task**

Hadoop(v2) MR job



Source: Hadoop: The Definitive Guide

Fault tolerance

- ❑ Comes from scalability and cost effectiveness
- ❑ HDFS:
 - ❑ Replication
- ❑ Map Reduce
 - ❑ Restarting failed tasks: map and reduce
 - ❑ Writing map output to FS
 - ❑ Minimizes re-computation

Coordination: Master

- **Master node takes care of coordination:**
 - **Task status:** (idle, in-progress, completed)
 - **Idle tasks** get scheduled as workers become available
 - When a map task completes, it sends the master the location and sizes of its R intermediate files, one for each reducer
 - Master pushes this info to reducers
- Master pings workers periodically to detect failures

Failures

☐ Task failure

- ☐ Task has failed - report error to node manager, appmaster, client.
- ☐ Task not responsive, JVM failure - Node manager restarts tasks.

☐ Application Master failure

- ☐ Application master sends heartbeats to resource manager.
- ☐ If not received, the resource manager retrieves job history of the run tasks.

☐ Node manager failure

Dealing with Failures


- **Map worker failure**
 - Map tasks completed or in-progress at worker are reset to idle
 - Reduce workers are notified when task is rescheduled on another worker
- **Reduce worker failure**
 - Only in-progress tasks are reset to idle
 - Reduce task is restarted
- **Master failure**
 - MapReduce task is aborted and client is notified

How many Map and Reduce jobs?

- M map tasks, R reduce tasks
- **Rule of a thumb:**
 - Make M much larger than the number of nodes in the cluster
 - One DFS chunk per map is common
 - Improves dynamic load balancing and speeds up recovery from worker failures
- **Usually R is smaller than M**
 - Because output is spread across R files

Task Granularity & Pipelining

- **Fine granularity tasks:** map tasks \gg machines
 - Minimizes time for fault recovery
 - Can do pipeline shuffling with map execution
 - Better dynamic load balancing



Refinements: Backup Tasks

- **Problem**

- Slow workers significantly lengthen the job completion time:
 - Other jobs on the machine
 - Bad disks
 - Weird things

- **Solution**


- Near end of phase, spawn backup copies of tasks
 - Whichever one finishes first “wins”

- **Effect**

- Dramatically shortens job completion time


Refinement: Combiners

- Often a Map task will produce many pairs of the form (k, v_1) , (k, v_2) , ... for the same key k
 - E.g., popular words in the word count example
- Can save network time by **pre-aggregating values in the mapper**:
 - $\text{combine}(k, \text{list}(v_1)) \rightarrow v_2$
 - Combiner is usually same as the reduce function
- Works only if reduce function is commutative and associative



Refinement: Combiners

- Back to our word counting example:
 - Combiner combines the values of all keys of a single mapper (single machine):



- Much less data needs to be copied and shuffled!

Refinement: Partition Function

- **Want to control how keys get partitioned**
 - Inputs to map tasks are created by contiguous splits of input file
 - Reduce needs to ensure that records with the same intermediate key end up at the same worker
- **System uses a default partition function:**
 - **$\text{hash}(\text{key}) \bmod R$**
- **Sometimes useful to override the hash function:**
 - E.g., $\text{hash}(\text{hostname}(\text{URL})) \bmod R$ ensures URLs from a host end up in the same output file

References:

- Jure Leskovec, Anand Rajaraman, Jeff Ullman. **Mining of Massive Datasets. 2nd edition.** - *Cambridge University Press.*
<http://www.mmds.org/>
- Tom White. **Hadoop: The definitive Guide.** Oreilly Press.