


Distributed Artificial Intelligence and Intelligent Agents

Programming with JADE (2)

Autumn 2004

JADE message sending



Structure of a JADE Message

- **Performative** - FIPA message *type* (INFORM, QUERY, PROPOSE, ...)
- Addressing
 - **Receiver**
 - **Sender** (initialized automatically)
- **Content** - This is the main content of the message
- **ConversationID** - Used to link messages in same conversation
- **Language** - Specifies which language is used in the content
- **Ontology** - Specifies which ontology is used in the content
- **Protocol** - Specifies the protocol
- **ReplyWith** - Another field to help distinguish answers
- **InReplyTo** - Sender uses to help distinguish answers
- **ReplyBy** - Used to set a time limit on an answer

JADE provides get and set methods for accessing all attributes

Sending messages

```
ACLMessage msg = new ACLMessage(ACLMessage.INFORM) ;  
msg.addReceiver(new AID("Peter", AID.ISLOCALNAME)) ;  
msg.setLanguage("English") ;  
msg.setOntology("Weather-forecast-ontology") ;  
msg.setContent("Today it's raining") ;  
send(msg) ;
```

Book Buying

```
// Message carrying a request for offer
```

```
ACLMessage cfp = newACLMessage(ACLMessage.CFP) ;  
    for (int i = 0; i < sellerAgents.length; ++i) {  
        cfp.addReceiver(sellerAgents[i]) ;  
    }  
cfp.setContent(targetBookTitle) ;  
myAgent.send(cfp) ;
```

Catalogue of Communicative Acts

Communicative act	Information passing	Requesting information	Negotiation	Action performing	Error handling
Accept-proposal			✓		
Agree				✓	
Cancel				✓	
Cfp			✓		
Confirm	✓				
Disconfirm	✓				
Failure					✓
Inform	✓				
Inform-if (macro act)	✓				
Inform-ref (macro act)	✓				
Not-understood					✓
Propagate				✓	
Propose			✓		
Proxy				✓	
Query-if		✓			
Query-ref		✓			
Refuse				✓	
Reject-proposal			✓		
Request				✓	
Request-when				✓	
Request-whenever				✓	
Subscribe		✓			

Receiving messages

- Receive:

```
ACLMessage msg = receive();  
if (msg != null) {  
    // Process the message  
}
```

- Blocking receive

```
ACLMessage msg = blockingReceive();
```

By using **blockingReceive()**, the receiving agent suspends all its activities until a message arrives

Receiving messages behaviour

```
/** Inner class OfferRequestsServer. This is the behaviour used by Book-seller
agents to serve incoming requests for offer from buyer agents. If the
requested book is in the local catalogue the seller agent replies with a
PROPOSE message specifying the price. Otherwise a REFUSE message is sent
back.
*/
private class OfferRequestsServer extends CyclicBehaviour {
    public void action() {
        ACLMessage msg = myAgent.receive();
        if (msg != null) {
            // Message received. Process it
            String title = msg.getContent();
            ACLMessage reply = msg.createReply();
            Integer price = (Integer) catalogue.get(title);
            if (price != null) {
                // The requested book is available for sale. Reply with the price
                reply.setPerformative(ACLMessage.PROPOSE);
                reply.setContent(String.valueOf(price.intValue()));
            }
            else {
                // The requested book is NOT available for sale.
                reply.setPerformative(ACLMessage.REFUSE);
                reply.setContent("not-available");
            }
            myAgent.send(reply);
        }
    }
} // End of inner class OfferRequestsServer
```


Blocking behaviour

```
public void action() {  
    ACLMessage msg = myAgent.receive();  
    if (msg != null) {  
        // Message received. Process it  
        ...  
    }  
    else {  
        block();  
    }  
}
```

The above code is the typical (and strongly suggested) pattern for receiving messages inside a behaviour.

Message templates

```
public void action() {  
    MessageTemplate mt =  
        MessageTemplate.MatchPerformative(ACLMessage.CFP);  
    ACLMessage msg = myAgent.receive(mt);  
    if (msg != null) {  
        // CFP Message received. Process it  
        ...  
    }  
    else {  
        block();  
    }  
}
```

Conversations

```
/**
Inner class RequestPerformer. This is the behaviour used by Book-buyer agents to
request seller agents the target book.
*/
private class RequestPerformer extends Behaviour {
private AID bestSeller;           // The agent who provides the best offer
private int bestPrice;           // The best offered price
private int repliesCnt = 0;      // The counter of replies from seller agents
private MessageTemplate mt;      // The template to receive replies
private int step = 0;
public void action() {
    switch (step) {
    case 0:
        // Send the cfp to all sellers
        ACLMessage cfp = new ACLMessage(ACLMessage.CFP);
        for (int i = 0; i < sellerAgents.length; ++i) {
            cfp.addReceiver(sellerAgents[i]);
        }
        cfp.setContent(targetBookTitle);
        cfp.setConversationId("book-trade");
        cfp.setReplyWith("cfp"+System.currentTimeMillis()); // Unique value
        myAgent.send(cfp);
        // Prepare the template to get proposals
        mt=MessageTemplate.and(MessageTemplate.MatchConversationId("book-trade"),
            MessageTemplate.MatchInReplyTo(cfp.getReplyWith()));
        step = 1;
        break;
    }
```

Conversations (cntd.)

```
case 1:
    // Receive all proposals/refusals from seller agents
    ACLMessage reply = myAgent.receive(mt);
    if (reply != null) {
        // Reply received
        if (reply.getPerformative() == ACLMessage.PROPOSE) {
            // This is an offer
            int price =
                Integer.parseInt(reply.getContent());
            if (bestSeller == null || price < bestPrice) {
                // This is the best offer at present
                bestPrice = price;
                bestSeller = reply.getSender();
            }
        }
        repliesCnt++;
        if (repliesCnt >= sellerAgents.length) {
            // We received all replies
            step = 2;
        }
    }
    else {
        block();
    }
break;
```

Conversations (cntd.)

case 2:

```
// Send the purchase order to the seller that
// provided the best offer
ACLMessage order=new
    ACLMessage(ACLMessage.ACCEPT_PROPOSAL);
order.addReceiver(bestSeller);
order.setContent(targetBookTitle);
order.setConversationId("book-trade");
order.setReplyWith("order"+System.currentTimeMillis());
myAgent.send(order);
// Prepare the template to get the purchase order reply
mt = MessageTemplate.and(
    MessageTemplate.MatchConversationId("book-trade"),
    MessageTemplate.MatchInReplyTo(order.getReplyWith()));
step = 3;
break;
```

Conversations (cntd.)

```
case 3:
    // Receive the purchase order reply
    reply = myAgent.receive(mt);
    if (reply != null) {
        // Purchase order reply received
        if (reply.getPerformative() == ACLMessage.INFORM) {
            // Purchase successful. We can terminate
            System.out.println(targetBookTitle+
                               "successfully purchased.");
            System.out.println("Price = "+bestPrice);
            myAgent.doDelete();
        }
        step = 4;
    }
    else {
        block();
    }
    break;
}
}
public boolean done() {
    return ((step == 2 && bestSeller == null) || step == 4);
}
} // End of inner class RequestPerformer
```