# **VAST As-Built Report**



## **Customer Deployment Documentation**

Cluster: selab-var-204 PSNT: selab-var-204

**Release:** release-5.3.1-sp3-1898015 **Management IP:** 10.143.11.204

CBox Hardware: supermicro\_gen5\_cbox, two dual-port NICs

CBox Quantity: 3

DBox Hardware: ceres\_v2

DBox Quantity: 1

#### **Table of Contents**

- 1. Executive Summary
- 2. Cluster Information
- 3. Hardware Inventory
- 4. Network Configuration
- 5. Logical Configuration
- 6. Security & Authentication
- 7. Data Protection
- 8. Enhanced Features
- 9. Appendix

## **Executive Summary**

This VAST As-Built Report provides a comprehensive technical documentation of the deployed VAST Data cluster infrastructure, configuration, and operational status. The report serves as a critical reference for system administrators, storage engineers, and technical stakeholders to understand the current state of the cluster deployment, validate configuration compliance, and support ongoing operations and troubleshooting. The Executive Summary consolidates key operational metrics, hardware inventory, and cluster health indicators into high-level overview tables that enable rapid assessment of cluster status and capacity utilization.

#### **Cluster Overview**

Description	Value	
ID	1	
Name	selab-var-204	
Management VIP	10.143.11.204	
URL	https://10.143.11.204/api/v7/clusters/1	
Build	release-5.3.1-sp3-1898015	
PSNT	selab-var-204	
GUID	127db70c-0197-5f4f-8af8-44bead61cda2	
Uptime 9 days, 19:19:58.596558		
Online Since 2025-10-08T01:02:57.509200Z		
Deployed	2025-08-07T18:57:44.259621Z	

#### **Hardware Overview**

Description	Value
CBoxes	3
CNodes	3
DBoxes	1
DNodes	2
Switches	0
Leaf	0
Spine	0

#### **Cluster Information**

The Cluster Information section provides detailed operational status and configuration parameters for the VAST Data cluster. This section captures essential cluster metadata including cluster identification, operational state, management network configuration, and feature flags that define the cluster's capabilities and current operational mode. The information presented here is critical for understanding the cluster's current operational status, validating proper configuration, and supporting troubleshooting activities. This data is collected directly from the cluster's management API and represents the real-time operational state of the system.

#### Cluster Name: selab-var-204

Function	Status	
State	ONLINE	
SSD RAID State	HEALTHY	
NVRAM RAID State	HEALTHY	
Memory RAID State	HEALTHY	
Leader State	UP	
Leader CNode	cnode-3-11	
Management CNode	cnode-3-11	
Management Inner VIP	172.16.4.204	
Management Inner VIP CNode	cnode-3-10	
Enabled	Yes	
Similarity Enabled	No	
Deduplication Active	Unknown	
Write-Back RAID Enabled	Yes	
Write-Back RAID Layout	DATA_6_PARITY_2	
DBox HA Support	No	
Rack Level Resiliency	No	
Metrics Disabled	No	

## **Hardware Summary**

The Hardware Summary section provides comprehensive inventory and operational status of all physical hardware components within the VAST Data cluster. This section includes detailed information about storage capacity utilization, compute nodes (CNodes), data nodes (DNodes), and their respective hardware specifications, operational status, and physical rack positioning. The capacity metrics show both logical and physical storage utilization, enabling capacity planning and performance optimization. Hardware inventory data is essential for understanding cluster scale, identifying hardware failures, planning maintenance windows, and ensuring proper rack organization for optimal cooling and cable management.

### **Storage Capacity**

Metric	Value	
Usable Capacity	245 TB	
Free Usable Capacity	60 TB	
Data Reduction Ratio (DRR)	1.6:1	
Physical Space	310 TB	
Physical Space In Use	234 TB	
Free Physical Space	76 TB	
Physical Space In Use %	76%	
Logical Space	385 TB	
Logical Space In Use	293 TB	
Free Logical Space	93 TB	
Logical Space In Use %	76%	


#### **CBox Inventory (Compute)**

ID	Model	Name/Serial Number	Status	Position
1	supermicro_gen5_cbox, two dual-port NICs	cbox-S929986X5306437	ACTIVE	U23
3	supermicro_gen5_cbox, two dual-port NICs	cbox-S929986X5306720	ACTIVE	U24
4	supermicro_gen5_cbox, two dual-port NICs	cbox-S929986X5306758	ACTIVE	U25

#### **DBox Inventory (Data)**

ID Model		Name/SN	Status	Position
1	ceres_v2	dbox-515-25042300200055	ACTIVE	U18

Physical Rack Layout		



## **Network Configuration**

The Network Configuration section provides comprehensive documentation of all network-related settings and connectivity parameters for the VAST Data cluster. This section includes cluster-wide network configuration, individual node network settings for both compute nodes (CNodes) and data nodes (DNodes), and network service configurations such as DNS and NTP. The network configuration data is essential for understanding cluster connectivity, troubleshooting network issues, validating network security settings, and ensuring proper network segmentation. This information supports network administrators in maintaining optimal network performance and security posture for the storage infrastructure.

#### **Network Configuration**

Setting	Value
Management VIPs	10.143.11.204
External Gateways	10.143.254.254
DNS Servers	10.140.3.248
NTP Servers	10.140.0.17
External Netmask	255.255.0.0
Auto Ports Ext Interface	outband
Ethernet MTU	9000
InfiniBand MTU	65520
IPMI Gateway	10.143.254.254
IPMI Netmask	255.255.0.0
B2B IPMI	False

#### **CNode Network Configuration**

ID	Hostname	Mgmt IP	IPMI IP	VAST OS	VMS Host
8	se-az-arrow-cb4-cn-1	10.143.11.81	10.143.11.82	12.14.19-1809895	False
2	se-az-arrow-cb4-cn-2	10.143.11.83	10.143.11.84	12.14.15-1791040	True
1	se-az-arrow-cb4-cn-3	10.143.11.85	10.143.11.86	12.12.15-1440723	False

#### **DNode Network Configuration**

ID	Hostname	Mgmt IP	IPMI IP	VAST OS	Position
4	se-az-arrow-db4-dn-1	10.143.11.41	10.143.11.42	12.14.15-1791040	right
5	se-az-arrow-db4-dn-2	10.143.11.43	10.143.11.44	12.14.15-1791040	left

#### **Logical Configuration**

The Logical Configuration section documents the logical organization and data protection policies configured within the VAST Data cluster. This section provides visibility into tenant configurations, data views, access policies, VIP pools, and data protection settings including snapshot programs and protection policies. Understanding the logical configuration is crucial for data governance, access control validation, backup and recovery planning, and ensuring compliance with organizational data protection requirements. This information enables administrators to verify proper data isolation, validate backup schedules, and ensure that data protection policies align with business continuity objectives.

Resource	Value	
Tenants 23 tenants configured		
Views	330 views configured	
View Policies 126 policies configured		
VIP Pools 42 pools configured		
Data Protection Policies 26 policies configured		

#### **Security & Authentication**

The Security & Authentication section provides comprehensive documentation of all security-related configurations and authentication mechanisms implemented within the VAST Data cluster. This section covers authentication services including Active Directory, LDAP, and NIS integration, as well as security features such as data encryption settings, external key management (EKM) configuration, and security policy enforcement. Understanding the security configuration is essential for compliance auditing, security posture assessment, access control validation, and ensuring that the storage infrastructure meets organizational security requirements and industry best practices. This information supports security administrators in maintaining a robust security framework for the storage environment.

Туре	Description	Function	Value
Authentication	Active Directory	Enabled	True
Authentication	Active Directory	Domain	Unknown
Security	Encryption	Enabled	False
Security	Encryption	Туре	INTERNAL
Security	Encryption	S3 AES Ciphers Only	Not Configured
Security	EKM	Servers	Not Configured
Security	EKM	Address	Not Configured
Security	EKM	Port	5696
Security	EKM	Auth Domain	Not Configured
Security	Secondary EKM	Address	Not Configured
Security	Secondary EKM	Port	5696