


gt :: CHEAT SHEET




Introduction

The gt package allows you to make beautiful, informative table displays from R data frames. The package provides functions for you to **structure**, **format**, and **style** the table to your heart's content.

The resulting tables can be easily displayed in Shiny apps and Quarto documents. And there are quite a few output formats for your tables, including HTML, LaTeX, RTF, and Word.

INSTALLATION `install.packages("gt")`

Using Python? Try out Great Tables!



Adding Structure

ADDING A HEADER AND FOOTER

`tab_header()` → add title and optional subtitle, can use `md()` or `html()` helpers

`tab_source_note()` → add text to table footer (above helpers can be used here too)

`tab_footnote()` → add footnote to footer; needs a *location* (see *Styling...* for this)

ADDING A STUB AND ROW GROUPS

`gt(rownames_col = "column")` → assign a column with row names to the stub

`gt(groupname_col = "column")` → use column with categoricals to group rows

ADDING COLUMN SPANNERS

`tab_spanner()` → add spanner over cols

`tab_spanner_delim()` → use delimited column names to set up multiple spanners

ADDING ORDER

`row_order()` → order rows within groups by one or more columns, complements

`row_group_order()` → reorder groups


Styling the Table

ONE FUNCTION FOR STYLING EVERYWHERE

`tab_style()` → apply styles to various locations

```
gt_tbl |> tab_style(style = list(styles), locations = list(locations))
```

THE DIFFERENT LOCATIONS OF A TABLE



THREE WAYS TO STYLE

`cell_fill()` → fill location with color

`cell_text()` → style location's text

`cell_borders()` → set up borders and define styles for them

YOU ALSO HAVE OTHER OPTIONS

`tab_options()` → many, many options for styling that applies to whole table

`opt_stylize()` → set a theme, 36 looks

`opt_table_font()` → set a font to use

Creating a gt Table

BASIC EXAMPLE WITH SAMPLE DATA

```
library(gt)

gt_tbl = gt(exibble)
gt_tbl
```

create GT object

display HTML table

OUTPUT

column labels									
num	char	factor	date	time	datetime	currency	row	group	
1.111e+01	apricot	one	2016-01-16	13:36	2018-01-01 02:22	40.860	row_1	grp_a	
2.222e+00	banana	two	2015-02-15	14:40	2018-02-02 14:33	17.850	row_2	grp_a	
3.333e+01	coconut	three	2015-03-15	15:45	2018-03-03 03:44	1.250	row_3	grp_a	
4.444e+02	durian	four	2015-04-15	16:50	2018-04-04 15:55	85100.000	row_4	grp_a	
5.550e+03	NA	five	2015-05-15	17:55	2018-05-05 04:00	1325.810	row_5	grp_b	
NA	fig	six	2015-06-15	NA	2018-06-06 15:11	13.285	row_6	grp_b	
7.770e+05	grapefruit	seven	NA	19:10	2018-07-07 05:22	NA	row_7	grp_b	
8.880e+05	honeydew	eight	2015-08-15	20:20	NA	0.440	row_8	grp_b	

table body

SAMPLE DATASETS `countrypops`, `sza`, `gtcars`, `sp500`, `films`, `pizzaplace`, `exibble`, `towny`, `peeps` + more

Formatting Data Values

FORMATTING BASICS

Formatting functions have the columns and rows options to specify which body values should be formatted.

columns = E* rows = E*	columns = "C" rows = E*	columns = "C" rows = 1:2	columns = E* rows = 1:2
format all values	format all C values	format some C values	format rows of values

E* means everything()

NUMERIC FORMATTING

- `fmt_number()` → decimal values
- `fmt_integer()` → integer values
- `fmt_percent()` → percentage values
- `fmt_scientific()` → scientific notation
- `fmt_engineering()` → engineering notation
- `fmt_number_si()` → decimal values with SI prefixes (k, M, G, etc.)

common options: `decimals` in 1,3,4,5 for fixed # of decimals / `scale_by` in 1,2,4,5 to multiply number before formatting / accounting in 1,2,3 to display in that notation / suffixing in 1,2 to condense large numbers / `locale` in 1-5 to localize formatted values to language/region.

DATE/TIME FORMATTING

`fmt_date()` → format with a date style preset

iso: "2000-02-29" (the default)

wday_month_day_year: "Tuesday, February 29, 2000"

wd_m_day_year: "Tue, Feb 29, 2000"

wday_day_month_year: "Tuesday 29 February 2000"

month_day_year: "February 29, 2000"

`fmt_time()` → format with a time style preset

iso: "14:35:00" (the default)

h_m_s_p: "2:35:00 PM"

h_m_p: "2:35 PM"

`fmt_datetime()` → format with date/time style presets or with format option for more control

FORMATTING INVOLVING GRAPHICS

`fmt_image()` → insert images to cells with filenames; `path / file_pattern` help resolve

`fmt_icon()` → add icons to cells containing FontAwesome short icon names (e.g., "cat")

`fmt_flag()` → add flag icons to cells w/ 2- or 3-letter country codes (e.g., "LU" or "LUX")

common to all: cells may have multiple instances of replaceable text for these formatters, they must be comma-separated though.

COLORIZING BODY CELLS

`data_color()` → apply color to a series of cells according to their value

domain = NULL palette = "Reds"	domain = c(0, 9) palette = "Reds"	domain = c(0, 6) na_color = "blue"
coloring to range of data	setting a fixed range	setting colors for NA/OOB values

ADDING NANOPLOTS

`cols_nanoplot()` → convert series of values (strings w/ vals or a list column) to tiny interactive plots in a new column

vals	nanoplots
1 20 23 67 37 23 214 7 18	
2 2.3 6.8 9.2 2.4 2 3.5 12.1 5.3 5.5	