


Shiny : : CHEAT SHEET



Build an App

Shiny makes it easy to create truly reactive data & AI apps in pure Python



Supports output from many popular packages

Collect user input with `input_*()`

Reactively render a plot output (re-execute when relevant `input` changes)

```
# app.py
import matplotlib.pyplot as plt
import numpy as np
from shiny.express import (
    input, render, ui
)

ui.input_slider(
    "n", "Sample Size", 0, 1000, 50
)


@render.plot
def dist():
    x = np.random.randn(input.n())
    plt.hist(x, range=[-3, 3])
```

Reactively reads the slider's value

Save as **app.py**

Include supporting code, images, etc. in same directory.

Launch apps via the VSCode extension or with the **shiny run** CLI



Shiny apps easily scale in complexity and sophistication thanks to its reactivity model and other opinionated design choices.

☺ Build with AI assistance:

gallery.shinyapps.io/assistant

💡 Get inspiration & templates:

- Run **shiny create** in terminal
- shiny.posit.co/py/templates
- shiny.posit.co/py/gallery




Inputs

Collect values from the user.

Reactively read input values with `input.<id>()`



Action



`ui.input_action_button(`
 id, label, ...)

`ui.input_action_link(`
 id, label, ...)

`ui.input_task_button(`
 id, label, ...)

`ui.input_checkbox(`
 id, label, value, ...)

`ui.input_checkbox_group(`
 id, label, choices, selected, ...)

`ui.input_dark_mode(id, mode)`

`ui.input_date(`
 id, label, value, ...)

`ui.input_date_range(`
 id, label, start, end, ...)

`ui.input_file(id, label, ...)`

`ui.input_numeric(`
 id, label, value, ...)

`ui.input_radio_buttons(`
 id, label, choices, selected, ...)

`ui.input_select(`
 id, label, choices, selected, ...)

Also `ui.input_selectize()`

`ui.input_slider(`
 id, label, min, max, value, ...)

`ui.input_switch(`
 id, label, value, ...)

`ui.input_text(`
 id, label, value, ...)

Also `ui.input_text_area()`

Share

Share your app in three ways:

1. **Host it on Posit Connect Cloud**, a cloud-based service from Posit. To deploy Shiny apps:



Create a free or professional account at connect.posit.cloud



Publish from GitHub or from VS Code or Positron using the Posit Publisher extension

2. **Purchase Posit Connect**, a publishing platform for R and Python. posit.co/connect

3. **Use open source deployment options**

shiny.posit.co/py/docs/deploy.html

Shinylive

Shinylive apps use WebAssembly to run entirely in a browser—no need for a special server to run Python.



- Edit and/or host Shinylive apps at shinylive.io
- Create a Shinylive version of an app to deploy with `shinylive export myapp site` Then deploy to a hosting site like Github or Netlify
- Embed Shinylive apps in Quarto sites, blogs, etc.

```
---
filters:
  - shinylive
---
```

An embedded Shinylive app:

```
```{shinylive-python}
#| standalone: true
[App.py code here...]
```
```

To embed a Shinylive app in a Quarto doc, include the bold syntax.

Outputs

Decorate a function with `@render.*` to reactively render Python outputs

`@render.data_frame`

| Species | Island | Bill Length(mm) | Body Mass(g) |
|-------------|--------|-----------------|--------------|
| Chlorophaps | Island | 45.70 | 3400 |
| Chlorophaps | Island | 50.00 | 4000 |
| Chlorophaps | Island | 45.30 | 3400 |
| Chlorophaps | Island | 46.00 | 3700 |

`@render.code`

```
area  pct1  share  perm
1 4582 2794.95  3.9603228  6.3
2 1584 2592.95  2.1496228  3.4
3 1539 2728.95  2.1892228  3.4
4 1252 3005.72  3.1119228  5.5
```


`@render.download`

Download


`@render.altair`



`@render.bokeh`



`@render.plot`



`@render.text`

Current value: 30

`@render.ui`

Current value: 30

`@render.image`



And many more via the shinywidgets project

`@render.plotly`



`@render.widget`



Reactivity

Reactive values work together with reactive functions. A reactive value must be read from within a reactive functions to avoid the error **No current reactive context**

Module located at **shiny.reactive**

Create a reactive value from other (reactive) values. Helps avoid redundant logic and computation.

Create a reactive UI output.

Perform side effects like logging, updating a database, etc.

```
from shiny import reactive
from shiny.express import (
    input, render, ui
)

ui.input_text("text", "Enter text")

@reactive.calc
def length():
    return len(input.text())

@render.text
def length_output():
    return f"{length()} characters"

@reactive.effect
def length_log():
    print(f"{length()} characters")
```

Reactive functions re-execute when any of their reactive dependencies (i.e., values) change. However, sometimes you want to ignore all but one (i.e., event):


Don't execute until **input.submit** is truthy (i.e. button is clicked)

```
ui.input_text("name", "Enter name")
ui.input_action_button("submit", "Submit")

@render.text
@reactive.event(input.submit)
def greeting():
    return f"Hello {input.name()}!"

@reactive.effect
@reactive.event(input.submit)
def log_name():
    print(f"Name submitted {input.name()}")
```

A **reactive.value()** can be useful for programmatically setting/reading a reactive value. This is often useful when the value can't be derived from **input** values alone.



User Interfaces (UI)

Design delightful UI with a collection of layouts, components, themes, & more.

PAGE LAYOUTS


```
with ui.sidebar():
    Sidebar
with ui.nav_panel():
    Multi-page

ui.page_opts(
    fillable=True,
    full_width=True
)
Filling (vertical) layout
Full-width page
```

CARDS

Visually group UI elements together with the **card()** component.

```
with ui.card():
    ui.card_header("Title")
    @render.plot
    def plot():
        ...
```



UI LAYOUTS

Multiple columns

```
with ui.layout_columns()
    12-col grid
with ui.layout_column_wrap()
    Equal-width cols
with ui.layout_sidebar()
    Resizable 2-cols
```

Multiple panels

```
with ui.navset_card_underline():
    with ui.nav_panel("One"):
        "1st panel"
    with ui.nav_panel("Two"):
        "2nd panel"
    with ui.nav_menu("Menu"):
        with ui.nav_panel("3"):
            "3rd panel"
```

Navigate a set of **nav_panel()**s in various ways with **navset_card_***



ACCORDIONS

```
with ui.accordion():
    with ui.accordion_panel("One"):
        "1st panel"
    with ui.accordion_panel("Two"):
        "2nd panel"
    with ui.accordion_panel("Three"):
        "3rd panel"
```

Tip: place within **ui.sidebar()** to group similar inputs



TOOLTIPS & ICONS

```
from faicons import icon_svg

with ui.tooltip():
    icon_svg("info-circle")
    "Tooltip message"
```



VALUE BOXES

```
with ui.value_box(
    showcase=icon
):
    "Title"
    "Value"
```



Custom UI

Make the app behave and look exactly how you want it with web tooling and theming **UI as HTML**

Shiny UI is powered by HTML (plus JS/CSS):

```
ui.page_fluid(class = "pt-3")
#> <div class="container-fluid pt-3"></div>
```

- Create bespoke experiences with custom HTML (**ui.tags**) and CSS/JS snippets: **ui.include_css()** / **ui.include_js()**.
- Can also interface with popular frameworks like React, Vue, Svelte, etc.

LOCAL FILES

Statically serve any file (image, CSS, JS, etc) by placing them in **www/ dir** (next to **app.py**)




THEMES

Choose from set of pre-packaged themes via **shinyswatch** or

change main colors / fonts via **brand-ym**


```
color:
  foreground: '#222'
  background: white
  primary: purple
  typography:
    fonts:
      - family: Inter
        source: google
```



Gen AI

Build streaming Gen AI interfaces like chatbots and more with the **Chat** and **MarkdownStream** components.

Use **Chat** to implement a streaming chat interface. Provide a callback to generate a response to **user_input** using an AI framework of your choice (e.g., chatlas, LangChain, etc).



```
from chatlas import ChatOpenAI
from shiny.express import ui

chat_client = ChatOpenAI()
chat = ui.Chat("chat")
chat.ui(
    messages=["**Hi!** How can I help?"]
)

@chat.on_user_submit
async def _(user_input: str):
    x = await chat_client.stream_async(
        user_input
    )
    await chat.append_message_stream(x)
```

Express / Core

- An **app.py** that imports from **shiny.express** uses 'Express mode' to make development faster.
- Express extends "Core" Shiny to make UI and server logic one in the same.
- Core may be more suitable for sophisticated apps where a decoupling of UI and server is beneficial.

```
import matplotlib.pyplot as plt
import numpy as np
from shiny import App, ui

app_ui = ui.page_fixed(
    ui.input_slider(
        "n", "Sample Size", 0, 100, 50
    )
)

def server(input):
    @render.plot
    def dist():
        x = np.random.randn(input.n())
        plt.hist(x, range=[-3, 3])

app = App(app_ui, server)
```