NETSTAT - CAPT ARUN PUNDIR

```
┌──(arun㉿kali)-[~]
└─$ ip route
default via 192.168.1.1 dev eth0 proto dhcp src 192.168.1.40 metric 100
192.168.1.0/24 dev eth0 proto kernel scope link src 192.168.1.40 metric 100

┌──(arun㉿kali)-[~]
└─$ netstat -rn
Kernel IP routing table
Destination     Gateway         Genmask         Flags   MSS Window  irt Iface
0.0.0.0         192.168.1.1     0.0.0.0         UG        0 0          0 eth0
192.168.1.0     0.0.0.0         255.255.255.0   U         0 0          0 eth0

┌──(arun㉿kali)-[~]
└─$
```

```
┌──(arun㉿kali)-[~]
└─$ netstat -ano
Active Internet connections (servers and established)
Proto Recv-Q Send-Q Local Address           Foreign Address         State       Timer
tcp        0      0 0.0.0.0:23              0.0.0.0:*               LISTEN      off (0.00/0/0)
tcp        0      0 0.0.0.0:22              0.0.0.0:*               LISTEN      off (0.00/0/0)
tcp        0      0 127.0.0.1:3306          0.0.0.0:*               LISTEN      off (0.00/0/0)
tcp        0      0 192.168.1.40:55368      34.107.243.93:443       TIME_WAIT   timewait (27.66/0/0)
tcp        0      0 192.168.1.40:55382      34.107.243.93:443       TIME_WAIT   timewait (27.66/0/0)
tcp6       0      0 :::23                   :::*                    LISTEN      off (0.00/0/0)
tcp6       0      0 :::22                   :::*                    LISTEN      off (0.00/0/0)
tcp6       0      0 :::21                   :::*                    LISTEN      off (0.00/0/0)
tcp6       0      0 :::80                   :::*                    LISTEN      off (0.00/0/0)
tcp6       0      0 127.0.0.1:80            127.0.0.1:58424         TIME_WAIT   timewait (2.32/0/0)
udp        0      0 192.168.1.40:68         192.168.1.1:67          ESTABLISHED off (0.00/0/0)
udp6       0      0 fe80::918:329d:a5e6:546 :::*                                off (0.00/0/0)
raw6       0      0 :::58                   :::*                    7           off (0.00/0/0)
Active UNIX domain sockets (servers and established)
Proto RefCnt Flags       Type       State         I-Node   Path
unix  3      [ ]         STREAM     CONNECTED     12353
unix  3      [ ]         STREAM     CONNECTED     17947
unix  3      [ ]         STREAM     CONNECTED     15731    /run/user/1000/at-spi/bus_0
unix  3      [ ]         STREAM     CONNECTED     13757
unix  3      [ ]         STREAM     CONNECTED     15995
unix  3      [ ]         STREAM     CONNECTED     17916
```

```
┌──(arun㉿kali)-[~]
└─$ netstat -ant | grep ESTABLISHED
tcp        0      0 192.168.1.40:49770      34.107.243.93:443       ESTABLISHED

┌──(arun㉿kali)-[~]
└─$
```

```
┌──(arun㉿kali)-[~]
└─$ netstat -tulpn
(Not all processes could be identified, non-owned process info
 will not be shown, you would have to be root to see it all.)
Active Internet connections (only servers)
Proto Recv-Q Send-Q Local Address           Foreign Address         State       PID/Program name
tcp        0      0 0.0.0.0:23              0.0.0.0:*               LISTEN      -
tcp        0      0 0.0.0.0:22              0.0.0.0:*               LISTEN      -
tcp        0      0 127.0.0.1:3306          0.0.0.0:*               LISTEN      -
tcp6       0      0 :::23                   :::*                    LISTEN      -
tcp6       0      0 :::22                   :::*                    LISTEN      -
tcp6       0      0 :::21                   :::*                    LISTEN      -
tcp6       0      0 :::80                   :::*                    LISTEN      -
udp6       0      0 fe80::918:329d:a5e6:546 :::*                                -
```

```
┌──(arun㉿kali)-[~]
└─$ netstat -rn
Kernel IP routing table
Destination     Gateway         Genmask         Flags   MSS Window  irtt Iface
0.0.0.0         192.168.1.1     0.0.0.0         UG        0 0          0 eth0
192.168.1.0     0.0.0.0         255.255.255.0   U         0 0          0 eth0
```

```
┌──(arun㉿kali)-[~]
└─$ netstat -ano
Active Internet connections (servers and established)
Proto Recv-Q Send-Q Local Address           Foreign Address         State       Timer
tcp        0      0 0.0.0.0:23              0.0.0.0:*               LISTEN      off (0.00/0/0)
tcp        0      0 0.0.0.0:22              0.0.0.0:*               LISTEN      off (0.00/0/0)
tcp        0      0 127.0.0.1:3306          0.0.0.0:*               LISTEN      off (0.00/0/0)
tcp        0      0 192.168.1.40:49770      34.107.243.93:443       ESTABLISHED keepalive (5.98/0/0)
tcp6       0      0 :::23                   :::*                    LISTEN      off (0.00/0/0)
tcp6       0      0 :::22                   :::*                    LISTEN      off (0.00/0/0)
tcp6       0      0 :::21                   :::*                    LISTEN      off (0.00/0/0)
tcp6       0      0 :::80                   :::*                    LISTEN      off (0.00/0/0)
udp        0      0 192.168.1.40:68         192.168.1.1:67          ESTABLISHED off (0.00/0/0)
udp6       0      0 fe80::918:329d:a5e6:546 :::*                                off (0.00/0/0)
raw6       0      0 :::58                   :::*                    7           off (0.00/0/0)
Active UNIX domain sockets (servers and established)
Proto RefCnt Flags       Type       State         I-Node   Path
unix  3      [ ]         SEQPACKET  CONNECTED     18778
unix  3      [ ]         STREAM     CONNECTED     12353
unix  3      [ ]         STREAM     CONNECTED     17947
unix  3      [ ]         STREAM     CONNECTED     15731    /run/user/1000/at-spi/bus_0
unix  3      [ ]         STREAM     CONNECTED     13757
unix  3      [ ]         STREAM     CONNECTED     15995
```

Recommend containment steps

1. Isolate the System (Immediate Priority)
   - Disconnect from network:
     - Windows: Disable adapter
     - netsh interface set interface "Ethernet" admin=disable
     - Linux:
     - ifconfig eth0 down
   - If in enterprise → move system to quarantine VLAN
2. Kill Suspicious Processes
   - Identify using:
   - netstat -ano (Windows)
   - netstat -tulpn (Linux)

- Then terminate:
    - Windows:
    - taskkill /PID <pid> /F
    - Linux:
    - kill -9 <pid>

3. Block Malicious IPs

- If suspicious foreign IP found:
    - Windows Firewall:
    - netsh advfirewall firewall add rule name="Block IP" dir=out action=block remoteip=<IP>
    - Linux (iptables):
    - iptables -A OUTPUT -d <IP> -j DROP

4. Disable Compromised Accounts

- If attack involves login/session abuse:
    - Disable user:
    - net user username /active:no (Windows)
    - passwd -l username (Linux)

5. Preserve Evidence (Very Important)

- Before deep cleanup:
    - Save outputs:

    - netstat -ano > netstat_log.txt
    - tasklist > processes.txt
    - Collect:
        - Logs (Event Viewer / syslog)
        - Memory dump (if advanced lab)

6. Stop Malicious Services / Ports

- If unknown service listening:
    - Disable service:
    - sc stop <service_name> (Windows)
    - systemctl stop <service> (Linux)
- Close unnecessary open ports via firewall

7. Patch & Remove Persistence

- Check:
    - Startup programs
    - Scheduled tasks
    - Registry (Windows)
- Remove backdoors:
    - Reverse shells
    - Cron jobs (Linux)

8. Run Security Tools

- Antivirus / EDR scan
- Tools:

    - Windows Defender
    - ClamAV (Linux)
    - Sysinternals (Autoruns, Process Explorer)

9. Reset Network Configuration

- If routing/DNS tampered:
- ipconfig /flushdns
- ipconfig /release
- ipconfig /renew

10. Change Credentials

- Change:
    - System passwords
    - SSH keys
    - Admin credentials