Netstat comds

```
zsh: corrupt history file /home/kali/.zsh_history
┌──(kali㉿kali)-[~]
└─$ sudo nano /etc/suricata/suricata.yaml
[sudo] password for kali:

┌──(kali㉿kali)-[~]
└─$ sudo suricata -c /etc/suricata/suricata.yaml -i eth0
i: suricata: This is Suricata version 8.0.4 RELEASE running in SYSTEM mode
i: threads: Threads created -> W: 2 FM: 1 FR: 1   Engine started.
```

kali@kali: ~

Text Editor
Simple Text Editor

Help

GNU nano 8.7.1 /etc/suricata/local.rules

```
# Rule 1 – ICMP Recon (detect pings only)
alert icmp any any → any any (msg:"ICMP Ping Detected"; itype:8; sid:1000001; rev:2;)

# Rule 2 – Nmap SYN Scan Detection
alert tcp any any → any any (flags:S,12; threshold:type threshold, track by_src, count 10, seconds 5; msg:"Possible Nmap SYN Scan"; sid:1000002; rev:2;)

# Rule 3 – Telnet Usage
alert tcp any any → any 23 (msg:"Telnet Traffic Detected"; sid:1000003; rev:1;)

# Rule 4 – FTP Credential Exposure
alert tcp any any → any 21 (content:"USER"; nocase; msg:"FTP USER Command Detected"; sid:1000004; rev:1;)
alert tcp any any → any 21 (content:"PASS"; nocase; msg:"FTP PASS Command Detected"; sid:1000005; rev:1;)

# Rule 5 – Multiple Port Hits (port scan)
alert tcp any any → any any (flags:S,12; threshold:type threshold, track by_src, count 5, seconds 10; msg:"Port Scan Detected"; sid:1000006; rev:2;)
```

Suricata rules file

[Read 15 lines]

^G Help	^O Write Out	^F Where Is	^K Cut	^T Execute	^C Location	M-U Undo	M-A Set Mark	M-] To Bracket	M-B Previous	◀ Back	^◀ Prev Word	^A Home
^X Exit	^R Read File	^\ Replace	^U Paste	^J Justify	^/ Go To Line	M-E Redo	M-6 Copy	^B Where Was	M-F Next	▶ Forward	^▶ Next Word	^E End