

Continuous-Variable Kinematic Computing: A Hydrodynamic Architecture

Author: Ivaylo Anastasov

ORCID: 0009-0004-9628-7057

Project Website: rakts-research.org

Repository: github.com/rt20bg/Anastasov_Theory

(Dated: June 2026)

Abstract

This paper presents a conceptual framework for continuous-variable analog computation based on the hydrodynamic principles of the **Rapid Alignment Kinematic Theory of Spin (RAKTS)**. We propose that information can be represented as geometric vectors evolving under the influence of a background field and nonlinear drag within a simulated medium. A universal Kinematic NAND gate is realized through background bias, and higher-order logic circuits (such as Half-Adders) are constructed via instantaneous logical composition rather than repeated physical simulation. Numerical experiments, including parallel multi-core robustness tests under thermal noise, demonstrate the stability of the proposed logical primitives. The work explores the potential of treating environmental interaction—typically modeled as destructive quantum decoherence—as a stabilizing computational resource.

1 Introduction: The Complementary Paradigm

Modern computing has primarily relied on discrete-state representations, whether through classical binary transistors (0 and 1) or the probabilistic superposition of qubits ($|0\rangle + |1\rangle$). While these approaches have achieved remarkable success, they face fundamental physical limitations. In discrete-state quantum computing, environmental decoherence remains a profound obstacle to scalability, requiring extreme cryogenic cooling and heavy error-correction overhead.

This work explores a complementary paradigm inspired by RAKTS, wherein information is encoded in continuous geometric states rather than discrete or probabilistic ones. Drawing inspiration from fluid dynamics and dissipative systems, we investigate whether environmental interactions can be harnessed as a stabilizing mechanism. The proposed model treats computation as the deterministic evolution of vector quantities under hydrodynamic-like forces, offering a noise-tolerant approach to logical operations.

2 RAKTS Vector Nodes vs. Qubits

In contrast to standard quantum qubits, which encode information in mathematical superpositions of orthogonal states, the fundamental unit of information in this framework is the **RAKTS Vector Node**.

A Vector Node stores data as a physical, continuous three-dimensional orientation interacting with a background stress-tensor field. Rather than existing as a probabilistic wave-function, the node behaves as a localized hydrodynamic singularity—a structured angular momentum vector within the Field Medium. Its state is strictly deterministic and defined by continuous real-space geometry rather than complex probability amplitudes.

Logic operations emerge from the physical tendency of this vector to align with the net force acting upon it. Rather than applying unitary matrix transformations (as in standard quantum logic gates), computation occurs through the induction of localized field gradients. When an input alters the local pressure of the medium, the Vector Node experiences a continuous kinematic torque. This torque forces the node to physically rotate and align with the new lowest-energy configuration of the field. Consequently, this model replaces the instantaneous discrete measurement collapse of quantum systems with a continuous, fluid-dynamic topological relaxation toward attractor states.

3 The Hydrodynamic Advantage: Noise as a Stabilizer

A central challenge in contemporary quantum computing is the loss of coherence due to thermal and electromagnetic interaction with the environment. In the RAKTS Kinematic Computing model, this interaction is reinterpreted fundamentally.

The nonlinear Landau-Lifshitz hydrodynamic drag acting on the vector nodes functions analogously to viscous dissipation in fluids. Instead of destroying computational states, this drag drives the system toward stable geometric configurations that correspond to logical outcomes. When an impulse is applied, the inherent viscosity acts as a geometric funnel, forcing the system to settle robustly. This perspective suggests that controlled dissipation can serve a constructive role, guiding the system toward correct macroscopic results without requiring extensive error correction, offering a potential pathway toward room-temperature topological processors.

4 Topological Pathfinding and Logic

Because the evolution of Vector Nodes follows continuous dynamics governed by force balance and dissipation, the framework naturally lends itself to problems with topological character. By structuring a computational problem (such as a maze or a database search) as a physical geometry of varied resistances within the Field Medium, an input excitation can traverse the entire grid simultaneously.

Unlike a classical algorithm that must iterate through possibilities sequentially, the Field Medium behaves analogously to a fluid under pressure. When an excitation wave is introduced, it branches outward, exploring all available topological pathways in parallel. Because the medium is viscous, pathways leading to "dead ends" rapidly build up internal back-pressure and halt flow. Conversely, the continuous path connecting the input to the

target output establishes a stable pressure gradient, allowing the flow to accelerate along the path of least resistance.

The system evolves according to the Principle of Least Action (Hamilton's Principle), allowing the fluid dynamics to deterministically and instantaneously locate the optimal route. This physical, parallel exploration mathematically mirrors the quadratic speedup of Grover's search algorithm in quantum mechanics and the processes of ground-state energy minimization in quantum annealing. However, Kinematic Computing achieves this result purely through macroscopic fluidic gradients, bypassing the need for fragile probabilistic superposition and subsequent measurement collapse.

5 Turing Completeness via Background Bias (The NAND Gate)

To establish computational universality, a universally programmable logic gate must be constructed. In standard computing, this requires transistors. In Kinematic Computing, universality is achieved intrinsically by introducing a constant **Background Field Bias**.

This weak background flow acts as a default logical state ("True" or "1"), functioning as an analog Inverter (NOT gate). When sufficiently strong opposing input vectors are introduced, their combined force overcomes the background bias, physically driving the local flow to a "False" or "0" state. This fluid-dynamic competition elegantly produces a perfect **Kinematic NAND Gate**. Since NAND is functionally complete, arbitrary Boolean circuits and algorithms can in principle be constructed within the same physical framework.




Figure 1: Simulation of a Universal Kinematic NAND Gate. Input impulses overcome the background field bias via hydrodynamic drag only when both A and B are active, deterministically flipping the output state from True to False without quantum superposition.

6 Logic Composition and Circuit Simulation

Solving the full set of differential equations (ODEs) for every gate in a complex circuit would be computationally prohibitive. A more efficient, hybrid methodology separates the physical simulation from logical derivation.

Only the four fundamental input combinations of the NAND gate require numerical integration of the governing ODEs. Once the steady-state vector configurations for these base cases are obtained physically, all other logical operations—including NOT, AND, OR, NOR, and XOR—are constructed through direct logical composition. Elementary arithmetic units, such as the Half-Adder, can likewise be assembled without additional physical simulation. This hybrid approach significantly accelerates simulation time while preserving the physical grounding of the core primitive.

7 Numerical Validation and Parallel Robustness Analysis

To assess the practical behavior of the proposed gates, extensive numerical experiments were performed using a parallel multi-core simulation framework (utilizing `joblib` for high-throughput execution). These included systematic parameter sweeps over background field strength and statistical robustness tests in which continuous Gaussian noise (simulating thermal fluctuations) was injected into the driving forces.

The results indicate that the Kinematic NAND gate maintains correct logical output across a substantial operational envelope. While initial simulations did not quantify absolute Signal-to-Noise Ratio (SNR) benchmarks, they confirmed a distinct critical threshold: below this threshold, the hydrodynamic drag consistently absorbs stochastic variations and drives the output vector toward the correct logical attractor. Above this noise threshold, logical fidelity degrades predictably as the kinetic energy of the noise overcomes the background bias.

These findings empirically support the hypothesis that dissipation acts as a stabilizing force in continuous computational models. Rather than requiring active quantum error correction protocols to detect and fix individual bit-flips, the physics of the Field Medium naturally suppresses moderate deviations, reducing the overall error-correction burden.

8 Discussion: Engineering Challenges

While the framework presents a robust conceptual alternative to classical digital and discrete quantum computing models, several important questions remain open. The most significant is the physical realization of the required background field and macroscopic hydrodynamic drag at scale.

While the numerical ODE models demonstrate clear logical functionality, mapping these continuous dynamics onto real physical hardware constitutes a substantial engineering challenge. Several candidate substrates merit future investigation:

- **Microfluidic Logic:** Utilizing highly viscous non-Newtonian fluids in nanoscale channels to physically manifest the required drag and background flow.

- **Magnonics and Spin-Ice:** Using spin-wave propagating materials where magnetic domain walls act as continuous vector nodes, subject to lattice friction (analogous to the Landau-Lifshitz damping parameter).
- **Optical Metamaterials:** Employing non-linear optical cavities where photon fluid dynamics mimic the required stress-tensor gradients.

Future work must bridge the gap between topological simulation and physical fabrication, determining which of these substrates can maintain the required energy efficiency while providing the necessary dissipative attractors.

9 Industrial Consequences

The realization of a Continuous-Variable Kinematic Computer carries profound implications for the future of computational hardware and cryptography. By leveraging environmental interaction rather than fighting it, processors can theoretically achieve quantum-like algorithmic advantages—such as dynamic topological cryptography and parallel database searching—without extreme cryogenic constraints. This approach could fundamentally shift the industry away from error-prone discrete qubits toward resilient, macroscopic analog hardware.

10 Conclusion

This work outlines a hydrodynamic approach to computation in which logical operations emerge from the relaxation of vector nodes under background bias. By combining targeted physical simulation with logical composition, the framework achieves both functional completeness and computational efficiency. The model provides a coherent, mathematically grounded basis for exploring noise-tolerant, room-temperature analog computation, establishing a new theoretical path for the next generation of hardware accelerators.

Keywords: analog computing, RAKTS, hydrodynamic computation, continuous logic, kinematic computing, background bias, dissipative systems, topological cryptography

References

- [1] Anastasov, I. *The Rapid Alignment Kinematic Theory of Spin (RAKTS)*. Zenodo (2026). DOI: 10.5281/zenodo.20531698