

Detecting Routines in Ride-sharing: Implications For Customer Management

Ryan Dew, Eva Ascarza, Oded Netzer, Nachum Sicherman

Routine: behavior with a defined, recurring, temporal structure, such that the same behavior occurs at roughly the same time, period after period

Routine: behavior with a defined, recurring, temporal structure, such that the same behavior occurs at roughly the same time, period after period



Routine: behavior with a defined, recurring, temporal structure, such that the same behavior occurs at roughly the same time, period after period



Routine: behavior with a defined, recurring, temporal structure, such that the same behavior occurs at roughly the same time, period after period



Routine: behavior with a defined, recurring, temporal structure, such that the same behavior occurs at roughly the same time, period after period

Yet, there are **no existing models** for identifying routines from transaction data!



Routines, Habits, and CRM

Behavioral Research

- Long history of research on habits, dating back to [James \(1890\)](#)
- *Habit*: Tendency to repeat behaviors without conscious thought ([Wood et al., 2002](#))
- Habits are a primary driver of unsustainable transportation choices ([White et al., 2019](#))
- Habit discontinuity: context changes can disrupt habits, and lead to deliberate consideration ([Verplanken et al., 2008](#))

Routines, Habits, and CRM

Behavioral Research

- Long history of research on habits, dating back to [James \(1890\)](#)
- *Habit*: Tendency to repeat behaviors without conscious thought ([Wood et al., 2002](#))
- Habits are a primary driver of unsustainable transportation choices ([White et al., 2019](#))
- Habit discontinuity: context changes can disrupt habits, and lead to deliberate consideration ([Verplanken et al., 2008](#))

Habits and CRM

- “Repeat buying habit”: repeat brand purchases ([Ehrenberg & Goodhardt, 1968](#))
- [Shah et al. \(2014\)](#): CRM with recurring behaviors like returns, purchasing on promotion, or purchasing low margin items
- “Habit stock” used to model smooth consumption over time ([Dynan 2000](#))
- Customers who continue to transact out of habit may be negatively affected by outreach ([Ascarza et al., 2016](#))
- Beyond RFM: clumpiness ([Zhang et al., 2015](#)), regularity ([Platzer & Reutterer, 2016](#))

**Why might
routines matter?**

Why might routines matter?

1. Greater share of routine means an increase in *overall usage*

Why might routines matter?

1. Greater share of routine means an increase in *overall usage*
2. Spillover effects: the more a company features in a customer's routine, the more it will be *top-of-mind* outside of the routine

Why might routines matter?

1. Greater share of routine means an increase in *overall usage*
2. Spillover effects: the more a company features in a customer's routine, the more it will be *top-of-mind* outside of the routine
3. Segmentation and targeting based on *types of routines*

Why might routines matter?

1. Greater share of routine means an increase in *overall usage*
2. Spillover effects: the more a company features in a customer's routine, the more it will be *top-of-mind* outside of the routine
3. Segmentation and targeting based on *types of routines*
4. Long-run customer value: routine users have a *higher lifetime value*

Why might routines matter?

1. Greater share of routine means an increase in *overall usage*
2. Spillover effects: the more a company features in a customer's routine, the more it will be *top-of-mind* outside of the routine
3. Segmentation and targeting based on *types of routines*
4. Long-run customer value: routine users have a *higher lifetime value*

This Project

1. Develop a novel, all-purpose model for identifying individual-level routines
2. Apply our model to a unique ride-sharing data set
3. Show that customers with a high level of routine usage **churn less**, and **spend more** in the long run
4. Explore how temporal routineness predicts and moderates other important customer outcomes, over and above: mere habit, routines in terms of “what,” and other regularity metrics

This Project

1. Develop a novel, all-purpose model for identifying individual-level routines
2. Apply our model to a unique ride-sharing data set
3. Show that customers with a high level of routine usage **churn less**, and **spend more** in the long run
4. Explore how temporal routineness predicts and moderates other important customer outcomes, over and above: mere habit, routines in terms of “what,” and other regularity metrics


In short: we show the “shape” of customers’ interactions matters!

Model

A Statistical Framework for Measuring Routineness


Model of Usage

From transaction data, we want to capture...



Model of Usage


From transaction data, we want to capture...



Big question: How much of a person's activity is part of a routine?

Model of Usage

From transaction data, we want to capture...



Big question: How much of a person's activity is part of a routine?

Dependent variable: Usage (y)

Customer i , Week w , Day d , Hour h

Time $t = (w, d, h)$, Day-hour $j = (d, h)$

$$y_{it} \sim \text{Poisson}(\lambda_{it})$$

$$\lambda_{it} = \underbrace{\exp(\alpha_{iw} + \mu_j)}_{\text{Random usage}} + \underbrace{\exp(\gamma_{iw} + \eta_{ij})}_{\text{Routine usage}}$$

Random usage **Routine usage**

- α_{iw} and γ_{iw} – Individual- and week-specific scaling terms
- μ_j – Common day-hour rate
- η_{ij} – Individual-specific day-hour rate

These random and routine usage terms give us a **structured decomposition** of overall usage.

Model-based Decomposition


$$y_{it} \sim \text{Poisson}(\lambda_{it})$$

$$\lambda_{it} = \underbrace{\exp(\alpha_{iw} + \mu_j)}_{\text{Random usage}} + \underbrace{\exp(\gamma_{iw} + \eta_{ij})}_{\text{Routine usage}}$$

Model-based Decomposition

$$y_{it} \sim \text{Poisson}(\lambda_{it})$$


$$\lambda_{it} = \underbrace{\exp(\alpha_{iw} + \mu_j)}_{\text{Random usage}} + \underbrace{\exp(\gamma_{iw} + \eta_{ij})}_{\text{Routine usage}}$$



Requests follow an individual-level
inhomogeneous Poisson point process

Model-based Decomposition

$$y_{it} \sim \text{Poisson}(\lambda_{it})$$
$$\lambda_{it} = \underbrace{\exp(\alpha_{iw} + \mu_j)}_{\text{Random usage}} + \underbrace{\exp(\gamma_{iw} + \eta_{ij})}_{\text{Routine usage}}$$



Requests follow an individual-level
inhomogeneous Poisson point process

Superposition of point processes:
If $Y_A \sim \text{PP}(\lambda_A)$ and $Y_B \sim \text{PP}(\lambda_B)$,
then $Y_A + Y_B \sim \text{PP}(\lambda_A + \lambda_B)$.

Random requests:

$$E_{iw}^{\text{Random}} = \sum_j \exp(\alpha_{iw} + \mu_j)$$

Routine requests:

$$E_{iw}^{\text{Routine}} = \sum_j \exp(\gamma_{iw} + \eta_{ij})$$

Model-based Decomposition

$$y_{it} \sim \text{Poisson}(\lambda_{it})$$
$$\lambda_{it} = \underbrace{\exp(\alpha_{iw} + \mu_j)}_{\text{Random usage}} + \underbrace{\exp(\gamma_{iw} + \eta_{ij})}_{\text{Routine usage}}$$



Requests follow an individual-level
inhomogeneous Poisson point process

Superposition of point processes:
If $Y_A \sim \text{PP}(\lambda_A)$ and $Y_B \sim \text{PP}(\lambda_B)$,
then $Y_A + Y_B \sim \text{PP}(\lambda_A + \lambda_B)$.

Random requests:

$$E_{iw}^{\text{Random}} = \sum_j \exp(\alpha_{iw} + \mu_j)$$

Routine requests:

$$E_{iw}^{\text{Routine}} = \sum_j \exp(\gamma_{iw} + \eta_{ij})$$

“Routineness”

How do we specify those intensity functions?

$$\lambda_{it} = \exp(\alpha_{iw} + \mu_j) + \exp(\gamma_{iw} + \eta_{ij})$$

How do we specify those intensity functions?

$$\lambda_{it} = \exp(\alpha_{iw} + \mu_j) + \exp(\gamma_{iw} + \eta_{ij})$$

Scaling terms for weekly variation:

$$\alpha_{iw} \sim \mathcal{N}(\alpha_{iw-1}, \tau)$$

$$\gamma_i(w) \sim \mathcal{GP}(\gamma_0, k_{\text{SE}}(w, w'; \phi_\gamma))$$

How do we specify those intensity functions?

$$\lambda_{it} = \exp(\alpha_{iw} + \mu_j) + \exp(\gamma_{iw} + \eta_{ij})$$

Scaling terms for weekly variation:

$$\alpha_{iw} \sim \mathcal{N}(\alpha_{iw-1}, \tau)$$

$$\gamma_i(w) \sim \mathcal{GP}(\gamma_0, k_{\text{SE}}(w, w'; \phi_\gamma))$$


 Gaussian process: a
Bayesian nonparametric prior
over a function space

Interlude: Gaussian processes


$$f(x) \sim \mathcal{GP}(m(x), k(x, x'))$$

Interlude: Gaussian processes


$$f(x) \sim \mathcal{GP}(m(x), k(x, x'))$$

Mean function  Covariance function
"Kernel" 

Interlude: Gaussian processes



Interlude: Gaussian processes



$$k_{\text{SE}}(x, x') = \sigma^2 \exp \left[-\frac{(x - x')^2}{2\rho^2} \right]$$

Interlude: Gaussian processes

$$f(x) \sim \mathcal{GP}(m(x), k(x, x'))$$

Mean function Covariance function
"Kernel"

$$f(x_1, \dots, x_N) \sim \mathcal{N}(m(x_1, \dots, x_N), K), \text{ s.t. } K_{ij} = k(x_i, x_j)$$

↑
↔
↓

$$k_{\text{SE}}(x, x') = \boxed{\sigma^2} \exp \left[-\frac{(x - x')^2}{2\rho^2} \right]$$

Amplitude
Lengthscale

Interlude: Gaussian processes


$$f(x) \sim \mathcal{GP}(m(x), k(x, x'))$$

Mean function Covariance function
"Kernel"

$$f(x_1, \dots, x_N) \sim \mathcal{N}(m(x_1, \dots, x_N), K), \text{ s.t. } K_{ij} = k(x_i, x_j)$$

$$k_{\text{SE}}(x, x') = \boxed{\sigma^2} \exp \left[-\frac{(x - x')^2}{2\rho^2} \right]$$

Amplitude Lengthscale



How do we specify those intensity functions?

$$\lambda_{it} = \exp(\alpha_{iw} + \mu_j) + \exp(\gamma_{iw} + \eta_{ij})$$

Scaling terms for weekly variation:

$$\alpha_{iw} \sim \mathcal{N}(\alpha_{iw-1}, \tau)$$

$$\gamma_i(w) \sim \mathcal{GP}(\gamma_0, k_{\text{SE}}(w, w'; \phi_\gamma))$$

 Gaussian process: a
Bayesian nonparametric prior
over a function space

How do we specify those intensity functions?

$$\lambda_{it} = \exp(\alpha_{iw} + \mu_j) + \exp(\gamma_{iw} + \eta_{ij})$$

Scaling terms for weekly variation:

$$\alpha_{iw} \sim \mathcal{N}(\alpha_{iw-1}, \tau)$$

Squared exponential kernel
with fixed smoothness

$$\gamma_i(w) \sim \mathcal{GP}(\gamma_0, k_{\text{SE}}(w, w'; \phi_\gamma))$$

↓ Gaussian process: a
Bayesian nonparametric prior
over a function space

How do we specify those intensity functions?

$$\lambda_{it} = \exp(\alpha_{iw} + \mu_j) + \exp(\gamma_{iw} + \eta_{ij})$$

Scaling terms for weekly variation:

$$\alpha_{iw} \sim \mathcal{N}(\alpha_{iw-1}, \tau)$$

Squared exponential kernel
with fixed smoothness

$$\gamma_i(w) \sim \mathcal{GP}(\gamma_0, k_{\text{SE}}(w, w'; \phi_\gamma))$$

 Gaussian process: a
Bayesian nonparametric prior
over a function space

Key Assumption

The routine scale, $\gamma_i(w)$ evolves
slowly over weeks

*Intuition: routines are by definition
“sticky” over time*

How do we specify those intensity functions?

$$\lambda_{it} = \exp(\alpha_{iw} + \mu_j) + \exp(\gamma_{iw} + \eta_{ij})$$

Scaling terms for weekly variation:

$$\alpha_{iw} \sim \mathcal{N}(\alpha_{iw-1}, \tau)$$

Squared exponential kernel
with fixed smoothness

$$\gamma_i(w) \sim \mathcal{GP}(\gamma_0, k_{\text{SE}}(w, w'; \phi_\gamma))$$

 Gaussian process: a
Bayesian nonparametric prior
over a function space

Key Assumption

The routine scale, $\gamma_i(w)$ evolves
slowly over weeks

*Intuition: routines are by definition
“sticky” over time*

Rate terms for day-hour variation:

$$\mu(d, h) \sim \mathcal{GP}(0, k_{\text{DH}}(d, h; \phi_\mu))$$

$$\eta_i(d, h) \sim \mathcal{GP}(0, k_{\text{DH}}(d, h; \phi_\eta))$$

How do we specify those intensity functions?

$$\lambda_{it} = \exp(\alpha_{iw} + \mu_j) + \exp(\gamma_{iw} + \eta_{ij})$$

Scaling terms for weekly variation:

$$\alpha_{iw} \sim \mathcal{N}(\alpha_{iw-1}, \tau)$$

Squared exponential kernel
with fixed smoothness

$$\gamma_i(w) \sim \mathcal{GP}(\gamma_0, k_{\text{SE}}(w, w'; \phi_\gamma))$$

↓ Gaussian process: a
Bayesian nonparametric prior
over a function space

Key Assumption

The routine scale, $\gamma_i(w)$ evolves
slowly over weeks

*Intuition: routines are by definition
“sticky” over time*

Rate terms for day-hour variation:

$$\mu(d, h) \sim \mathcal{GP}(0, k_{\text{DH}}(d, h; \phi_\mu))$$

$$\eta_i(d, h) \sim \mathcal{GP}(0, k_{\text{DH}}(d, h; \phi_\eta))$$

Novel day-hour kernel

Novel Day-hour Kernel

Our novel *day-hour kernel* lets us put a
probability distribution over routines,
where:

- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

Novel Day-hour Kernel

Our novel *day-hour kernel* lets us put a
probability distribution over routines,
where:

- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

$$k_{\text{DH}}(\mathbf{d}, \mathbf{h}; \phi) = \Omega_{d,d'} \times \exp \left[-\frac{2}{\rho^2} \sin^2 \left(\frac{\pi |h - h'|}{24} \right) \right]$$

Novel Day-hour Kernel

Our novel *day-hour kernel* lets us put a
probability distribution over routines,
where:

- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

*Covariance across days
(unstructured)*

$$k_{\text{DH}}(\mathbf{d}, \mathbf{h}; \phi) = \boxed{\Omega_{d,d'}} \times \exp \left[-\frac{2}{\rho^2} \sin^2 \left(\frac{\pi|h - h'|}{24} \right) \right]$$

Novel Day-hour Kernel

Our novel *day-hour kernel* lets us put a
probability distribution over routines,
where:

- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

*Covariance across days
(unstructured)*

$$k_{\text{DH}}(\mathbf{d}, \mathbf{h}; \phi) = \boxed{\Omega_{d,d'}} \times \boxed{\exp \left[-\frac{2}{\rho^2} \sin^2 \left(\frac{\pi|h-h'|}{24} \right) \right]}$$

Cyclic variation across hours

Novel Day-hour Kernel


Our novel *day-hour kernel* lets us put a **probability distribution over routines**, where:

- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

*Covariance across days
(unstructured)*

$$k_{\text{DH}}(\mathbf{d}, \mathbf{h}; \phi) = \boxed{\Omega_{d,d'}} \times \boxed{\exp \left[-\frac{2}{\rho^2} \sin^2 \left(\frac{\pi |h - h'|}{24} \right) \right]}$$

Cyclic variation across hours



Novel Day-hour Kernel


Our novel *day-hour kernel* lets us put a **probability distribution over routines**, where:

- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

*Covariance across days
(unstructured)*

$$k_{\text{DH}}(\mathbf{d}, \mathbf{h}; \phi) = \boxed{\Omega_{d,d'}} \times \boxed{\exp \left[-\frac{2}{\rho^2} \sin^2 \left(\frac{\pi |h - h'|}{24} \right) \right]}$$

Cyclic variation across hours



Novel Day-hour Kernel


Our novel *day-hour kernel* lets us put a **probability distribution over routines**, where:

- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

*Covariance across days
(unstructured)*

$$k_{\text{DH}}(\mathbf{d}, \mathbf{h}; \phi) = \boxed{\Omega_{d,d'}} \times \boxed{\exp \left[-\frac{2}{\rho^2} \sin^2 \left(\frac{\pi |h - h'|}{24} \right) \right]}$$

Cyclic variation across hours



Novel Day-hour Kernel


Our novel *day-hour kernel* lets us put a **probability distribution over routines**, where:

- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

*Covariance across days
(unstructured)*

$$k_{\text{DH}}(\mathbf{d}, \mathbf{h}; \phi) = \boxed{\Omega_{d,d'}} \times \boxed{\exp \left[-\frac{2}{\rho^2} \sin^2 \left(\frac{\pi |h - h'|}{24} \right) \right]}$$

Cyclic variation across hours



Novel Day-hour Kernel


Our novel *day-hour kernel* lets us put a **probability distribution over routines**, where:

- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

*Covariance across days
(unstructured)*

$$k_{\text{DH}}(\mathbf{d}, \mathbf{h}; \phi) = \boxed{\Omega_{d,d'}} \times \boxed{\exp \left[-\frac{2}{\rho^2} \sin^2 \left(\frac{\pi |h - h'|}{24} \right) \right]}$$

Cyclic variation across hours



Novel Day-hour Kernel

Our novel *day-hour kernel* lets us put a **probability distribution over routines**, where:


- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

Covariance across days
(unstructured)

$$k_{\text{DH}}(\mathbf{d}, \mathbf{h}; \phi) = \boxed{\Omega_{d,d'}} \times \boxed{\exp \left[-\frac{2}{\rho^2} \sin^2 \left(\frac{\pi |h - h'|}{24} \right) \right]}$$

Cyclic variation across hours

Linkages across days



Novel Day-hour Kernel

Our novel *day-hour kernel* lets us put a **probability distribution over routines**, where:


- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

Covariance across days
(unstructured)

$$k_{\text{DH}}(\mathbf{d}, \mathbf{h}; \phi) = [\Omega_{d,d'}] \times \exp \left[-\frac{2}{\rho^2} \sin^2 \left(\frac{\pi |h - h'|}{24} \right) \right]$$

Cyclic variation across hours

Linkages across days



Smooth,
24-hour cycle

How do we specify those intensity functions?

$$\lambda_{it} = \exp(\alpha_{iw} + \mu_j) + \exp(\gamma_{iw} + \eta_{ij})$$

Baselines for weekly variation:

$$\begin{aligned}\alpha_{iw} &\sim \mathcal{N}(\alpha_{iw-1}, \tau) && \text{Squared exponential kernel} \\ &\quad \text{with fixed smoothness} \\ \gamma_i(w) &\sim \mathcal{GP}(\gamma_0, k_{\text{SE}}(w, w'; \phi_\gamma)) \\ &\quad \text{Gaussian process: a} \\ &\quad \text{Bayesian nonparametric prior} \\ &\quad \text{over a function space}\end{aligned}$$

Day-hour variation:

$$\begin{aligned}\mu(d, h) &\sim \mathcal{GP}(0, k_{\text{DH}}(d, h; \phi_\mu)) \\ \eta_i(d, h) &\sim \mathcal{GP}(0, k_{\text{DH}}(d, h; \phi_\eta))\end{aligned}$$

Novel day-hour kernel

Key Assumption

The routine scale, $\gamma_i(w)$ evolves slowly over weeks

Intuition: routines are by definition “sticky” over time

How do we specify those intensity functions?

$$\lambda_{it} = \exp(\alpha_{iw} + \mu_j) + \exp(\gamma_{iw} + \eta_{ij})$$

Baselines for weekly variation:

$\alpha_{iw} \sim \mathcal{N}(\dots)$ Smoothness
 $\gamma_i(w) \sim \mathcal{GP}(\gamma_0, k_{SE}(w, w'; \phi_\gamma))$

Key Assumption

The routine scale, $\gamma_i(w)$ evolves slowly over weeks

- This structure basically buys us two things:
1. A decomposition of total usage into “random” and “routine”
Gaussian process: a Bayesian nonparametric prior over a function space
 2. An individual-level estimate of what that routine is (η_{ij})

Day-hour variation:

$$\mu(d, h) \sim \mathcal{GP}(0, k_{DH}(d, h; \phi_\mu))$$

$$\eta_i(d, h) \sim \mathcal{GP}(0, k_{DH}(d, h; \phi_\eta))$$

Novel day-hour kernel




Results

Application to Ride-sharing Data

Ride-sharing Data

- Collaboration with a NYC-based ride-sharing company




Total Customers	2,000
Total Weeks (Training)	38
Total Weeks (Holdout)	10
Number of Sessions	86,952
Sessions / Customer	43.48
Sessions / Customer / Week	3.10
Weeks in Data / Customer	14.02



Ride-sharing Data

- Collaboration with a NYC-based ride-sharing company

Total Customers	2,000
Total Weeks (Training)	38
Total Weeks (Holdout)	10
Number of Sessions	86,952
Sessions / Customer	43.48
Sessions / Customer / Week	3.10
Weeks in Data / Customer	14.02






Ride-sharing Data

- Collaboration with a NYC-based ride-sharing company

Total Customers	2,000
Total Weeks (Training)	38
Total Weeks (Holdout)	10
Number of Sessions	86,952
Sessions / Customer	43.48
Sessions / Customer / Week	3.10
Weeks in Data / Customer	14.02

Basic unit of analysis:
a “session”



“Quasi-simulation”

- 500 real customers + 15 fake customers with specific usage patterns

“Quasi-simulation”




- 500 real customers + 15 fake customers with specific usage patterns

Case 1: Random then Routine

“Quasi-simulation”

- 500 real customers + 15 fake customers with specific usage patterns




Case 1: Random then Routine



“Quasi-simulation”

- 500 real customers + 15 fake customers with specific usage patterns

Case 1: Random then Routine



“Quasi-simulation”




- 500 real customers + 15 fake customers with specific usage patterns

Case 2: Routine then Churn

“Quasi-simulation”

- 500 real customers + 15 fake customers with specific usage patterns




Case 2: Routine then Churn



“Quasi-simulation”


- 500 real customers + 15 fake customers with specific usage patterns

Case 2: Routine then Churn




Real Case Studies

Case Study: Customer 110




Real Case Studies

Case Study: Customer 110




Case Study: Customer 647



Many types of routines




Many types of routines



“Night owls”

Many types of routines




“Morning and night”

Validation

Can we trust these results?


Validation

Can we trust these results?



Validation

Can we trust these results?



Prediction of transaction times:

- Predict timing of routine rides
- 100+% improvement over “universal” routine

Implications

Why should we care about routines?

Are routine customers more valuable?

	<i>Dependent variable:</i>			
	# Sessions		Activity	
	<i>OLS</i>		<i>Logistic</i>	
	Full Holdout	Last 5 Weeks	Full Holdout	Last 5 Weeks
	(1)	(2)	(3)	(4)
Requests ($w = 38$)	2.224*** (0.223)	0.597*** (0.141)	0.383*** (0.108)	0.180** (0.057)
Recency	-0.189*** (0.042)	-0.106*** (0.026)	-0.140*** (0.010)	-0.124*** (0.010)
Frequency	0.095*** (0.007)	0.049*** (0.004)	-0.00002 (0.002)	0.004* (0.002)
Routine ($w = 38$)	5.750*** (0.436)	3.284*** (0.275)	1.110** (0.385)	0.307* (0.147)
Observations	2,000	2,000	2,000	2,000
R ²	0.567	0.425		

Note:

*p<0.05; **p<0.01; ***p<0.001
Intercept omitted for clarity.

Are routine customers more valuable?

	<i>Dependent variable:</i>			
	# Sessions		Activity	
	<i>OLS</i>		<i>Logistic</i>	
	Full Holdout	Last 5 Weeks	Full Holdout	Last 5 Weeks
	(1)	(2)	(3)	(4)
Requests ($w = 38$)	2.224*** (0.223)	0.597*** (0.141)	0.383*** (0.108)	0.180** (0.057)
Recency	-0.189*** (0.042)	-0.106*** (0.026)	-0.140*** (0.010)	-0.124*** (0.010)
Frequency	0.095*** (0.007)	0.049*** (0.004)	-0.00002 (0.002)	0.004* (0.002)
Routine ($w = 38$)	5.750*** (0.436)	3.284*** (0.275)	1.110** (0.385)	0.307* (0.147)
Observations	2,000	2,000	2,000	2,000
R ²	0.567	0.425		

Model-based
Routineness
(Week 38)

Note:

*p<0.05; **p<0.01; ***p<0.001
Intercept omitted for clarity.

Are routine customers more valuable?

Total
Requests
(Week 38)

	Dependent variable:			
	# Sessions		Activity	
	<i>OLS</i>		<i>Logistic</i>	
	Full Holdout	Last 5 Weeks	Full Holdout	Last 5 Weeks
	(1)	(2)	(3)	(4)
Requests ($w = 38$)	2.224*** (0.223)	0.597*** (0.141)	0.383*** (0.108)	0.180** (0.057)
Recency	-0.189*** (0.042)	-0.106*** (0.026)	-0.140*** (0.010)	-0.124*** (0.010)
Frequency	0.095*** (0.007)	0.049*** (0.004)	-0.00002 (0.002)	0.004* (0.002)
Routine ($w = 38$)	5.750*** (0.436)	3.284*** (0.275)	1.110** (0.385)	0.307* (0.147)
Observations	2,000	2,000	2,000	2,000
R ²	0.567	0.425		

Model-based
Routineness
(Week 38)

Note:

* $p < 0.05$; ** $p < 0.01$; *** $p < 0.001$
Intercept omitted for clarity.

Are routine customers more valuable?

		Dependent variable:			
		# Sessions		Activity	
		OLS	Logistic	OLS	Logistic
Total Requests (Week 38)	Requests ($w = 38$)	2.224*** (0.223)	0.597*** (0.141)	0.383*** (0.108)	0.180** (0.057)
RF(M) Controls (Week 38)	Recency	-0.189*** (0.042)	-0.106*** (0.026)	-0.140*** (0.010)	-0.124*** (0.010)
	Frequency	0.095*** (0.007)	0.049*** (0.004)	-0.00002 (0.002)	0.004* (0.002)
Model-based Routineness (Week 38)	Routine ($w = 38$)	5.750*** (0.436)	3.284*** (0.275)	1.110** (0.385)	0.307* (0.147)
	Observations	2,000	2,000	2,000	2,000
	R ²	0.567	0.425		

Note:

*p<0.05; **p<0.01; ***p<0.001
Intercept omitted for clarity.

Are routine customers more valuable?

		Dependent variable:			
		# Sessions		Activity	
		<i>OLS</i>		<i>Logistic</i>	
		Full Holdout	Last 5 Weeks	Full Holdout	Last 5 Weeks
		(1)	(2)	(3)	(4)
Total Requests (Week 38)	Requests ($w = 38$)	2.224*** (0.223)	0.597*** (0.141)	0.383*** (0.108)	0.180** (0.057)
	Recency	-0.189*** (0.042)	-0.106*** (0.026)	-0.140*** (0.010)	-0.124*** (0.010)
	Frequency	0.095*** (0.007)	0.049*** (0.004)	-0.00002 (0.002)	0.004* (0.002)
RF(M) Controls (Week 38)	Routine ($w = 38$)	5.750*** (0.436)	3.284*** (0.275)	1.110** (0.385)	0.307* (0.147)
	Observations	2,000	2,000	2,000	2,000
	R ²	0.567	0.425		

Note:

*p<0.05; **p<0.01; ***p<0.001
Intercept omitted for clarity.

Key result: The number of rides *coming from a routine* is a significant predictor of **short- and long-run usage and retention**.

More to the story...

**Are routine customers better in
other ways?**

More to the story...

Are routine customers better in other ways?

	<i>Dependent variable:</i>	
	Accept Proposal	Request Again
	(1)	(2)
Routineness	0.084***	0.208***
# Requests (Week 38)	-0.021*	0.321***
Price	-0.031***	-0.052**
Driver ETA	-0.050***	-0.002
ETA Destination	-0.012***	-0.017
Speed	0.074***	-0.034
Pickup Walking Dist.	-0.041***	-0.006
# Passengers Req.	-0.003	0.025
Routineness x Price	-0.001	0.037**
Routineness x Driver ETA	0.009***	0.005
Routineness x ETA Destination	-0.0002	-0.009
Routineness x Speed	0.162***	-0.089
Routineness x Pickup Walking Dist.	-0.008***	-0.0002
Routineness x # Passengers Req.	-0.001	0.019
Pickup Delay		-0.027***
Dropoff Delay		-0.010
Dropoff Walking Dist.		-0.012
# On-board (Pickup)		-0.015
# On-board (Dropoff)		0.002
Max On-board		0.012
Routineness x Pickup Delay		0.018**
Routineness x Dropoff Delay		0.007
Routineness x Dropoff Walking Dist.		0.005
Routineness x # On-board (Pickup)		0.013
Routineness x # On-board (Dropoff)		0.001
Routineness x Max On-board		-0.011
Other Controls	Yes	Yes
Observations	38,166	14,704
R ²	0.052	0.068

Note:

*p<0.1; **p<0.05; ***p<0.01

More to the story...

Are routine customers better in other ways?

	<i>Dependent variable:</i>	
	Accept Proposal (1)	Request Again (2)
Routineness	0.084***	0.208***
# Requests (Week 38)	-0.021*	0.321***
Price	-0.031***	-0.052**
Driver ETA	-0.050***	-0.002
ETA Destination	-0.012***	-0.017
Speed	0.074***	-0.034
Pickup Walking Dist.	-0.041***	-0.006
# Passengers Req.	-0.003	0.025
Routineness x Price	-0.001	0.037**
Routineness x Driver ETA	0.009***	0.005
Routineness x ETA Destination	-0.0002	-0.009
Routineness x Speed	0.162***	-0.089
Routineness x Pickup Walking Dist.	-0.008***	-0.0002
Routineness x # Passengers Req.	-0.001	0.019
Pickup Delay		-0.027***
Dropoff Delay		-0.010
Dropoff Walking Dist.		-0.012
# On-board (Pickup)		-0.015
# On-board (Dropoff)		0.002
Max On-board		0.012
Routineness x Pickup Delay		0.018**
Routineness x Dropoff Delay		0.007
Routineness x Dropoff Walking Dist.		0.005
Routineness x # On-board (Pickup)		0.013
Routineness x # On-board (Dropoff)		0.001
Routineness x Max On-board		-0.011
Other Controls	Yes	Yes
Observations	38,166	14,704
R ²	0.052	0.068

Note:

*p<0.1; **p<0.05; ***p<0.01

More to the story...

Are routine customers better in other ways?

In ride-sharing, we find highly routine customers are...

- More likely to accept ride proposals and request again

Main effect

	Dependent variable:	
	Accept Proposal (1)	Request Again (2)
Routineness	0.084***	0.208***
# Requests (Week 38)	-0.021*	0.321***
Price	-0.031***	-0.052**
Driver ETA	-0.050***	-0.002
ETA Destination	-0.012***	-0.017
Speed	0.074***	-0.034
Pickup Walking Dist.	-0.041***	-0.006
# Passengers Req.	-0.003	0.025
Routineness x Price	-0.001	0.037**
Routineness x Driver ETA	0.009***	0.005
Routineness x ETA Destination	-0.0002	-0.009
Routineness x Speed	0.162***	-0.089
Routineness x Pickup Walking Dist.	-0.008***	-0.0002
Routineness x # Passengers Req.	-0.001	0.019
Pickup Delay		-0.027***
Dropoff Delay		-0.010
Dropoff Walking Dist.		-0.012
# On-board (Pickup)		-0.015
# On-board (Dropoff)		0.002
Max On-board		0.012
Routineness x Pickup Delay		0.018**
Routineness x Dropoff Delay		0.007
Routineness x Dropoff Walking Dist.		0.005
Routineness x # On-board (Pickup)		0.013
Routineness x # On-board (Dropoff)		0.001
Routineness x Max On-board		-0.011
Other Controls	Yes	Yes
Observations	38,166	14,704
R ²	0.052	0.068

Note:

*p<0.1; **p<0.05; ***p<0.01

More to the story...

Are routine customers better in other ways?

In ride-sharing, we find highly routine customers are...

- More likely to accept ride proposals and request again
- Less price sensitive
- Somewhat more picky about the rides they take
- Somewhat less sensitive to bad service (pickup delay)

Main effect

Moderating effects

	Accept Proposal (1)	Request Again (2)
Routineness	0.084***	0.208***
# Requests (Week 38)	-0.021*	0.321***
Price	-0.031***	-0.052**
Driver ETA	-0.050***	-0.002
ETA Destination	-0.012***	-0.017
Speed	0.074***	-0.034
Pickup Walking Dist.	-0.041***	-0.006
# Passengers Req.	-0.003	0.025
Routineness x Price	-0.001	0.037**
Routineness x Driver ETA	0.009***	0.005
Routineness x ETA Destination	-0.0002	-0.009
Routineness x Speed	0.162***	-0.089
Routineness x Pickup Walking Dist.	-0.008***	-0.0002
Routineness x # Passengers Req.	-0.001	0.019
Pickup Delay		-0.027***
Dropoff Delay		-0.010
Dropoff Walking Dist.		-0.012
# On-board (Pickup)		-0.015
# On-board (Dropoff)		0.002
Max On-board		0.012
Routineness x Pickup Delay		0.018**
Routineness x Dropoff Delay		0.007
Routineness x Dropoff Walking Dist.		0.005
Routineness x # On-board (Pickup)		0.013
Routineness x # On-board (Dropoff)		0.001
Routineness x Max On-board		-0.011
Other Controls	Yes	Yes
Observations	38,166	14,704
R ²	0.052	0.068

Note:

*p<0.1; **p<0.05; ***p<0.01

Routines of “what” vs. “when”

**Consumers can have routines in
both *when* and *what* they buy.**

Routines of “what” vs. “when”

Consumers can have routines in both *when* and *what* they buy.

- In ride-sharing: are people routine in *where* people are going, in addition to *when* they're going?
- Data: full set of locations for each customer, measured by “block”
- Two metrics of **location dispersion**:
 - Shannon entropy
 - “CRT dispersion”

Routines of “what” vs. “when”

Consumers can have routines in both *when* and *what* they buy.

- In ride-sharing: are people routine in *where* people are going, in addition to *when* they’re going?
- Data: full set of locations for each customer, measured by “block”
- Two metrics of **location dispersion**:
 - Shannon entropy
 - “CRT dispersion”

Entropy: given the empirical distribution \mathbf{p} of locations, $\ell = 1, \dots, L$:

$$\text{Entropy} = - \sum_{\ell=1}^L p_k \log p_k$$


CRT Dispersion: given L unique locations in K total trips:

$$\text{CRT Disp.} = \frac{L}{\log K}$$

Routines of “what” vs. “when”

Consumers can have routines in both *when* and *what* they buy.

- In ride-sharing: are people routine in *where* people are going, in addition to *when* they’re going?
- Data: full set of locations for each customer, measured by “block”
- Two metrics of **location dispersion**:
 - Shannon entropy
 - “CRT dispersion”



Routines of “what” vs. “when”

Consumers can have routines in both *when* and *what* they buy.

- In ride-sharing: are people routine in *where* people are going, in addition to *when* they’re going?
- Data: full set of locations for each customer, measured by “block”
- Two metrics of **location dispersion**:
 - Shannon entropy
 - “CRT dispersion”

	<i>Dependent variable:</i>	
	# Requests <i>OLS</i> (1)	Activity <i>logistic</i> (2)
Requests ($w = 38$)	2.263*** (0.225)	0.381*** (0.108)
Recency	-0.193*** (0.042)	-0.140*** (0.010)
Frequency	0.093*** (0.009)	0.0002 (0.003)
Routine ($w = 38$)	5.593*** (0.453)	1.132*** (0.396)
Entropy	-1.753 (1.092)	0.080 (0.240)
CRT Disp.	0.159 (0.199)	-0.011 (0.046)
Observations	2,000	2,000
R ²	0.568	

Note:

*p<0.1; **p<0.05; ***p<0.01

Intercept omitted for clarity.

Routines of “what” vs. “when”

Consumers can have routines in both *when* and *what* they buy.

- In ride-sharing: are people routine in *where* people are going, in addition to *when* they’re going?
- Data: full set of locations for each customer, measured by “block”
- Two metrics of **location dispersion**:
 - Shannon entropy
 - “CRT dispersion”

	Dependent variable:	
	# Requests OLS (1)	Activity <i>logistic</i> (2)
Requests ($w = 38$)	2.263*** (0.225)	0.381*** (0.108)
Recency	-0.193*** (0.042)	-0.140*** (0.010)
Frequency	0.093*** (0.009)	0.0002 (0.003)
Routine ($w = 38$)	5.593*** (0.453)	1.132*** (0.396)
Entropy	-1.753 (1.092)	0.080 (0.240)
CRT Disp.	0.159 (0.199)	-0.011 (0.046)
Observations	2,000	2,000
R ²	0.568	

Note:

*p<0.1; **p<0.05; ***p<0.01

Intercept omitted for clarity.

Summary

- **Methodological:** Our model decomposes transaction histories into routine and random components
 - Gaussian process with **novel day-hour kernel** allows for precise individual-level routine estimates
 - Nesting GP in an inhomogeneous Poisson process → **structured decomposition** of usage
 - The result: a novel routineness metric
- **Substantive:** The shape of a customer's transaction history matters!
 - Additional evidence for the role of habit, and specifically routines, for CRM
 - A new “KPI” for predicting customer value: **higher routineness = higher value**
 - Routine customers are **also better in other ways**: price sensitivity, resilience to disruptions
 - Temporal routines are distinct from “what” (or “where”) routines

Thank you!

Questions / comments?

ryandew@wharton.upenn.edu

Working paper available at www.rtdew.com