

# Detecting Routines in Ride-sharing: Implications For Customer Management

**Ryan Dew**, Eva Ascarza, Oded Netzer, Nachum Sicherman

**Routine:** behavior with a defined, recurring, temporal structure, such that the same behavior occurs at roughly the same time, period after period

**Routine:** behavior with a defined, recurring, temporal structure, such that the same behavior occurs at roughly the same time, period after period



**Routine:** behavior with a defined, recurring, temporal structure, such that the same behavior occurs at roughly the same time, period after period



**Routine:** behavior with a defined, recurring, temporal structure, such that the same behavior occurs at roughly the same time, period after period



**Routine:** behavior with a defined, recurring, temporal structure, such that the same behavior occurs at roughly the same time, period after period

Yet, there are **no existing models** for identifying routines from transaction data!



# Routines, Habits, and CRM

## Behavioral Research

- Long history of research on habits, dating back to [James \(1890\)](#)
- *Habit*: Tendency to repeat behaviors without conscious thought ([Wood et al., 2002](#))
- Habits are a primary driver of unsustainable transportation choices ([White et al., 2019](#))
- Habit discontinuity: context changes can disrupt habits, and lead to deliberate consideration ([Verplanken et al., 2008](#))

# Routines, Habits, and CRM

## Behavioral Research

- Long history of research on habits, dating back to [James \(1890\)](#)
- *Habit*: Tendency to repeat behaviors without conscious thought ([Wood et al., 2002](#))
- Habits are a primary driver of unsustainable transportation choices ([White et al., 2019](#))
- Habit discontinuity: context changes can disrupt habits, and lead to deliberate consideration ([Verplanken et al., 2008](#))

## Habits and CRM

- “Repeat buying habit”: repeat brand purchases ([Ehrenberg & Goodhardt, 1968](#))
- [Shah et al. \(2014\)](#): CRM with recurring behaviors like returns, purchasing on promotion, or purchasing low margin items
- “Habit stock” used to model smooth consumption over time ([Dynan 2000](#))
- Customers who continue to transact out of habit may be negatively affected by outreach ([Ascarza et al., 2016](#))
- Beyond RFM: clumpiness ([Zhang et al., 2015](#)), regularity ([Platzer & Reutterer, 2016](#))

**Why might  
routines matter?**

## Why might routines matter?

1. Greater share of routine means an increase in *overall usage*

## Why might routines matter?

1. Greater share of routine means an increase in *overall usage*
2. Spillover effects: the more a company features in a customer's routine, the more it will be *top-of-mind* outside of the routine

## Why might routines matter?

1. Greater share of routine means an increase in *overall usage*
2. Spillover effects: the more a company features in a customer's routine, the more it will be *top-of-mind* outside of the routine
3. Segmentation and targeting based on *types of routines*

## Why might routines matter?

1. Greater share of routine means an increase in *overall usage*
2. Spillover effects: the more a company features in a customer's routine, the more it will be *top-of-mind* outside of the routine
3. Segmentation and targeting based on *types of routines*
4. Analyzing customers' *share of routine*

## Why might routines matter?

1. Greater share of routine means an increase in *overall usage*
2. Spillover effects: the more a company features in a customer's routine, the more it will be *top-of-mind* outside of the routine
3. Segmentation and targeting based on *types of routines*
4. Analyzing customers' *share of routine*
5. Long-run customer value: routine users have a *higher lifetime value*

# Why might routines matter?

1. Greater share of routine means an increase in *overall usage*
2. Spillover effects: the more a company features in a customer's routine, the more it will be *top-of-mind* outside of the routine
3. Segmentation and targeting based on *types of routines*
4. Analyzing customers' *share of routine*
5. Long-run customer value: routine users have a *higher lifetime value*

# This Project

1. Develop a novel, all-purpose model for identifying individual-level routines
2. Apply our model to a unique ride-sharing data set
3. Show that customers with a high level of routine usage **churn less**, and **spend more** in the long run
4. Explore how temporal routineness predicts and moderates other important customer outcomes, over and above: mere habit, routines in terms of “what,” and other regularity metrics

# This Project

1. Develop a novel, all-purpose model for identifying individual-level routines
2. Apply our model to a unique ride-sharing data set
3. Show that customers with a high level of routine usage **churn less**, and **spend more** in the long run
4. Explore how temporal routineness predicts and moderates other important customer outcomes, over and above: mere habit, routines in terms of “what,” and other regularity metrics


**In short: we show the “shape” of customers’ interactions matters!**

# Model

A Statistical Framework for Measuring Routineness


# Model of Usage

From transaction data, we want to capture...



# Model of Usage


From transaction data, we want to capture...



**Big question:** How much of a person's activity is part of a routine?

# Model of Usage

From transaction data, we want to capture...



**Big question:** How much of a person's activity is part of a routine?

**Dependent variable:** Usage ( $y$ )

Customer  $i$ , Week  $w$ , Day  $d$ , Hour  $h$

Time  $t = (w, d, h)$ , Day-hour  $j = (d, h)$

$$y_{it} \sim \text{Poisson}(\lambda_{it})$$

$$\lambda_{it} = \underbrace{\exp(\alpha_{iw} + \mu_j)}_{\text{Random usage}} + \underbrace{\exp(\gamma_{iw} + \eta_{ij})}_{\text{Routine usage}}$$

**Random usage**      **Routine usage**

- $\alpha_{iw}$  and  $\gamma_{iw}$  – Individual- and week-specific scaling terms
- $\mu_j$  – Common day-hour rate
- $\eta_{ij}$  – Individual-specific day-hour rate

These random and routine usage terms give us a **structured decomposition** of overall usage.

# Model-based Decomposition


$$y_{it} \sim \text{Poisson}(\lambda_{it})$$

$$\lambda_{it} = \underbrace{\exp(\alpha_{iw} + \mu_j)}_{\text{Random usage}} + \underbrace{\exp(\gamma_{iw} + \eta_{ij})}_{\text{Routine usage}}$$

# Model-based Decomposition

$$y_{it} \sim \text{Poisson}(\lambda_{it})$$


$$\lambda_{it} = \underbrace{\exp(\alpha_{iw} + \mu_j)}_{\text{Random usage}} + \underbrace{\exp(\gamma_{iw} + \eta_{ij})}_{\text{Routine usage}}$$



Requests follow an individual-level  
**inhomogeneous Poisson point process**

# Model-based Decomposition

$$y_{it} \sim \text{Poisson}(\lambda_{it})$$
$$\lambda_{it} = \underbrace{\exp(\alpha_{iw} + \mu_j)}_{\text{Random usage}} + \underbrace{\exp(\gamma_{iw} + \eta_{ij})}_{\text{Routine usage}}$$



Requests follow an individual-level  
**inhomogeneous Poisson point process**

*Superposition of point processes:*  
If  $Y_A \sim \text{PP}(\lambda_A)$  and  $Y_B \sim \text{PP}(\lambda_B)$ ,  
then  $Y_A + Y_B \sim \text{PP}(\lambda_A + \lambda_B)$ .

Random requests:


$$E_{iw}^{\text{Random}} = \sum_j \exp(\alpha_{iw} + \mu_j)$$

Routine requests:

$$E_{iw}^{\text{Routine}} = \sum_j \exp(\gamma_{iw} + \eta_{ij})$$

# Model-based Decomposition

$$y_{it} \sim \text{Poisson}(\lambda_{it})$$
$$\lambda_{it} = \underbrace{\exp(\alpha_{iw} + \mu_j)}_{\text{Random usage}} + \underbrace{\exp(\gamma_{iw} + \eta_{ij})}_{\text{Routine usage}}$$



Requests follow an individual-level  
**inhomogeneous Poisson point process**

*Superposition of point processes:*  
If  $Y_A \sim \text{PP}(\lambda_A)$  and  $Y_B \sim \text{PP}(\lambda_B)$ ,  
then  $Y_A + Y_B \sim \text{PP}(\lambda_A + \lambda_B)$ .

Random requests:

$$E_{iw}^{\text{Random}} = \sum_j \exp(\alpha_{iw} + \mu_j)$$

Routine requests:

$$E_{iw}^{\text{Routine}} = \sum_j \exp(\gamma_{iw} + \eta_{ij})$$

“Routineness”

# How do we specify those intensity functions?

$$\lambda_{it} = \exp(\alpha_{iw} + \mu_j) + \exp(\gamma_{iw} + \eta_{ij})$$

# How do we specify those intensity functions?

$$\lambda_{it} = \exp(\alpha_{iw} + \mu_j) + \exp(\gamma_{iw} + \eta_{ij})$$

Scaling terms for weekly variation:

$$\alpha_{iw} \sim \mathcal{N}(\alpha_{iw-1}, \tau)$$

$$\gamma_i(w) \sim \mathcal{GP}(\gamma_0, k_{\text{SE}}(w, w'; \phi_\gamma))$$

# How do we specify those intensity functions?

$$\lambda_{it} = \exp(\alpha_{iw} + \mu_j) + \exp(\gamma_{iw} + \eta_{ij})$$

Scaling terms for weekly variation:

$$\alpha_{iw} \sim \mathcal{N}(\alpha_{iw-1}, \tau)$$

$$\gamma_i(w) \sim \mathcal{GP}(\gamma_0, k_{\text{SE}}(w, w'; \phi_\gamma))$$

 Gaussian process: a  
Bayesian nonparametric prior  
over a function space

# Interlude: Gaussian processes


$$f(x) \sim \mathcal{GP}(m(x), k(x, x'))$$

# Interlude: Gaussian processes


$$f(x) \sim \mathcal{GP}(m(x), k(x, x'))$$

Mean function  Covariance function  
"Kernel" 

# Interlude: Gaussian processes



# Interlude: Gaussian processes



$$k_{\text{SE}}(x, x') = \sigma^2 \exp \left[ -\frac{(x - x')^2}{2\rho^2} \right]$$

# Interlude: Gaussian processes

$$f(x) \sim \mathcal{GP}(m(x), k(x, x'))$$

Mean function Covariance function  
"Kernel"

$$f(x_1, \dots, x_N) \sim \mathcal{N}(m(x_1, \dots, x_N), K), \text{ s.t. } K_{ij} = k(x_i, x_j)$$

↑  
↔  
↓

$$k_{\text{SE}}(x, x') = \boxed{\sigma^2} \exp \left[ -\frac{(x - x')^2}{2\rho^2} \right]$$

Amplitude  
Lengthscale

# Interlude: Gaussian processes


$$f(x) \sim \mathcal{GP}(m(x), k(x, x'))$$

Mean function Covariance function  
"Kernel"

$$f(x_1, \dots, x_N) \sim \mathcal{N}(m(x_1, \dots, x_N), K), \text{ s.t. } K_{ij} = k(x_i, x_j)$$

$$k_{\text{SE}}(x, x') = \boxed{\sigma^2} \exp \left[ -\frac{(x - x')^2}{2\rho^2} \right]$$

Amplitude Lengthscale



# How do we specify those intensity functions?

$$\lambda_{it} = \exp(\alpha_{iw} + \mu_j) + \exp(\gamma_{iw} + \eta_{ij})$$

Scaling terms for weekly variation:

$$\alpha_{iw} \sim \mathcal{N}(\alpha_{iw-1}, \tau)$$

$$\gamma_i(w) \sim \mathcal{GP}(\gamma_0, k_{\text{SE}}(w, w'; \phi_\gamma))$$

 Gaussian process: a  
Bayesian nonparametric prior  
over a function space

# How do we specify those intensity functions?

$$\lambda_{it} = \exp(\alpha_{iw} + \mu_j) + \exp(\gamma_{iw} + \eta_{ij})$$

Scaling terms for weekly variation:

$$\alpha_{iw} \sim \mathcal{N}(\alpha_{iw-1}, \tau)$$

Squared exponential kernel  
with fixed smoothness

$$\gamma_i(w) \sim \mathcal{GP}(\gamma_0, k_{\text{SE}}(w, w'; \phi_\gamma))$$

↓ Gaussian process: a  
Bayesian nonparametric prior  
over a function space

# How do we specify those intensity functions?

$$\lambda_{it} = \exp(\alpha_{iw} + \mu_j) + \exp(\gamma_{iw} + \eta_{ij})$$

Scaling terms for weekly variation:

$$\alpha_{iw} \sim \mathcal{N}(\alpha_{iw-1}, \tau)$$

Squared exponential kernel  
with fixed smoothness

$$\gamma_i(w) \sim \mathcal{GP}(\gamma_0, k_{\text{SE}}(w, w'; \phi_\gamma))$$

 Gaussian process: a  
Bayesian nonparametric prior  
over a function space

## Key Assumption

The routine scale,  $\gamma_i(w)$  evolves  
slowly over weeks

*Intuition: routines are by definition  
“sticky” over time*

# How do we specify those intensity functions?

$$\lambda_{it} = \exp(\alpha_{iw} + \mu_j) + \exp(\gamma_{iw} + \eta_{ij})$$

Scaling terms for weekly variation:

$$\alpha_{iw} \sim \mathcal{N}(\alpha_{iw-1}, \tau)$$

Squared exponential kernel  
with fixed smoothness

$$\gamma_i(w) \sim \mathcal{GP}(\gamma_0, k_{\text{SE}}(w, w'; \phi_\gamma))$$

 Gaussian process: a  
Bayesian nonparametric prior  
over a function space

## Key Assumption

The routine scale,  $\gamma_i(w)$  evolves  
slowly over weeks

*Intuition: routines are by definition  
“sticky” over time*

Rate terms for day-hour variation:

$$\mu(d, h) \sim \mathcal{GP}(0, k_{\text{DH}}(d, h; \phi_\mu))$$

$$\eta_i(d, h) \sim \mathcal{GP}(0, k_{\text{DH}}(d, h; \phi_\eta))$$

# How do we specify those intensity functions?

$$\lambda_{it} = \exp(\alpha_{iw} + \mu_j) + \exp(\gamma_{iw} + \eta_{ij})$$

Scaling terms for weekly variation:

$$\alpha_{iw} \sim \mathcal{N}(\alpha_{iw-1}, \tau)$$

Squared exponential kernel  
with fixed smoothness

$$\gamma_i(w) \sim \mathcal{GP}(\gamma_0, k_{\text{SE}}(w, w'; \phi_\gamma))$$

↓ Gaussian process: a  
Bayesian nonparametric prior  
over a function space

## Key Assumption

The routine scale,  $\gamma_i(w)$  evolves  
slowly over weeks

*Intuition: routines are by definition  
“sticky” over time*

Rate terms for day-hour variation:

$$\mu(d, h) \sim \mathcal{GP}(0, k_{\text{DH}}(d, h; \phi_\mu))$$

$$\eta_i(d, h) \sim \mathcal{GP}(0, k_{\text{DH}}(d, h; \phi_\eta))$$

Novel day-hour kernel

# Novel Day-hour Kernel

Our novel *day-hour kernel* lets us put a  
**probability distribution over routines**,  
where:

- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

# Novel Day-hour Kernel

Our novel *day-hour kernel* lets us put a  
**probability distribution over routines**,  
where:

- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

$$k_{\text{DH}}(\mathbf{d}, \mathbf{h}; \phi) = \Omega_{d,d'} \times \exp \left[ -\frac{2}{\rho^2} \sin^2 \left( \frac{\pi |h - h'|}{24} \right) \right]$$

# Novel Day-hour Kernel

Our novel *day-hour kernel* lets us put a  
**probability distribution over routines**,  
where:

- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

*Covariance across days  
(unstructured)*

$$k_{\text{DH}}(\mathbf{d}, \mathbf{h}; \phi) = \boxed{\Omega_{d,d'}} \times \exp \left[ -\frac{2}{\rho^2} \sin^2 \left( \frac{\pi|h - h'|}{24} \right) \right]$$

# Novel Day-hour Kernel

Our novel *day-hour kernel* lets us put a  
**probability distribution over routines**,  
where:

- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

*Covariance across days  
(unstructured)*

$$k_{\text{DH}}(\mathbf{d}, \mathbf{h}; \phi) = \boxed{\Omega_{d,d'}} \times \boxed{\exp \left[ -\frac{2}{\rho^2} \sin^2 \left( \frac{\pi|h-h'|}{24} \right) \right]}$$

*Cyclic variation across hours*

# Novel Day-hour Kernel


Our novel *day-hour kernel* lets us put a **probability distribution over routines**, where:

- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

*Covariance across days  
(unstructured)*

$$k_{\text{DH}}(\mathbf{d}, \mathbf{h}; \phi) = \boxed{\Omega_{d,d'}} \times \boxed{\exp \left[ -\frac{2}{\rho^2} \sin^2 \left( \frac{\pi |h - h'|}{24} \right) \right]}$$

*Cyclic variation across hours*



# Novel Day-hour Kernel


Our novel *day-hour kernel* lets us put a **probability distribution over routines**, where:

- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

*Covariance across days  
(unstructured)*

$$k_{\text{DH}}(\mathbf{d}, \mathbf{h}; \phi) = \boxed{\Omega_{d,d'}} \times \boxed{\exp \left[ -\frac{2}{\rho^2} \sin^2 \left( \frac{\pi |h - h'|}{24} \right) \right]}$$

*Cyclic variation across hours*



# Novel Day-hour Kernel


Our novel *day-hour kernel* lets us put a **probability distribution over routines**, where:

- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

*Covariance across days  
(unstructured)*

$$k_{\text{DH}}(\mathbf{d}, \mathbf{h}; \phi) = \boxed{\Omega_{d,d'}} \times \boxed{\exp \left[ -\frac{2}{\rho^2} \sin^2 \left( \frac{\pi |h - h'|}{24} \right) \right]}$$

*Cyclic variation across hours*



# Novel Day-hour Kernel


Our novel *day-hour kernel* lets us put a **probability distribution over routines**, where:

- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

*Covariance across days  
(unstructured)*

$$k_{\text{DH}}(\mathbf{d}, \mathbf{h}; \phi) = \boxed{\Omega_{d,d'}} \times \boxed{\exp \left[ -\frac{2}{\rho^2} \sin^2 \left( \frac{\pi |h - h'|}{24} \right) \right]}$$

*Cyclic variation across hours*



# Novel Day-hour Kernel


Our novel *day-hour kernel* lets us put a **probability distribution over routines**, where:

- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

*Covariance across days  
(unstructured)*

$$k_{\text{DH}}(\mathbf{d}, \mathbf{h}; \phi) = \boxed{\Omega_{d,d'}} \times \boxed{\exp \left[ -\frac{2}{\rho^2} \sin^2 \left( \frac{\pi |h - h'|}{24} \right) \right]}$$

*Cyclic variation across hours*



# Novel Day-hour Kernel

Our novel *day-hour kernel* lets us put a **probability distribution over routines**, where:


- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

Covariance across days  
(unstructured)

$$k_{\text{DH}}(\mathbf{d}, \mathbf{h}; \phi) = \boxed{\Omega_{d,d'}} \times \boxed{\exp \left[ -\frac{2}{\rho^2} \sin^2 \left( \frac{\pi |h - h'|}{24} \right) \right]}$$

Cyclic variation across hours

Linkages across days



# Novel Day-hour Kernel

Our novel *day-hour kernel* lets us put a **probability distribution over routines**, where:


- Certain days are more related than others
- Certain hours are more related than others
- Hours operate over a 24 hour cycle

Covariance across days  
(unstructured)

$$k_{\text{DH}}(\mathbf{d}, \mathbf{h}; \phi) = [\Omega_{d,d'}] \times \exp \left[ -\frac{2}{\rho^2} \sin^2 \left( \frac{\pi |h - h'|}{24} \right) \right]$$

Cyclic variation across hours

Linkages across days



Smooth,  
24-hour cycle

# How do we specify those intensity functions?

$$\lambda_{it} = \exp(\alpha_{iw} + \mu_j) + \exp(\gamma_{iw} + \eta_{ij})$$

Baselines for weekly variation:

$$\begin{aligned}\alpha_{iw} &\sim \mathcal{N}(\alpha_{iw-1}, \tau) && \text{Squared exponential kernel} \\ &\quad \text{with fixed smoothness} \\ \gamma_i(w) &\sim \mathcal{GP}(\gamma_0, k_{\text{SE}}(w, w'; \phi_\gamma)) \\ &\quad \text{Gaussian process: a} \\ &\quad \text{Bayesian nonparametric prior} \\ &\quad \text{over a function space}\end{aligned}$$

Day-hour variation:

$$\begin{aligned}\mu(d, h) &\sim \mathcal{GP}(0, k_{\text{DH}}(d, h; \phi_\mu)) \\ \eta_i(d, h) &\sim \mathcal{GP}(0, k_{\text{DH}}(d, h; \phi_\eta))\end{aligned}$$

Novel day-hour kernel

## Key Assumption

The routine scale,  $\gamma_i(w)$  evolves slowly over weeks

*Intuition: routines are by definition “sticky” over time*

# How do we specify those intensity functions?

$$\lambda_{it} = \exp(\alpha_{iw} + \mu_j) + \exp(\gamma_{iw} + \eta_{ij})$$

Baselines for weekly variation:

$\alpha_{iw} \sim \mathcal{N}(\dots)$  Smoothness  
 $\gamma_i(w) \sim \mathcal{GP}(\gamma_0, k_{SE}(w, w'; \phi_\gamma))$

Key Assumption

The routine scale,  $\gamma_i(w)$  evolves slowly over weeks

- This structure basically buys us two things:
1. A decomposition of total usage into “random” and “routine”  
Gaussian process: a Bayesian nonparametric prior over a function space
  2. An individual-level estimate of what that routine is ( $\eta_{ij}$ )

Day-hour variation:

$$\mu(d, h) \sim \mathcal{GP}(0, k_{DH}(d, h; \phi_\mu))$$

$$\eta_i(d, h) \sim \mathcal{GP}(0, k_{DH}(d, h; \phi_\eta))$$

Novel day-hour kernel




# Results

Application to Ride-sharing Data

# Ride-sharing Data

- Collaboration with a NYC-based ride-sharing company




Total Customers	2,000
Total Weeks (Training)	38
Total Weeks (Holdout)	10
Number of Sessions	86,952
Sessions / Customer	43.48
Sessions / Customer / Week	3.10
Weeks in Data / Customer	14.02



# Ride-sharing Data

- Collaboration with a NYC-based ride-sharing company

Total Customers	2,000
Total Weeks (Training)	38
Total Weeks (Holdout)	10
Number of Sessions	86,952
Sessions / Customer	43.48
Sessions / Customer / Week	3.10
Weeks in Data / Customer	14.02






# Ride-sharing Data

- Collaboration with a NYC-based ride-sharing company


Total Customers	2,000
Total Weeks (Training)	38
Total Weeks (Holdout)	10
Number of Sessions	86,952
Sessions / Customer	43.48
Sessions / Customer / Week	3.10
Weeks in Data / Customer	14.02

Basic unit of analysis:  
a “session”




# Real Case Studies

Case Study: Customer 110




# Real Case Studies

Case Study: Customer 110



Case Study: Customer 647



# Many types of routines




# Many types of routines



“Night owls”

# Many types of routines



“Morning and night”

# Validation

Can we trust these results?



# Implications

Why should we care about routines?

# Are routine customers more valuable?

	<i>Dependent variable:</i>			
	# Sessions		Activity	
	<i>OLS</i>		<i>Logistic</i>	
	Full Holdout	Last 5 Weeks	Full Holdout	Last 5 Weeks
	(1)	(2)	(3)	(4)
Requests ( $w = 38$ )	2.224*** (0.223)	0.597*** (0.141)	0.383*** (0.108)	0.180** (0.057)
Recency	-0.189*** (0.042)	-0.106*** (0.026)	-0.140*** (0.010)	-0.124*** (0.010)
Frequency	0.095*** (0.007)	0.049*** (0.004)	-0.00002 (0.002)	0.004* (0.002)
Routine ( $w = 38$ )	5.750*** (0.436)	3.284*** (0.275)	1.110** (0.385)	0.307* (0.147)
Observations	2,000	2,000	2,000	2,000
R <sup>2</sup>	0.567	0.425		

*Note:*

\*p<0.05; \*\*p<0.01; \*\*\*p<0.001  
Intercept omitted for clarity.

# Are routine customers more valuable?

	<i>Dependent variable:</i>			
	# Sessions		Activity	
	<i>OLS</i>		<i>Logistic</i>	
	Full Holdout	Last 5 Weeks	Full Holdout	Last 5 Weeks
	(1)	(2)	(3)	(4)
Requests ( $w = 38$ )	2.224*** (0.223)	0.597*** (0.141)	0.383*** (0.108)	0.180** (0.057)
Recency	-0.189*** (0.042)	-0.106*** (0.026)	-0.140*** (0.010)	-0.124*** (0.010)
Frequency	0.095*** (0.007)	0.049*** (0.004)	-0.00002 (0.002)	0.004* (0.002)
Routine ( $w = 38$ )	5.750*** (0.436)	3.284*** (0.275)	1.110** (0.385)	0.307* (0.147)
Observations	2,000	2,000	2,000	2,000
R <sup>2</sup>	0.567	0.425		

*Note:*

\*p<0.05; \*\*p<0.01; \*\*\*p<0.001  
Intercept omitted for clarity.

Model-based  
Routineness  
(Week 38)

# Are routine customers more valuable?

Total  
Requests  
(Week 38)

	Dependent variable:			
	# Sessions		Activity	
	<i>OLS</i>		<i>Logistic</i>	
	Full Holdout	Last 5 Weeks	Full Holdout	Last 5 Weeks
	(1)	(2)	(3)	(4)
Requests ( $w = 38$ )	2.224*** (0.223)	0.597*** (0.141)	0.383*** (0.108)	0.180** (0.057)
Recency	-0.189*** (0.042)	-0.106*** (0.026)	-0.140*** (0.010)	-0.124*** (0.010)
Frequency	0.095*** (0.007)	0.049*** (0.004)	-0.00002 (0.002)	0.004* (0.002)
Routine ( $w = 38$ )	5.750*** (0.436)	3.284*** (0.275)	1.110** (0.385)	0.307* (0.147)
Observations	2,000	2,000	2,000	2,000
R <sup>2</sup>	0.567	0.425		

Model-based  
Routineness  
(Week 38)

Note:

\*p<0.05; \*\*p<0.01; \*\*\*p<0.001  
Intercept omitted for clarity.

# Are routine customers more valuable?

		Dependent variable:			
		# Sessions		Activity	
		OLS	Logistic	OLS	Logistic
Total Requests (Week 38)	Requests ( $w = 38$ )	2.224*** (0.223)	0.597*** (0.141)	0.383*** (0.108)	0.180** (0.057)
RF(M) Controls (Week 38)	Recency	-0.189*** (0.042)	-0.106*** (0.026)	-0.140*** (0.010)	-0.124*** (0.010)
	Frequency	0.095*** (0.007)	0.049*** (0.004)	-0.00002 (0.002)	0.004* (0.002)
Model-based Routineness (Week 38)	Routine ( $w = 38$ )	5.750*** (0.436)	3.284*** (0.275)	1.110** (0.385)	0.307* (0.147)
	Observations	2,000	2,000	2,000	2,000
	R <sup>2</sup>	0.567	0.425		

*Note:*

\*p<0.05; \*\*p<0.01; \*\*\*p<0.001  
Intercept omitted for clarity.

# Are routine customers more valuable?

		Dependent variable:			
		# Sessions		Activity	
		<i>OLS</i>		<i>Logistic</i>	
		Full Holdout	Last 5 Weeks	Full Holdout	Last 5 Weeks
		(1)	(2)	(3)	(4)
Total Requests (Week 38)	Requests ( $w = 38$ )	2.224*** (0.223)	0.597*** (0.141)	0.383*** (0.108)	0.180** (0.057)
	Recency	-0.189*** (0.042)	-0.106*** (0.026)	-0.140*** (0.010)	-0.124*** (0.010)
	Frequency	0.095*** (0.007)	0.049*** (0.004)	-0.00002 (0.002)	0.004* (0.002)
RF(M) Controls (Week 38)	Routine ( $w = 38$ )	5.750*** (0.436)	3.284*** (0.275)	1.110** (0.385)	0.307* (0.147)
	Observations	2,000	2,000	2,000	2,000
	R <sup>2</sup>	0.567	0.425		

Note:

\*p<0.05; \*\*p<0.01; \*\*\*p<0.001  
Intercept omitted for clarity.

**Key result:** The number of rides *coming from a routine* is a significant predictor of **short- and long-run usage and retention**.

# **More to the story...**

**Are routine customers better in  
other ways?**

# More to the story...

**Are routine customers better in other ways?**

	<i>Dependent variable:</i>	
	Accept Proposal	Request Again
	(1)	(2)
Routineness	0.084***	0.208***
# Requests (Week 38)	-0.021*	0.321***
Price	-0.031***	-0.052**
Driver ETA	-0.050***	-0.002
ETA Destination	-0.012***	-0.017
Speed	0.074***	-0.034
Pickup Walking Dist.	-0.041***	-0.006
# Passengers Req.	-0.003	0.025
Routineness x Price	-0.001	0.037**
Routineness x Driver ETA	0.009***	0.005
Routineness x ETA Destination	-0.0002	-0.009
Routineness x Speed	0.162***	-0.089
Routineness x Pickup Walking Dist.	-0.008***	-0.0002
Routineness x # Passengers Req.	-0.001	0.019
Pickup Delay		-0.027***
Dropoff Delay		-0.010
Dropoff Walking Dist.		-0.012
# On-board (Pickup)		-0.015
# On-board (Dropoff)		0.002
Max On-board		0.012
Routineness x Pickup Delay		0.018**
Routineness x Dropoff Delay		0.007
Routineness x Dropoff Walking Dist.		0.005
Routineness x # On-board (Pickup)		0.013
Routineness x # On-board (Dropoff)		0.001
Routineness x Max On-board		-0.011
Other Controls	Yes	Yes
Observations	38,166	14,704
R <sup>2</sup>	0.052	0.068

*Note:*

\*p<0.1; \*\*p<0.05; \*\*\*p<0.01

# More to the story...

**Are routine customers better in other ways?**

	<i>Dependent variable:</i>	
	Accept Proposal (1)	Request Again (2)
Routineness	0.084***	0.208***
# Requests (Week 38)	-0.021*	0.321***
Price	-0.031***	-0.052**
Driver ETA	-0.050***	-0.002
ETA Destination	-0.012***	-0.017
Speed	0.074***	-0.034
Pickup Walking Dist.	-0.041***	-0.006
# Passengers Req.	-0.003	0.025
Routineness x Price	-0.001	0.037**
Routineness x Driver ETA	0.009***	0.005
Routineness x ETA Destination	-0.0002	-0.009
Routineness x Speed	0.162***	-0.089
Routineness x Pickup Walking Dist.	-0.008***	-0.0002
Routineness x # Passengers Req.	-0.001	0.019
Pickup Delay		-0.027***
Dropoff Delay		-0.010
Dropoff Walking Dist.		-0.012
# On-board (Pickup)		-0.015
# On-board (Dropoff)		0.002
Max On-board		0.012
Routineness x Pickup Delay		0.018**
Routineness x Dropoff Delay		0.007
Routineness x Dropoff Walking Dist.		0.005
Routineness x # On-board (Pickup)		0.013
Routineness x # On-board (Dropoff)		0.001
Routineness x Max On-board		-0.011
Other Controls	Yes	Yes
Observations	38,166	14,704
R <sup>2</sup>	0.052	0.068

*Note:*

\*p<0.1; \*\*p<0.05; \*\*\*p<0.01

# More to the story...

## Are routine customers better in other ways?

In ride-sharing, we find highly routine customers are...

- More likely to accept ride proposals and request again

### Main effect

	Dependent variable:	
	Accept Proposal (1)	Request Again (2)
Routineness	0.084***	0.208***
# Requests (Week 38)	-0.021*	0.321***
Price	-0.031***	-0.052**
Driver ETA	-0.050***	-0.002
ETA Destination	-0.012***	-0.017
Speed	0.074***	-0.034
Pickup Walking Dist.	-0.041***	-0.006
# Passengers Req.	-0.003	0.025
Routineness x Price	-0.001	0.037**
Routineness x Driver ETA	0.009***	0.005
Routineness x ETA Destination	-0.0002	-0.009
Routineness x Speed	0.162***	-0.089
Routineness x Pickup Walking Dist.	-0.008***	-0.0002
Routineness x # Passengers Req.	-0.001	0.019
Pickup Delay		-0.027***
Dropoff Delay		-0.010
Dropoff Walking Dist.		-0.012
# On-board (Pickup)		-0.015
# On-board (Dropoff)		0.002
Max On-board		0.012
Routineness x Pickup Delay		0.018**
Routineness x Dropoff Delay		0.007
Routineness x Dropoff Walking Dist.		0.005
Routineness x # On-board (Pickup)		0.013
Routineness x # On-board (Dropoff)		0.001
Routineness x Max On-board		-0.011
Other Controls	Yes	Yes
Observations	38,166	14,704
R <sup>2</sup>	0.052	0.068

Note:

\*p<0.1; \*\*p<0.05; \*\*\*p<0.01

# More to the story...

## Are routine customers better in other ways?

In ride-sharing, we find highly routine customers are...

- More likely to accept ride proposals and request again
- Less price sensitive
- Somewhat more picky about the rides they take
- Somewhat less sensitive to bad service (pickup delay)

### Main effect

### Moderating effects

	Dependent variable:	
	Accept Proposal (1)	Request Again (2)
Routineness	0.084***	0.208***
# Requests (Week 38)	-0.021*	0.321***
Price	-0.031***	-0.052**
Driver ETA	-0.050***	-0.002
ETA Destination	-0.012***	-0.017
Speed	0.074***	-0.034
Pickup Walking Dist.	-0.041***	-0.006
# Passengers Req.	-0.003	0.025
Routineness x Price	-0.001	0.037**
Routineness x Driver ETA	0.009***	0.005
Routineness x ETA Destination	-0.0002	-0.009
Routineness x Speed	0.162***	-0.089
Routineness x Pickup Walking Dist.	-0.008***	-0.0002
Routineness x # Passengers Req.	-0.001	0.019
Pickup Delay		-0.027***
Dropoff Delay		-0.010
Dropoff Walking Dist.		-0.012
# On-board (Pickup)		-0.015
# On-board (Dropoff)		0.002
Max On-board		0.012
Routineness x Pickup Delay		0.018**
Routineness x Dropoff Delay		0.007
Routineness x Dropoff Walking Dist.		0.005
Routineness x # On-board (Pickup)		0.013
Routineness x # On-board (Dropoff)		0.001
Routineness x Max On-board		-0.011
Other Controls	Yes	Yes
Observations	38,166	14,704
R <sup>2</sup>	0.052	0.068

Note:

\*p<0.1; \*\*p<0.05; \*\*\*p<0.01

# Routines of “what” vs. “when”

**Consumers can have routines in  
both *when* and *what* they buy.**

# Routines of “what” vs. “when”

**Consumers can have routines in both *when* and *what* they buy.**

- In ride-sharing: are people routine in *where* people are going, in addition to *when* they're going?
- Data: full set of locations for each customer, measured by “block”
- Two metrics of **location dispersion**:
  - Shannon entropy
  - “CRT dispersion”

# Routines of “what” vs. “when”

**Consumers can have routines in both *when* and *what* they buy.**

- In ride-sharing: are people routine in *where* people are going, in addition to *when* they’re going?
- Data: full set of locations for each customer, measured by “block”
- Two metrics of **location dispersion**:
  - Shannon entropy
  - “CRT dispersion”

**Entropy:** given the empirical distribution  $\mathbf{p}$  of locations,  $\ell = 1, \dots, L$ :

$$\text{Entropy} = - \sum_{\ell=1}^L p_k \log p_k$$


**CRT Dispersion:** given  $L$  unique locations in  $K$  total trips:

$$\text{CRT Disp.} = \frac{L}{\log K}$$

# Routines of “what” vs. “when”

Consumers can have routines in both *when* and *what* they buy.

- In ride-sharing: are people routine in *where* people are going, in addition to *when* they’re going?
- Data: full set of locations for each customer, measured by “block”
- Two metrics of **location dispersion**:
  - Shannon entropy
  - “CRT dispersion”



# Routines of “what” vs. “when”

**Consumers can have routines in both *when* and *what* they buy.**

- In ride-sharing: are people routine in *where* people are going, in addition to *when* they’re going?
- Data: full set of locations for each customer, measured by “block”
- Two metrics of **location dispersion**:
  - Shannon entropy
  - “CRT dispersion”

	<i>Dependent variable:</i>	
	# Requests <i>OLS</i> (1)	Activity <i>logistic</i> (2)
Requests ( $w = 38$ )	2.263*** (0.225)	0.381*** (0.108)
Recency	-0.193*** (0.042)	-0.140*** (0.010)
Frequency	0.093*** (0.009)	0.0002 (0.003)
Routine ( $w = 38$ )	5.593*** (0.453)	1.132*** (0.396)
Entropy	-1.753 (1.092)	0.080 (0.240)
CRT Disp.	0.159 (0.199)	-0.011 (0.046)
Observations	2,000	2,000
R <sup>2</sup>	0.568	

*Note:*

\*p<0.1; \*\*p<0.05; \*\*\*p<0.01

Intercept omitted for clarity.

# Routines of “what” vs. “when”

**Consumers can have routines in both *when* and *what* they buy.**

- In ride-sharing: are people routine in *where* people are going, in addition to *when* they’re going?
- Data: full set of locations for each customer, measured by “block”
- Two metrics of **location dispersion**:
  - Shannon entropy
  - “CRT dispersion”

	Dependent variable:	
	# Requests OLS (1)	Activity <i>logistic</i> (2)
Requests ( $w = 38$ )	2.263*** (0.225)	0.381*** (0.108)
Recency	-0.193*** (0.042)	-0.140*** (0.010)
Frequency	0.093*** (0.009)	0.0002 (0.003)
Routine ( $w = 38$ )	5.593*** (0.453)	1.132*** (0.396)
Entropy	-1.753 (1.092)	0.080 (0.240)
CRT Disp.	0.159 (0.199)	-0.011 (0.046)
Observations	2,000	2,000
R <sup>2</sup>	0.568	

Note:

\*p<0.1; \*\*p<0.05; \*\*\*p<0.01

Intercept omitted for clarity.

# Summary

- **Methodological:** Our model decomposes transaction histories into routine and random components
  - Gaussian process with **novel day-hour kernel** allows for precise individual-level routine estimates
  - Nesting GP in an inhomogeneous Poisson process → **structured decomposition** of usage
  - The result: a novel routineness metric
- **Substantive:** The shape of a customer's transaction history matters!
  - Additional evidence for the role of habit, and specifically routines, for CRM
  - A new “KPI” for predicting customer value: **higher routineness = higher value**
  - Routine customers are **also better in other ways**: price sensitivity, resilience to disruptions
  - Temporal routines are distinct from “what” (or “where”) routines

# Thank you!

Questions / comments?

[ryandew@wharton.upenn.edu](mailto:ryandew@wharton.upenn.edu)

*Working paper available at [www.rtdew.com](http://www.rtdew.com)*