


Ink Morrow

WHERE STORIES GROW CLAWS

5.0 EDITION

System Architecture & Design Rationale

The boundaries, contracts, and decisions that keep canon trustworthy

For maintainers and technical reviewers / November 2026

System Architecture & Design Rationale

InkMorrow 5.0 is a single-owner playable-fiction system. This book explains the current production boundaries, reuse decisions and limits; historical writing-suite routes are not part of its runtime.

Contents

Source-grounded narrative context
B7 readable books, Bookshelf and reading copies
B6 listening to saved fiction
B5 retained visual collection
B4 editorial architecture
B3 creative and narration architecture
Product and system context
Module and responsibility map
Fresh storage and startup order
The playable graph
Canon commit and spend accounting
Reader, privacy and asynchronous UI
Limits, performance and extension decisions
Bounded consistency pipeline
People and episode framing
Fourth-wall permission
Clear influence and evidence
Memory and adjudication foundations
Media and portability boundary

01 Source-grounded narrative context

The current fiction compiler retains complete effective cast/reference fields and separates persistent ledger truth from a bounded attention selection. It explicitly retrieves relationships, active goals, commitments, resources and resolved records; actor relevance includes both sides of a relationship and established scene actors. A read-only narrative-memory projection joins selected fact events to their exact original evidence on the chosen ancestry. Initial facts and records without exact quotes are labelled accordingly; owner assertions, submitted input and narration remain distinct sources. No derived claim becomes a new canonical event.

Past structured attempts are recovered from their producing beats, including a refusal superseded by later sufficient grounds. At most twelve relevant attempts are projected; only those selected states are expanded as JSON. Chapter context reads the applicable editorial revision and indexed anchor ordinals, including an empty next chapter, without reconstructing the entire manuscript. Handoff points to changed records, scene source, intentions, unresolved commitments and recorded milestones. Plans do not become completed payoffs.

The final next-move gate follows history/handoff inside the existing two-message JSON request contract. It guides causal NPC activity without crisis/novelty quotas or player authorship. Existing capacity accounting counts every added byte; protected truth/ownership/character anchors are retained or the call is refused. No schema, planner/critic call, autonomous scheduler, accepted-prose rewrite or new save collection is added. Derived context is rebuilt locally from current records.

02 B7 readable books, Bookshelf and reading copies

Gate separates **Make a readable book** from **Keep playing elsewhere**. A book uses the viewed path and inspection moment without activating it. Set title, author credit, language and optional front/back matter. Details are private server drafts and recover after reload; edits invalidate the current preview. Preview shows contents, included cover/placed art, sample prose and exclusions. Empty planned groups, Ask, directions, private references, other paths and audio do not enter the frozen PublicationDocument. Prose itself may contain fictional secrets.

Build frozen edition renders selected formats or all nine locally: DOCX, ODT, RTF, EPUB, PDF, HTML, Markdown, plain text and JSON. Every adapter uses the same immutable source. EPUB places art on a separate page immediately before its prose. A build is a durable job, independent of later story changes. Reopen a retained edition to inspect/cancel a running job. Restart marks abandoned jobs interrupted; navigation/restart never silently rebuilds. A partial failure retains successful formats. Missing/damaged files remain unavailable until an explicit local build; verified identical files can be reused for free. Earlier editions stay frozen.

Bookshelf loads bounded pages of retained books, audio and owner-only story art. Filter the collection, download available formats, play prepared MP3, or return to the source story. Older source, interrupted jobs and unavailable bytes are labelled. Loading the collection starts no renderer, model request or full-story download. Removing a book edition revokes its links and releases only files with no other edition pins. Source fiction remains intact. Private `.inkmorrow5` saves preserve all paths and source images, but exclude prepared books/audio, jobs and reading-link authority. Download prepared editions separately.

Reading links appear only when an administrator configures `PUBLIC_SHARE_BASE_URL` as an HTTP(S) origin and separately provides reachable hosting/allowed-host/proxy configuration. Local export works with sharing unconfigured. Review the exact frozen contents, choose expiry and explicitly create a link. Anyone possessing it can read that copy until expiry/revocation; downloaded copies cannot be retracted. Copy the URL, or select it manually if clipboard access fails. Stored link listings show expiry/revocation, never recoverable bearer tokens. Create a new link if lost.

The new current-fiction adapter stores only a SHA-256 capability hash. Its token travels in a URL fragment and an Authorization header, not a query/path or request log. The unauthenticated adapter serves only the immutable reader-safe document; all owner edition/assets/job APIs remain behind owner/origin/CSRF guards. Reader responses and pages use no-store/noindex/no-referrer, render text safely and make no AI call. Retired authoring and legacy share APIs remain disabled in production. This feature supplies no automatic hosting/deployment or promise of public reachability.

Schema 29 is appended without altering earlier migration source checksums. Source snapshots embed bounded art bytes in one synchronous read cut, independent of later media removal. Initial limits: 96 MiB per source, 1,000 sources / 512 MiB aggregate, 20 queued/running jobs, 10,000 retained jobs, 256 MiB per output and 2 GiB available rendered files. GC marks unreferenced files unavailable before unlink; new pins require availability. No story prose, private state or provider spend is rewritten.

03 B6 listening to saved fiction

Desk and Gallery offer **Listen to saved text**. Choose the configured MP3-capable Narrator voice, Read aloud, Auto-read or an audiobook edition, and a saved passage, path, chapter or volume. **Preview listening plan (free)** freezes that selection and shows segment counts, cached reuse, maximum synthesis calls and exposure. Only selected narrative prose goes to the Narrator: no Ask, private references, owner directions, correction records or sibling paths. Generated prose itself may contain fictional secrets; this is not semantic spoiler filtering.

A new purchase needs consent scoped to that immutable plan. Synthesis is sequential, with no transport retry, recursive splitting or purchased PCM fallback. Read aloud caps at 16 segments; Auto-read/audiobooks at 512. A unit caps at 16 MiB and an edition at 512 MiB. Choose a smaller passage/chapter/volume if preflight rejects the range. There is a 20-job installation queue and a conservative 4 GiB retained-audio quota.

The shared player keeps a labelled source, preparation progress, cancellation and Return action across rooms. Pause/Stop playback differs from **Cancel remaining synthesis**. Voice choice and playback speed are device preferences; changing speed and replaying a cached edition are free. A story/path change pauses Auto-read and requests cancellation of its remaining synthesis. A failed cancellation is reported rather than treated as confirmation. Tap to resume handles browser autoplay refusal without another purchase. Lock clears private playback UI.

Cancellation prevents undispatched units; dispatched work may still cost money and produce reusable cache bytes. Restart interrupts unfinished work without automatic resumption. Review a new plan to reuse completed units and purchase only permitted missing units. A disappeared or corrupt reviewed cache hit fails instead of silently buying a replacement. Retained job status shows known dollars and unknown-cost attempts separately. A late status reply cannot revive a cancelled player display.

Audio editions retain their source and are labelled older when the selected path has moved on. Download the MP3 separately. Private playable saves carry aggregate spend but exclude synthesized audio, listening plans/jobs, credentials and resumable purchase authority. Keep cold installation backups for configured database/media.

04 B5 retained visual collection

Gallery now lists the story-owned image collection in metadata pages of forty, including unplaced uploads and painting results. Thumbnails load lazily; Preview shows the full image, provenance and bounded retained-use metadata. Choose a cover, private reference or ancestral passage before placing an existing image. Placement and removal are local actions; earlier path snapshots and retained collection bytes remain available. New painting is one explicitly reviewed Illustrator purchase. A changed path, cancellation or restart cannot silently attach a late result: validated bytes remain ready and unplaced, and known/unknown spend remains visible. There is no automatic retry or reference-image conditioning.

The existing 400-image story ceiling remains. Every inventory member is an owned retained root; this batch exposes no permanent asset deletion or garbage collection. Playable save v2 carries all owned images and optional inventory descriptions and provenance, but no painting jobs, action keys, consent or provider credentials. Import creates new image identities and a fresh inventory concurrency value.

Visual Library offers selected-reference bundles (`.inkrefs`): worlds, characters and Scribes with normalized images and private lore/motives. Preview names matching existing entries; import always makes independent copies. A repeated identical import action returns the original copies, changed bytes conflict, and deleted results are reported rather than recreated. Bundles omit credentials, purchase journals and image-conditioning permission. They are unencrypted private files, not reader-safe books or full installation backups.

05 B4 editorial architecture

`editorial-migration-v26.js` adds immutable complete-value editorial revisions with parent/producing-beat closure and a snapshot head. `editorial-model.js` represents chapters with after/through narrative anchors and exactly one final open tail. `editorial.js` provides bounded selected-ancestry outline/boundary reads, free preview and one atomic local adoption command through the existing receipt/fence contract. New records cap at 64 volumes, 512 chapters and 64 KiB; aggregate creative/ reference/editorial revisions share the 10,000 cap. Snapshots do not duplicate full layouts or rewrite historical JSON.

Virtual defaults materialize existing episode grouping in memory. Published revision heads resolve only on their selected branch history. Gap fallback groups keep every narrative passage visible. Empty plans create no prose, and future passages enter the active open tail. `editorial-save.js` validates producer/parent/ anchor ancestry and unchanged heads, then supplies a temporary stripped projection to existing B3/frozen-v1 validators. Import remaps revision IDs, parent/producer and passage anchors; layout-local group identities remain scoped to the copied story.

The existing PublicationDocument resolver applies effective groups before any of its nine adapters. Original prose, placed images, exact evidence, episode phase and scene framing keep their own authority. Wording/display overlays remain D1-gated. Chronicle has a paged historical outline and the full-height private editor; late callbacks are fenced on Close/Back/room changes/Lock. See B4-DELIVERY.md and genuine schema-25 fixtures for preservation evidence. All six PDFs are regenerated together at this final checkpoint.

06 B3 creative and narration architecture

Schema 25 appends `creative-migration-v25.js`. `creative-collections.js` owns immutable story-local configuration/reference revisions, deterministic legacy baselines, optimistic local commands, receipts and cancellation fences. Snapshots store revision heads; effective state overlays references for current/historical views. Template provenance is inert, never a live foreign reference. Adopting a reference creates no canonical event. Typed campaign sections reuse existing fact kinds, visibility, knowledge and evidence.

`context-compiler.js` resolves ownership, branch truth/knowledge, current intent, established scene, creative settings, Scribe craft and provisional opportunities. Recent narrative links survive intervening local/Ask records; stable fact IDs retrieve older selected constraints outside the compact working set. Preflight removes whole older passages if needed while retaining binding authority/latest prose. `generation-plan.js` checks every potential quality stage against declared model context/output capacities before dispatch. Serialized UTF-8 bytes plus protocol overhead form a conservative bound, not tokenizer precision. Actual stages recheck reviewed capacities and fixed output/reasoning allowances.

`narrative-assembly.js` separates ordinary narration, owner-authorized performed Say and asides. Exact segment hashes/ranges, occurrence status and paragraph boundary preserve the owner's words and support evidence exclusion. Response v2 classifies intention/attempt/reported claim/event and actual goal outcomes. The opportunity scheduler nominates categories independently of fact cardinality. `creative-save.js` validates producers, parents, subject/ancestry, complete shapes, bindings, unchanged baselines/heads and source closure before import remaps IDs. Frozen save-v1 modules and migration 24 remain untouched. See B3-DELIVERY.md for limits and fixtures; current source manuals and PDFs are updated together.

07 Product and system context

The durable product is one readable story with alternate paths, not a transcript that must later be converted into canon. The normal player is a reader-director outside the cast. Follow and Steer are complete experiences; Inhabit grants explicit control of one cast member and can be released.

An Express process serves static native-JavaScript modules and a protected API. SQLite holds identity, auth, providers and playable state. Normalized raster files live under a configured private media root. Remote models are untrusted proposal generators reached only at reviewed purchase boundaries.

The production composer creates auth, provider and fiction services. It does not instantiate the retired writing, continuity, catalogue, image-backfill, audiobook, transfer or public-share runtime. Current-fiction listening and reading copies are independent active services. legacy-runtime.js is an explicit internal test and reuse seam; server.js always selects legacyEnabled:false.

Historical tables and migrations remain for tested infrastructure reuse. Their presence is not a compatibility promise or a live product surface. The database family is new, and old databases are refused before normal SQLite startup.

No per-character background agent, speculative continuation or offline simulation runs. A player's return does not advance fictional time, and local recaps do not call a provider.

The B1 current-fiction workspace uses `workspace-state.js` for normalized room/task routes and bounded device preferences/bookmarks, and `workspace-shell.js` for the five room adapters and shared contribution sheet. The existing app composes domain actions and preserves one story authority. Same-story room changes keep the lifecycle epoch and paid operation intact; story/global changes invalidate stale callbacks. No legacy runtime or second transcript is mounted.

Bookmarks contain only story/path/passage identities and a relative paragraph anchor, never prose or private facts. Restoration outside the loaded window uses existing ancestry-checked history/evidence reads and validates revision/path before painting. Invalid positions fall back with an explanation. Schema 24 adds indexed ancestry jumps, visible-history links, fact-event projections, immutable exact-source evidence, private owner drafts and local receipts/fences. `workspace-queries.js` separates view path, inspection boundary, presentation head and actual action target. Timeline defaults to 40 records (maximum 80); Codex pages hold 40. Filters run before pagination and context-bound cursors reject a different inspection. Narrative passages exclude Ask/local records. `private-drafts.js` serializes revision-checked writes and stores acknowledged submission identities before dispatch. Drafts, bookmarks and request authority never enter playable saves. Version 2 saves carry new evidence; frozen version-1 validators and dependencies preserve old-save acceptance. Gallery’s complete retained/unplaced collection remains B5 work.

08 Module and responsibility map

Component	Responsibility
server.js / core/storage.js	Environment, safe bind, shared data-path selection
app.js	Security order, service composition, current routers, static delivery
modules/auth and providers	Owner sessions, CSRF, credentials and logical roles
fiction/model.js	Strict domain shapes and deterministic transitions
fiction/store	Immutable history, ancestry, revisions and transactions
fiction/service.js and memory.js	Bounded relevant authoritative context
fiction/resistance.js and director.js	Structured rulings and scene opportunities
fiction/service and quality modules	Reviewed, bounded model work and accounting
fiction/media, gallery, publication, editions, listening, saves	Retained art, frozen books/reading copies, reviewed audio and private copies
fiction/library and library-model	Reusable visual references, frozen setup copies, separate image journal
frontend/app/fiction	Shelf, start, reader, controls, dialogs and route fencing

Stores and domain validators should remain usable with isolated databases and mocked transport. UI components receive their dependencies rather than reimplementing authority checks. Rendering reader state is distinct from the private snapshot sent to a storyteller.

Common publication adapters and raster validation are reused without remounting the old authoring APIs. The canonical SVG lockup is also reused across README, app, authentication and manual rendering; typography is not independently recreated at each surface.

09 Fresh storage and startup order

The release identifies itself as 5.0.0, database family ink-morrow-5, schema 29 and SQLite application ID 0x494D3530. Package identities agree across root, backend, frontend and E2E. Playable saves separately identify their own format and version; these are not interchangeable schema numbers.

Before connecting SQLite to an existing source, preflight copies the database and its WAL/rollback journal into a unique private temporary directory. It does not copy shared memory; SQLite may rebuild that only beside the copy. Regular-file and source-change checks protect the inspection boundary.

Identity markers, supported version, migration ledger, quick_check and foreign keys must pass before the original enters normal WAL/migration/reconciliation. A recognized old family, unknown SQLite file, orphan journal, future version, invalid ledger or failed scratch copy is rejected. No fallback opens an old source merely because scratch space ran out.

The retained migration chain constructs the fresh schema transactionally. Migration rollback preserves the prior ledger/version. This does not make earlier product-family databases upgradeable. Operators must stop other writers; scratch preflight is not a live backup or an adversarial filesystem lock.

The shared storage resolver keeps server and terminal recovery on the same file. Default data is separate from the old series, and in-memory test runs receive disposable media storage rather than writing into the real installation.

10 The playable graph

A game identifies its active branch and optimistic revision. Each branch points to an exact historical head and optional parent/fork moment. Immutable beats link to their parent and carry the resulting state snapshot. Local corrections, preferences, control handoffs and episode actions are history too, distinct from narrated opening/scene prose and outside-story clarification.

A snapshot carries cast, knowledge, facts, commitments, relationships, resources, control, preferences, episode framing, director history, adjudications and image placements. Forking restores that exact state; switching branches does not merge their futures. A bounded reader window is not a lifetime history limit.

Every mutation checks the expected game revision and rejects concurrent changes. A pending paid operation excludes conflicting mutations. Network work runs outside the database transaction; the final commit rechecks ownership, revision, branch and reviewed provider plan before appending one accepted beat.

Initial facts and immutable changes are the authoritative memory history. A current 128-fact snapshot is only a working set. Retrieval chooses current versions on the selected ancestry; corrections supersede and retirement excludes, without deleting historical evidence. Sibling-path events cannot become context.

The graph is also the save boundary. Import validates all identities, references and ancestry before assigning fresh local IDs and committing a new game.

11 Canon commit and spend accounting

A reply begins with validated intent, expected revision and idempotency key. Successful replay returns the existing result without another provider call. Changed input under the same key is rejected. A repeated unchanged structured ruling is resolved locally before provider availability or quality checks.

For new work, the request is journalled, then each actual model call is recorded pending before dispatch. The proposal contains prose plus bounded structured effects. Local validation never makes an intermediate draft canonical. Quality, when enabled, can review and repair within its disclosed ceiling.

Commit appends the accepted beat, derived snapshot, request outcome and accounting in the same transaction after stale checks. Late or invalid output cannot append a scene. Its known charge still counts; uncertainty is represented explicitly rather than rounded to zero.

Per-call rows allow mixed known/unknown charges across one quality sequence. Parent-only historical entries are included only where no call rows exist, so the two accounting layers are not summed twice. Recent reader metadata is bounded and omits rejected prose and reviewer explanations.

Restart interrupts abandoned requests and calls. A late completion may improve the billing record but cannot revive the abandoned operation or bypass a changed story. Recovery reads are free and never invent a replacement purchase.

12 Reader, privacy and asynchronous UI

The static HTML begins gated. Authentication completes before private startup, story requests, provider requests or private rendering. Lock clears story text, cast, facts, drafts and credential fields; route/liveness tokens discard late responses that belong to an old story or locked session.

Controls show immediate loading or busy states before delayed network work. Reviewing and submitting are separate states, both protected against duplicate actions. Cancelling a review preserves the direction; a failed request reconciles through free reads without auto-submitting. Leaving a view does not claim to cancel transport already dispatched.

The reader receives filtered public records, not complete snapshots. Memory and evidence endpoints verify current ancestry and filter private or retired entries before result limits. Source links distinguish local records from narrated proof. Untrusted text is rendered as text, not executable HTML.

Provider context is a different boundary: relevant hidden facts and motives may be deliberately sent to the selected storyteller or reviewers. A model can leak them in prose despite instructions. Reader projection is mechanically filtered; semantic secrecy in generated text is not proven by that filtering.

Books consume the same reader-safe projection across formats. Saves intentionally contain private state and all paths, and therefore require a different exposure description.

13 Limits, performance and extension decisions

Bound	Purpose
24 cast members	Bounded active character context
128 facts in a snapshot	Bounded working set, not erased lifetime history
12 effects per response	Inspectable deterministic mutation
40 paths per story	Bounded alternate-history graph
80 shelf rows per page	Reach all stories without an unbounded response
32 recall results	Useful search without downloading all memory
200 placed moments / 400 retained assets	Bound current and historical art
10,000 moments in a save	Conservative portable-graph processing

Context uses bounded recent prose and relevant historical records rather than whole-manuscript replay. No embeddings server or local background model is required. Limits reject work before purchases where known; they do not justify deleting a player's commitments or pretending an unknown charge is zero.

Future extensions should preserve one authoritative graph, explicit paid authority and distinct reader/provider/save projections. A new optional model call needs a bounded plan, per-call accounting, cancellation/staleness semantics, consent scope and adversarial fixtures.

Do not add a second manual prose workflow, hidden autonomous progression, numerical relationship grinding or compatibility adapters merely to retain old UI vocabulary. Such changes alter the approved game and need a deliberate product decision rather than incidental refactoring.

14 Bounded consistency pipeline

Branch snapshots select quality_mode off, standard, memory or both. A server-owned plan hashes mode, role/provider/model identities, endpoint, timeout and maximum calls into a review identity. Quality replies require that identity. Credentials are never part of the hash or public plan. All required roles are resolved before dispatch and every subsequent boundary; stale story or provider changes abort.

The pipeline proposes a draft, validates its structured effects without mutation, then optionally asks the selected standard and/or memory roles to review it. Reviewers return approval or bounded issues with direct candidate quotations, never canon changes. A single repair uses the original authoritative context. The replacement passes the same structural checks and every selected review. Only the final accepted beat enters the ordinary atomic commit. Model approval does not bypass application-owned adjudication, evidence or character ownership.

Schema 21 adds fiction_calls beneath fiction_requests. Each call has a bounded index, role, purpose, model, status and billing data. Off caps at one call, one reviewer at four, and both at six. Transport retries are disabled. Spend is the union of call rows and legacy parent-only purchases, not their double-counted sum. Mixed known/unknown costs survive failure and restart. Reader APIs expose bounded call metadata, not candidates or review explanations. Saves export aggregate spend and the branch setting, never call/replay identities or consent.

15 People and episode framing

Relationship facts optionally identify a qualitative facet and a directed cast pair. Affection, trust, cooperation and expectations remain independent. The develop effect changes only a relationship's description, with exact passage or input evidence, immutable prior provenance and the inhabited-person boundary. It cannot rewrite world facts, change the facet or grant a challenge.

Episode snapshots hold a public question, up to six public goal identifiers, descriptive phase and a payoff beat. A narrated goal-resolution change can move the episode to payoff; a later scene permits aftermath. No phase changes the player-owned active/ended status. Questions, phases and evidence restore through rewind and copy-import. The director offers rest after a recorded payoff.

The local recap endpoint reads only current ancestry: three narrated summaries, six active public commitments and twelve active public relationships. Kind, visibility and status are filtered before bounded memory selection. No provider, whole-history prompt, autonomous character queue or offline simulation is added.

16 Fourth-wall permission

Living-world snapshots carry a Never/Rarely/Freely preference and the last narrated scene index containing an accepted address. Never is the default; Story-shaping and out-of-story Ask disable character asides. Rarely requires a six-scene index gap; Freely permits consecutive fitting addresses. Preference changes do not reset the cooldown. The same snapshot/save graph preserves it without a separate timer.

The existing narration response may include one bounded structured aside. The server checks permission, cast identity and character ownership, appends the named address to saved prose, and advances its index in the same atomic commit. Effects and challenge evidence are validated against ordinary prose, not appended asides. There is no extra provider request. The protocol cannot prove that unrestricted model prose contains no unstructured fourth-wall language.

17 Clear influence and evidence

Reader directions carry moment or ongoing scope. Only a successful ongoing Steer replaces branch-local focus; one-moment detours and failures do not. Locally derived invitations use public state and fill drafts only. Explicit challenge review is a read-only, revision-checked endpoint: it reveals a prior ruling only when unchanged. Reply commits recheck that same revision, so a free review cannot silently become a newly billable attempt after a concurrent change. A free repeated ruling remains available when a former provider configuration is unavailable.

Public memory search filters before its result bound, and source reads verify active ancestry. Changes can carry an earlier evidence identity; save validation requires it on parent ancestry and import remaps it. The shelf uses bounded 80-story pages instead of silently hiding everything after 200 stories.

18 Memory and adjudication foundations

The bounded snapshot cache is not the only copy of story facts. Immutable initial facts and per-beat changes form a branch-local version history. Retrieval folds the latest version of each fact on the selected ancestry, excludes explicit retirements, ranks relevant entries and returns a bounded result. Working-set compaction drops cached entries only; correction and export preserve their history.

Story-shaping and Living-world are independent of character ownership and severity. Structured challenges define named approaches and explicit evidence requirements. Application code adjudicates from recorded public facts and character knowledge; models receive the decision, not permission to rewrite it. A matching prior basis replays locally without a provider call. The request journal, stale checks and atomic commit still apply. Model-returned outcome/evidence are checked, but this is not a semantic proof that every generated sentence agrees. Open-ended dialogue remains model-dependent and must not be advertised as mechanically adjudicated.

19 Media and portability boundary

The new game owns immutable branch-state illustration placements and story-scoped normalized raster assets. Media never becomes prose or truth. A dedicated Illustrator role uses the game request journal and exact revision/path checks. Upload/description changes remain local. Files are staged under random keys; asset insertion, placement snapshot and terminal paid accounting share one database transaction.

The game projects only the selected ancestry's prose and placements into the existing PublicationDocument. EPUB splits images into individual fixed-layout spine items; prose stays reflowable. All adapters share one privacy-filtered document. Playable saves are separate bounded gzip-JSON graphs carrying every snapshot and image, with no credentials or request authority. Validation uses ancestry intervals to reject future/cross-path evidence before a transactional copy with remapped identities.

The /api/fiction/catalog namespace is independent of the retired catalogue API. Schema 22 adds fiction_templates, fiction_template_assets and image requests; schema 23 adds the separate fiction_template_drafts journal. Entries have revisions, bounded typed fields and one current normalized image. CRUD is local. AI reference development is seed-based, idempotent and capped at two calls only when invalid JSON needs one correction; its result remains unsaved until explicit CRUD. Explicit image generation is single-attempt and accounted. Deletion scrubs content and removes its owned image while retaining both spend journals.

Story creation takes trusted template snapshots and fresh copies of selected images, then inserts the story graph and image ownership in one transaction. Failure discards only its uncommitted copies. There is no live catalogue foreign key in story state. World lore and character motives/background remain private bounded narrator context; public state exposes only visible reference metadata. A Scribe supplies craft, not cast ownership. Catalogue edits cannot rewrite a running story.

Branch-local visuals target cover, world, Scribe or a current cast identity. Historical assets remain available to rewind and saves. Books include the current cover and passage illustrations, not reference portraits or private setup notes.