

Probabilistic Parsing: Issues & Improvement

Deep Processing Techniques for NLP

Ling571

January 25, 2017

Roadmap

- Probabilistic Parsing:
 - PCFG issues
 - Modeling improvements on PCFGs
 - Parent annotation
 - Lexicalization
 - Markovization
 - Reranking
- Efficiency improvements on PCFGs
 - Beam thresholding
 - Heuristic filtering

Issues with PCFGs

- Independence assumptions:
 - Rule expansion is context-independent
 - Allows us to multiply probabilities


- Is this valid?

	Pronoun	Non-pronoun
Subject	91%	9%
Object	34%	66%

- In Treebank: roughly equi-probable
- How can we handle this?
 - Condition on Subj/Obj with parent annotation

Issues with PCFGs

- Insufficient lexical conditioning
 - Present in pre-terminal rules
- Are there cases where other rules should be conditioned on words?



Different verbs & prepositions have different attachment preferences

Parser Issues

- PCFGs make many (unwarranted) independence assumptions
 - Structural Dependency
 - NP →→ Pronoun: much more likely in subject position
 - Lexical Dependency
 - Verb subcategorization
 - Coordination ambiguity

Improving PCFGs: Structural Dependencies

- How can we capture Subject/Object asymmetry?
 - E.g., $NP_{subj} \rightarrow \rightarrow \text{Pron}$ vs $NP_{Obj} \rightarrow \rightarrow \text{Pron}$
- Parent annotation:
 - Annotate each node with parent in parse tree
 - E.g., NP^S vs NP^{VP}
 - Also annotate pre-terminals:
 - RB^{ADVP} vs RB^{VP}
 - IN^{SBAR} vs IN^{PP}
- Can also split rules on other conditions

[illegible]

Parent Annotation

- Advantages:
 - Captures structural dependency in grammars
- Disadvantages:
 - Increases number of rules in grammar
 - Decreases amount of training per rule
- Strategies to search for optimal # of rules


Improving PCFGs: Lexical Dependencies

- Lexicalized rules:
 - Best known parsers: Collins, Charniak parsers
 - Each non-terminal annotated with its lexical head
 - E.g. verb with verb phrase, noun with noun phrase
 - Each rule must identify RHS element as head
 - Heads propagate up tree
 - Conceptually like adding 1 rule per head value
 - $VP(\text{dumped}) \rightarrow \rightarrow VBD(\text{dumped})NP(\text{sacks})PP(\text{into})$
 - $VP(\text{dumped}) \rightarrow \rightarrow VBD(\text{dumped})NP(\text{cats})PP(\text{into})$

Lexicalized PCFGs

- Also, add head tag to non-terminals
 - Head tag: Part-of-speech tag of head word
 - $VP(\text{dumped}) \rightarrow VBD(\text{dumped})NP(\text{sacks})PP(\text{into})$
 - $VP(\text{dumped}, VBD) \rightarrow VBD(\text{dumped}, VBD)NP(\text{sacks}, NNS)PP(\text{into}, IN)$
- Two types of rules:
 - Lexical rules: pre-terminal \rightarrow word
 - Deterministic, probability 1
 - Internal rules: all other expansions
 - Must estimate probabilities

Lexicalized Parse Tree



Internal Rules

Top $\rightarrow\rightarrow$ S(prefer,V)

S(prefer,V) $\rightarrow\rightarrow$ NP(I,Pron) VP(prefer,V)

NP(I,Pron) $\rightarrow\rightarrow$ Pron(I,Pron)

VP(prefer,V) $\rightarrow\rightarrow$ V(prefer,V) NP(flight,NN)

NP(flight,NN) $\rightarrow\rightarrow$ Det(a,Det) Nom(flight,NN)

PP(on,IN) $\rightarrow\rightarrow$ IN(on,IN) NP(NWA,NNP)

Lexical Rules

Pron(I,Pron) $\rightarrow\rightarrow$ I

V(prefer,V) $\rightarrow\rightarrow$ prefer

Det(a,Det) $\rightarrow\rightarrow$ a

NN(flight,NN) $\rightarrow\rightarrow$ flight


IN(on,IN) $\rightarrow\rightarrow$ on

NNP(NWA,NNP) $\rightarrow\rightarrow$ NWA


PLCFGs

- Issue: Too many rules
 - No way to find corpus with enough examples
- (Partial) Solution: Independence assumed
 - Condition rule on
 - Category of LHS, head
 - Condition head on
 - Category of LHS and parent's head

$$P(T, S) = \prod_{n \in T} p(r(n) \mid n, h(n)) * p(h(n) \mid n, h(m(n)))$$



Disambiguation Example



Disambiguation Example

$$\begin{aligned} &P(VP \rightarrow VBDNPPP \mid VP, \textit{dumped}) \\ &= \frac{C(VP(\textit{dumped}) \rightarrow VBDNPPP)}{\sum_{\beta} C(VP(\textit{dumped}) \rightarrow \beta)} \\ &= 6 / 9 = 0.67 \end{aligned}$$

$$\begin{aligned} &p(VP \rightarrow VBDNP \mid VP, \textit{dumped}) \\ &= \frac{C(VP(\textit{dumped}) \rightarrow VBDNP)}{\sum_{\beta} C(VP(\textit{dumped}) \rightarrow \beta)} \\ &= 0 / 9 = 0 \end{aligned}$$


$$\begin{aligned} &p(\textit{int o} \mid PP, \textit{dumped}) \\ &= \frac{C(X(\textit{dumped}) \rightarrow \dots PP(\textit{int o}) \dots)}{\sum_{\beta} C(X(\textit{dumped}) \rightarrow \dots PP \dots)} \\ &= 2 / 9 = 0.22 \end{aligned}$$

$$\begin{aligned} &p(\textit{int o} \mid PP, \textit{sacks}) \\ &= \frac{C(X(\textit{sacks}) \rightarrow \dots PP(\textit{int o}) \dots)}{\sum_{\beta} C(X(\textit{sacks}) \rightarrow \dots PP \dots)} \\ &= 0 / 0 \end{aligned}$$

CNF Factorization & Markovization

- CNF factorization:
 - Converts n-ary branching to binary branching
 - Can maintain information about original structure
 - Neighborhood history and parent
- Issue:
 - Potentially explosive
 - If keep all context: $72 \rightarrow 10K$ non-terminals!!!
- How much context should we keep?
 - What Markov order?

Different Markov Orders



Markovization & Costs

(Mohri & Roark 2006)

PCFG	Time (s)	Words/s	$ V $	$ P $	LR	LP	F
Right-factored	4848	6.7	10105	23220	69.2	73.8	71.5
Right-factored, Markov order-2	1302	24.9	2492	11659	68.8	73.8	71.3
Right-factored, Markov order-1	445	72.7	564	6354	68.0	73.0	70.5
Right-factored, Markov order-0	206	157.1	99	3803	61.2	65.5	63.3
Parent-annotated, Right-factored, Markov order-2	7510	4.3	5876	22444	76.2	78.3	77.2

Improving PCFGs: Tradeoffs

- Tensions:
 - Increase accuracy:
 - Increase specificity
 - E.g. Lexicalizing, Parent annotation, Markovization, etc
 - Increases grammar
 - Increases processing times
 - Increases training data requirements
- How can we balance?

Efficiency

- PCKY is $|G|n^3$
 - Grammar can be huge
 - Grammar can be extremely ambiguous
 - 100s of analyses not unusual, esp. for long sentences
- However, only care about best parses
 - Others can be pretty bad
- Can we use this to improve efficiency?

Beam Thresholding

- Inspired by beam search algorithm
- Assume low probability partial parses unlikely to yield high probability overall
 - Keep only top k most probably partial parses
 - Retain only k choices per cell
 - For large grammars, could be 50 or 100
 - For small grammars, 5 or 10

Heuristic Filtering

- Intuition: Some rules/partial parses are unlikely to end up in best parse. Don't store those in table.
- Exclusions:
 - Low frequency: exclude singleton productions
 - Low probability: exclude constituents x s.t. $p(x) < 10^{-200}$
 - Low relative probability:
 - Exclude x if there exists y s.t. $p(y) > 100 * p(x)$

Reranking

- Issue: Locality
 - PCFG probabilities associated with rewrite rules
 - Context-free grammars
 - Approaches create new rules incorporating context:
 - Parent annotation, Markovization, lexicalization
 - Other problems:
 - Increase rules, sparseness
- Need approach that incorporates broader, global info

Discriminative Parse Reranking

- General approach:
 - Parse using (L)PCFG
 - Obtain top-N parses
 - Re-rank top-N parses using better features
- Discriminative reranking
 - Use arbitrary features in reranker (MaxEnt)
 - E.g. right-branching-ness, speaker identity, conjunctive parallelism, fragment frequency, etc

Reranking Effectiveness

- How can reranking improve?
 - N-best includes the correct parse
- Estimate maximum improvement
 - **Oracle** parse selection
 - Selects correct parse from N-best
 - If it appears
- E.g. Collins parser (2000)
 - Base accuracy: 0.897
 - Oracle accuracy on 50-best: 0.968
- Discriminative reranking: 0.917