

secure boot log

```
ddr pll init OK
nor flash secure boot
NOTICE: Booting Trusted Firmware
NOTICE: BL1: v2.3():V2.0_TO-3-g4ae38097
NOTICE: BL1: Built : 13:39:47, Mar 7 2022
INFO: BL1: RAM 0x19004000 - 0x1900f000
INFO: Using crypto library 'mbed TLS'
INFO: BL1: Loading BL2
INFO: Using FIP in nor flash mode
INFO: Loading image id=6 at address 0x80040000
INFO: nor flash security mode
INFO: Image id=6 loaded: 0x405064c - 0x4050abb
INFO: Using FIP in nor flash mode
INFO: Loading image id=1 at address 0x405064c
INFO: nor flash security mode
INFO: Image id=1 loaded: 0x4000088 - 0x405064c
NOTICE: BL1: Booting BL2
INFO: Entry point address = 0x4000088
INFO: SPSR = 0x1d3
```

```
memory dont need repair
memory dont need repair
flash lock: changed status reg 0x0 to 0x1c
disable quad mode
flash status is 1c, 2, 0
SF: Detected W25Q128FV with page size 256 Bytes, erase size 64 KiB, total 16 MiB
MMC: timeout:10000
timeout:10000
timeout:10000
Card did not respond to voltage select!
rtsmmc: 0
## Checking for 'FDT'/'FDT Image' at 83775e80
Using 'config@1' configuration
Verifying Hash Integrity ... OK
Data Start: 0x83775f34
Verifying Hash Integrity ... sha256,rsa2048:verity_key1+ OK
TIMEOUT: 1000000
```

```
## Loading kernel from FIT Image at 80400000 ...
Using 'config@1' configuration
Verifying Hash Integrity ... OK
Trying 'kernel@1' kernel subimage
Description: Linux kernel
Created: 2024-11-16 3:17:08 UTC
Type: Kernel Image
Compression: uncompressed
Data Start: 0x804000c0
Data Size: 3375776 Bytes = 3.2 MiB
Architecture: ARM
OS: Linux
Load Address: 0x81000000
Entry Point: 0x81000000
Sign algo: sha256,rsa2048:verity_key1
Sign value: 0523bcba866457b5a37e07d55320a853e260524af013ef6e420141e6be66fecf81a6f5b7d1fef2a2b94e223abc9975e954a2ee25bd01d81abf099f851c7ee1847f642fba7bf717abf7c6a8f
Timestamp: unavailable
Verifying Hash Integrity ... sha256,rsa2048:verity_key1+ OK
## Flattened Device Tree blob at 03775f34
Booting using the fdt blob at 0x83775f34
Loading Kernel Image
OK
```