# Swagger

1inch Orderbook API

GET https://api.1inch.dev/orderbook/v4.0/{chain}/address/{address}

Get limit orders belonging to the specified address

Network

◆ Ethereum ⌄

Parameters

chain number * (path)

```
1
```

address string * (path)

address in hexadecimal format

```
0x1234567890ABCDEF1234567890ABCDEF
```

page number (query)

Pagination step, default: 1 (page = offset / limit)

```
1
```

limit integer (query)

Number of limit orders to receive (default: 100, max: 500)

```
100
```

statuses string (query)

A comma-separated list of statuses by which limit orders will be filtered. Valid statuses include: 1 - Valid orders, 2 - Temporarily invalid orders, 3 - Invalid orders.

```
1,2,3
```

sortBy string (query)

```
⌄
```

takerAsset string (query)

Address of the taker asset

```
0x1234567890ABCDEF1234567890ABCDEF
```

makerAsset string (query)

Address of the maker asset

```
0x1234567890ABCDEF1234567890ABCDEF
```

swagger.response

Code: 200

Array of queried limit orders

Schema:

- ⌄ GetLimitOrdersV4Response object
  - signature * string
  - orderHash * string
  - createDateTime * string
  - remainingMakerAmount * string
 - makerBalance * string
  - makerAllowance * string
  - ⌄ data * any
    - ⌄ allOf[0] LimitOrderV4Data object
      - makerAsset * string
      - takerAsset * string
      - maker * string
      - receiver string
      - makingAmount * string
      - takingAmount * string
      - salt * string
      - extension string
      - makerTraits string
  - makerRate * string
  - takerRate * string
  - isMakerContract * boolean
  - orderInvalidReason * string

Code: 400

Input data is invalid or address is not provided

Schema:

- ⌄ object
  - ⌄ statusCode integer (Enum)
    - 400
  - message string
  - ⌄ error string (Enum)
    - Bad Request

Authorization - API KEY

API KEY

Sign in for automatic API key authentication.

Try it

NodeJS   Python   cURL   Go

```
const axios = require("axios");

async function httpCall() {
  const url =
```

```
  "https://api.1inch.dev/orderbook/v4.0/1/address/0x1234567890ABCDEF1234567890
ABCDEF12345678";

const config = {
  headers: undefined,
  params: {
    page: 1,
    limit: 100,
    statuses: "1,2,3",
    takerAsset: "0x1234567890ABCDEF1234567890ABCDEF12345678",
    makerAsset: "0x1234567890ABCDEF1234567890ABCDEF12345678",
  },
  paramsSerializer: {
    indexes: null,
  },
};
```

Response

Click the try-it button to test your API call and see the real-time response right here.