









Q

SeriesEpochManager

A helper contract to manage nonce with the series

Quick links

Functions

Events

Functions

epoch

```
function epoch(
    address maker,
    uint96 series
) public view returns(uint256)
```

Returns nonce for maker and series

Parameters:

Name	Туре	Description
maker	address	
series	uint96	

Return values

Туре	Description
uint256	Nonce for maker and series

increase Epoch

```
function increaseEpoch(
    uint96 series
) external
```

Advances nonce by one

Parameters:

Name	Туре	Description
series	uint96	

advance Epoch

```
function advanceEpoch(
    uint96 series,
    uint256 amount
) public
```

Advances nonce by specified amount

Parameters:

Name	Туре	Description
series	uint96	
amount	uint256	

epochEquals

```
function epochEquals(
    address maker,
    uint256 series,
    uint256 makerNonce
) public view returns(bool)
```

Checks if maker has specified makerNonce for series

Parameters:

Name	Туре	Description
maker	address	
series	uint256	
makerNonce	uint256	

Return values

Туре	Description
bool	True if maker has specified nonce. Otherwise, false

Events

EpochIncreased

```
event EpochIncreased(
    address indexed maker,
    uint256 series,
    uint256 newNonce
);
```

Emitted when epoch increased

Parameters:

Name	Туре	Description
maker	address	
series	uint256	
newNonce	uint256	



© 2025 1inch Limited Privacy Policy Terms of Service Commercial API Terms of Use