





50 mm Calibration Bar (1:1)

(Bottom: B.Cu) - (100%)

* (Mirrored)






0 10 20 30 40 50



PAGE 2: TOP COPPER LAYER (F.Cu) - NORMAL

[illegible]

* ■■■■■■■■■■ (Normal) ■■■■■■■■■■■■■■■■■■■■■■ GC9A01



PAGE 3: ASSEMBLY MAP & PINOUT GUIDE

(BOM)

■■■■■■■■■■ (Bill of Materials):

- U1: Seed Studio Xiao ESP32-C3 (MCU 2.4GHz)
- DISP1: GC9A01 240x240 Round TFT (7-Pin Header)
- U3: MPU6050 6-Axis IMU (Fall Detector 8-Pin)
- U2_CONN: Pulse Express (MAX32664D/MAX30102 JST-SH 6P)
- BZ1: Active Buzzer 9x5.5mm (3.3V)
- Q1: S8050 NPN Transistor (SOT-23)
- R1, R2: 200k Ω Resistors 1% (0805 SMD - Battery Sense)
- R3: 1k Ω Resistor (0805 SMD - Buzzer Base)
- R4: 100k Ω Resistor (0805 SMD - Pull-Down)
- C1: 100nF Capacitor (0805 SMD - ADC Filter)
- F1: 0.5A Resettable PTC Fuse (1206 SMD)
- SW1: SPDT Slide Switch (PCM12 SMD)
- J1: JST-PH 2-Pin Battery Connector (2.0mm)
- D1: SS14 Schottky Diode (SMA SMD - 5V Boost)

