

QuadOpt

v1.0

Generated by Doxygen 1.8.9.1

Tue May 26 2015 16:54:50

Contents

1	Data Structure Index	1
1.1	Data Structures	1
2	File Index	3
2.1	File List	3
3	Data Structure Documentation	5
3.1	matrix Struct Reference	5
3.1.1	Detailed Description	5
3.1.2	Field Documentation	5
3.1.2.1	columns	5
3.1.2.2	diagonals	5
3.1.2.3	rows	5
3.1.2.4	size	5
3.1.2.5	start	5
3.2	problem Struct Reference	5
3.2.1	Detailed Description	6
3.2.2	Field Documentation	6
3.2.2.1	A	6
3.2.2.2	accuracy	6
3.2.2.3	active_set	6
3.2.2.4	b	7
3.2.2.5	check_time	7
3.2.2.6	constraints_count	7
3.2.2.7	E	7
3.2.2.8	equality_count	7
3.2.2.9	F	7
3.2.2.10	g	7
3.2.2.11	gk	7
3.2.2.12	h	7
3.2.2.13	has_solution	7
3.2.2.14	has_start_point	7

3.2.2.15	inequality_count	7
3.2.2.16	is_sparse	8
3.2.2.17	lagrange	8
3.2.2.18	max_iter	8
3.2.2.19	max_micro_sec	8
3.2.2.20	p	8
3.2.2.21	Q	8
3.2.2.22	q	8
3.2.2.23	Q_inv	8
3.2.2.24	solution	8
3.2.2.25	solution_value	8
3.2.2.26	sparse_A	8
3.2.2.27	sparse_E	8
3.2.2.28	sparse_F	8
3.2.2.29	sparse_Q	8
3.2.2.30	sparse_Q_inv	8
3.2.2.31	step	8
3.2.2.32	variable_count	8
3.2.2.33	z	9
3.2.2.34	z0	9
3.3	sparse_matrix Struct Reference	9
3.3.1	Detailed Description	9
3.3.2	Field Documentation	9
3.3.2.1	A	9
3.3.2.2	cA	9
3.3.2.3	columns	9
3.3.2.4	rA	9
3.3.2.5	rows	9
3.3.2.6	size	9
3.4	work_set Struct Reference	9
3.4.1	Detailed Description	10
3.4.2	Field Documentation	10
3.4.2.1	count	10
3.4.2.2	data	10
3.4.2.3	max_count	10
4	File Documentation	11
4.1	TDDD77/matlab/quadopt.c File Reference	11
4.1.1	Function Documentation	11
4.1.1.1	mexFunction	11

4.2	TDDD77/matrixlibrary/include/matLib.h File Reference	11
4.2.1	Macro Definition Documentation	13
4.2.1.1	DOUBLE	13
4.2.1.2	FORMAT_STRING	13
4.2.1.3	PRECISION	13
4.2.2	Typedef Documentation	13
4.2.2.1	matrix	13
4.2.2.2	value	13
4.2.3	Function Documentation	13
4.2.3.1	add_matrices	13
4.2.3.2	add_matrices_with_return	14
4.2.3.3	add_rows	14
4.2.3.4	check_boundaries	14
4.2.3.5	compare_elements	14
4.2.3.6	compare_matrices	14
4.2.3.7	create_identity_matrix	14
4.2.3.8	create_matrix	14
4.2.3.9	create_zero_matrix	14
4.2.3.10	crout	14
4.2.3.11	derivate_matrix_with_return	14
4.2.3.12	divide_column_with_scalar	14
4.2.3.13	divide_matrix_with_scalar	14
4.2.3.14	divide_row_with_scalar	15
4.2.3.15	dot_product	15
4.2.3.16	first_nonzero_in_column_index	15
4.2.3.17	first_nonzero_in_row_index	15
4.2.3.18	forward_backward	15
4.2.3.19	free_matrix	15
4.2.3.20	gauss_jordan	15
4.2.3.21	gauss_jordan_solver	15
4.2.3.22	get_column_vector	15
4.2.3.23	get_column_vector_with_return	15
4.2.3.24	get_determinant	15
4.2.3.25	get_diagonal	15
4.2.3.26	get_inverse	16
4.2.3.27	get_inverse_of_2x2	16
4.2.3.28	get_inverse_of_2x2_with_return	16
4.2.3.29	get_matrix_with_only_pivots	16
4.2.3.30	get_row_vector	16
4.2.3.31	get_row_vector_with_return	16

4.2.3.32	get_sub_matrix	16
4.2.3.33	get_value	16
4.2.3.34	get_value_without_check	16
4.2.3.35	get_zero_matrix	16
4.2.3.36	insert_array	16
4.2.3.37	insert_column_vector	16
4.2.3.38	insert_row_vector	16
4.2.3.39	insert_sub_matrix	17
4.2.3.40	insert_value	17
4.2.3.41	insert_value_without_check	17
4.2.3.42	is_matrix	17
4.2.3.43	is_non_negative_diagonal_matrix	17
4.2.3.44	is_non_negative_matrix	17
4.2.3.45	is_zero_matrix	17
4.2.3.46	largest_element_in_column_index	17
4.2.3.47	least_square	17
4.2.3.48	matlib_fabs	17
4.2.3.49	matrix_contains	17
4.2.3.50	matrix_copy	17
4.2.3.51	matrix_copy_data	17
4.2.3.52	min	18
4.2.3.53	multiply_column_with_scalar	18
4.2.3.54	multiply_matrices	18
4.2.3.55	multiply_matrices_naive	18
4.2.3.56	multiply_matrices_optimized	18
4.2.3.57	multiply_matrices_with_return	18
4.2.3.58	multiply_matrix_with_scalar	18
4.2.3.59	multiply_row_with_scalar	18
4.2.3.60	print_matrix	18
4.2.3.61	product_of_column	18
4.2.3.62	product_of_row	18
4.2.3.63	smallest_element_in_column_index	18
4.2.3.64	solve_linear	18
4.2.3.65	solve_linear_with_return	19
4.2.3.66	strassen_matrices	19
4.2.3.67	strassen_matrices_with_return	19
4.2.3.68	subtract_matrices	19
4.2.3.69	subtract_matrices_with_return	19
4.2.3.70	sum_of_column	19
4.2.3.71	sum_of_row	19

4.2.3.72	switch_rows	19
4.2.3.73	transform_to_reduced_row_echelon_form	19
4.2.3.74	transpose_matrix	19
4.2.3.75	transpose_matrix_with_return	19
4.3	TDDD77/matrixlibrary/include/sparse_lib.h File Reference	19
4.3.1	Typedef Documentation	20
4.3.1.1	sparse_matrix	20
4.3.2	Function Documentation	20
4.3.2.1	conjugate_gradient	20
4.3.2.2	copy_sparse_matrix	20
4.3.2.3	create_empty_sparse_matrix	20
4.3.2.4	create_sparse_matrix	20
4.3.2.5	free_sparse_matrix	20
4.3.2.6	matrix_sparsity	20
4.3.2.7	multiply_sparse_matrix_matrix	20
4.3.2.8	multiply_sparse_matrix_vector	21
4.3.2.9	print_sparse_matrix	21
4.3.2.10	sparse_to_normal	21
4.3.2.11	transpose_sparse_matrix	21
4.3.2.12	transpose_sparse_matrix_with_return	21
4.4	TDDD77/matrixlibrary/src/matLib.c File Reference	21
4.4.1	Function Documentation	23
4.4.1.1	add_matrices	23
4.4.1.2	add_matrices_with_return	23
4.4.1.3	add_rows	23
4.4.1.4	check_boundaries	23
4.4.1.5	compare_elements	23
4.4.1.6	compare_matrices	23
4.4.1.7	create_identity_matrix	23
4.4.1.8	create_matrix	23
4.4.1.9	create_zero_matrix	23
4.4.1.10	crout	23
4.4.1.11	derivate_matrix_with_return	23
4.4.1.12	divide_column_with_scalar	23
4.4.1.13	divide_matrix_with_scalar	24
4.4.1.14	divide_row_with_scalar	24
4.4.1.15	dot_product	24
4.4.1.16	first_nonzero_in_column_index	24
4.4.1.17	first_nonzero_in_row_index	24
4.4.1.18	forward_backward	24

4.4.1.19	<code>free_matrix</code>	24
4.4.1.20	<code>gauss_jordan</code>	24
4.4.1.21	<code>gauss_jordan_solver</code>	24
4.4.1.22	<code>get_column_vector</code>	24
4.4.1.23	<code>get_column_vector_with_return</code>	24
4.4.1.24	<code>get_determinant</code>	24
4.4.1.25	<code>get_diagonal</code>	25
4.4.1.26	<code>get_inverse</code>	25
4.4.1.27	<code>get_inverse_of_2x2</code>	25
4.4.1.28	<code>get_inverse_of_2x2_with_return</code>	25
4.4.1.29	<code>get_matrix_with_only_pivots</code>	25
4.4.1.30	<code>get_row_vector</code>	25
4.4.1.31	<code>get_row_vector_with_return</code>	25
4.4.1.32	<code>get_sub_matrix</code>	25
4.4.1.33	<code>get_value</code>	25
4.4.1.34	<code>get_value_without_check</code>	25
4.4.1.35	<code>get_zero_matrix</code>	25
4.4.1.36	<code>insert_array</code>	25
4.4.1.37	<code>insert_column_vector</code>	25
4.4.1.38	<code>insert_row_vector</code>	26
4.4.1.39	<code>insert_sub_matrix</code>	26
4.4.1.40	<code>insert_value</code>	26
4.4.1.41	<code>insert_value_without_check</code>	26
4.4.1.42	<code>is_matrix</code>	26
4.4.1.43	<code>is_non_negative_diagonal_matrix</code>	26
4.4.1.44	<code>is_non_negative_matrix</code>	26
4.4.1.45	<code>is_zero_matrix</code>	26
4.4.1.46	<code>largest_element_in_column_index</code>	26
4.4.1.47	<code>least_square</code>	26
4.4.1.48	<code>matlib_fabs</code>	26
4.4.1.49	<code>matrix_contains</code>	26
4.4.1.50	<code>matrix_copy</code>	26
4.4.1.51	<code>matrix_copy_data</code>	27
4.4.1.52	<code>min</code>	27
4.4.1.53	<code>multiply_column_with_scalar</code>	27
4.4.1.54	<code>multiply_matrices</code>	27
4.4.1.55	<code>multiply_matrices_naive</code>	27
4.4.1.56	<code>multiply_matrices_optimized</code>	27
4.4.1.57	<code>multiply_matrices_with_return</code>	27
4.4.1.58	<code>multiply_matrix_with_scalar</code>	27

4.4.1.59	multiply_row_with_scalar	27
4.4.1.60	print_matrix	27
4.4.1.61	product_of_column	27
4.4.1.62	product_of_row	27
4.4.1.63	smallest_element_in_column_index	27
4.4.1.64	solve_linear	28
4.4.1.65	solve_linear_with_return	28
4.4.1.66	strassen_matrices	28
4.4.1.67	strassen_matrices_with_return	28
4.4.1.68	subtract_matrices	28
4.4.1.69	subtract_matrices_with_return	28
4.4.1.70	sum_of_column	28
4.4.1.71	sum_of_row	28
4.4.1.72	switch_rows	28
4.4.1.73	transform_to_reduced_row_echelon_form	28
4.4.1.74	transpose_matrix	28
4.4.1.75	transpose_matrix_with_return	28
4.5	TDDD77/matrixlibrary/src/sparse_lib.c File Reference	28
4.5.1	Function Documentation	29
4.5.1.1	conjugate_gradient	29
4.5.1.2	copy_sparse_matrix	29
4.5.1.3	create_empty_sparse_matrix	29
4.5.1.4	create_sparse_matrix	29
4.5.1.5	free_sparse_matrix	29
4.5.1.6	matrix_sparsity	29
4.5.1.7	multiply_sparse_matrix_matrix	29
4.5.1.8	multiply_sparse_matrix_vector	29
4.5.1.9	print_sparse_matrix	30
4.5.1.10	sparse_to_normal	30
4.5.1.11	transpose_sparse_matrix	30
4.5.1.12	transpose_sparse_matrix_with_return	30
4.6	TDDD77/quadopt/include/problem.h File Reference	30
4.6.1	Typedef Documentation	31
4.6.1.1	problem	31
4.6.2	Function Documentation	31
4.6.2.1	create_problem	31
4.6.2.2	free_problem	31
4.6.2.3	get_active_conditions	31
4.6.2.4	get_active_conditions_rhs	31
4.6.2.5	get_solution_value	31

4.6.2.6	get_sparse_active_conditions	31
4.6.2.7	is_feasible_point	31
4.6.2.8	print_problem	31
4.6.2.9	print_solution	31
4.6.2.10	time_to_exit	31
4.7	TDDD77/quadopt/include/simplex.h File Reference	31
4.7.1	Function Documentation	32
4.7.1.1	simplex_phase_1	32
4.8	TDDD77/quadopt/include/solver.h File Reference	32
4.8.1	Function Documentation	32
4.8.1.1	quadopt_solver	32
4.8.1.2	remove_constraint	32
4.9	TDDD77/quadopt/include/subproblem.h File Reference	32
4.9.1	Function Documentation	32
4.9.1.1	solve_subproblem	32
4.10	TDDD77/quadopt/include/trans_con.h File Reference	32
4.10.1	Function Documentation	33
4.10.1.1	create_objective	33
4.10.1.2	trans_dyn_cons	33
4.10.1.3	trans_ineq_cons	33
4.11	TDDD77/quadopt/include/work_set.h File Reference	33
4.11.1	Typedef Documentation	33
4.11.1.1	work_set	33
4.11.2	Function Documentation	33
4.11.2.1	work_set_append	33
4.11.2.2	work_set_clear	34
4.11.2.3	work_set_contains	34
4.11.2.4	work_set_create	34
4.11.2.5	work_set_free	34
4.11.2.6	work_set_print	34
4.11.2.7	work_set_remove	34
4.12	TDDD77/quadopt/src/problem.c File Reference	34
4.12.1	Function Documentation	34
4.12.1.1	create_problem	34
4.12.1.2	fill_constraint_matrices	35
4.12.1.3	free_problem	35
4.12.1.4	get_active_conditions	35
4.12.1.5	get_active_conditions_rhs	35
4.12.1.6	get_solution_value	35
4.12.1.7	get_sparse_active_conditions	35

4.12.1.8	is_feasible_point	35
4.12.1.9	print_problem	35
4.12.1.10	print_solution	35
4.12.1.11	time_to_exit	35
4.13	TDDD77/quadopt/src/simplex.c File Reference	35
4.13.1	Function Documentation	36
4.13.1.1	convert_geq_to_leq	36
4.13.1.2	create_basis	36
4.13.1.3	insert_constraints	36
4.13.1.4	insert_objective_function	36
4.13.1.5	insert_simplex_variables	36
4.13.1.6	is_neg_tableau_row	36
4.13.1.7	min_test	36
4.13.1.8	neg_equality	36
4.13.1.9	remove_variables	36
4.13.1.10	set_variables	36
4.13.1.11	simplex_min	36
4.13.1.12	simplex_phase_1	36
4.13.1.13	split_eq_variables	36
4.13.1.14	split_ineq_variables	36
4.14	TDDD77/quadopt/src/solver.c File Reference	36
4.14.1	Function Documentation	37
4.14.1.1	copy_solution	37
4.14.1.2	fill_active_set	37
4.14.1.3	prefill_set	37
4.14.1.4	quadopt_solver	37
4.14.1.5	remove_constraint	37
4.14.1.6	take_step	37
4.15	TDDD77/quadopt/src/subproblem.c File Reference	37
4.15.1	Function Documentation	37
4.15.1.1	KKT_sub	37
4.15.1.2	KKT_sub_sparse	37
4.15.1.3	range_space	37
4.15.1.4	range_space_sparse	37
4.15.1.5	solve_subproblem	37
4.16	TDDD77/quadopt/src/trans_con.c File Reference	37
4.16.1	Function Documentation	38
4.16.1.1	create_objective	38
4.16.1.2	fix_g	38
4.16.1.3	insert_A_matrices	38

4.16.1.4	insert_B_matrices	38
4.16.1.5	insert_fx	38
4.16.1.6	insert_identity_matrices	38
4.16.1.7	insert_u_identity_matrices	38
4.16.1.8	insert_x_identity_matrices	38
4.16.1.9	trans_dyn_cons	38
4.16.1.10	trans_ineq_cons	38
4.17	TDDD77/quadopt/src/work_set.c File Reference	38
4.17.1	Function Documentation	39
4.17.1.1	work_set_append	39
4.17.1.2	work_set_clear	39
4.17.1.3	work_set_contains	39
4.17.1.4	work_set_create	39
4.17.1.5	work_set_free	39
4.17.1.6	work_set_print	39
4.17.1.7	work_set_remove	39

Chapter 1

Data Structure Index

1.1 Data Structures

Here are the data structures with brief descriptions:

matrix	5
problem	5
sparse_matrix	9
work_set	9

Chapter 2

File Index

2.1 File List

Here is a list of all files with brief descriptions:

TDDD77/matlab/ quadopt.c	11
TDDD77/matrixlibrary/include/ matLib.h	11
TDDD77/matrixlibrary/include/ sparse_lib.h	19
TDDD77/matrixlibrary/src/ matLib.c	21
TDDD77/matrixlibrary/src/ sparse_lib.c	28
TDDD77/quadopt/include/ problem.h	30
TDDD77/quadopt/include/ simplex.h	31
TDDD77/quadopt/include/ solver.h	32
TDDD77/quadopt/include/ subproblem.h	32
TDDD77/quadopt/include/ trans_con.h	32
TDDD77/quadopt/include/ work_set.h	33
TDDD77/quadopt/src/ problem.c	34
TDDD77/quadopt/src/ simplex.c	35
TDDD77/quadopt/src/ solver.c	36
TDDD77/quadopt/src/ subproblem.c	37
TDDD77/quadopt/src/ trans_con.c	37
TDDD77/quadopt/src/ work_set.c	38

Chapter 3

Data Structure Documentation

3.1 matrix Struct Reference

```
#include <matLib.h>
```

Data Fields

- `size_t` [columns](#)
- `size_t` [rows](#)
- `size_t` [size](#)
- `value * start`
- `bool` [diagonals](#)

3.1.1 Detailed Description

Uncomment to allow parallel operations This is the core-struct in this library. All matrix-operations are based on this Struct.

3.1.2 Field Documentation

3.1.2.1 `size_t` [columns](#)

3.1.2.2 `bool` [diagonals](#)

3.1.2.3 `size_t` [rows](#)

3.1.2.4 `size_t` [size](#)

3.1.2.5 `value*` [start](#)

The documentation for this struct was generated from the following file:

- TDDD77/matrixlibrary/include/[matLib.h](#)

3.2 problem Struct Reference

```
#include <problem.h>
```

Data Fields

- `matrix * Q`
- `matrix * Q_inv`
- `sparse_matrix * sparse_Q`
- `sparse_matrix * sparse_Q_inv`
- `bool is_sparse`
- `matrix * q`
- `size_t variable_count`
- `size_t equality_count`
- `matrix * E`
- `sparse_matrix * sparse_E`
- `matrix * h`
- `size_t inequality_count`
- `matrix * F`
- `sparse_matrix * sparse_F`
- `matrix * g`
- `matrix * A`
- `sparse_matrix ** sparse_A`
- `matrix * b`
- `size_t constraints_count`
- `bool has_start_point`
- `matrix * z0`
- `matrix * z`
- `matrix * solution`
- `value solution_value`
- `bool has_solution`
- `matrix * p`
- `matrix * gk`
- `value step`
- `matrix * lagrange`
- `work_set * active_set`
- `value accuracy`
- `int max_iter`
- `int max_micro_sec`
- `bool check_time`

3.2.1 Detailed Description

Allocates the problem and sets all necessary variables

3.2.2 Field Documentation

3.2.2.1 `matrix* A`

All constraints left-hand side coefficients.

3.2.2.2 `value accuracy`

3.2.2.3 `work_set* active_set`

The active constraints.

3.2.2.4 matrix* b

All constraints right-hand side constraints.

3.2.2.5 bool check_time**3.2.2.6 size_t constraints_count**

Total number of constraints.

3.2.2.7 matrix* E

Equality constraints left-hand side coefficient.

3.2.2.8 size_t equality_count

Number of equality constraints (Rows in the equality constraints matrices).

3.2.2.9 matrix* F

Larger-than constraints left-hand side coefficient.

3.2.2.10 matrix* g

Larger-than constraints right-hand side constraint.

3.2.2.11 matrix* gk

$gk = Qz + q$, help matrix for the subproblem.

See also

[Q](#)
[z](#)
[q](#)

3.2.2.12 matrix* h

Equality constraints right-hand side constraint.

3.2.2.13 bool has_solution**3.2.2.14 bool has_start_point****3.2.2.15 size_t inequality_count**

Number of larger-than constraints (Rows in the larger-than constraints matrices).

3.2.2.16 `bool is_sparse`

3.2.2.17 `matrix* lagrange`

The lagrange multipliers.

3.2.2.18 `int max_iter`

3.2.2.19 `int max_micro_sec`

3.2.2.20 `matrix* p`

Current step direction towards the solution.

3.2.2.21 `matrix* Q`

The matrix containing the quadratic optimization problem.

3.2.2.22 `matrix* q`

The matrix containing the linear optimization problem.

3.2.2.23 `matrix* Q_inv`

Q inverse.

3.2.2.24 `matrix* solution`

The final point in the solution.

3.2.2.25 `value solution_value`

The value of the solution point.

3.2.2.26 `sparse_matrix** sparse_A`

3.2.2.27 `sparse_matrix* sparse_E`

3.2.2.28 `sparse_matrix* sparse_F`

3.2.2.29 `sparse_matrix* sparse_Q`

3.2.2.30 `sparse_matrix* sparse_Q_inv`

3.2.2.31 `value step`

How far we will step towards the solution.

3.2.2.32 `size_t variable_count`

The number of variables in the problem.

3.2.2.33 `matrix* z`

The current point in the solution.

3.2.2.34 `matrix* z0`

The starting point for the solution.

The documentation for this struct was generated from the following file:

- TDDD77/quadopt/include/[problem.h](#)

3.3 `sparse_matrix` Struct Reference

```
#include <sparse_lib.h>
```

Data Fields

- `size_t` [size](#)
- `size_t` [rows](#)
- `size_t` [columns](#)
- `value *` [A](#)
- `size_t *` [rA](#)
- `size_t *` [cA](#)

3.3.1 Detailed Description

Store sparse matrix using COO (coordinate list)

3.3.2 Field Documentation

3.3.2.1 `value* A`

3.3.2.2 `size_t* cA`

3.3.2.3 `size_t columns`

3.3.2.4 `size_t* rA`

3.3.2.5 `size_t rows`

3.3.2.6 `size_t size`

The documentation for this struct was generated from the following file:

- TDDD77/matrixlibrary/include/[sparse_lib.h](#)

3.4 `work_set` Struct Reference

```
#include <work_set.h>
```

Data Fields

- `size_t` [max_count](#)
- `size_t` [count](#)
- `size_t` * [data](#)

3.4.1 Detailed Description

Structure for storing different sets

3.4.2 Field Documentation

3.4.2.1 `size_t` count

Number of elements in the work set.

3.4.2.2 `size_t`* data

Array of elements in the work set.

3.4.2.3 `size_t` max_count

Maximum number of elements in the work set

The documentation for this struct was generated from the following file:

- [TDDD77/quadopt/include/work_set.h](#)

Chapter 4

File Documentation

4.1 TDDD77/matlab/quadopt.c File Reference

```
#include "mex.h"
#include "../quadopt/include/solver.h"
#include "../quadopt/include/problem.h"
```

Functions

- void [mexFunction](#) (int *nlhs*, mxArray **plhs*[], int *nrhs*, const mxArray **prhs*[])

4.1.1 Function Documentation

4.1.1.1 void [mexFunction](#) (int *nlhs*, mxArray * *plhs*[], int *nrhs*, const mxArray * *prhs*[])

This functions creates an interface between MATLAB and the solver together with the matrixlibrary. It also converts MATLAB structured matrices into the matrixlibrary structure.

4.2 TDDD77/matrixlibrary/include/matLib.h File Reference

```
#include <stdio.h>
#include <stdlib.h>
#include <stdbool.h>
#include <string.h>
```

Data Structures

- struct [matrix](#)

Macros

- #define [DOUBLE](#)
- #define [FORMAT_STRING](#) "%f "
- #define [PRECISION](#) 0.0001

Typedefs

- typedef double [value](#)
- typedef struct [matrix](#) [matrix](#)

Functions

- [matrix](#) * [create_matrix](#) (size_t row, size_t col)
- [matrix](#) * [create_zero_matrix](#) (size_t row, size_t col)
- [matrix](#) * [create_identity_matrix](#) (size_t row, size_t col)
- [value](#) [dot_product](#) ([matrix](#) *r, [matrix](#) *v)
- void [free_matrix](#) ([matrix](#) *mat)
- void [print_matrix](#) ([matrix](#) *mat)
- bool [check_boundaries](#) (size_t row, size_t col, [matrix](#) *mat)
- bool [insert_array](#) ([value](#) arr[], [matrix](#) *mat)
- bool [compare_matrices](#) ([matrix](#) *a, [matrix](#) *b)
- bool [is_matrix](#) ([matrix](#) *a, [matrix](#) *b)
- bool [insert_value](#) ([value](#) insert, size_t row, size_t col, [matrix](#) *mat)
- void [insert_value_without_check](#) ([value](#) insert, size_t row, size_t col, [matrix](#) *mat)
- [value](#) [get_value](#) (size_t row, size_t col, [matrix](#) *mat)
- [value](#) [get_value_without_check](#) (size_t row, size_t col, [matrix](#) *mat)
- bool [add_matrices](#) ([matrix](#) *a, [matrix](#) *b, [matrix](#) *c)
- [matrix](#) * [add_matrices_with_return](#) ([matrix](#) *a, [matrix](#) *b)
- bool [subtract_matrices](#) ([matrix](#) *a, [matrix](#) *b, [matrix](#) *c)
- [matrix](#) * [subtract_matrices_with_return](#) ([matrix](#) *a, [matrix](#) *b)
- bool [multiply_matrices](#) ([matrix](#) *a, [matrix](#) *b, [matrix](#) *c)
- bool [multiply_matrices_naive](#) ([matrix](#) *a, [matrix](#) *b, [matrix](#) *c)
- bool [multiply_matrices_optimized](#) ([matrix](#) *a, [matrix](#) *b, [matrix](#) *c)
- [matrix](#) * [strassen_matrices_with_return](#) ([matrix](#) *a, [matrix](#) *b)
- bool [strassen_matrices](#) ([matrix](#) *a, [matrix](#) *b, [matrix](#) *c)
- [matrix](#) * [multiply_matrices_with_return](#) ([matrix](#) *a, [matrix](#) *b)
- [value](#) [get_determinant](#) ([matrix](#) *a)
- bool [get_inverse](#) ([matrix](#) *a, [matrix](#) *c)
- [matrix](#) * [get_inverse_of_2x2_with_return](#) ([matrix](#) *a)
- bool [get_inverse_of_2x2](#) ([matrix](#) *a, [matrix](#) *b)
- bool [solve_linear](#) ([matrix](#) *a, [matrix](#) *x, [matrix](#) *b)
- [matrix](#) * [solve_linear_with_return](#) ([matrix](#) *a, [matrix](#) *b)
- bool [crout](#) ([matrix](#) *a, [matrix](#) *l, [matrix](#) *u)
- void [forward_backward](#) ([matrix](#) *l, [matrix](#) *u, [matrix](#) *x, [matrix](#) *b)
- void [least_square](#) ([matrix](#) *a, [matrix](#) *x, [matrix](#) *b)
- bool [gauss_jordan](#) ([matrix](#) *a)
- bool [gauss_jordan_solver](#) ([matrix](#) *a, [matrix](#) *x, [matrix](#) *b)
- [matrix](#) * [get_matrix_with_only_pivots](#) ([matrix](#) *a)
- [value](#) [min](#) ([value](#) a, [value](#) b)
- size_t [largest_element_in_column_index](#) (size_t column, size_t start, [matrix](#) *a)
- size_t [smallest_element_in_column_index](#) (size_t column, size_t start, [matrix](#) *a)
- size_t [first_nonzero_in_column_index](#) (size_t column, size_t start, [matrix](#) *a)
- size_t [first_nonzero_in_row_index](#) (size_t row, size_t start, [matrix](#) *a)
- void [add_rows](#) (size_t row1, size_t row2, [matrix](#) *a)
- bool [transpose_matrix](#) ([matrix](#) *a, [matrix](#) *b)
- [matrix](#) * [transpose_matrix_with_return](#) ([matrix](#) *a)
- [value](#) [sum_of_row](#) (size_t row, [matrix](#) *mat)
- [value](#) [sum_of_column](#) (size_t column, [matrix](#) *mat)
- [value](#) [product_of_row](#) (size_t row, [matrix](#) *mat)

- [value product_of_column](#) (size_t column, [matrix](#) *mat)
- void [multiply_matrix_with_scalar](#) (value scal, [matrix](#) *mat)
- void [divide_matrix_with_scalar](#) (value scal, [matrix](#) *mat)
- void [multiply_row_with_scalar](#) (value scal, size_t row, [matrix](#) *mat)
- void [divide_row_with_scalar](#) (value scal, size_t row, [matrix](#) *mat)
- void [multiply_column_with_scalar](#) (value scal, size_t col, [matrix](#) *mat)
- void [divide_column_with_scalar](#) (value scal, size_t col, [matrix](#) *mat)
- bool [get_row_vector](#) (size_t row, [matrix](#) *a, [matrix](#) *b)
- [matrix](#) * [get_row_vector_with_return](#) (size_t row, [matrix](#) *a)
- bool [insert_row_vector](#) (size_t row, [matrix](#) *a, [matrix](#) *b)
- bool [switch_rows](#) (size_t row1, size_t row2, [matrix](#) *a)
- bool [get_column_vector](#) (size_t column, [matrix](#) *a, [matrix](#) *b)
- [matrix](#) * [get_column_vector_with_return](#) (size_t column, [matrix](#) *a)
- bool [insert_column_vector](#) (size_t column, [matrix](#) *a, [matrix](#) *b)
- bool [get_sub_matrix](#) (size_t start_row, size_t end_row, size_t start_col, size_t end_col, [matrix](#) *a, [matrix](#) *b)
- bool [insert_sub_matrix](#) (size_t start_row, size_t end_row, size_t start_col, size_t end_col, [matrix](#) *b, [matrix](#) *a)
- [matrix](#) * [matrix_copy](#) ([matrix](#) *source)
- void [matrix_copy_data](#) ([matrix](#) *A, [matrix](#) *B)
- bool [is_zero_matrix](#) ([matrix](#) *v)
- bool [is_non_negative_matrix](#) ([matrix](#) *v)
- bool [is_non_negative_diagonal_matrix](#) ([matrix](#) *A)
- bool [get_diagonal](#) ([matrix](#) *a, [matrix](#) *b)
- [matrix](#) * [derivate_matrix_with_return](#) (size_t var, [matrix](#) *a)
- void [transform_to_reduced_row_echelon_form](#) ([matrix](#) *M)
- bool [matrix_contains](#) (value a, [matrix](#) *b)
- int [compare_elements](#) (value a, value b)
- [matrix](#) * [get_zero_matrix](#) (size_t rows, size_t columns)
- value [matlib_fabs](#) (value a)

4.2.1 Macro Definition Documentation

4.2.1.1 #define DOUBLE

Only standardlibraries Uncomment which mode you want the library to run in

4.2.1.2 #define FORMAT_STRING "%f "

4.2.1.3 #define PRECISION 0.0001

4.2.2 Typedef Documentation

4.2.2.1 typedef struct matrix matrix

4.2.2.2 typedef double value

Setup for the preprocessor depending on mode

4.2.3 Function Documentation

4.2.3.1 bool add_matrices ([matrix](#) * a, [matrix](#) * b, [matrix](#) * c)

Adds a and b into c

4.2.3.2 `matrix* add_matrices_with_return (matrix * a, matrix * b)`

Adds a and b by returning a pointer a matrix with a+b

4.2.3.3 `void add_rows (size_t row1, size_t row2, matrix * a)`

Adds each element in row1 and row 2 and puts the result on row2

4.2.3.4 `bool check_boundaries (size_t row, size_t col, matrix * mat)`

Checks if the position exists in the matrix

4.2.3.5 `int compare_elements (value a, value b)`

Compare two element values

4.2.3.6 `bool compare_matrices (matrix * a, matrix * b)`

Returns true if matrices a and b look the same

4.2.3.7 `matrix* create_identity_matrix (size_t row, size_t col)`

Creates a identity matrix

4.2.3.8 `matrix* create_matrix (size_t row, size_t col)`

Create a matrix

4.2.3.9 `matrix* create_zero_matrix (size_t row, size_t col)`

Is normally not needed for this implementation but might be needed on others

4.2.3.10 `bool crout (matrix * a, matrix * l, matrix * u)`

Crout algorithm to divide matrix a into l and u that holds a=lu

4.2.3.11 `matrix* derivate_matrix_with_return (size_t var, matrix * a)`

Returns a pointer to a matrix with the derivative of var if the a matrix second order coefficients

4.2.3.12 `void divide_column_with_scalar (value scal, size_t col, matrix * mat)`

Divides a column with a scalar

4.2.3.13 `void divide_matrix_with_scalar (value scal, matrix * mat)`

Divides matrix mat with scalar

4.2.3.14 void divide_row_with_scalar (value *scal*, size_t *row*, matrix * *mat*)

Divides a row with a scalar

4.2.3.15 value dot_product (matrix * *r*, matrix * *v*)

Calculate the dot product

4.2.3.16 size_t first_nonzero_in_column_index (size_t *column*, size_t *start*, matrix * *a*)

Returns on which row the first nonzzero element is in the column is after start returns -1 if no nonzzero element is found

4.2.3.17 size_t first_nonzero_in_row_index (size_t *row*, size_t *start*, matrix * *a*)

Returns on which column the first nonzzero element is in the column is after start returns -1 if no nonzzero element is found

4.2.3.18 void forward_backward (matrix * *l*, matrix * *u*, matrix * *x*, matrix * *b*)

Solves $lux=b$ using backward and forward substitution

4.2.3.19 void free_matrix (matrix * *mat*)

Destroy a matrix

4.2.3.20 bool gauss_jordan (matrix * *a*)

Gauss eliminates the matrix *a*

4.2.3.21 bool gauss_jordan_solver (matrix * *a*, matrix * *x*, matrix * *b*)

Solves the system of linear equations using gauss jordan

4.2.3.22 bool get_column_vector (size_t *column*, matrix * *a*, matrix * *b*)

Takes column vector from matrix *a* and puts it into *b*

4.2.3.23 matrix* get_column_vector_with_return (size_t *column*, matrix * *a*)

Takes column vector from matrix *a* and return a pointer to the row vector

4.2.3.24 value get_determinant (matrix * *a*)

Returns the determinant of matrix *a*

4.2.3.25 bool get_diagonal (matrix * *a*, matrix * *b*)

Takes the diagonal in *a* and puts it into *b*

4.2.3.26 `bool get_inverse (matrix * a, matrix * c)`

Calculates the inverse of a and puts it into c

4.2.3.27 `bool get_inverse_of_2x2 (matrix * a, matrix * b)`

4.2.3.28 `matrix* get_inverse_of_2x2_with_return (matrix * a)`

4.2.3.29 `matrix* get_matrix_with_only_pivots (matrix * a)`

Returns a matrix with only pivots elements from a

4.2.3.30 `bool get_row_vector (size_t row, matrix * a, matrix * b)`

Takes row vector from matrix a and puts it into b

4.2.3.31 `matrix* get_row_vector_with_return (size_t row, matrix * a)`

Returns row vector row from matrix a with a pointer to a matrix

4.2.3.32 `bool get_sub_matrix (size_t start_row, size_t end_row, size_t start_col, size_t end_col, matrix * a, matrix * b)`

Get a sub matrix from a

4.2.3.33 `value get_value (size_t row, size_t col, matrix * mat)`

Get a value from matrix

4.2.3.34 `value get_value_without_check (size_t row, size_t col, matrix * mat)`

As get_value without check

4.2.3.35 `matrix* get_zero_matrix (size_t rows, size_t columns)`

Creates new matrix with zero values

4.2.3.36 `bool insert_array (value arr[], matrix * mat)`

Insert a array into the matrix

4.2.3.37 `bool insert_column_vector (size_t column, matrix * a, matrix * b)`

Inserts column vector a into matrix b at position column

4.2.3.38 `bool insert_row_vector (size_t row, matrix * a, matrix * b)`

Inserts row vector a into b:s row

4.2.3.39 `bool insert_sub_matrix (size_t start_row, size_t end_row, size_t start_col, size_t end_col, matrix * b, matrix * a)`

4.2.3.40 `bool insert_value (value insert, size_t row, size_t col, matrix * mat)`

Insert a value into matrix

4.2.3.41 `void insert_value_without_check (value insert, size_t row, size_t col, matrix * mat)`

As insert_value without check

4.2.3.42 `bool is_matrix (matrix * a, matrix * b)`

Return true if the matrix are the same

4.2.3.43 `bool is_non_negative_diagonal_matrix (matrix * A)`

Checks if all elements along the diagonal in a symmetric matrix is positive

4.2.3.44 `bool is_non_negative_matrix (matrix * v)`

Checks if all elements in a matrix is positive

4.2.3.45 `bool is_zero_matrix (matrix * v)`

Checks if all elements in a matrix is equal to zero

4.2.3.46 `size_t largest_element_in_column_index (size_t column, size_t start, matrix * a)`

Returns on which row the largest element in the column is after start

4.2.3.47 `void least_square (matrix * a, matrix * x, matrix * b)`

If no solution can be found with solve_linear, this function finds the closest one

4.2.3.48 `value matlib_fabs (value a)`

Returns the absolute value of a

4.2.3.49 `bool matrix_contains (value a, matrix * b)`

Return true if b contains value a

4.2.3.50 `matrix* matrix_copy (matrix * source)`

Copy and return new matrix.

4.2.3.51 `void matrix_copy_data (matrix * A, matrix * B)`

Copies all the data from matrix A into matrix B

4.2.3.52 `value min (value a, value b)`

Returns the lowest of the two values

4.2.3.53 `void multiply_column_with_scalar (value scal, size_t col, matrix * mat)`

Multiplies a column with a scalar

4.2.3.54 `bool multiply_matrices (matrix * a, matrix * b, matrix * c)`

Multiply a and b into c. $c=a*b$

4.2.3.55 `bool multiply_matrices_naive (matrix * a, matrix * b, matrix * c)`

4.2.3.56 `bool multiply_matrices_optimized (matrix * a, matrix * b, matrix * c)`

4.2.3.57 `matrix* multiply_matrices_with_return (matrix * a, matrix * b)`

Multiply a and b by returning a pointer to a new matrix with $a*b$

4.2.3.58 `void multiply_matrix_with_scalar (value scal, matrix * mat)`

Multiplies matrix mat with scalar

4.2.3.59 `void multiply_row_with_scalar (value scal, size_t row, matrix * mat)`

Multiplies a row with a scalar

4.2.3.60 `void print_matrix (matrix * mat)`

Prints the matrix

4.2.3.61 `value product_of_column (size_t column, matrix * mat)`

Return the product of a column in matrix mat

4.2.3.62 `value product_of_row (size_t row, matrix * mat)`

Return the product of a row in matrix mat

4.2.3.63 `size_t smallest_element_in_column_index (size_t column, size_t start, matrix * a)`

Returns on which row the smallest element in the column is after start

4.2.3.64 `bool solve_linear (matrix * a, matrix * x, matrix * b)`

Solves $Ax=B$

4.2.3.65 `matrix* solve_linear_with_return (matrix * a, matrix * b)`

Solves $ax=b$ by returning a pointer to x

4.2.3.66 `bool strassen_matrices (matrix * a, matrix * b, matrix * c)`

4.2.3.67 `matrix* strassen_matrices_with_return (matrix * a, matrix * b)`

4.2.3.68 `bool subtract_matrices (matrix * a, matrix * b, matrix * c)`

Subtract a and b into c . $c=a-b$

4.2.3.69 `matrix* subtract_matrices_with_return (matrix * a, matrix * b)`

Subtracts a and b by returning a pointer a matrix with $a-b$

4.2.3.70 `value sum_of_column (size_t column, matrix * mat)`

Return the sum of a column in matrix mat

4.2.3.71 `value sum_of_row (size_t row, matrix * mat)`

Return the sum of a row in matrix mat

4.2.3.72 `bool switch_rows (size_t row1, size_t row2, matrix * a)`

Switches rows in a

4.2.3.73 `void transform_to_reduced_row_echelon_form (matrix * M)`

4.2.3.74 `bool transpose_matrix (matrix * a, matrix * b)`

Transposes matrix a into b

4.2.3.75 `matrix* transpose_matrix_with_return (matrix * a)`

Transposes matrix a by returning a pointer to a 's transpose

4.3 TDDD77/matrixlibrary/include/sparse_lib.h File Reference

```
#include <matLib.h>
```

Data Structures

- struct [sparse_matrix](#)

Typedefs

- typedef struct [sparse_matrix](#) [sparse_matrix](#)

Functions

- `sparse_matrix * create_sparse_matrix (matrix *Ain, int size)`
- `sparse_matrix * create_empty_sparse_matrix (size_t size)`
- `matrix * sparse_to_normal (sparse_matrix *S)`
- `size_t matrix_sparsity (matrix *A)`
- `bool multiply_sparse_matrix_vector (sparse_matrix *A, matrix *x, matrix *Ax)`
- `matrix * multiply_sparse_matrix_matrix (sparse_matrix *A, matrix *B)`
- `sparse_matrix * copy_sparse_matrix (sparse_matrix *Ain)`
- `void transpose_sparse_matrix (sparse_matrix *Ain)`
- `sparse_matrix * transpose_sparse_matrix_with_return (sparse_matrix *Ain)`
- `void print_sparse_matrix (sparse_matrix *S)`
- `void free_sparse_matrix (sparse_matrix *S)`
- `bool conjugate_gradient (sparse_matrix *A, matrix *x, matrix *b)`

4.3.1 Typedef Documentation

4.3.1.1 typedef struct `sparse_matrix` `sparse_matrix`

4.3.2 Function Documentation

4.3.2.1 `bool conjugate_gradient (sparse_matrix * A, matrix * x, matrix * b)`

Solves $Ax = b$, x should be set to 0. Is not used, due to not working with MATLAB gate.

4.3.2.2 `sparse_matrix* copy_sparse_matrix (sparse_matrix * Ain)`

Copies a sparse matrix and returns it

4.3.2.3 `sparse_matrix* create_empty_sparse_matrix (size_t size)`

Creates an empty sparse matrix

4.3.2.4 `sparse_matrix* create_sparse_matrix (matrix * Ain, int size)`

Creates a sparse matrix out of a normal matrix

4.3.2.5 `void free_sparse_matrix (sparse_matrix * S)`

Frees allocated memory of the sparse matrix

4.3.2.6 `size_t matrix_sparsity (matrix * A)`

Returns number of elements != 0

4.3.2.7 `matrix* multiply_sparse_matrix_matrix (sparse_matrix * A, matrix * B)`

Multiplies sparse matrix with a normal matrix. Returns a normal matrix.

4.3.2.8 `bool multiply_sparse_matrix_vector (sparse_matrix * A, matrix * x, matrix * Ax)`

Multiplies sparse matrix with normal vector, stores result in normal matrix Ax

4.3.2.9 `void print_sparse_matrix (sparse_matrix * S)`

Prints sparse matrix

4.3.2.10 `matrix* sparse_to_normal (sparse_matrix * S)`

Converts sparse matrix to normal matrix

4.3.2.11 `void transpose_sparse_matrix (sparse_matrix * Ain)`

Transposes input sparse matrix

4.3.2.12 `sparse_matrix* transpose_sparse_matrix_with_return (sparse_matrix * Ain)`

Transposes a sparse matrix and returns it in a new sparse matrix

4.4 TDDD77/matrixlibrary/src/matLib.c File Reference

```
#include <matLib.h>
```

Functions

- `matrix * create_matrix (size_t row, size_t col)`
- `matrix * create_zero_matrix (size_t row, size_t col)`
- `matrix * create_identity_matrix (size_t row, size_t col)`
- `void free_matrix (matrix *mat)`
- `value dot_product (matrix *r, matrix *v)`
- `void print_matrix (matrix *mat)`
- `bool check_boundaries (size_t row, size_t col, matrix *mat)`
- `bool insert_array (value arr[], matrix *mat)`
- `bool compare_matrices (matrix *a, matrix *b)`
- `bool is_matrix (matrix *a, matrix *b)`
- `bool insert_value (value insert, size_t row, size_t col, matrix *mat)`
- `void insert_value_without_check (value insert, size_t row, size_t col, matrix *mat)`
- `value get_value (size_t row, size_t col, matrix *mat)`
- `value get_value_without_check (size_t row, size_t col, matrix *mat)`
- `bool add_matrices (matrix *a, matrix *b, matrix *c)`
- `matrix * add_matrices_with_return (matrix *a, matrix *b)`
- `bool subtract_matrices (matrix *a, matrix *b, matrix *c)`
- `matrix * subtract_matrices_with_return (matrix *a, matrix *b)`
- `bool multiply_matrices (matrix *a, matrix *b, matrix *c)`
- `bool multiply_matrices_naive (matrix *a, matrix *b, matrix *c)`
- `bool multiply_matrices_optimized (matrix *a, matrix *b, matrix *c)`
- `matrix * strassen_matrices_with_return (matrix *a, matrix *b)`
- `bool strassen_matrices (matrix *a, matrix *b, matrix *c)`
- `matrix * multiply_matrices_with_return (matrix *a, matrix *b)`

- [value get_determinant](#) ([matrix](#) *a)
- [bool get_inverse](#) ([matrix](#) *a, [matrix](#) *c)
- [matrix * get_inverse_of_2x2_with_return](#) ([matrix](#) *a)
- [bool get_inverse_of_2x2](#) ([matrix](#) *a, [matrix](#) *b)
- [bool solve_linear](#) ([matrix](#) *a, [matrix](#) *x, [matrix](#) *b)
- [matrix * solve_linear_with_return](#) ([matrix](#) *a, [matrix](#) *b)
- [bool crout](#) ([matrix](#) *a, [matrix](#) *l, [matrix](#) *u)
- [void forward_backward](#) ([matrix](#) *l, [matrix](#) *u, [matrix](#) *x, [matrix](#) *b)
- [void least_square](#) ([matrix](#) *a, [matrix](#) *x, [matrix](#) *b)
- [bool gauss_jordan](#) ([matrix](#) *a)
- [bool gauss_jordan_solver](#) ([matrix](#) *a, [matrix](#) *x, [matrix](#) *b)
- [matrix * get_matrix_with_only_pivots](#) ([matrix](#) *a)
- [value min](#) ([value](#) a, [value](#) b)
- [size_t largest_element_in_column_index](#) ([size_t](#) column, [size_t](#) start, [matrix](#) *a)
- [size_t smallest_element_in_column_index](#) ([size_t](#) column, [size_t](#) start, [matrix](#) *a)
- [size_t first_nonzero_in_column_index](#) ([size_t](#) column, [size_t](#) start, [matrix](#) *a)
- [size_t first_nonzero_in_row_index](#) ([size_t](#) row, [size_t](#) start, [matrix](#) *a)
- [void add_rows](#) ([size_t](#) row1, [size_t](#) row2, [matrix](#) *a)
- [bool transpose_matrix](#) ([matrix](#) *a, [matrix](#) *b)
- [matrix * transpose_matrix_with_return](#) ([matrix](#) *a)
- [value sum_of_row](#) ([size_t](#) row, [matrix](#) *mat)
- [value sum_of_column](#) ([size_t](#) column, [matrix](#) *mat)
- [value product_of_row](#) ([size_t](#) row, [matrix](#) *mat)
- [value product_of_column](#) ([size_t](#) column, [matrix](#) *mat)
- [void multiply_matrix_with_scalar](#) ([value](#) scal, [matrix](#) *mat)
- [void divide_matrix_with_scalar](#) ([value](#) scal, [matrix](#) *mat)
- [void multiply_row_with_scalar](#) ([value](#) scal, [size_t](#) row, [matrix](#) *mat)
- [void divide_row_with_scalar](#) ([value](#) scal, [size_t](#) row, [matrix](#) *mat)
- [void multiply_column_with_scalar](#) ([value](#) scal, [size_t](#) col, [matrix](#) *mat)
- [void divide_column_with_scalar](#) ([value](#) scal, [size_t](#) col, [matrix](#) *mat)
- [bool get_row_vector](#) ([size_t](#) row, [matrix](#) *a, [matrix](#) *b)
- [matrix * get_row_vector_with_return](#) ([size_t](#) row, [matrix](#) *a)
- [bool insert_row_vector](#) ([size_t](#) row, [matrix](#) *a, [matrix](#) *b)
- [bool switch_rows](#) ([size_t](#) row1, [size_t](#) row2, [matrix](#) *a)
- [bool get_column_vector](#) ([size_t](#) column, [matrix](#) *a, [matrix](#) *b)
- [matrix * get_column_vector_with_return](#) ([size_t](#) column, [matrix](#) *a)
- [bool insert_column_vector](#) ([size_t](#) column, [matrix](#) *a, [matrix](#) *b)
- [bool get_sub_matrix](#) ([size_t](#) start_row, [size_t](#) end_row, [size_t](#) start_col, [size_t](#) end_col, [matrix](#) *a, [matrix](#) *b)
- [bool insert_sub_matrix](#) ([size_t](#) start_row, [size_t](#) end_row, [size_t](#) start_col, [size_t](#) end_col, [matrix](#) *b, [matrix](#) *a)
- [matrix * matrix_copy](#) ([matrix](#) *source)
- [void matrix_copy_data](#) ([matrix](#) *a, [matrix](#) *b)
- [bool is_zero_matrix](#) ([matrix](#) *v)
- [bool is_non_negative_matrix](#) ([matrix](#) *v)
- [bool is_non_negative_diagonal_matrix](#) ([matrix](#) *A)
- [bool get_diagonal](#) ([matrix](#) *a, [matrix](#) *b)
- [matrix * derivate_matrix_with_return](#) ([size_t](#) var, [matrix](#) *a)
- [void transform_to_reduced_row_echelon_form](#) ([matrix](#) *M)
- [bool matrix_contains](#) ([value](#) a, [matrix](#) *b)
- [int compare_elements](#) ([value](#) a, [value](#) b)
- [matrix * get_zero_matrix](#) ([size_t](#) rows, [size_t](#) columns)
- [value matlib_fabs](#) ([value](#) a)

4.4.1 Function Documentation

4.4.1.1 `bool add_matrices (matrix * a, matrix * b, matrix * c)`

Adds a and b into c

4.4.1.2 `matrix* add_matrices_with_return (matrix * a, matrix * b)`

Adds a and b by returning a pointer a matrix with a+b

4.4.1.3 `void add_rows (size_t row1, size_t row2, matrix * a)`

Adds each element in row1 and row 2 and puts the result on row2

4.4.1.4 `bool check_boundaries (size_t row, size_t col, matrix * mat)`

Checks if the position exists in the matrix

4.4.1.5 `int compare_elements (value a, value b)`

Compare two element values

4.4.1.6 `bool compare_matrices (matrix * a, matrix * b)`

Returns true if matrices a and b look the same

4.4.1.7 `matrix* create_identity_matrix (size_t row, size_t col)`

Creates a identity matrix

4.4.1.8 `matrix* create_matrix (size_t row, size_t col)`

Create a matrix

4.4.1.9 `matrix* create_zero_matrix (size_t row, size_t col)`

Is normally not needed for this implementation but might be needed on others

4.4.1.10 `bool crout (matrix * a, matrix * l, matrix * u)`

Crout algorithm to divide matrix a into l and u that holds a=lu

4.4.1.11 `matrix* derivate_matrix_with_return (size_t var, matrix * a)`

Returns a pointer to a matrix with the derivative of var if the a matrix second order coefficients

4.4.1.12 `void divide_column_with_scalar (value scal, size_t col, matrix * mat)`

Divides a column with a scalar

4.4.1.13 void divide_matrix_with_scalar (value *scal*, matrix * *mat*)

Divides matrix *mat* with scalar

4.4.1.14 void divide_row_with_scalar (value *scal*, size_t *row*, matrix * *mat*)

Divides a row with a scalar

4.4.1.15 value dot_product (matrix * *r*, matrix * *v*)

Calculate the dot product

4.4.1.16 size_t first_nonzero_in_column_index (size_t *column*, size_t *start*, matrix * *a*)

Returns on which row the first nonzoro element is in the column is after *start* returns -1 if no nonzoro element is found

4.4.1.17 size_t first_nonzero_in_row_index (size_t *row*, size_t *start*, matrix * *a*)

Returns on which column the first nonzoro element is in the column is after *start* returns -1 if no nonzoro element is found

4.4.1.18 void forward_backward (matrix * *l*, matrix * *u*, matrix * *x*, matrix * *b*)

Solves $lux=b$ using backward and forward substitution

4.4.1.19 void free_matrix (matrix * *mat*)

Destroy a matrix

4.4.1.20 bool gauss_jordan (matrix * *a*)

Gauss eliminates the matrix *a*

4.4.1.21 bool gauss_jordan_solver (matrix * *a*, matrix * *x*, matrix * *b*)

Solves the system of linear equations using gauss jordan

4.4.1.22 bool get_column_vector (size_t *column*, matrix * *a*, matrix * *b*)

Takes column vector from matrix *a* and puts it into *b*

4.4.1.23 matrix* get_column_vector_with_return (size_t *column*, matrix * *a*)

Takes column vector from matrix *a* and return a pointer to the row vector

4.4.1.24 value get_determinant (matrix * *a*)

Returns the determinant of matrix *a*

4.4.1.25 bool get_diagonal (matrix * a, matrix * b)

Takes the diagonal in a and puts it into b

4.4.1.26 bool get_inverse (matrix * a, matrix * c)

Calculates the inverse of a and puts it into c

4.4.1.27 bool get_inverse_of_2x2 (matrix * a, matrix * b)**4.4.1.28 matrix* get_inverse_of_2x2_with_return (matrix * a)****4.4.1.29 matrix* get_matrix_with_only_pivots (matrix * a)**

Returns a matrix with only pivots elements from a

4.4.1.30 bool get_row_vector (size_t row, matrix * a, matrix * b)

Takes row vector from matrix a and puts it into b

4.4.1.31 matrix* get_row_vector_with_return (size_t row, matrix * a)

Returns row vector row from matrix a with a pointer to a matrix

4.4.1.32 bool get_sub_matrix (size_t start_row, size_t end_row, size_t start_col, size_t end_col, matrix * a, matrix * b)

Get a sub matrix from a

4.4.1.33 value get_value (size_t row, size_t col, matrix * mat)

Get a value from matrix

4.4.1.34 value get_value_without_check (size_t row, size_t col, matrix * mat)

As get_value without check

4.4.1.35 matrix* get_zero_matrix (size_t rows, size_t columns)

Creates new matrix with zero values

4.4.1.36 bool insert_array (value arr[], matrix * mat)

Insert a array into the matrix

4.4.1.37 bool insert_column_vector (size_t column, matrix * a, matrix * b)

Inserts column vector a into matrix b at position column

4.4.1.38 `bool insert_row_vector (size_t row, matrix * a, matrix * b)`

Inserts row vector a into b's row

4.4.1.39 `bool insert_sub_matrix (size_t start_row, size_t end_row, size_t start_col, size_t end_col, matrix * b, matrix * a)`

4.4.1.40 `bool insert_value (value insert, size_t row, size_t col, matrix * mat)`

Insert a value into matrix

4.4.1.41 `void insert_value_without_check (value insert, size_t row, size_t col, matrix * mat)`

As insert_value without check

4.4.1.42 `bool is_matrix (matrix * a, matrix * b)`

Return true if the matrix are the same

4.4.1.43 `bool is_non_negative_diagonal_matrix (matrix * A)`

Checks if all elements along the diagonal in a symmetric matrix is positive

4.4.1.44 `bool is_non_negative_matrix (matrix * v)`

Checks if all elements in a matrix is positive

4.4.1.45 `bool is_zero_matrix (matrix * v)`

Checks if all elements in a matrix is equal to zero

4.4.1.46 `size_t largest_element_in_column_index (size_t column, size_t start, matrix * a)`

Returns on which row the largest element in the column is after start

4.4.1.47 `void least_square (matrix * a, matrix * x, matrix * b)`

If no solution can be found with solve_linear, this function finds the closest one

4.4.1.48 `value matlib_fabs (value a)`

Returns the absolute value of a

4.4.1.49 `bool matrix_contains (value a, matrix * b)`

Return true if b contains value a

4.4.1.50 `matrix* matrix_copy (matrix * source)`

Copy and return new matrix.

4.4.1.51 `void matrix_copy_data (matrix * A, matrix * B)`

Copies all the data from matrix A into matrix B

4.4.1.52 `value min (value a, value b)`

Returns the lowest of the two values

4.4.1.53 `void multiply_column_with_scalar (value scal, size_t col, matrix * mat)`

Multiplies a column with a scalar

4.4.1.54 `bool multiply_matrices (matrix * a, matrix * b, matrix * c)`

Multiply a and b into c. $c=a*b$

4.4.1.55 `bool multiply_matrices_naive (matrix * a, matrix * b, matrix * c)`

4.4.1.56 `bool multiply_matrices_optimized (matrix * a, matrix * b, matrix * c)`

4.4.1.57 `matrix* multiply_matrices_with_return (matrix * a, matrix * b)`

Multiply a and b by returning a pointer to a new matrix with $a*b$

4.4.1.58 `void multiply_matrix_with_scalar (value scal, matrix * mat)`

Multiplies matrix mat with scalar

4.4.1.59 `void multiply_row_with_scalar (value scal, size_t row, matrix * mat)`

Multiplies a row with a scalar

4.4.1.60 `void print_matrix (matrix * mat)`

Prints the matrix

4.4.1.61 `value product_of_column (size_t column, matrix * mat)`

Return the product of a column in matrix mat

4.4.1.62 `value product_of_row (size_t row, matrix * mat)`

Return the product of a row in matrix mat

4.4.1.63 `size_t smallest_element_in_column_index (size_t column, size_t start, matrix * a)`

Returns on which row the smallest element in the column is after start

4.4.1.64 `bool solve_linear (matrix * a, matrix * x, matrix * b)`

Solves $Ax=B$

4.4.1.65 `matrix* solve_linear_with_return (matrix * a, matrix * b)`

Solves $ax=b$ by returning a pointer to x

4.4.1.66 `bool strassen_matrices (matrix * a, matrix * b, matrix * c)`

4.4.1.67 `matrix* strassen_matrices_with_return (matrix * a, matrix * b)`

4.4.1.68 `bool subtract_matrices (matrix * a, matrix * b, matrix * c)`

Subtract a and b into c . $c=a-b$

4.4.1.69 `matrix* subtract_matrices_with_return (matrix * a, matrix * b)`

Subtracts a and b by returning a pointer a matrix with $a-b$

4.4.1.70 `value sum_of_column (size_t column, matrix * mat)`

Return the sum of a column in matrix mat

4.4.1.71 `value sum_of_row (size_t row, matrix * mat)`

Return the sum of a row in matrix mat

4.4.1.72 `bool switch_rows (size_t row1, size_t row2, matrix * a)`

Switches rows in a

4.4.1.73 `void transform_to_reduced_row_echelon_form (matrix * M)`

4.4.1.74 `bool transpose_matrix (matrix * a, matrix * b)`

Transposes matrix a into b

4.4.1.75 `matrix* transpose_matrix_with_return (matrix * a)`

Transposes matrix a by returning a pointer to a 's transpose

4.5 TDDD77/matrixlibrary/src/sparse_lib.c File Reference

```
#include <sparse_lib.h>
#include <math.h>
```


Functions

- `sparse_matrix * create_sparse_matrix (matrix *Ain, int size)`
- `sparse_matrix * create_empty_sparse_matrix (size_t size)`
- `matrix * sparse_to_normal (sparse_matrix *S)`
- `size_t matrix_sparsity (matrix *A)`
- `bool multiply_sparse_matrix_vector (sparse_matrix *A, matrix *x, matrix *Ax)`
- `matrix * multiply_sparse_matrix_matrix (sparse_matrix *A, matrix *B)`
- `sparse_matrix * copy_sparse_matrix (sparse_matrix *Ain)`
- `void transpose_sparse_matrix (sparse_matrix *Ain)`
- `sparse_matrix * transpose_sparse_matrix_with_return (sparse_matrix *Ain)`
- `void print_sparse_matrix (sparse_matrix *S)`
- `void free_sparse_matrix (sparse_matrix *S)`
- `bool conjugate_gradient (sparse_matrix *A, matrix *x, matrix *b)`

4.5.1 Function Documentation

4.5.1.1 `bool conjugate_gradient (sparse_matrix * A, matrix * x, matrix * b)`

Solves $Ax = b$, x should be set to 0. Is not used, due to not working with MATLAB gate.

4.5.1.2 `sparse_matrix* copy_sparse_matrix (sparse_matrix * Ain)`

Copies a sparse matrix and returns it

4.5.1.3 `sparse_matrix* create_empty_sparse_matrix (size_t size)`

Creates an empty sparse matrix

4.5.1.4 `sparse_matrix* create_sparse_matrix (matrix * Ain, int size)`

Creates a sparse matrix out of a normal matrix

4.5.1.5 `void free_sparse_matrix (sparse_matrix * S)`

Frees allocated memory of the sparse matrix

4.5.1.6 `size_t matrix_sparsity (matrix * A)`

Returns number of elements != 0

4.5.1.7 `matrix* multiply_sparse_matrix_matrix (sparse_matrix * A, matrix * B)`

Multiplies sparse matrix with a normal matrix. Returns a normal matrix.

4.5.1.8 `bool multiply_sparse_matrix_vector (sparse_matrix * A, matrix * x, matrix * Ax)`

Multiplies sparse matrix with normal vector, stores result in normal matrix Ax

4.5.1.9 void print_sparse_matrix (sparse_matrix * S)

Prints sparse matrix

4.5.1.10 matrix* sparse_to_normal (sparse_matrix * S)

Converts sparse matrix to normal matrix

4.5.1.11 void transpose_sparse_matrix (sparse_matrix * Ain)

Transposes input sparse matrix

4.5.1.12 sparse_matrix* transpose_sparse_matrix_with_return (sparse_matrix * Ain)

Transposes a sparse matrix and returns it in a new sparse matrix

4.6 TDDD77/quadopt/include/problem.h File Reference

```
#include <matLib.h>
#include <work_set.h>
#include <sparse_lib.h>
```

Data Structures

- struct [problem](#)

Typedefs

- typedef struct [problem](#) [problem](#)

Functions

- [problem](#) * [create_problem](#) ([matrix](#) *Q, [matrix](#) *q, [matrix](#) *E, [matrix](#) *h, [matrix](#) *F, [matrix](#) *g, [matrix](#) *z0, int max_iter, int max_micro_sec)
- void [print_problem](#) ([problem](#) *prob)
- void [free_problem](#) ([problem](#) *prob)
- [matrix](#) * [get_active_conditions](#) ([problem](#) *prob)
- [sparse_matrix](#) * [get_sparse_active_conditions](#) ([problem](#) *prob)
- [matrix](#) * [get_active_conditions_rhs](#) ([problem](#) *prob)
- bool [get_solution_value](#) ([problem](#) *prob)
- void [print_solution](#) ([problem](#) *prob)
- bool [time_to_exit](#) ([problem](#) *prob, double time_spent)
- bool [is_feasible_point](#) ([matrix](#) *z, [problem](#) *prob)

4.6.1 Typedef Documentation

4.6.1.1 typedef struct problem problem

4.6.2 Function Documentation

4.6.2.1 `problem* create_problem (matrix * Q, matrix * q, matrix * E, matrix * h, matrix * F, matrix * g, matrix * z0, int max_iter, int max_micro_sec)`

Puts matrices to a problem struct

4.6.2.2 `void free_problem (problem * prob)`

Deallocates all the problems resources

4.6.2.3 `matrix* get_active_conditions (problem * prob)`

Returns a matrix with the currently active constraints

4.6.2.4 `matrix* get_active_conditions_rhs (problem * prob)`

Returns a matrix with the right hand side of the currently active constraints

4.6.2.5 `bool get_solution_value (problem * prob)`

Calculates the optimum value given by the solution point

4.6.2.6 `sparse_matrix* get_sparse_active_conditions (problem * prob)`

4.6.2.7 `bool is_feasible_point (matrix * z, problem * prob)`

4.6.2.8 `void print_problem (problem * prob)`

Prints the matrices defined in the problem struct

4.6.2.9 `void print_solution (problem * prob)`

Prints optimal point and optimal value

4.6.2.10 `bool time_to_exit (problem * prob, double time_spent)`

Exits solver if maximal iterations or microseconds have been fulfilled

4.7 TDDD77/quadopt/include/simplex.h File Reference

```
#include <problem.h>
```

Functions

- bool `simplex_phase_1` (`problem` *`prob`)

4.7.1 Function Documentation

4.7.1.1 bool `simplex_phase_1` (`problem` * `prob`)

4.8 TDDD77/quadopt/include/solver.h File Reference

```
#include <problem.h>
#include <matLib.h>
```

Functions

- bool `remove_constraint` (`problem` *`prob`)
- `matrix` * `quadopt_solver` (`problem` *`prob`)

4.8.1 Function Documentation

4.8.1.1 `matrix`* `quadopt_solver` (`problem` * `prob`)

Solves a quadratic problem using the active set method

4.8.1.2 bool `remove_constraint` (`problem` * `prob`)

Removes the active constraint with the most negative lagrange multiplier

4.9 TDDD77/quadopt/include/subproblem.h File Reference

```
#include <problem.h>
```

Functions

- void `solve_subproblem` (`problem` *`prob`)

4.9.1 Function Documentation

4.9.1.1 void `solve_subproblem` (`problem` * `prob`)

Solves the subproblem for active set

4.10 TDDD77/quadopt/include/trans_con.h File Reference

```
#include <matLib.h>
#include <stdbool.h>
```

Functions

- bool [trans_dyn_cons](#) (matrix *A, matrix *B, matrix *k, matrix *E, matrix *h, size_t card_x)
- bool [trans_ineq_cons](#) (matrix *Fx, matrix *gx, matrix *F, matrix *g, size_t card_x, size_t card_u, size_t N, matrix *x_lim, matrix *u_lim)
- bool [create_objective](#) (int n, matrix *Qin, matrix *P, matrix *R, matrix *Q)

4.10.1 Function Documentation

4.10.1.1 bool [create_objective](#) (int *n*, matrix * *Qin*, matrix * *P*, matrix * *R*, matrix * *Q*)

4.10.1.2 bool [trans_dyn_cons](#) (matrix * *A*, matrix * *B*, matrix * *k*, matrix * *E*, matrix * *h*, size_t *card_x*)

Dynamic constraints (A and B with initial values K) transforms to equality constraints (E and h).

4.10.1.3 bool [trans_ineq_cons](#) (matrix * *Fx*, matrix * *gx*, matrix * *F*, matrix * *g*, size_t *card_x*, size_t *card_u*, size_t *N*, matrix * *x_lim*, matrix * *u_lim*)

4.11 TDDD77/quadopt/include/work_set.h File Reference

```
#include <stdbool.h>
```

Data Structures

- struct [work_set](#)

Typedefs

- typedef struct [work_set](#) [work_set](#)

Functions

- [work_set](#) * [work_set_create](#) (size_t ws_max)
- bool [work_set_free](#) ([work_set](#) *ws)
- bool [work_set_append](#) ([work_set](#) *ws, size_t val)
- bool [work_set_remove](#) ([work_set](#) *ws, size_t val)
- void [work_set_print](#) ([work_set](#) *ws)
- bool [work_set_contains](#) ([work_set](#) *ws, size_t item)
- void [work_set_clear](#) ([work_set](#) *ws)

4.11.1 Typedef Documentation

4.11.1.1 typedef struct [work_set](#) [work_set](#)

4.11.2 Function Documentation

4.11.2.1 bool [work_set_append](#) ([work_set](#) * *ws*, size_t *val*)

Adds an element to the set

4.11.2.2 void work_set_clear (work_set * ws)

Clears the set

4.11.2.3 bool work_set_contains (work_set * ws, size_t item)

Checks if the set is containing the item

4.11.2.4 work_set* work_set_create (size_t ws_max)

Creates a new work set

4.11.2.5 bool work_set_free (work_set * ws)

Removes and deallocates the set

4.11.2.6 void work_set_print (work_set * ws)

Prints all current elements in the set

4.11.2.7 bool work_set_remove (work_set * ws, size_t val)

Removes an element from the set

4.12 TDDD77/quadopt/src/problem.c File Reference

```
#include <problem.h>
```

Functions

- void [fill_constraint_matrices](#) (problem *prob)
- problem * [create_problem](#) (matrix *Q, matrix *q, matrix *E, matrix *h, matrix *F, matrix *g, matrix *z0, int max_iter, int max_micro_sec)
- void [print_problem](#) (problem *prob)
- void [free_problem](#) (problem *prob)
- matrix * [get_active_conditions](#) (problem *prob)
- sparse_matrix * [get_sparse_active_conditions](#) (problem *prob)
- matrix * [get_active_conditions_rhs](#) (problem *prob)
- bool [get_solution_value](#) (problem *prob)
- void [print_solution](#) (problem *prob)
- bool [time_to_exit](#) (problem *prob, double time_spent)
- bool [is_feasible_point](#) (matrix *z, problem *prob)

4.12.1 Function Documentation

4.12.1.1 problem* create_problem (matrix * Q, matrix * q, matrix * E, matrix * h, matrix * F, matrix * g, matrix * z0, int max_iter, int max_micro_sec)

Puts matrices to a problem struct

4.12.1.2 void fill_constraint_matrices (problem * prob)

4.12.1.3 void free_problem (problem * prob)

Deallocates all the problems resources

4.12.1.4 matrix* get_active_conditions (problem * prob)

Returns a matrix with the currently active constraints

4.12.1.5 matrix* get_active_conditions_rhs (problem * prob)

Returns a matrix with the right hand side of the currently active constraints

4.12.1.6 bool get_solution_value (problem * prob)

Calculates the optimum value given by the solution point

4.12.1.7 sparse_matrix* get_sparse_active_conditions (problem * prob)

4.12.1.8 bool is_feasible_point (matrix * z, problem * prob)

4.12.1.9 void print_problem (problem * prob)

Prints the matrices defined in the problem struct

4.12.1.10 void print_solution (problem * prob)

Prints optimal point and optimal value

4.12.1.11 bool time_to_exit (problem * prob, double time_spent)

Exits solver if maximal iterations or microseconds have been fulfilled

4.13 TDDD77/quadopt/src/simplex.c File Reference

```
#include <simplex.h>
```

Functions

- bool [is_neg_tableau_row](#) (int row, matrix *tableau)
- int [min_test](#) (int column, matrix *tableau)
- void [neg_equality](#) (problem *prob, work_set *virtual_vars)
- void [convert_geq_to_leq](#) (problem *prob, work_set *virtual_vars, matrix **Fr, matrix **gr)
- matrix * [split_ineq_variables](#) (problem *prob, matrix *Fr)
- matrix * [split_eq_variables](#) (problem *prob)
- work_set * [create_basis](#) (problem *prob)
- void [insert_constraints](#) (problem *prob, matrix *tableau, matrix *Et, matrix *Ft, matrix *gr)
- void [insert_simplex_variables](#) (problem *prob, work_set *virtual_vars, matrix *tableau)

- void `insert_objective_function` (problem *prob, matrix *tableau)
- void `remove_variables` (problem *prob, matrix *tableau)
- bool `simplex_min` (problem *prob, matrix *tableau, work_set *basis)
- void `set_variables` (problem *prob, work_set *basis, matrix *tableau)
- bool `simplex_phase_1` (problem *prob)

4.13.1 Function Documentation

4.13.1.1 void `convert_geq_to_leq` (problem * *prob*, work_set * *virtual_vars*, matrix ** *Fr*, matrix ** *gr*)

4.13.1.2 work_set* `create_basis` (problem * *prob*)

4.13.1.3 void `insert_constraints` (problem * *prob*, matrix * *tableau*, matrix * *Et*, matrix * *Ft*, matrix * *gr*)

4.13.1.4 void `insert_objective_function` (problem * *prob*, matrix * *tableau*)

4.13.1.5 void `insert_simplex_variables` (problem * *prob*, work_set * *virtual_vars*, matrix * *tableau*)

4.13.1.6 bool `is_neg_tableau_row` (int *row*, matrix * *tableau*)

4.13.1.7 int `min_test` (int *column*, matrix * *tableau*)

4.13.1.8 void `neg_equality` (problem * *prob*, work_set * *virtual_vars*)

4.13.1.9 void `remove_variables` (problem * *prob*, matrix * *tableau*)

4.13.1.10 void `set_variables` (problem * *prob*, work_set * *basis*, matrix * *tableau*)

4.13.1.11 bool `simplex_min` (problem * *prob*, matrix * *tableau*, work_set * *basis*)

4.13.1.12 bool `simplex_phase_1` (problem * *prob*)

4.13.1.13 matrix* `split_eq_variables` (problem * *prob*)

4.13.1.14 matrix* `split_ineq_variables` (problem * *prob*, matrix * *Fr*)

4.14 TDDD77/quadopt/src/solver.c File Reference

```
#include <stdio.h>
#include <solver.h>
#include <math.h>
#include <subproblem.h>
#include <time.h>
#include <simplex.h>
```

Functions

- bool `fill_active_set` (problem *prob)
- bool `take_step` (problem *prob)
- void `copy_solution` (problem *prob)
- void `prefill_set` (problem *prob)
- bool `remove_constraint` (problem *prob)
- matrix * `quadopt_solver` (problem *prob)

4.14.1 Function Documentation

4.14.1.1 void copy_solution (problem * *prob*)

4.14.1.2 bool fill_active_set (problem * *prob*)

4.14.1.3 void prefill_set (problem * *prob*)

4.14.1.4 matrix* quadopt_solver (problem * *prob*)

Solves a quadratic problem using the active set method

4.14.1.5 bool remove_constraint (problem * *prob*)

Removes the active constraint with the most negative lagrange multiplier

4.14.1.6 bool take_step (problem * *prob*)

4.15 TDDD77/quadopt/src/subproblem.c File Reference

```
#include <subproblem.h>
#include <matLib.h>
#include <solver.h>
#include <assert.h>
```

Functions

- void range_space_sparse (sparse_matrix *A, problem *prob)
- void range_space (matrix *A, problem *prob)
- void KKT_sub_sparse (sparse_matrix *A, problem *prob)
- void KKT_sub (matrix *A, problem *prob)
- void solve_subproblem (problem *prob)

4.15.1 Function Documentation

4.15.1.1 void KKT_sub (matrix * *A*, problem * *prob*)

4.15.1.2 void KKT_sub_sparse (sparse_matrix * *A*, problem * *prob*)

4.15.1.3 void range_space (matrix * *A*, problem * *prob*)

4.15.1.4 void range_space_sparse (sparse_matrix * *A*, problem * *prob*)

4.15.1.5 void solve_subproblem (problem * *prob*)

Solves the subproblem for active set

4.16 TDDD77/quadopt/src/trans_con.c File Reference

```
#include <trans_con.h>
#include <assert.h>
```

Functions

- bool [insert_x_identity_matrices](#) (matrix *F, size_t card_x, size_t N)
- bool [insert_fx](#) (matrix *F, matrix *Fx, size_t card_x, size_t N)
- bool [insert_u_identity_matrices](#) (matrix *F, size_t card_u, size_t N)
- bool [fix_g](#) (matrix *g, matrix *gx, matrix *x_lim, matrix *u_lim, size_t N)
- bool [insert_identity_matrices](#) (matrix *E, size_t card_x)
- bool [insert_A_matrices](#) (matrix *E, matrix *A)
- bool [insert_B_matrices](#) (matrix *E, matrix *B, size_t N)
- bool [trans_dyn_cons](#) (matrix *A, matrix *B, matrix *k, matrix *E, matrix *h, size_t card_x)
- bool [trans_ineq_cons](#) (matrix *Fx, matrix *gx, matrix *F, matrix *g, size_t card_x, size_t card_u, size_t N, matrix *x_lim, matrix *u_lim)
- bool [create_objective](#) (int n, matrix *Qin, matrix *P, matrix *R, matrix *Q)

4.16.1 Function Documentation

4.16.1.1 bool [create_objective](#) (int n, matrix * *Qin*, matrix * *P*, matrix * *R*, matrix * *Q*)

4.16.1.2 bool [fix_g](#) (matrix * *g*, matrix * *gx*, matrix * *x_lim*, matrix * *u_lim*, size_t *N*)

4.16.1.3 bool [insert_A_matrices](#) (matrix * *E*, matrix * *A*)

4.16.1.4 bool [insert_B_matrices](#) (matrix * *E*, matrix * *B*, size_t *N*)

4.16.1.5 bool [insert_fx](#) (matrix * *F*, matrix * *Fx*, size_t *card_x*, size_t *N*)

4.16.1.6 bool [insert_identity_matrices](#) (matrix * *E*, size_t *card_x*)

4.16.1.7 bool [insert_u_identity_matrices](#) (matrix * *F*, size_t *card_u*, size_t *N*)

4.16.1.8 bool [insert_x_identity_matrices](#) (matrix * *F*, size_t *card_x*, size_t *N*)

4.16.1.9 bool [trans_dyn_cons](#) (matrix * *A*, matrix * *B*, matrix * *k*, matrix * *E*, matrix * *h*, size_t *card_x*)

Dynamic constraints (A and B with initial values K) transforms to equality constraints (E and h).

4.16.1.10 bool [trans_ineq_cons](#) (matrix * *Fx*, matrix * *gx*, matrix * *F*, matrix * *g*, size_t *card_x*, size_t *card_u*, size_t *N*, matrix * *x_lim*, matrix * *u_lim*)

4.17 TDDD77/quadopt/src/work_set.c File Reference

```
#include <stdlib.h>
#include <stdio.h>
#include <work_set.h>
```

Functions

- [work_set](#) * [work_set_create](#) (size_t ws_max)
- bool [work_set_append](#) ([work_set](#) *ws, size_t val)
- bool [work_set_remove](#) ([work_set](#) *ws, size_t val)

- bool `work_set_free` (`work_set *ws`)
- void `work_set_print` (`work_set *ws`)
- bool `work_set_contains` (`work_set *ws`, `size_t item`)
- void `work_set_clear` (`work_set *ws`)

4.17.1 Function Documentation

4.17.1.1 `bool work_set_append (work_set * ws, size_t val)`

Adds an element to the set

4.17.1.2 `void work_set_clear (work_set * ws)`

Clears the set

4.17.1.3 `bool work_set_contains (work_set * ws, size_t item)`

Checks if the set is containing the item

4.17.1.4 `work_set* work_set_create (size_t ws_max)`

Creates a new work set

4.17.1.5 `bool work_set_free (work_set * ws)`

Removes and deallocates the set

4.17.1.6 `void work_set_print (work_set * ws)`

Prints all current elements in the set

4.17.1.7 `bool work_set_remove (work_set * ws, size_t val)`

Removes an element from the set

