

Comparing Natural Language Embeddings for Libc Functions as Rich Labels

Bachelor defense

Ruben Triwari

Ludwig Maximilian University Munich

19, February 2025

Ruben Triwari 1 / 1:

Outline


Motivation & Research Objective

Methodology

Results


Limitations

Conclusion & Future Work



Ruben Triwari 2 / 11

Motivation



- → Encoding natural language was a huge factor in recent nlp advancements
- → Information described as a vector can be used in many downstream task
- → That motivates encoding binary code and describing them as a vector
- → That motivates using NLP tools to encode binary code

Ruben Triwari 3 / 11


Motivation

Motivation & Research Objective

```
factorial(int):
                                                                                  push
                                                                                           rbp
                                                                                            rbp, rsp
                                                                                   mov
                                                                                           rbx
                                                                                   push
                                                                                           rsp, 24
                                                                                   sub
                                                                                            DWORD PTR [rbp-20], edi
                                                                                   mov
                                                                                            DWORD PTR [rbp-20]. 0
                                                                                   cmp
unsigned long long factorial(int n) {
                                                                                   ine
                                                                                            .L2
  // Base case: Factorial of 0 is 1
                                                                                   mov
                                                                                            eax, 1
  if (n == 0) {
                                                                                   jmp
                                                                                            .L3
    return 1:
                                                    Compiler
                                                                                 L2:
                                                                                            eax, DWORD PTR [rbp-20]
                                                                                   mov
  // Recursive case: n! = n * (n-1)!
                                                                                           rbx. eax
                                                                                   movsx
  return n * factorial(n - 1);
                                                                                            eax, DWORD PTR [rbp-20]
                                                                                  mov
                                                                                   sub
                                                                                            eax, 1
                                                                                   mov
                                                                                            edi. eax
                                                                                           factorial(int)
                                                                                   call.
                                                                                   imul.
                                                                                           rax, rbx
                                                                                .L3:
                                                                                            rbx, QWORD PTR [rbp-8]
                                                                                  mov
                                                                                  leave
                                                                                   ret
```

Ruben Triwari 4 / 11

Motivation & Research Objective



Ruben Triwari


 $\mathcal{L}(o, I) \in \mathbb{R}$

Research Objectives

Motivation & Research Objective

- ► Compare diffrent approaches generating an Embedding with NLP tools
 - 1. Embed function names with SentenceTransformer
 - 2. Embed function comments with SentenceTransformer
 - 3. Embed Code-Llama code summaries with SentenceTransformer
- Compare NLP approach to the existing Code2Vec Model
- Propose a new way comparing embedding spaces

Ruben Triwari 6 / 11



Ruben Triwari 7 / 11

Denotational Semantics

Ruben Triwari 8 / 1:

HALLO

Ruben Triwari 9 / 11

HALLO

Ruben Triwari 10 / 11

Discussion

Ruben Triwari 11 / 1