

42081 - SISTEMAS OPERATIVOS E DE TEMPO-REAL

Duration: 2h00m

2021-2022

Evam Regular Period

L'Auiii, i	Bututon, 2noon
#MEC:	Name:
Note 1	all answers should be properly justified. Just answering Yes/No or writing numerical results without indicating the equations and values used implies that the corresponding answer will not be considered.
Note 2	the weight of each question is placed at the beginning, between square brackets. E.g. "[0.5]".
Note 3	several answers have a limited size. In such cases the maximum number of lines that can be used is indicated at the end of the question. E.g. "[5 lines]" means that up to 5 lines of text can be used for the answer. Diagrams/figures are not size-limited. Just the text.

Part I – Short Questions (6/20 points)

- 1. [1.0] Consider the following statement: "All Real-Time tasks must have an associated deadline". Do you agree? Justify! [6 lines]
- 2. [1.0] Identify three factors that can contribute to the variation of the Worst-Case Execution Time of a task. [8 lines]
- 3. [1.0] Consider a set of three tasks with periods 25, 30 and 50 t.u., scheduled in a tick-based OS. Compute the optimum value for the tick value, providing a brief justification. [6 lines]
- 4. [1.0] Consider a task set composed of independent periodic tasks, scheduled with preemption. If this task set is schedulable with Rate-Monotonic, then it can be assumed that is also schedulable with EDF? Why? [4 lines]
- 5. [1.0] One of the code optimization techniques is called "cycle expansion". Explain briefly how this technique is applied in practice (you can use an example, if you wish) and indicate one potential benefit and one potential drawback. [6 lines]
- 6. [1.0] Regarding cache, multi-core systems have additional problems with respect to single-core ones? If so, which ones? [6 lines]

Part II – Development Questions (14/20 points)

- 1. [7.0] An industrial milling machine with numerical control has 3 orthogonal axes, each equipped with closed-loop position control and range-limit sensors for their protection, and also two milling cutter pressure sensors to detect jam situations. The global control is performed by a CPU that executes six tasks concurrently. It is used an EDF scheduler, tasks are preemptible and deadlines are set to the period/mit. The tasks are characterized as follows:
 - τ_1 reads instructions from a control program written in a high-level language, one at each iteration, and transforms them into simple movements used by task τ_2 . It is fired whenever the execution of an instruction ends.
 - \triangleright Sporadic, C₁=1 ms, mit₁=50 ms
 - τ_2 interprets the movements generated by task τ_1 and generates the set-points appropriate for each of the axes.
 - \triangleright Periodic C₂=5 ms, T₂=20 ms
 - τ_3 to τ_5 perform the closed loop control of each axis.
 - Periodic $C_{3-5}=1$ ms, $T_{3-5}=5$ ms
 - τ₆ is activated by triggering any of the protection sensors and stops the machine in safe conditions.
 - \triangleright Aperiodic, C₆=1 ms, R₆=10 ms, R = maximum allowable response time for a single event
 - a) [1.0] Determine, justifying, if it is possible to guarantee the scalability of the set of tasks τ_1 to τ_5 , by using a criteria based on utilization rate.
 - b) [4.0] Admitting now that the relative deadlines of tasks τ_3 to τ_5 are D_{3-5} =4 ms, determine **analytically** if the task set is schedulable.
 - c) [2.0] It is intended to use a server to handle task τ_6 . Select a suitable server and determine the parameters that allow to comply with the task's response time constraint. Justify clearly your reasoning.

2. [7.0] Consider the task set described below, where R_1 , R_2 and R_3 are shared resources that require mutual exclusion and $E_i(R_i)$ stands for the worst-case time that task τ_i spends on R_j . $E_i(R_j) = 0$ means that task τ_i does not use R_j . The system is scheduled with RM and nested shared resource access is not allowed.

	Ci	$T_i=D_i$	$E_i(R_1)$	E _i (R ₂)	E _i (R ₃)
τ_1	2	5	1	0	1
τ_2	2	10	0	1	0
τ_3	5	20	2	4	1

- a) [1.0] Is preemption disabling a suitable method for handling shared resources in this case? If not, provide an example. [Diagram + 4 lines]
- b) [2.0] Assume that it is used PCP. Compute the blocking times for each task.
- c) [4.0] Determine **analytically** if the system is schedulable with PCP.