

LogicPaper: Reference Manual & Compatibility Matrix

1. String Strategy

Filter Name: format_string

Description: Handles text manipulation.

Operation	Description & Arguments	Syntax	Result	Example Result
upper	Converts text to uppercase.	company format_string('upper')	THE VERY LONG COMPANY NAME LIMITED PARTNERSHIP GLOBAL EDITION	"text" -> "TEXT"
lower	Converts text to lowercase.	company format_string('lower')	the very long company name limited partnership global edition	"TEXT" -> "text"
title	Capitalizes First Letter of Each Word.	company format_string('title')	The Very Long Company Name Limited Partnership Global Edition	"john doe" -> "John Doe"
capitalize	Capitalizes only first character.	company format_string('capitalize')	The very long company name limited partnership global edition	"john doe" -> "John doe"
swapcase	Inverts case.	company format_string('swapcase')	tHE vERY LONG cOMPANY nAME LIMITED pARTNERSHIP gLOBAL eDITION	"PyThon" -> "pYtHON"
trim	Removes whitespace.	company format_string('trim')	The Very Long Company Name Limited Partnership Global Edition	" text " -> "text"
reverse	Reverses characters.	id format_string('reverse')	500-PROC	"abc" -> "cba"
prefix	Adds text before value. Arg: Prefix text.	id format_string('prefix', 'Ref: ')	Ref: CORP-005	"123" -> "Ref: 123"
suffix	Adds text after value. Arg: Suffix text.	company format_string('suffix', '(HQ)')	The Very Long Company Name Limited Partnership Global Edition (HQ)	"Acme" -> "Acme (HQ)"
truncate	Cuts text if exceeds limit. Arg: Max chars (int).	company format_string('truncate', '10')	The Very L...	"Long text..." -> "Long te..."
snake	To snake_case.	company format_string('snake')	the_very_long_company_name_limited_partnership_global_edition	"Logic Paper" -> "logic_paper"
kebab	To kebab-case.	company format_string('kebab')	the-very-long-company-name-limited-partnership-global-edition	"Logic Paper" -> "logic-paper"
slug	To URL slug.	company format_string('slug')	the-very-long-company-name-limited-partnership-global-edition	"H&M!" -> "hm"

2. Number Strategy

Filter Name: format_number

Description: Handles numeric formats.

Operation	Description & Arguments	Syntax	Result	Example Result
int	Converts to Integer. Opt: Format (e.g. '03d').	risk_score format_number('int') risk_score format_number('int', '03d')	10 010	5.9 -> "5" 5 -> "005"
float	Converts to Float. Arg: Precision.	revenue_q4 format_number('float', '2')	9999999.99	10 -> "10.00"
round	Rounds number. Arg: Precision.	growth_pct format_number('round', '2')	1.00	3.6 -> "4"
separator	Thousand/decimal sep. Args: '.', or ',',	revenue_q4 format_number('separator', ',.')	9,999,999.99	1234.5 -> "1.234,50"
currency	Formats money. Opt: ISO Code.	revenue_q4 format_number('currency', 'USD')	US\$ 9.999.999,99	1000 -> "\$1,000.00"
percent	Formats % (x100).	growth_pct format_number('percent')	100%	0.25 -> "25%"
scientific	Scientific notation.	revenue_q4 format_number('scientific')	9,99999999E6	1000 -> "1E3"
humanize	Short format (K, M).	revenue_q4 format_number('humanize')	10M	1500 -> "1.5K"
ordinal	Ordinal number. Req: Locale.	risk_score format_number('ordinal', 'en')	10th	3 -> "3rd"
spell_out	Number in words. Arg: Lang (en, pt).	risk_score format_number('spell_out', 'en')	ten	10 -> "ten"

3. Date Strategy

Filter Name: format_date

Description: Handles dates.

Operation	Description & Arguments	Syntax	Result	Example Result
iso	ISO 8601 (YYYY-MM-DD).	founded_date format_date('iso')	1900-01-01	"2025-12-25"
short	Short local date. Req: Locale.	founded_date format_date('short', 'en')	1/1/00	"12/25/25"
medium	Medium local date. Req: Locale.	founded_date format_date('medium', 'en')	Jan 1, 1900	"Dec 25, 2025"
long	Long local date. Req: Locale.	founded_date format_date('long', 'pt')	1 de janeiro de 1900	"25 de dezembro de 2025"
full	Full date w/ day. Req: Locale.	founded_date format_date('full', 'en')	Monday, January 1, 1900	"Thursday, December 25, 2025"
fmt	Custom strftime. Arg: Pattern.	founded_date format_date('fmt', '%d/%m')	01/01	"25/12"
year	Extracts year.	founded_date format_date('year')	1900	"2025"
month_name	Full month name. Req: Locale.	founded_date format_date('month_name', 'en')	January	"December"
add_days	Add/Sub days. Arg: Int.	founded_date format_date('add_days', '5', 'iso')	1900-01-06	2025-01-01 -> 2025-01-06
add_years	Add/Sub years. Arg: Int.	founded_date format_date('add_years', '1', 'iso')	1901-01-01	2025 -> 2026

4. Logic Strategy

Filter Name: format_logic

Description: Conditionals & Mapping.

Operation	Description & Arguments	Syntax	Result	Example Result
default	Fallback if empty. Arg: Value.	ceo_name format_logic('default', 'Vacant')	Vacant	"" -> "Vacant"
empty_if	Empty if match. Arg: Target.	risk_score format_logic('empty_if', '10')		"10" -> ""
mapping	Switch/Case. Syntax: K=V.	risk_score format_logic('10=Active', '0=Inactive')	Active	"1" -> "Active"
fallback	Implicit Else.	risk_score format_logic('1=Yes', 'Other')	Other	"5" -> "Other"

5. Boolean Strategy

Filter Name: format_bool

Description: 0/1 to Text/Symbol.

Operation	Description & Arguments	Syntax	Result	Example Result
bool	To 'True'/'False'.	is_public format_bool('bool')	True	1 -> "True"
bool (map)	Custom text. Args: T, F.	is_public format_bool('bool', 'Yes', 'No')	Yes	True -> "Yes" False -> "No"
check	Checkbox symbol.	is_public format_bool('check')	☒	True -> " ☒ False -> " ☐

6. Mask Strategy

Filter Name: format_mask

Description: Privacy masking.

Operation	Description & Arguments	Syntax	Result	Example Result
mask	Generic pattern (#). Arg: Pattern.	card_token format_mask('mask', '####-####')	4111-1111	"12345678" -> "1234-5678"
email	Masks username.	email_contact format_mask('email')	c***@verylongdomainnamecom pany.com	"john@doe.com" -> "j***@doe.com"
credit_card	Last 4 digits only.	card_token format_mask('credit_card')	**** * 1111	"1234...1234" -> "**** **** 1234"
name	Initials + ***.	ceo_name format_mask('name')	A***** W***** *****	"John Doe" -> "J*** D***"

7. Image Strategy

Filter Name: format_image

Description: Dynamic images.

Operation	Description & Arguments	Syntax	Result	Example Result
image	Explicit dims (cm). Args: W, H.	logo_img format_image('5', '3')		(Image resized to 5x3 cm)
image (auto)	Width + Auto H. Args: W, 'auto'.	logo_img format_image('10', 'auto')		(Image width 10cm, height proportional)