

Command Line

1) git clone <https://github.com/rubymarroquin/CSE-110-Lab-1.git>

```
rubymarroquin — zsh — 95x28
Last login: Mon Sep 27 16:54:48 on console
rubymarroquin@Rubys-MBP ~ % git clone https://github.com/rubymarroquin/CSE-110-Lab-1.git
Cloning into 'CSE-110-Lab-1'...
remote: Enumerating objects: 3, done.
remote: Counting objects: 100% (3/3), done.
remote: Compressing objects: 100% (2/2), done.
remote: Total 3 (delta 0), reused 0 (delta 0), pack-reused 0
Unpacking objects: 100% (3/3), done.
rubymarroquin@Rubys-MBP ~ % git config --global credential.helper osxkeychain
```

2) cd CSE-110-Lab-1

```
rubymarroquin@Rubys-MBP ~ % cd CSE-110-Lab-1
rubymarroquin@Rubys-MBP CSE-110-Lab-1 % ls
README.md
```

3) git checkout -b add-read-me

```
README.md
rubymarroquin@Rubys-MBP CSE-110-Lab-1 % git checkout -b add-read-me
Switched to a new branch 'add-read-me'
```

4)

```
rubymarroquin@Rubys-MBP CSE-110-Lab-1 % ls
README.md
rubymarroquin@Rubys-MBP CSE-110-Lab-1 % vi README.md
rubymarroquin@Rubys-MBP CSE-110-Lab-1 %
```

```
CSE-110-Lab-1 — vi README.md — 80x24
# CSE-110-Lab-1
Lab 1 for CSE 110 class. This is an individual lab.
Ruby Marroquin's User Page
~
~
~
~
```

5) git commit -m "Update readme file"

```
CSE-110-Lab-1 — -zsh — 80x24
[rubymarroquin@Rubys-MBP CSE-110-Lab-1 % git add .
[rubymarroquin@Rubys-MBP CSE-110-Lab-1 % git commit -m "Update readme file"
[add-read-me 1e7dec2] Update readme file
  Committer: Ruby Marroquin <rubymarroquin@Rubys-MBP.san.rr.com>
Your name and email address were configured automatically based
on your username and hostname. Please check that they are accurate.
You can suppress this message by setting them explicitly:

    git config --global user.name "Your Name"
    git config --global user.email you@example.com

After doing this, you may fix the identity used for this commit with:

    git commit --amend --reset-author

1 file changed, 2 insertions(+), 1 deletion(-)
rubymarroquin@Rubys-MBP CSE-110-Lab-1 %
```

6) git push

```
[rubymarroquin@Rubys-MBP CSE-110-Lab-1 % git push --set-upstream origin add-read-]
me
Username for 'https://github.com': rubycmarroquin
[Password for 'https://rubycmarroquin@github.com':
Enumerating objects: 5, done.
Counting objects: 100% (5/5), done.
Delta compression using up to 8 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (3/3), 354 bytes | 354.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0)
remote:
remote: Create a pull request for 'add-read-me' on GitHub by visiting:
remote:      https://github.com/rubycmarroquin/CSE-110-Lab-1/pull/new/add-read-m
e
remote:
To https://github.com/rubycmarroquin/CSE-110-Lab-1.git
 * [new branch]      add-read-me -> add-read-me
Branch 'add-read-me' set up to track remote branch 'add-read-me' from 'origin'.
rubymarroquin@Rubys-MBP CSE-110-Lab-1 %
```

VSCode UI

