

BRANT RADIANT

RE-VERBER-RAY



HEATERS LIMITED

AGRICULTURAL



PRODUCT FEATURES

- Two-Stage Operation Provides Superior Comfort.
- BTU/h Inputs of 65,000 to 150,000.
- Available in Tube Lengths of 20 to 60 Ft.
- Coated Titanium Stabilized or Aluminized Combustion Chamber.
- Coated Aluminized Radiant Tubes.
- Highly Polished Aluminum Reflectors.
- Water Resistant Burner Control Box.
- External Operational Indicator Lights.
- Potted (water resistant) Circuitry with Self-Diagnostic Capabilities.
- Hot Surface Ignition with Flame Rod Sensing.
- Optional Stainless Steel Upgrades Available.

PRODUCT FEATURES COMPARISON CHART

	RVA2	AG2	AG1
Highly Polished Aluminum Reflectors	•	●	•
Stainless Steel Combustion Chamber	•		
Coated Aluminized Radiant Tubes	•	●	•
Stainless Steel Burner Control Box	•		
Hot Surface Ignition	•	●	•
Type 1 Rubber Hose	•	●	•
Two-stage Technology	•	●	
Potted "Waterproof" Circuitry	•	●	•
Waterproofed Control Box and Electrical Attachments	•	●	•
Optional 'U' or 'L' Configurations Available	•	●	•
24 Volt Control Option	•	●	•

SERIES

○ RVA2

● AG2

○ AG1

AG2 SERIES

AGRICULTURAL GAS FIRED DUAL-STAGE INFRARED HEATERS

The AG2 Series is specifically designed for poultry and non-corrosive agricultural environments. From start-to-finish, producers using infrared heaters have realized higher quality chicks, lower mortality rates, improved animal performance and reduced fuel consumption. Save 20-50% on your fuel bill using radiant tube heat versus other heating appliances. For use in poultry, dairy, barns, shops, arenas and much more.



BRANT RADIANT HEATERS LTD.

34 Scott Ave.
Paris, ON N3L 3R1

Phone: 1-519-442-7823
Toll Free: 1-800-387-4778
Fax: 1-519-442-7321
E-mail: sales@brantradiant.com
Website: www.brantradiant.com

VISIT OUR WEBSITE FOR:

Product Specs • C.A.D. Library
Parts Support • Design Guidelines
Dealer Locator • Theory of Infrared
Applications • and More!

AG2 SERIES

SPECIFICATIONS

PRODUCT SPECIFICATIONS

Input Range:	65,000 to 150,000 BTU/h
Lengths:	20-60 Ft.
Gas Type:	Natural or Propane
Combustion Chamber:	Titanium Stabilized or Aluminized Steel
Radiant Tubes:	Coated Aluminum
Certification:	CSA, IAS
Limited Warranty:	1-3-5 (Components-Tubes-Burner)

OPTIONAL EQUIPMENT

U or L Configurations:	Available (RUP, REP)
Stainless Steel Upgrades:	Available (AGAO-SS, SSTAO, SSRAO)
24V Controls:	Standard
Indicator Lights:	Standard
Three-prong Power Cord	Standard
Protective Guards:	Available (PG)
Side Shield Extensions:	Available (SSE)
Aluminum Steel Tubes:	Available (ALUM-AO)

Reference the AG Accessory List for additional upgrade options and accessories.

ELECTRICAL

- 120V, 60Hz, 3-wire.
- 4.8A starting, 1.1A running.

CONTROLS

- Water resistant microprocessor circuitry provides soft-lockout and self-diagnostic capabilities.
- 24V thermostatic control (Field supplied 24V).

TUBE CONSTRUCTION

- As shown to left
- 4" x 10' 16 ga. construction.
- Labor saving, interlocking swaged tube design.

REFLECTORS

- Highly polished aluminum.
- End caps included.
- Tension springs.
- 0° – 45° rotatable angle.

IGNITION/SENSE

- Hot surface ignition.
- Flame rod sense.

VENTING

- Venting options for roof or sidewall.
- Optional unvented use with WVE-GALV.

GAS CONNECTION

- 1/2" male NPT.
- 36" Type 1 Rubber Hose.

GAS PRESSURES

- MAN: 3.5" NAT or 10.0" LP
- MIN: 5.0" NAT or 11.0" LP
- MAX: 14.0" NAT or 14.0" LP

COMBUSTION AIR

- Required in harsh environments.
- Equipped for ducted air intake from roof or sidewall.

KIT CONTENTS

- All hangers & hose.
- Reflector end caps.
- Turbulator baffles.

AVAILABLE AG2 MODELS & CLEARANCES

MODEL #	GAS*	BTU/H HIGH FIRE	BTU/H LOW FIRE	LENGTH	WEIGHT	MOUNTING HEIGHTS**
AG2-20-65	N or LP	65,000	50,000	21'-7"	120 lbs.	6' to 9'
AG2-20-75	N or LP	75,000	50,000	21'-7"	120 lbs.	7' to 10'
AG2-20-80	N or LP	80,000	52,000	21'-7"	120 lbs.	8' to 14'
AG2-30-65	N or LP	65,000	50,000	31'-3"	160 lbs.	6' to 9'
AG2-30-75	N or LP	75,000	50,000	31'-3"	160 lbs.	7' to 10'
AG2-30-80	N or LP	80,000	52,000	31'-3"	160 lbs.	8' to 14'
AG2-30-100	N or LP	100,000	65,000	31'-3"	160 lbs.	8' to 14'
AG2-40-65	N or LP	65,000	50,000	40'-11"	190 lbs.	6' to 9'
AG2-40-75	N or LP	75,000	50,000	40'-11"	190 lbs.	7' to 12'
AG2-40-80	N or LP	80,000	52,000	40'-11"	190 lbs.	8' to 14'
AG2-40-100	N or LP	100,000	65,000	40'-11"	190 lbs.	7' to 13'
AG2-40-125	N or LP	125,000	95,000	40'-11"	190 lbs.	9' to 13'
AG2-40-150	N or LP	150,000	100,000	40'-11"	190 lbs.	10' to 14'
AG2-50-100	N or LP	100,000	65,000	50'-7"	235 lbs.	8' to 12'
AG2-50-125	N or LP	125,000	95,000	50'-7"	235 lbs.	9' to 14'
AG2-50-150	N or LP	150,000	100,000	50'-7"	235 lbs.	10' to 14'
AG2-60-150	N or LP	150,000	100,000	60'-3"	265 lbs.	10' to 14'

* Specify natural (N) or propane (LP) gas. ** Recommended mounting heights are provided as a guideline. Actual conditions may dictate variations from the above data.

0° Mounting Angle 45° Mounting Angle 0° W/ 1 Side Shield 0° W/ 2 Side Shields



DISTRIBUTED BY:



AG2 CLEARANCES TO COMBUSTIBLES (IN.)

MODEL NO.	MOUNTING ANGLE	FRONT	BEHIND	TOP	BELOW
AG2-(20,30,40)-65,75	0°	9	9	6	60
	45°	39	8	10	60
	W/1 side shield	29	8	6	60
	W/2 side shields	9	9	6	60
	20 ft. from burner	7	7	6	30
AG2-(20,30,40,50)-80,100	0°	14	14	6	66
	45°	39	8	10	66
	W/1 side shield	29	8	6	66
	W/2 side shields	16	16	6	66
	20 ft. from burner	7	7	6	30
AG2-(40,50)-125	0°	20	20	6	76
	45°	58	8	10	76
	W/1 side shield	42	8	6	76
	W/2 side shields	20	20	6	76
	20 ft. from burner	7	7	6	30
AG2-(40,50,60)-150	0°	24	24	6	81
	45°	58	8	10	81
	W/1 side shield	42	8	6	81
	W/2 side shields	23	23	6	81
	20 ft. from burner	11	11	6	44

Always maintain the published clearances to combustibles.

Clearances published in AG2 Series manual and on warning label supersede data shown on this brochure.