

# Scaling Up Group Steiner Tree Search on Graphs: A Two-hop Label Based Approach

The road map of this supplement is as follows.

- In Section S1, we show the pseudo code of HL4GST.
- In Section S2, we provide proofs that are omitted in the main contents.
- In Section S3, we discuss complexities of the proposed algorithms in detail.
- In Section S4, we demonstrate that the label update process in state-of-the-art methods [4, 7] has a larger time cost than the new label update process in BatchM4GST.

## Algorithm S1. The HL4GST algorithm

**Input:** a graph  $G(V, E, w)$  with mock components

**Output:** a set  $L$  of 2-hop labels

---

```

1: Initialize  $L = L' = \emptyset$ 
2: for each sorted vertex  $u \in V$  in parallel do
3:   Initialize  $H(u) = 0, Q = \{u \mid H(u)\}$ 
4:   while  $Q \neq \emptyset$  do
5:     Pop  $v$  out of  $Q$  with the priority value of  $H(v)$ 
6:     if  $r(u) < r(v)$  or  $Query(u, v, L') \leq H(v)$  then
7:       Continue to Line 4
8:     Insert  $(u, H(v))$  into  $L'(v)$ 
9:     for each vertex  $x \in N(v)$  do
10:      if  $x \notin H$  then
11:        if  $H(v) + w(x, v) < 2M$  then
12:          Insert  $x$  into  $Q$  with the priority value of  $H(x) = H(v) + w(x, v)$ 
13:        else if  $H(x) > H(v) + w(x, v)$  then
14:          Update  $x$  in  $Q$  with the priority value of  $H(x) = H(v) + w(x, v)$ 
15: for each vertex  $u \in V$  in parallel do
16:   Sort labels in  $L'(u)$  by the ranks of inside hubs from high to low
17: for each vertex  $u \in V$  in parallel do
18:   for each sorted label  $(v, d(u, v)) \in L'(u)$  do
19:     Compute  $d'(u, v)$ : the queried distance between  $u$  and  $v$  using  $L'_{>r(v)}(u)$  and  $L'(v)$ 
20:     if  $d'(u, v) > d(u, v)$  then
21:       Insert  $(v, d(u, v))$  into  $L(u)$ 
22: Return  $L$ 

```

---

## S1. THE PSEUDO CODE OF HL4GST

The proposed HL4GST follows a state-of-the-art parallel implementation [1] of the Pruned Landmark Labeling framework, given that other parallel executions [2, 3] do not suit weighted graphs. We demonstrate the pseudo code of HL4GST as Algorithm S1. The differences between Algorithm S1 and Algorithm 1 in the main contents are as follows.

- Algorithm S1 incorporates an original GST-customized filtering technique. Specifically, If  $H$  does not contain  $x$  yet in Line 10, then HL4GST checks whether

$$H(v) + w(x, v) < 2M. \quad (S1)$$

If it is, HL4GST inserts  $x$  into  $Q$ . Otherwise, it does not perform this insertion operation.

- Algorithm S1 follows the parallel implementation modifications in [1]. In particular, it pushes each vertex  $u \in V$  into a thread pool in the decreasing order of vertex ranks, for parallelly and roughly sequentially processing each  $u \in V$  in Line 2. It employs both a rank pruning technique and the distance query pruning method in Line 6, and uses  $L'$  to store labels generated in Line 8. Due to the parallel nature of this process,  $L'$  could contain redundant labels. it eliminates redundant labels in Lines 15-21. The details are as follows.

It contains a fast label cleaning process for identifying and removing redundant labels. For each  $u \in V$ , it sorts labels in  $L'(u)$  by hub ranks from high to low (Line 16), for fast querying shortest distances as follows. Specifically, for each  $u \in V$ , it sequentially enumerates each sorted label  $(v, d(u, v)) \in L'(u)$  (Line 18). Let  $L'_{>r(v)}(u)$  be the set of enumerated labels in  $L'(u)$ , i.e., the set of labels with hubs of higher ranks than  $r(v)$  in  $L'(u)$ . It uses  $L'_{>r(v)}(u)$  and  $L'(v)$  to query the distance between  $u$  and  $v$  as  $d'(u, v)$ . If  $d'(u, v) > d(u, v)$ , which means that  $(v, d(u, v)) \in L'(u)$  is not redundant, then it inserts this label into  $L(u)$  (Line 21). After this fast label cleaning process, it returns  $L$  ultimately.

**Enhancements of HL4GST for label maintenance:** As discussed in the main contents, to enable fast label maintenance in dynamic scenarios, we use Pruning Point Record (PPR) [4] to record the pruning information in HL4GST. For a pair of vertices  $v_i$  and  $v_j$ ,  $PPR[v_i, v_j]$  is a set of vertices. If  $r(u) > r(v)$  and  $Query(u, v, L') \leq H(v)$  in Line 6, we insert  $u$  into  $PPR[v, h_c]$ , and also insert  $v$  into  $PPR[u, h_c]$ , where  $h_c \in C(u) \cap C(v)$  is the common hub for the queried distance between  $u$  and  $v$  in Line 6. Moreover, if  $d'(u, v) \leq d(u, v)$  in Line 20, we insert  $u$  into  $PPR[v, h_c]$ , and insert  $v$  into  $PPR[u, h_c]$ , where  $h_c$  is the common hub for the queried distance between  $u$  and  $v$  using  $L'_{>r(v)}(u)$  and  $L'(v)$ . This step is necessary for performing the fast label cleaning process in dynamic cases.

## S2. PROOFS OF THEOREMS

We demonstrate theorems and proofs as follows.

**Theorem 1.** *A set of 2-hop labels that satisfies the GST-customized 2-hop cover constraint supports the query of a shortest path between every pair of a vertex  $v \in V$  and a candidate vertex group  $g \in \Gamma_{all}$ .*

*Proof.* We show that we can query the shortest distance/path between every pair of a vertex  $v \in V$  and a candidate vertex group  $g \in \Gamma_{all}$  using a set  $L$  of 2-hop labels that satisfies the above constraint as follows. There are two different cases:

1. Case 1: there is a path between  $v$  and  $g$  on the original graph. Since each mock edge weight  $M$  is larger than the total weight of all non-mock edges, a shortest path between  $v$  and  $v_g$  on the transformed graph contains a shortest path between  $v$  and  $g$  on the original graph. Since  $|\{v, v_g\} \cap D| < 2$ , there is a common hub vertex  $u \in C(v) \cap C(v_g)$  in a shortest path between  $v$  and  $v_g$ . Thus, we can use  $L$  to query the shortest distance between  $v$  and  $v_g$ , which is smaller than  $2M$  and equals the shortest distance between  $v$  and  $g$  on the original graph plus  $M$ . Hence, equivalently, we can use  $L$  to query the shortest distance between  $v$  and  $g$ . Furthermore, since there is no mock vertex in the middle of a shortest path between  $v$  and  $v_g$  on the transformed graph, we can also iteratively query the shortest path between  $v$  and  $g$  on the original graph by adding predecessors into labels.
2. Case 2: there is no path between  $v$  and  $g$  on the original graph. Thus,  $v$  and  $v_g$  are not properly connected, and there may not be a common hub vertex  $u \in C(v) \cap C(v_g)$ . If there is no common hub vertex  $u \in C(v) \cap C(v_g)$ , then we can directly deduce that there is no path between  $v$  and  $g$  on the original graph. If there is a common hub vertex  $u \in C(v) \cap C(v_g)$ , then since  $v$  and  $v_g$  are not properly connected on the transformed graph, there must be at least one mock vertex in the middle of any path between  $v$  and  $v_g$ , and as a result the queried distance of any path between  $v$  and  $v_g$  is no smaller than  $2M$ , which still indicates that there is no path between  $v$  and  $g$  on the original graph.

Hence, this theorem holds.  $\square$

**Theorem 2.** *A set of 2-hop labels that has the GST-customized canonical property is minimal for meeting the GST-customized 2-hop cover constraint.*

*Proof.* Consider a set  $L$  of 2-hop labels that has the GST-customized canonical property. For every pair of properly connected vertices  $v_i$  and  $v_j$  such that  $|\{v_i, v_j\} \cap D| < 2$ , let  $v_k$  be the vertex with the highest rank in all shortest paths between  $v_i$  and  $v_j$ . We have  $v_k \notin D$  and  $v_k \in C(v_i) \cap C(v_j)$ , since  $v_k$  has the highest rank in all shortest paths between  $v_i$  and  $v_k$ , as well as between  $v_j$  and  $v_k$ , and no vertices in these shortest paths can be hubs of  $v_k$ , except itself. Thus,  $L$  meets the GST-customized 2-hop cover constraint. Moreover, consider an arbitrary label  $(v_i, d_{v_i v_j}) \in L(v_j)$ . We have (i)  $v_i$  and  $v_j$  are properly connected; (ii)  $|\{v_i, v_j\} \cap D| < 2$ ; and (iii) the rank of  $v_i$  is the highest among all vertices in all shortest paths between  $v_i$  and  $v_j$ . Thus, there is no other vertex  $v_k \in C(v_i) \cap C(v_j)$  in a shortest path between  $v_i$  and  $v_j$ , i.e., deleting this arbitrary label makes  $L$  not satisfy the GST-customized 2-hop cover constraint any more. Hence, this theorem holds.  $\square$

**Theorem 3.** *The set  $L$  of 2-hop labels generated by HL4GST has the GST-customized canonical property, and thus is minimal for meeting the GST-customized 2-hop cover constraint.*

*Proof.* Let  $L^{can}$  be the set of labels that has the GST-customized canonical property. We prove that every label in  $L^{can}$  is also in  $L$  as follows.

Consider an arbitrary label  $(u, d_{vu}) \in L^{can}(v)$ . We observe that (i)  $u$  and  $v$  are properly connected; (ii)  $|\{u, v\} \cap D| < 2$ ; and (iii) the rank of  $u$  is the highest among all vertices in all

shortest paths between  $u$  and  $v$ . Thus, we have  $d_{vu} < 2M$ , and the generation of the above label cannot be pruned by GST-customized pruning technique in Line 11 of HL4GST. Further consider the labeling process for hub  $u$  in HL4GST. HL4GST generates labels with hub  $u$  by spreading  $u$  to other vertices, starting from  $u$ , via a Dijkstra-style process. Suppose that the spread of hub  $u$  to  $v$  along a shortest path between  $u$  and  $v$  stops at a middle vertex  $v'$  due to the query pruning technique in Line 6 of HL4GST. This means that, before inserting  $(u, d_{v'u})$  into  $L'(v')$ , the queried distance between  $u$  and  $v'$  is no larger than  $d_{v'u}$ . As a result, there must be a common hub vertex  $z \in C(u) \cap C(v')$  such that  $z$  is in a shortest path between  $u$  and  $v'$ , and  $r(z) > r(u)$ . This contradicts with the fact that the rank of  $u$  is the highest among all vertices in all shortest paths between  $u$  and  $v'$ . Consequently, the spread of hub  $u$  to  $v$  along a shortest path between  $u$  and  $v$  cannot stop at a middle vertex, and as a result HL4GST inserts  $(u, d_{vu})$  into  $L'(v)$ .

We further show that HL4GST also inserts  $(u, d_{vu})$  into  $L(v)$  as follows. When it checks  $(u, d_{vu}) \in L'(v)$  in Line 18 during the cleaning process, it computes  $d'(u, v)$  using  $L'_{>r(u)}(v)$  and  $L'(u)$ . If  $d'(u, v) \leq d_{vu}$ , then there must be a common hub vertex  $z \in C(u) \cap C(v)$  such that  $z$  is in a shortest path between  $u$  and  $v$ , and  $r(z) > r(u)$ . This contradicts with the fact that the rank of  $u$  is the highest among all vertices in all shortest paths between  $u$  and  $v$ . Consequently,  $d'(u, v) > d_{vu}$  and HL4GST also inserts  $(u, d_{vu})$  into  $L(v)$ . Hence, every label in  $L^{can}$  is also in  $L$ .

We further prove that every label not in  $L^{can}$  is not in  $L$  as follows. Suppose that there is a label  $(u, d_{vu}) \in L(v) \setminus L^{can}(v)$ . We observe that (i)  $u$  and  $v$  are not properly connected; or (ii)  $|\{u, v\} \cap D| = 2$ ; or (iii) the rank of  $u$  is not the highest among all vertices in all shortest paths between  $u$  and  $v$ . If  $u$  and  $v$  are not properly connected or  $|\{u, v\} \cap D| = 2$ , then  $d_{vu} \geq 2M$ , and the generation of the above label will be pruned by GST-customized pruning technique in Line 11 of HL4GST, which means that  $(u, d_{vu}) \notin L(v)$ . Otherwise, we consider the case where the rank of  $u$  is not the highest among all vertices in all shortest paths between  $u$  and  $v$  as follows. Let  $z$  be the vertex with the highest rank in all shortest paths between  $u$  and  $v$ . We have  $(z, d_{zv}) \in L'_{>r(u)}(v)$  and  $(z, d_{zu}) \in L'(u)$ . As a result, HL4GST computes  $d'(u, v)$  as a value no larger than  $d_{vu}$  in Line 19, and does not insert  $(u, d_{vu})$  into  $L$ . Hence, every label not in  $L^{can}$  is not in  $L$ . In conclusion, we have  $L^{can} = L$ . By Theorem 2, this theorem holds.  $\square$


**Theorem 4.** *Given a graph and a corresponding set of 2-hop labels that satisfies the GST-customized 2-hop cover constraint, after a batch of edge insertions and edge weight decreases, the maintained set of labels by BatchM4GST-Insert satisfies the above constraint for the updated graph.*

*Proof.* Consider a pair of vertices  $s$  and  $t$ . We use  $p'(s, t)$  to denote a shortest path between  $s$  and  $t$  after the change. Let  $u'$  be the vertex with the highest rank in all shortest paths between  $s$  and  $t$  after the change, and  $u' \in p'(s, t)$ . Also let  $d'(s, t)$  be the shortest distance between  $s$  and  $t$  after the change. Suppose that  $|\{s, t\} \cap D| < 2$  and  $d'(s, t) < 2M$ , i.e.,  $s$  and  $t$  are properly connected after the change.

Let  $E_{in} = \{(a_1, b_1), \dots, (a_i, b_i)\}$  be the set of changed edges on  $p'(s, t)$ , i.e.,  $E_{in} \subseteq E_c$ . Notably,  $E_{in}$  could be empty. Without loss of generality, suppose that  $a_x$  is closer to  $s$  than  $b_x$  along  $p'(s, t)$  for each  $x \in [1, i]$ , and  $u'$  is between  $(a_k, b_k)$  and  $(a_{k+1}, b_{k+1})$ , as illustrated in Figure S1. Since there are only edge insertions and edge weight decreases,  $p'(u', b_k)$  is a shortest path between  $u'$  and  $b_k$  both before and after the change, and  $u'$  has the highest rank in all shortest paths between  $u'$  and  $b_k$  both before and after the change. We also have  $|\{u', b_k\} \cap D| < 2$  and  $d'(u', b_k) < 2M$ .

Suppose that  $u'$  is not a hub of  $b_k$  before the maintenance. Since the given set of 2-hop labels satisfies the GST-customized 2-hop cover constraint, to correctly query  $d'(u', b_k)$ , there must be a vertex  $z$  such that  $z \in C(u') \cap C(b_k)$ ,  $r(z) > r(u')$ , and  $z$  is in a shortest path between  $u'$  and  $b_k$ . This contradicts with the assumption that  $u'$  has the highest rank in all shortest paths between  $u'$  and  $b_k$ . Thus,  $(u', d'(b_k, u')) \in L(b_k)$ , and further  $(u', d'(a_{k+1}, u')) \in L(a_{k+1})$ , before the maintenance. BatchM4GST-Insert calls *DIFFUSE* to re-spread hub  $u'$  from  $b_k$  to  $s$ , and from  $a_{k+1}$  to  $t$ , along  $p'(s, t)$ . Thus,  $(u', d'(s, u')) \in L(s)$ , and similarly  $(u', d'(t, u')) \in L(t)$ , after the maintenance. Hence, for every pair of properly connected vertices  $v_i$  and  $v_j$  such that  $|\{v_i, v_j\} \cap D| < 2$ , there is a common hub vertex  $u \in C(v_i) \cap C(v_j)$  on a shortest path between  $v_i$  and  $v_j$ , i.e., the set of labels maintained by BatchM4GST-Insert still satisfies the GST-customized 2-hop cover constraint. This theorem holds.  $\square$

**Theorem 5.** *Given a graph and a corresponding set of 2-hop labels that satisfies the GST-customized 2-hop cover constraint, after a batch of edge deletions and edge weight increases, the maintained set of labels by BatchM4GST-Delete satisfies the above constraint for the updated graph.*



**Fig. S1.** An illustration for the correctness proofs of the proposed maintenance algorithms.

*Proof.* We use the notations in the proof of Theorem 4. Consider an arbitrary label  $(z, d(z, x)) \in L(x)$  before the change. If this label corresponds to a path that passes through a changed edge, i.e.,  $d'(z, x) \geq d(z, x)$ , then BatchM4GST-Delete must call *SPREAD*<sub>1</sub> to set  $L(x)[z]$  to  $\infty$ .

Subsequently, consider a pair of vertices  $s$  and  $t$  such that  $|\{s, t\} \cap D| < 2$  and  $d'(s, t) < 2M$ , i.e.,  $s$  and  $t$  are properly connected after the change. We use  $p'(s, t)$  to denote a shortest path between  $s$  and  $t$  after the change. Let  $u'$  be the vertex with the highest rank in all shortest paths between  $s$  and  $t$  after the change, and  $u' \in p'(s, t)$ .

Before the maintenance, let  $y$  be the vertex farthest to  $u'$  along  $p'(u', b_k)$  such that  $u'$  is a hub of  $y$ , and the corresponding label-contained distance value is  $d'(u', y)$ . Let  $x$  be the neighbor of  $y$  along  $p'(u', b_k)$  such that  $u'$  is not a hub of  $x$ , or  $u'$  is a hub of  $x$  but the corresponding label-contained distance value is not  $d'(u', x)$ .

If  $u'$  is a hub of  $x$  but the corresponding label-contained distance value is not  $d'(u', x)$  before the maintenance, then we must have  $d'(u', x) > d(u', x)$ . In this case, BatchM4GST-Delete must call *SPREAD*<sub>1</sub> to set  $L(x)[u']$  to  $\infty$ , and then call *SPREAD*<sub>2</sub> and *SPREAD*<sub>3</sub> to re-spread hub  $u'$  from  $y$  to  $x$ , and ultimately to  $s$ , along  $p'(s, t)$ , i.e., to generate a new label  $(u', d'(u', s)) \in L(s)$ .

If  $u'$  is not a hub of  $x$  before the maintenance, then there must be a vertex  $z$  such that  $z \in C(u') \cap C(x)$ ,  $r(z) > r(u')$ , and  $z$  is in a shortest path between  $u'$  and  $x$ , and  $u' \in PPR[x, z]$  and  $x \in PPR[u', z]$  before the maintenance. Since  $u'$  is the vertex with the highest rank in all shortest paths between  $u'$  and  $x$  after the change,  $z$  is not in a shortest path between  $u'$  and  $x$  after the change. To meet this condition, either  $L(u')[z]$  or  $L(x)[z]$  increases after the graph change. Thus, BatchM4GST-Delete must call *SPREAD*<sub>1</sub> to set either  $L(u')[z]$  or  $L(x)[z]$  to  $\infty$ . In either case, using the above *PPR*, it performs *SPREAD*<sub>2</sub> and *SPREAD*<sub>3</sub> to re-spread hub  $u'$  from  $y$  to  $x$ , and ultimately to  $s$ , along  $p'(s, t)$ , i.e., to generate a new label  $(u', d'(u', s)) \in L(s)$ .

Therefore, in either case, we have  $(u', d'(u', s)) \in L(s)$ , and similarly  $(u', d'(u', t)) \in L(t)$  after the maintenance. Hence, for every pair of properly connected vertices  $v_i$  and  $v_j$  such that  $|\{v_i, v_j\} \cap D| < 2$ , there is a common hub vertex  $u \in C(v_i) \cap C(v_j)$  on a shortest path between  $v_i$  and  $v_j$ , i.e., the set of labels maintained by BatchM4GST-Delete still satisfies the GST-customized 2-hop cover constraint. This theorem holds.  $\square$

### S3. COMPLEXITIES OF ALGORITHMS

#### A. Complexities of HL4GST

The time complexity of the proposed HL4GST is

$$O(|E| \cdot \delta \cdot (\delta + \log |V|))$$

in a single thread environment, where  $\delta$  is the average number of labels associated with each vertex. The details are as follows. First, the labeling process in Lines 1-14 takes  $O(|E| \cdot \delta \cdot (\delta + \log |V|))$  time. The reason is that, for each label inserted into  $L'(v)$  in Line 8, it may insert  $|N(v)|$  elements into  $Q$  in Line 12, and for each element in  $Q$ , it takes  $O(\log |V|)$  time to pop it out in Line 5 (e.g., using Fibonacci heap [5]) and  $O(\delta)$  time to query a distance in Line 6. Second, the sorting process in Lines 15-16 takes  $O(|V| \cdot \delta \cdot \log \delta)$  time. Since we generally have  $|E| \gg |V|$ , the above complexity is covered by that of the labeling process. Third, the cleaning process in Lines 17-21 takes  $O(|V| \cdot \delta^2)$  time, given that a distance query that costs  $O(\delta)$  is required for cleaning each label. The cost of  $O(|V| \cdot \delta^2)$  is also covered by that of the labeling process. On the other hand, the space complexity of HL4GST is  $O(|V| \cdot \delta)$  without *PPR*, and  $O(|E| \cdot \delta)$  with *PPR*.

#### B. Complexities of BatchM4GST-Insert

The proposed BatchM4GST-Insert has a time complexity of

$$O(|E_c| \cdot \delta^2 + Y \cdot (\log Y + d_a \cdot \delta))$$

in a single thread environment, where  $Y$  is the number of update labels, and  $d_a$  is the average degree of vertices that are associated with these labels. The details are as follows. First, populating

$CL$  in Lines 1-18 takes  $O(|E_c| \cdot \delta^2)$  time, since each distance query in Lines 5 and 13 costs  $O(\delta)$ . Second,  $DIFFUSE$  takes  $O(Y \cdot (\log Y + d_a \cdot \delta))$  time. The reason is that, since  $O(|CL|) = O(Y)$ , the initialization steps in Lines 21-23 takes  $O(Y \cdot \log Y)$  time. Moreover,  $DIFFUSE$  pops  $O(Y)$  elements out of the priority queue. Each pop operation takes  $O(\log Y)$  times. After each pop, it searches  $O(d_a)$  neighbors, and a distance query that costs  $O(\delta)$  may be conducted in each search. On the other hand, due to the cost of  $PPR$ , the space complexity of BatchM4GST-Insert is  $O(|E| \cdot \delta)$ .

### C. Complexities of BatchM4GST-Delete

The proposed BatchM4GST-Delete has a time complexity of

$$O(|E_c| \cdot \delta + Y \cdot (\log Y + d_a \cdot \delta + \kappa \cdot (d_a + \delta)))$$

in a single thread environment, where  $\kappa$  is the average number of  $PPR$  elements of each vertex-hub pair. The details are as follows. First, it pushes labels into  $AL_1$  in Lines 2-8 in  $O(|E_c| \cdot \delta)$  time. Then, it performs  $SPREAD_1$  in  $O(Y \cdot d_a)$  time, since there are  $O(Y)$  labels deactivated, and each deactivation is followed by  $O(d_a)$  neighbor searches. Subsequently, it performs  $SPREAD_2$  in  $O(Y \cdot \kappa \cdot (d_a + \delta))$  time, since for each of  $O(Y)$  tuples in  $AL_2$ , it checks  $O(\kappa)$   $PPR$  elements in Line 19, while checking each  $PPR$  element takes  $O(d_a + \delta)$  time, due to the cost of  $O(d_a)$  for computing  $d1(x, t)$  and  $d1(t, x)$  in Lines 21 and 28, and the cost of  $O(\delta)$  for querying distances in Lines 23 and 30. After that, similar to  $DIFFUSE$  in BatchM4GST-Insert, it performs  $SPREAD_3$  in  $O(Y \cdot (\log Y + d_a \cdot \delta))$  time, given that  $O(|AL_3|) = O(Y)$ . In the end, due to the cost of  $PPR$ , the space complexity of BatchM4GST-Delete is  $O(|E| \cdot \delta)$ .

## S4. THE LABEL UPDATE PROCESS IN STATE-OF-THE-ART METHODS

As discussed in the main contents, the label update process in state-of-the-art methods [4, 7] has a larger time cost than the new label update process in the proposed BatchM4GST. Specifically, the state-of-the-art methods may unnecessarily update a label multiple times, while BatchM4GST updates a specific label at most once even in batch cases. We discuss this in detail.

We take DecreaseAsyn in [4] as an example to show the label update process in state-of-the-art methods. We refer to DecreaseAsyn as InsertAsyn in the main experiments. It maintains labels after an edge weight decrease or an edge insertion, and can be parallelly implemented in batch cases [7]. Another state-of-the-art method, IncreaseAsyn in [4] that deals with an edge weight increase or an edge deletion, has a similar label update process with DecreaseAsyn.

We first briefly introduce the state-of-the-art DecreaseAsyn, and then analyze the label update process in DecreaseAsyn in detail, as follows.

### A. A brief introduction of the state-of-the-art DecreaseAsyn

We show the pseudo code of DecreaseAsyn as Algorithm S2. Suppose that the weight of an edge  $(a, b) \in E$  decreases from  $w_0(a, b)$  to  $w_1(a, b)$ . The idea of DecreaseAsyn is to update all outdated label-contained distance values that correspond to paths that pass through the old  $(a, b)$ , first for labels of  $a$  and  $b$ , and then neighbors of  $a$  and  $b$ , and then neighbors of neighbors, etc.

DecreaseAsyn first initializes two empty sets:  $CL^c$  and  $CL^n$  (Line 1). It uses  $CL^c$  to record new labels of  $a$  and  $b$  in Lines 2-17. DecreaseAsyn uses  $CL^c$  to record new labels of  $b$  as follows. For each  $(v, d_{va}) \in L(a)$ , if  $r(v) \geq r(b)$  (Line 3), which means that  $v$  could be a hub of  $b$ , then it checks whether the queried distance between  $v$  and  $b$  is larger than  $d_{va} + w_1(a, b)$ . If it is, then we can generate a new label  $(v, d_{va} + w_1(a, b)) \in L(b)$ . Thus, it sets  $L(b)[v] = d_{va} + w_1(a, b)$ , and pushes  $(b, v, d_{va} + w_1)$  into  $CL^c$  (Line 5), for iteratively updating more labels in later processes. Otherwise, it conducts the above step when  $v \in C(b) \& L(b)[v] > d_{va} + w_1(a, b)$  (Line 7), and then inserts  $v$  into  $PPR[b, h_c]$ , and also inserts  $b$  into  $PPR[v, h_c]$ , where  $h_c$  is the common hub responsible for the queried distance between  $v$  and  $b$ . The condition that  $v \in C(b) \& L(b)[v] > d_{va} + w_1(a, b)$  means that  $v$  is already a hub of  $b$ , and  $L(b)[v]$  is larger than, but should be decreased to,  $d_{va} + w_1(a, b)$ . This step is necessary for combining DecreaseAsyn and IncreaseAsyn together to deal with fully dynamic cases where edge weights may alternately increase and decrease. After that, it uses  $CL^c$  to record new labels of  $a$  similarly (Lines 10-17).

Subsequently, while  $CL^c \neq \emptyset$ , DecreaseAsyn iteratively uses the *ProDecrease* procedure to update more labels (Line 18).  $CL^c$  and  $CL^n$  are the sets of updated labels in the last and current iterations, respectively. To perform these iterations, it sets  $CL^c = CL^n$  and  $CL^n = \emptyset$  after using *ProDecrease* in each iteration. In *ProDecrease*, for each  $(u, v, d_u) \in CL^c$  (Line 20), it checks each neighbor  $u_n$  of  $u$  (Line 21). If  $r(v) > r(u_n)$ , which means that  $v$  could be a hub of  $u_n$ , then it checks

```

Input: the original  $G_0(V, E_0, w_0)$ , the updated  $G_1(V, E_1, w_1)$ ,  $(a, b)$ ,  $L$ ,  $PPR$ 
Output: the maintained  $L$  and  $PPR$ 
1:  $CL^C = CL^N = \emptyset$ 
2: for each label  $(v, d_{va}) \in L(a)$  do
3:   if  $r(v) \geq r(b)$  then
4:     if  $Query(v, b, L) > d_{va} + w_1(a, b)$  then
5:        $L(b)[v] = d_{va} + w_1(a, b)$ ,  $CL^C.push((b, v, d_{va} + w_1(a, b)))$ 
6:     else
7:       if  $v \in C(b)$  &  $L(b)[v] > d_{va} + w_1(a, b)$  then
8:          $L(b)[v] = d_{va} + w_1(a, b)$ ,  $CL^C.push((b, v, d_{va} + w_1(a, b)))$ 
9:          $PPR[b, h_c].push(v)$ ,  $PPR[v, h_c].push(b)$ 
10: for each label  $(v, d_{vb}) \in L(b)$  do
11:   if  $r(v) \geq r(a)$  then
12:     if  $Query(v, a, L) > d_{vb} + w_1(a, b)$  then
13:        $L(a)[v] = d_{vb} + w_1(a, b)$ ,  $CL^C.push((a, v, d_{vb} + w_1(a, b)))$ 
14:     else
15:       if  $v \in C(a)$  &  $L(a)[v] > d_{vb} + w_1(a, b)$  then
16:          $L(a)[v] = d_{vb} + w_1(a, b)$ ,  $CL^C.push((a, v, d_{vb} + w_1(a, b)))$ 
17:          $PPR[a, h_c].push(v)$ ,  $PPR[v, h_c].push(a)$ 
18: while  $CL^C \neq \emptyset$  do  $ProDecrease(CL^C, CL^N)$ ,  $CL^C = CL^N$ ,  $CL^N = \emptyset$ 
19: Return  $L$  and  $PPR$ 

```

$j \in [d_a + 2, Y]$ , it sequentially updates  $L(v_j)[v_0] = W + 1 + d_a - i + 2$  through the path between  $v_i$  and  $v_j$  for each  $i \in [2, d_a + 1]$ . As a result, they update label-contained distance values  $O(Y \cdot d_a)$  times. Since each label update in an iterative call of *ProDecrease* induces  $O(d_a)$  distance queries in the next iterative call, *DecreaseAsyn* conducts  $O(Y \cdot d_a^2)$  distance queries. Since each distance query takes  $O(\delta)$  time, the label update process in *DecreaseAsyn* costs  $O(Y \cdot d_a^2 \cdot \delta)$ .

In comparison, as discussed before, the new label update process in the proposed *BatchM4GST* has a smaller time cost of

$$O(Y \cdot (\log Y + d_a \cdot \delta)),$$

given that we generally have  $d_a^2 \cdot \delta \gg \log Y + d_a \cdot \delta$ .

## REFERENCES FOR THE SUPPLEMENT

1. K. Lakhoria, R. Kannan, Q. Dong, and V. Prasanna, "Planting trees for scalable and efficient canonical hub labeling," *Proc. VLDB Endow.* **13** (2019).
2. W. Li, M. Qiao, L. Qin, Y. Zhang, L. Chang, and X. Lin, "Scaling distance labeling on small-world networks," in *Proceedings of the 2019 International Conference on Management of Data*, (2019), pp. 1060–1077.
3. R. Jin, Z. Peng, W. Wu, F. Dragan, G. Agrawal, and B. Ren, "Parallelizing pruned landmark labeling: dealing with dependencies in graph algorithms," in *Proceedings of the 34th ACM International Conference on Supercomputing*, (2020), pp. 1–13.
4. M. Zhang, L. Li, W. Hua, and X. Zhou, "Efficient 2-hop labeling maintenance in dynamic small-world networks," in *2021 IEEE 37th International Conference on Data Engineering*, (IEEE, 2021), pp. 133–144.
5. M. L. Fredman and R. E. Tarjan, "Fibonacci heaps and their uses in improved network optimization algorithms," *Journal of the ACM* **34**, 596–615 (1987).
6. M. Zhang, L. Li, and X. Zhou, "An experimental evaluation and guideline for path finding in weighted dynamic network," *Proc. VLDB Endow.* **14**, 2127–2140 (2021).
7. M. Zhang, L. Li, G. Trajcevski, A. Zufle, and X. Zhou, "Parallel hub labeling maintenance with high efficiency in dynamic small-world networks," *IEEE Transactions on Knowl. Data Eng.* (2023).
8. Y. Li, L. H. U, M. L. Yiu, and N. M. Kou, "An experimental study on hub labeling based shortest path algorithms," *Proc. VLDB Endow.* **11**, 445–457 (2017).
9. W. Li, M. Qiao, L. Qin, Y. Zhang, L. Chang, and X. Lin, "Distance labeling: on parallelism, compression, and ordering," *The VLDB J.* **31**, 129–155 (2021).