

Week-14-Structures and Unions: Attempt review | REC-CIS - Google Chrome

Not secure | rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=151646&cmid=405

REC-CIS

Quiz navigation

1

2

Show one page at a time

Finish review

StatusFinished

StartedSunday, 12 January 2025, 6:48 PM

CompletedSunday, 12 January 2025, 7:00 PM

Duration11 mins 50 secs

Question 1

Correct

Flag question

You are transporting some boxes through a tunnel, where each box is a parallelepiped, and is characterized by its length, width and height.

The height of the tunnel **41** feet and the width can be assumed to be infinite. A box can be carried through the tunnel only if its height is strictly less than the tunnel's height. Find the volume of each box that can be successfully transported to the other end of the tunnel. Note: Boxes cannot be rotated.

Input Format

The first line contains a single integer ***n***, denoting the number of boxes.

n lines follow with three integers on each separated by single spaces - ***length_i***, ***width_i*** and ***height_i***, which are length, width and height in feet of the ***i***-th box.

Constraints

Week-14-Structures and Unions: Attempt review | REC-CIS - Google Chrome

Not secure | rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=151646&cmid=405

REC-CIS

```
1 #include<stdio.h>
2 struct box{
3     int l,w,b;
4 };
5 int main()
6 {
7     int n;
8     scanf("%d",&n);
9     struct box arr[n];
10    for(int i=0;i<n;i++){
11        scanf("%d %d %d",&arr[i].l,&arr[i].w,&arr[i].b);
12    }for (int i=0;i<n;i++){
13        if(arr[i].b<41){
14            printf("%d\n",arr[i].l*arr[i].w*arr[i].b);
15        }
16    }
17 }
```

	Input	Expected	Got	
✓	4	125	125	✓
	5 5 5	80	80	
	1 2 40			
	10 5 41			

Week-14-Structures and Unions: Attempt review | REC-CIS - Google Chrome

Not secure | rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=151646&cmid=405

REC-CIS

Question 2
Correct
Flag question

You are given n triangles, specifically, their sides a_i , b_i and c_i . Print them in the same style but sorted by their areas from the smallest one to the largest one. It is guaranteed that all the areas are different.

The best way to calculate a volume of the triangle with sides a , b and c is Heron's formula:

$$S = \sqrt{p * (p - a) * (p - b) * (p - c)}$$

where $p = (a + b + c) / 2$.

Input Format

First line of each test file contains a single integer n . n lines follow with a_i , b_i and c_i on each separated by single spaces.

Constraints

$1 \leq n \leq 100$
 $1 \leq a_i, b_i, c_i \leq 70$
 $a_i + b_i > c_i$, $a_i + c_i > b_i$ and $b_i + c_i > a_i$

Output Format

Print exactly n lines. On each line print 3 integers separated by single spaces, which are a_i , b_i and c_i of the corresponding

Week-14-Structures and Unions: Attempt review | REC-CIS - Google Chrome

Not secure | rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=151646&cmid=405

REC-CIS

Answer: (penalty regime: 0 %)

```

1 #include<stdio.h>
2 struct sides{
3     int a,b,c;
4 };
5 int vol(int a,int b,int c){
6     return a*b*c;
7 }int main(){
8     int n;
9     scanf("%d",&n);
10    struct sides s[n];
11    for(int i=0;i<n;i++){
12        scanf("%d %d %d",&s[i].a,&s[i].b,&s[i].c);
13    }for(int i=0;i<n;i++){
14        for (int j=0;j<n;j++){
15            if(i!=j){
16                if(vol(s[i].a,s[i].b,s[i].c)<vol(s[j].a,s[j].b,s[j].c)){
17                    struct sides temp=s[j];
18                    s[j]=s[i];
19                    s[i]=temp;
20                }
21            }
22        }
23    }for(int i=0;i<n;i++){
24        printf("%d %d %d\n",s[i].a,s[i].b,s[i].c);
25    }
26 }

```

	Input	Expected	Got	
✓	3	3 4 5	3 4 5	✓
	7 24 25	5 12 13	5 12 13	
	5 12 13	7 24 25	7 24 25	
	3 4 5			

Passed all tests! ✓

