



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

## EXPERIMENT- 08

**Student Name:** Ruchi Sharma

**UID:** 23BCS10713

**Branch:** BE-CSE

**Section/Group:** KRG 1(B)

**Semester:** 05

**Date of Performance:** 23/10/25

**Subject Name:** ADBMS

**Subject Code:** 23CSP-333

### Medium-Level Problem

**1. Aim:** To understand and implement transactions in PostgreSQL, including the use of BEGIN, COMMIT, ROLLBACK, and SAVEPOINT commands to ensure data integrity and control over changes.

### 2. Objective:

- Learn about implicit and explicit transactions.
- Understand **ACID** properties (Atomicity, Consistency, Isolation, Durability).
- Implement transaction control using **COMMIT**, **ROLLBACK**, and **SAVEPOINT**.
- Manage partial rollbacks using savepoints.

### 3. DBMS script and output:

```
CREATE TABLE Students (  
    Id INT PRIMARY KEY,  
    Name VARCHAR(50) UNIQUE,  
    Age INT,  
    Class INT  
);
```

```
INSERT INTO Students (ID, Name, Age, Class) VALUES  
(1,'Aarav',17,8),  
(2,'Vikram',16,4),  
(3,'Priya',15,6),  
(4,'Rohan',16,7),  
(5,'Sita',17,8),  
(6,'Kiran',15,6);
```

```
-- IMPLICIT TRANSACTION  
UPDATE Students SET Name = 'XYZ' WHERE Id = 6;
```

```
-- EXPLICIT TRANSACTION
BEGIN TRANSACTION;
UPDATE Students SET Name = 'AMAN' WHERE Id = 1;
COMMIT;

-- ROLLBACK
BEGIN TRANSACTION;
UPDATE Students SET Name = 'TEMP' WHERE Id = 3;
ROLLBACK;

-- SAVEPOINTS
BEGIN TRANSACTION;
INSERT INTO Students(Id, Name, Age, Class) VALUES (7, 'Alice', 18, 10);
SAVEPOINT sp1;

INSERT INTO Students(Id, Name, Age, Class) VALUES (8, 'Bob', 17, 11);
SAVEPOINT sp2;

INSERT INTO Students(Id, Name, Age, Class) VALUES (9, 'Charlie', 16, 9);

-- Undo last insertion only
ROLLBACK TO SAVEPOINT sp2;

-- Continue
INSERT INTO Students(Id, Name, Age, Class) VALUES (10, 'Dina', 15, 8);

-- Undo all after sp1
ROLLBACK TO SAVEPOINT sp1;

COMMIT;

SELECT * FROM Students;
```

## 4. Output:

	id [PK] integer	name character varying (50)	age integer	class integer
1	2	Vikram	16	4
2	3	Priya	15	6
3	4	Rohan	16	7
4	5	Sita	17	8
5	6	XYZ	15	6
6	1	AMAN	17	8
7	7	Alice	18	10

## Hard-Level Problem

**1. Aim:** Design a robust PostgreSQL transaction system for the **students** table where multiple student records are inserted within a single transaction. If any insertion fails (due to duplicate or invalid data), only that particular insertion should be rolled back using **savepoints**, ensuring previously successful inserts remain intact.

## 2. Objective:

- Implement transaction management with error handling.
- Use **SAVEPOINTS** to rollback partial transactions.
- Maintain data integrity during multi-step insert operations.
- Handle exceptions gracefully in PostgreSQL using `DO $$ BEGIN ... EXCEPTION ... END $$;`

## 3. DBMS script and output:

```
DROP TABLE IF EXISTS students;
```

```
CREATE TABLE students (  
    id SERIAL PRIMARY KEY,  
    name VARCHAR(50) UNIQUE,  
    age INT,  
    class INT  
);
```

```
DO $$  
DECLARE  
BEGIN  
    BEGIN  
        INSERT INTO students(name, age, class) VALUES ('Anisha',16,8);  
        RAISE NOTICE 'Inserted record: Anisha';  
    EXCEPTION WHEN unique_violation THEN  
        RAISE NOTICE 'Duplicate entry: Anisha skipped';  
    END;  
  
    BEGIN  
        INSERT INTO students(name, age, class) VALUES ('Neha',17,8);  
        RAISE NOTICE 'Inserted record: Neha';
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
EXCEPTION WHEN unique_violation THEN
    RAISE NOTICE 'Duplicate entry: Neha skipped';
END;

BEGIN
    INSERT INTO students(name, age, class) VALUES ('Mayank',19,9);
    RAISE NOTICE 'Inserted record: Mayank';
EXCEPTION WHEN unique_violation THEN
    RAISE NOTICE 'Duplicate entry: Mayank skipped';
END;

BEGIN
    INSERT INTO students(name, age, class) VALUES ('Anisha',17,9);
    RAISE NOTICE 'Inserted record: Anisha (second)';
EXCEPTION WHEN unique_violation THEN
    RAISE NOTICE 'Duplicate entry: Anisha (second) skipped';
END;

BEGIN
    INSERT INTO students(name, age, class) VALUES ('Riya',18,10);
    RAISE NOTICE 'Inserted record: Riya';
EXCEPTION WHEN unique_violation THEN
    RAISE NOTICE 'Duplicate entry: Riya skipped';
END;
END;
$$;

SELECT * FROM students;
```

## 5. Output:

	id [PK] integer	name character varying (50)	age integer	class integer
1	1	Anisha	16	8
2	2	Neha	17	8
3	3	Mayank	19	9
4	5	Riya	18	10