

Computer Graphics

by Ruen-Rone Lee
ICL/ITRI



OpenGL at a Glance

What is OpenGL

OpenGL Processing Pipeline

OpenGL Shaders

OpenGL Shading Language

OpenGL Utilities

A Simple OpenGL Framework with GLUT



What is OpenGL

Standard Graphics APIs



What is OpenGL



- ◆ **OpenGL (Open Graphics Library) is an open standard for cross-language, cross-platform API specification**
- ◆ **OpenGL is not a programming language**
- ◆ **OpenGL is a set of **APIs** (Application Programming Interface) that is used to write 2D/3D graphics applications**



OpenGL Evolution

Source: Wikipedia

◆ Fixed Function Pipeline (1992~2003)

- OpenGL 1.1 - Texture objects
- OpenGL 1.2 - 3D textures, BGRA and packed pixel formats[20]
- OpenGL 1.3 - Multitexturing, multisampling, texture compression
- OpenGL 1.4 - Depth textures
- OpenGL 1.5 - Vertex Buffer Object (VBO), Occlusion Queries[21]

◆ Programmable Pipeline (2004~present)

- OpenGL 2.0 - GLSL 1.1, MRT, Non Power of Two textures, Point Sprites,[22] Two-sided stencil[21]
- OpenGL 2.1 - GLSL 1.2, Pixel Buffer Object (PBO), sRGB Textures[21]
- OpenGL 3.0 - GLSL 1.3, Texture Arrays, Conditional rendering, Frame Buffer Object (FBO)[23]
- OpenGL 3.1 - GLSL 1.4, Instancing, Texture Buffer Object, Uniform Buffer Object, Primitive restart[24]
- OpenGL 3.2 - GLSL 1.5, Geometry Shader, Multi-sampled textures[25]
- OpenGL 3.3 - GLSL 3.30 Backports as much function as possible from the OpenGL 4.0 specification
- OpenGL 4.0 - GLSL 4.00 Tessellation on GPU, shaders with 64-bit precision,[26]
- OpenGL 4.1 - GLSL 4.10 Developer-friendly debug outputs, compatibility with OpenGL ES 2.0,[27]
- OpenGL 4.2 - GLSL 4.20 Shaders with atomic counters, draw transform feedback instanced, shader packing, performance improvements
- OpenGL 4.3 - GLSL 4.30 Compute shaders leveraging GPU parallelism, shader storage buffer objects, high-quality ETC2/EAC texture compression, increased memory security, a multi-application robustness extension, compatibility with OpenGL ES 3.0,[28]
- OpenGL 4.4 - GLSL 4.40 Buffer Placement Control, Efficient Asynchronous Queries, Shader Variable Layout, Efficient Multiple Object Binding, Streamlined Porting of Direct3D applications, Bindless Texture Extension, Sparse Texture Extension,[29]
- OpenGL 4.5 - GLSL 4.50 Direct State Access (DSA), Flush Control, Robustness, OpenGL ES 3.1 API and shader compatibility, DX11 emulation features
- OpenGL 4.6 - GLSL 4.60 More efficient geometry processing and shader execution, more information, no error context, polygon offset clamp, SPIR-V, anisotropic filtering

Other Graphics APIs

◆ Direct3D

- **Proprietary** Microsoft Windows 3D graphics API



◆ Vulkan

- New cross-platform 3D graphics and compute API by Khronos group



◆ OpenGL ES

- OpenGL for Embedded Systems



◆ Web-based OpenGL



- JavaScript interface for OpenGL-ES-2.x API



◆ ...



OpenGL vs. Direct3D



Source: "OpenGL vs. Direct3D – Who is the Winner of Graphics API" by Hunter Lin, 2016.



Capability of OpenGL

◆ Flight Simulator




Flight Gear



Capability of OpenGL

- ◆ **Benchmarks**
 - **Unigine's Benchmarks**



Why OpenGL

- ◆ **Cross-platform**

- Windows, Mac OSX, Linux, ...

- ◆ **Portable**

- ◆ **Better backward compatibility**

- ◆ **Run on various hardware platforms**

- PC, embedded device, smart phone, game console, ...
- OpenGL ES was adopted in iOS, Android, and Symbian OS



OpenGL Command Syntax

glVertex3fv

<u>Prefix</u>	<u>Function</u>	<u>No. of parameters</u> +	<u>Data type</u> + <u>v (vector)</u>
gl	Vertex	1	b (byte)
glu	Color	2	s (short)
glut	Enable	3	i (int)
glx	Disable	4	f (float)
...	d (double)
			...

OpenGL Data Types

<i>Suffix</i>	<i>Data type</i>	<i>Typical C-Language Type</i>	<i>OpenGL Type Definition</i>
b	8-bit integer	signed char	GLbyte
s	16-bit integer	short	GLshort
i	32-bit integer	Int or long	GLint, GLsizei
f	32-bit floating-point	float	GLfloat, GLclampf
d	64-bit floating-point	double	GLdouble, GLclampd
ub	8-bit unsigned integer	unsigned char	GLubyte, GLboolean
us	16-bit unsigned integer	unsigned short	GLushort
ui	32-bit unsigned integer	unsigned int or unsigned long	GLuint, GLenum, GLbitfield

OpenGL Data Types

- ◆ In consideration of portability, OpenGL defined data types should be used throughout the application
 - Be careful when you mixed the usage of C++ data types and OpenGL data types

Data Model	short	int	long	long long	pointer
LP64	16	32	64	64	64
LLP64	16	32	32	64	64

Many 64-bit compilers today use the LP64 model (including Solaris, AIX, HP, Linux, Mac OS X, and IBM z/OS native compilers). Microsoft's VC++ compiler uses the LLP64 model.

long \neq GLint in Linux and Mac OS!!

Also, there is no “long long” in OpenGL data types




OpenGL Pipeline


Fixed Function Pipeline
Programmable Pipeline



OpenGL Pipeline (Fixed Function)




OpenGL Pipeline (Programmable)



OpenGL Pipeline

◆ Difference between fixed and programmable



OpenGL Shaders and GLSL


***Various Shaders
OpenGL Shading Language***



OpenGL Shaders

◆ A user-defined program designed to run on some stage of a graphics processor

- Vertex Shader
- Tessellation
 - Tessellation Control Shader
 - Tessellation Evaluation Shader
- Geometry Shader
- Fragment Shader



OpenGL Shading Language

- ◆ **High-Level shading Language based on C programming language**
- ◆ **Similar to NVIDIA's Cg and Microsoft's HLSL**
- ◆ **Hardware vendors will provide shader compiler to optimize for their hardware architecture**

OpenGL Shading Language

GLSL Version	OpenGL Version	Date	Shader Preprocessor
1.10.59	2.0	April 2004	#version 110
1.20.8	2.1	September 2006	#version 120
1.30.10	3.0	August 2008	#version 130
1.40.08	3.1	March 2009	#version 140
1.50.11	3.2	August 2009	#version 150
3.30.6	3.3	February 2010	#version 330
4.00.9	4.0	March 2010	#version 400
4.10.6	4.1	July 2010	#version 410
4.20.11	4.2	August 2011	#version 420
4.30.8	4.3	August 2012	#version 430
4.40	4.4	July 2013	#version 440
4.50	4.5	August 2014	#version 450
4.60	4.6	July 2017	#version 460

A GLSL Shader Example

```
1  #version 330
2
3  layout (std140) uniform Materials {
4      vec4 diffuse;
5      vec4 ambient;
6      vec4 specular;
7      float shininess;
8  };
9
10 layout (std140) uniform Lights {
11     vec3 l_dir;    // camera space
12 };
13
14 in Data {
15     vec3 normal;
16     vec4 eye;
17 } DataIn;
18
19 out vec4 colorOut;
20
21 void main() {
22
23     // set the specular term to black
24     vec4 spec = vec4(0.0);
25
26     // normalize both input vectors
27     vec3 n = normalize(DataIn.normal);
28     vec3 e = normalize(vec3(DataIn.eye));
29
30     float intensity = max(dot(n,l_dir), 0.0);
31
32     // if the vertex is lit compute the specular color
33     if (intensity > 0.0) {
34         // compute the half vector
35         vec3 h = normalize(l_dir + e);
36         // compute the specular term into spec
37         float intSpec = max(dot(h,n), 0.0);
38         spec = specular * pow(intSpec,shininess);
39     }
40     colorOut = max(intensity * diffuse + spec, ambient);
41 }
```

Version no.

Constant variables

Input Variables

Output Variable

Main()

C-like language

- Data types
- Structure
- Assignment
- Function
- Conditional branch
- Loop
- Augmented operators
 - Vector
 - Matrix
- ...

OpenGL Useful Libraries

GLUT
GLEW
GLM



OpenGL Useful Libraries -- GLEW

- ◆ **The OpenGL Extension Wrangler Library**
- ◆ **A cross-platform open-source C/C++ extension loading library**
- ◆ **GLEW provides efficient run-time mechanisms for determining which OpenGL extensions are supported on the target platform**
- ◆ **Current version supports**
 - **OpenGL 4.6**
 - **OpenGL, WGL, GLX extensions**
 - **<http://glew.sourceforge.net/>**



OpenGL Extension

- ◆ **A mechanism to provide additional functionality**
 - **New functions**
 - **New constants**
 - **Relax or remove restrictions on existing OpenGL functions**



OpenGL Extension

◆ Advantages

- Develop new functionality before new API spec is released
- Hardware vendors can expose their new hardware features via extension first
- Extension becomes core function (or extension) after being approved by ARB



OpenGL Extension

◆ Disadvantages

- It is vendor specific before the extension becomes an ARB extension or core API
- You must query the existence of specific extension before you use it
- Compatibility might be an issue if an application was using a vendor specific extension

◆ GLEW can help in querying and loading OpenGL extensions



OpenGL Useful Libraries – glm

- ◆ Wavefront OBJ model file format reader/writer/manipulator
 - **Not OpenGL Mathematics Library**
- ◆ Includes routines for generating smooth normals with preservation of edges, welding redundant vertices & texture coordinate generation (spheremap and planar projections) + more.
- ◆ Used to load 3D models in OBJ file format
- ◆ <http://devernay.free.fr/hacks/glm/>



OpenGL Useful Libraries -- GLUT

- ◆ OpenGL Utility Toolkit
- ◆ A window system independent toolkit for writing OpenGL programs
- ◆ **GLUT is not open source**
- ◆ Alternative:
 - Freeglut: <http://freeglut.sourceforge.net/>
- ◆ Application frameworks provide support to control the platform's Windowing system and event handling.




OpenGL Framework

A Simple OpenGL Framework with GLUT




OpenGL Application Framework



Shader Creation Flow

- ◆ **Compilation – Check for syntax error**
- ◆ **Link – Check for Resource availability**



OpenGL Using GLUT

◆ Example (Render a rectangle)

```
#include <freeglut/glut.h>  ← Include header file

int main(int argc, char* argv[])
{
    Display mode setting
    Window creation
    {
        glutInit(&argc, argv);
        glutInitDisplayMode(GLUT_SINGLE | GLUT_RGB);
        glutInitWindowSize(800, 600);
        glutInitWindowPosition(0, 0);
        glutCreateWindow("GLRect");

        glutDisplayFunc(RenderScene);
        glutReshapeFunc(ChangeSize);
    }  ← Callback functions registration

    SetupRC();  ← State initialization

    glutMainLoop();  ← Event handling loop

    return 0;
}
```

GLUT functions

- ◆ `glutInit` **is used to initialize the GLUT library**
- ◆ `glutInitDisplayMode` **set the initial display mode with color model and various buffer modes**
- ◆ `glutWindowSize` **set the window size in pixels**
- ◆ `glutCreateWindow` **create window**
- ◆ `glutDisplayFunc` **set the display callback**
- ◆ `glutReshapeFunc` **set the reshape callback**
- ◆ `glutMainLoop` **enter the GLUT event processing loop**

OpenGL Using GLUT

◆ Example (Render a rectangle)

■ State Initialization

```
// Setup the rendering state
```

```
void SetupRC(void)
```

```
{
```

```
    // Set clear color to blue
```

```
    glClearColor(0.0f, 0.0f, 1.0f, 1.0f);
```

```
}
```

↑
R

↑
G

↑
B

↑
A

Set the clear color
but not yet do the clear operation

OpenGL Using GLUT

- ◆ **Example (Render a rectangle)**
 - **Display callback function**

```
// Called to draw scene
void RenderScene(void)
{
    // Clear the window with current clearing color
    glClear(GL_COLOR_BUFFER_BIT);

    // Set current drawing color to red
    //           R      G      B
    glColor3f(1.0f, 0.0f, 0.0f);

    // Draw a filled rectangle with current color
    glRectf(-25.0f, 25.0f, 25.0f, -25.0f);

    // Flush drawing commands
    glFlush();
}
```

OpenGL Using GLUT

- ◆ **Example (Render a rectangle)**
 - **Equivalent functions to glRectf(...)**

```
// Called to draw scene
void RenderScene(void)
{
    ...

    // Draw a filled rectangle with current color
    // glRectf(-25.0f, 25.0f, 25.0f, -25.0f);
    glBegin(GL_POLYGON);
        glVertex2f(-25.0f, 25.0f);
        glVertex2f(25.0f, 25.0f);
        glVertex2f(25.0f, -25.0f);
        glVertex2f(-25.0f, -25.0f);
    glEnd();

    // Flush drawing commands
    glFlush();
}
```

OpenGL Using GLUT

◆ Example (Render a rectangle)

■ Reshape callback function

```
// Called by GLUT library when the window has changed size
void ChangeSize(int w, int h)
{
    // Prevent a divide by zero
    if(h == 0) h = 1;

    // Set Viewport to window dimensions
    glViewport(0, 0, w, h);

    // Reset coordinate system
    glMatrixMode(GL_PROJECTION);
    glLoadIdentity();

    // Establish clipping volume (left, right, bottom, top, near, far)
    GLfloat aspectRatio = (GLfloat)w / (GLfloat)h;
    if (w <= h)
        glOrtho (-100.0, 100.0, -100 / aspectRatio, 100.0 / aspectRatio, 1.0, -1.0);
    else
        glOrtho (-100.0 * aspectRatio, 100.0 * aspectRatio, -100.0, 100.0, 1.0, -1.0);

    glMatrixMode(GL_MODELVIEW);
    glLoadIdentity();
}
```


The display callback

- ◆ **The display callback is executed when**
 - Window is first opened
 - Window is reshaped
 - Window is exposed
 - Post a redisplay message
- ◆ **Every GLUT program must have a display callback**

OpenGL Reference Links

- ◆ **Khronos OpenGL web page**
 - <http://www.khronos.org/opengl/>
- ◆ **Official OpenGL web page**
 - <http://www.opengl.org/>



Q&A

