rudheerrajana/CSA02-192526 | New Tab | Online C Compiler (Editor) | Ask Gemini
programiz.com/c-programming/online-compiler/ | Ask Google | Verify it's you
Continue where you left off: Chrome can restore your tabs every time you restart. To turn this on, go to Settings.
Programiz
C Online Compiler

Get Photoshop in Creative Cloud Pro
Now ₹399/mo for Students
Learn more
Adobe
First year only. Annual plan, billed monthly. New subscribers only.
Programiz PRO ›

main.c

Run

```c
/* The meter register is a 16-bit counter. */
typedef unsigned short meter_t;

unsigned int consumption(meter_t previous, meter_t current)
{
    /* Unsigned 16-bit subtraction handles rollover automatically. */
    return (meter_t)(current - previous);
}

int main(void)
{
    printf("sizeof(meter_t) = %zu bytes, maximum reading = %u\n",
           sizeof(meter_t), (unsigned)USHRT_MAX);

    printf("Consumption: %u units\n", consumption(1200, 1530));
    printf("Consumption: %u units\n", consumption(65400, 120));

    return 0;
}
```

Output

```
sizeof(meter_t) = 2 bytes, maximum reading = 65535
Consumption: 330 units
Consumption: 256 units
```

```c
#include <stdio.h>
#include <limits.h>

/* The meter register is a 16-bit counter. */
typedef unsigned short meter_t;

unsigned int consumption(meter_t previous, meter_t current)
{
    /* Unsigned 16-bit subtraction handles rollover automatically. */
    return (meter_t)(current - previous);
}

int main(void)
{
    printf("sizeof(meter_t) = %zu bytes, maximum reading = %u\n",
           sizeof(meter_t), (unsigned)USHRT_MAX);

    printf("Consumption: %u units\n", consumption(1200, 1530));
    printf("Consumption: %u units\n", consumption(65400, 120));

    return 0;
}
```