

Insert here your thesis' task.



**FACULTY
OF INFORMATION
TECHNOLOGY
CTU IN PRAGUE**

Master's thesis

SimpleObjectMachine implementation

Bc. Rudolf Rovňák

Department of Theoretical Computer Science

Supervisor: Ing. Petr Máj

November 19, 2020

Acknowledgements

THANKS (remove entirely in case you do not wish to thank anyone)

Declaration

I hereby declare that the presented thesis is my own work and that I have cited all sources of information in accordance with the Guideline for adhering to ethical principles when elaborating an academic final thesis.

I acknowledge that my thesis is subject to the rights and obligations stipulated by the Act No.121/2000 Coll., the Copyright Act, as amended, in particular that the Czech Technical University in Prague has the right to conclude a license agreement on the utilization of this thesis as a school work under the provisions of Article 60 (1) of the Act.

In Prague on November 19, 2020

.....

Czech Technical University in Prague
Faculty of Information Technology
© 2020 Rudolf Rovňák. All rights reserved.

This thesis is school work as defined by Copyright Act of the Czech Republic. It has been submitted at Czech Technical University in Prague, Faculty of Information Technology. The thesis is protected by the Copyright Act and its usage without author's permission is prohibited (with exceptions defined by the Copyright Act).

Citation of this thesis

Rovňák, Rudolf. *SimpleObjectMachine implementation*. Master's thesis. Czech Technical University in Prague, Faculty of Information Technology, 2020.

Abstrakt

V několika větách shrňte obsah a přínos této práce v českém jazyce.

Klíčová slova Replace with comma-separated list of keywords in Czech.

Abstract

Summarize the contents and contribution of your work in a few sentences in English language.

Keywords Replace with comma-separated list of keywords in English.

Contents

Introduction	1
1 State-of-the-art	3
2 Analysis and design	5
2.1 SOM design and features	5
2.1.1 Data types	5
2.1.2 Classes	5
2.1.3 Class hierarchy	5
2.1.4 Syntax	6
2.2 Interpretation	7
2.2.1 AST interpretation	7
2.2.2 Bytecode interpretation	7
2.3 Optimization	8
2.4 Virtual Machine	8
2.4.1 Garbage collection	8
3 Realisation	9
Conclusion	11
Bibliography	13
A Acronyms	15
B Contents of enclosed CD	17

List of Figures

Introduction

State-of-the-art

Analysis and design

2.1 SOM design and features

Simple Object Machine (SOM) is a minimal Smalltalk dialect used primarily for teaching construction of virtual machines. Key characteristics according to official website ([1]) are:

- clarity of implementation over performance,
- common language features such as: objects, classes, closures, non-local returns
- interpreter optimizations, threading, garbage collectors are different across various implementations.

2.1.1 Data types

2.1.2 Classes

Classes are the cornerstone of SOM - in Smalltalk, everything is an object and each object has its class. Classes can contain fields and methods. Only single inheritance is supported - given class can only extend one other class. Object methods are dispatched dynamically in SOM and there is a keyword to explicitly call a superclass' method.

SOM implements a non-local return from methods. This gives us the ability to exit the execution of a block (or a closure) to the place where the original method calling the block returns.

2.1.3 Class hierarchy

As SOM is an object oriented language, everything is represented as an object. To enable more convenient work with classes and objects, every class is a subclass of `Object`. This enables som universal interface to be used.

2. ANALYSIS AND DESIGN

Protocol of an `Object` class is:

- `class` - returns the class of an object,
- `=` - value equality comparison,
- `==` - reference equality comparison,
- `isNil` - check, if the object is `nil`,
- `asString` - converts the object into a string,
- `value` - evaluate (interesting for blocks),
- `print`, `println` - prints the object,
- `error:` - error reporting,
- `subClassResponsibility` - can be used to indicate the method should be implemented in the subclass of a given class,
- `doesNotUnderstand:arguments:` - can be used for error handling when a method is not implemented.

2.1.4 Syntax

Following example summarizes the syntax of SOM programming language:

```
MyClass = SuperClass (  
  | field | "Instance side field"  
  
  foo: arg = primitive "This method is implemented in the VM"  
  
  examples = (  
    | aMethodVariable |  
    1234 "an integer".  
    3.14 "a double".  
    'a string'.  
    "a comment".  
    #aSymbol.  
    aVariable := aVariable := 3 + 4.  
    field select: [:e | e == #bar] "A message send with a closure"  
    ↑ aVariable "Return"  
  )  
  ----  
  | classField | "Class side field"  
)
```

Some notable keywords or tokens are:

- `self` is used to reference the object the method is from, comparable to C++/Java `this`,

- `super` is used to reference the superclass of a class,
- `:=` is used to assign value into a variable/field,
- `^` is used for return,
- quotes are used to delimit a comment.

2.2 Interpretation

Once the source code is parsed, the next step is executing it – this step is called *interpretation*. Interpretation is As per [2], an interpreter for a language L can be defined as a mechanism for the direct execution of all programs from L. It executes each element of the program without reference to other elements.

It is however very rare that any language is interpreted directly. In most cases of non-trivial languages, the interpretation process is preceded by parsing or compiling into some form of *intermediate representation*. According to [2], this process removes lexical noise (comments, formatting), elements can be abstracted/combined (into keywords, operations etc.) and reordered into execution order (for example operators in an algebraic expression).

The choice of intermediate representation is therefore vital. It can determine a lot of aspects of interpretation - from the way of distributing the interpreted program to time and space complexity of the interpreter.

2.2.1 AST interpretation

Abstract syntax tree (AST) is a tree representation of the source code of a computer program that conveys the structure of the source code. Each node in the tree represents a construct occurring in the source code [3].

As the name suggests, AST represents the source code in the form of a tree. During the transformation from the source code to AST, some information is omitted. Information that is vital for AST's according to [3] is:

- variables – their types, location of their definition/declaration,
- order of commands/operations,
- components of operators and their position (for example left and right operands for a binary operator),
- identifiers and corresponding values.

2.2.2 Bytecode interpretation

Using a form of bytecode. Effective, requires:

- designing the bytecode (instructions, bytecode file formats),

- AST to bytecode translation (AST \rightarrow bytecode instructions),
- actual bytecode interpretation.

Bytecode interpretation permits easier optimization.

2.3 Optimization

- dead code elimination,
- constant propagation,
- others...

2.4 Virtual Machine

Decide on memory hierarchy, garbage collection...

2.4.1 Garbage collection

The process of *garbage collection* performed by *garbage collector (GC)* is the process of allocating and freeing memory during application runtime. The main advantage of this mechanics is to prevent *memory leaks* – parts of a program that allocate memory without freeing it when it is not needed [4]. Most modern high-level programming languages implement some form of garbage collection.

Realisation

Conclusion

Bibliography

- [1] SOM. SOM: A minimal Smalltalk for teaching and research on Virtual Machines. 2020, [cit. 2020-11-17]. Available from: <https://som-st.github.io/>
- [2] Wolczko, M. Execution mechanisms Part I: Interpretation. [online], 2015, [cit. 2020-10-31]. Available from: <https://www.dropbox.com/s/1fav564dvx20qsw/2%20AST%20Interpretation.pdf>
- [3] DeepSource Corp. Abstract Syntax Tree. [cit. 2020-11-4]. Available from: <https://deepsource.io/glossary/ast/>
- [4] Boersma, E. Memory leak detection - How to find, eliminate, and avoid. January 2020, [cit. 2020-11-5]. Available from: <https://raygun.com/blog/memory-leak-detection/>

Acronyms

AST Abstract syntax tree

GC Garbage collector

SOM Simple Object Machine

VM Virtual machine

Contents of enclosed CD

	readme.txt	the file with CD contents description
	exe	the directory with executables
	src	the directory of source codes
	wbdcm	implementation sources
	thesis	the directory of \LaTeX source codes of the thesis
	text	the thesis text directory
	thesis.pdf	the thesis text in PDF format
	thesis.ps	the thesis text in PS format