

OAuth 2.0 Integration Guide

Integration Details required for the Authorization Server:

Callback URL: To be integrated into the application created on IDP.

Base URLs:

Stage/Non-Prod Environment(Recommended Only for Testing/Sanity):

<https://stage.moveinsync.com/mis-auth/login/oauth2/code/{registration-id}>

Prod Environment: <https://auth.moveinsync.com/mis-auth/login/oauth2/code/{registration-id}>

Note: registration-id is the buid that should be shared by the MoveInSync team along with this documentation

Logout URL (Optional):

Stage/Non-Prod Environment(Recommended Only for Testing/Sanity):

<https://stage.moveinsync.com/mis-auth/sso/logout>

Prod Environment: <https://auth.moveinsync.com/mis-auth/sso/logout>

Details required by us to integrate your Authorization server with MoveInSync Application:

Details	Sample Data	Description
ClientId	927706843971-2bbjjb9vtarrp54a1m8n9pdousa4cqak.apps.googleusercontent.com/	Client ID generated during Application generation on IDP
Client Secret	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	Client Secret generated during Application generation on IDP
Scopes	"openid", "email"	Scopes provided for the application
AuthorizationURL	https://accounts.google.com/o/oauth2/v2/auth	Authorization URL to be Given By IDP for Login Page redirection

Token URL	https://www.googleapis.com/oauth2/v4/token	Token URL for exchanging Auth token for an Access token
JWK Set URL	https://www.googleapis.com/oauth2/v3/certs	JSON Web Key (JWK) Set URL for key verification

User Info URL	https://www.googleapis.com/oauth2/v3/userinfo	API to fetch User Details using the Access token (<i>Optional</i>)
---------------	---	---

Sample Screenshot of configuring the OAUTH SSO on Microsoft Azure

App Registration: Step - 1:

[Home](#) > [App registrations](#) >

Register an application ...

* Name

The user-facing display name for this application (this can be changed later).

Moveinsync - SSO ✓

Supported account types

Who can use this application or access this API?

- ☒ Accounts in this organizational directory only (MoveInSync Technology Solutions Pvt Ltd only - Single tenant)
- ☐ Accounts in any organizational directory (Any Microsoft Entra ID tenant - Multitenant)
- ☐ Accounts in any organizational directory (Any Microsoft Entra ID tenant - Multitenant) and personal Microsoft accounts (e.g. Skype, Xbox)
- ☐ Personal Microsoft accounts only

[Help me choose...](#)

Redirect URI (optional)

We'll return the authentication response to this URI after successfully authenticating the user. Providing this now is optional and it can be changed later, but a value is required for most authentication scenarios.

Web [https://auth.moveinsync.com/mis-auth/login/oauth2/code/site-name](#) ✓

Register an app you're working on here. Integrate gallery apps and other apps from outside your organization by adding from [Enterprise applications](#).

By proceeding, you agree to the [Microsoft Platform Policies](#) [↗](#)

[Register](#)

App Registration: Step - 2: ClientId and Authorisations URLs:

The screenshot shows the 'Endpoints' section of the Azure Portal for the 'MoveinSync SSO' application. The left sidebar contains navigation links: Home, App registrations, MoveinSync SSO, and a search bar. Below the search bar are links for 'Delete', 'Endpoints', and 'Preview features'. The main content area is titled 'Endpoints' and lists various endpoints for the application. The endpoints are categorized into 'Authority URL' and 'OAuth 2.0' endpoints. The 'Authority URL' section includes links for 'Accounts in this organizational directory only', 'Accounts in any organizational directory', 'Accounts in any organizational directory and personal Microsoft accounts', and 'Personal Microsoft accounts only'. The 'OAuth 2.0' section includes links for 'authorization endpoint (v2)', 'token endpoint (v2)', 'authorization endpoint (v1)', and 'token endpoint (v1)'. Below these are links for 'SAML-P sign-on endpoint', 'SAML-P sign-out endpoint', 'WS-Federation sign-on endpoint', and 'Federation metadata document'.

Endpoints

Authority URL (Accounts in this organizational directory only)
<https://login.microsoftonline.com/efd28390-a20c-4f6f-bb1f-ae56dba93b67>

Authority URL (Accounts in any organizational directory)
<https://login.microsoftonline.com/organizations>

Authority URL (Accounts in any organizational directory and personal Microsoft accounts)
<https://login.microsoftonline.com/common>

Authority URL (Personal Microsoft accounts only)
<https://login.microsoftonline.com/consumers>

OAuth 2.0 authorization endpoint (v2)
<https://login.microsoftonline.com/efd28390-a20c-4f6f-bb1f-ae56dba93b67/oauth2/v2.0/authorize>

OAuth 2.0 token endpoint (v2)
<https://login.microsoftonline.com/efd28390-a20c-4f6f-bb1f-ae56dba93b67/oauth2/v2.0/token>

OAuth 2.0 authorization endpoint (v1)
<https://login.microsoftonline.com/efd28390-a20c-4f6f-bb1f-ae56dba93b67/oauth2/authorize>

OAuth 2.0 token endpoint (v1)
<https://login.microsoftonline.com/efd28390-a20c-4f6f-bb1f-ae56dba93b67/oauth2/token>

SAML-P sign-on endpoint
<https://login.microsoftonline.com/efd28390-a20c-4f6f-bb1f-ae56dba93b67/saml2>

SAML-P sign-out endpoint
<https://login.microsoftonline.com/efd28390-a20c-4f6f-bb1f-ae56dba93b67/saml2>

WS-Federation sign-on endpoint
<https://login.microsoftonline.com/efd28390-a20c-4f6f-bb1f-ae56dba93b67/wsfed>

Federation metadata document
<https://login.microsoftonline.com/efd28390-a20c-4f6f-bb1f-ae56dba93b67/federationmetadata/2007-06/federationmetadata.xml>

App Registration: Step - 3: ClientSecrets :

The screenshot shows the 'Certificates & secrets' section of the Azure Portal for the 'MoveinSync SSO' application. The left sidebar contains navigation links: Home, App registrations, MoveinSync SSO, and a search bar. Below the search bar are links for 'Overview', 'Quickstart', 'Integration assistant', 'Diagnose and solve problems', and 'Manage'. The 'Manage' section is expanded, showing links for 'Branding & properties', 'Authentication', 'Certificates & secrets', 'Token configuration', 'API permissions', 'Expose an API', 'App roles', 'Owners', 'Roles and administrators', and 'Manifest'. The main content area is titled 'Certificates & secrets' and shows a table with columns for 'Description', 'Expires', 'Value', and 'Secret ID'. There is one entry in the table: 'mis Prod' with an expiration date of '25/09/2026' and a value of 'fcb8Q~m-xxbQcLqqCGFt1KFbN4hxFUbp...'. A 'New client secret' button is located above the table. A notification banner at the top right says 'Update application credentials' and 'Successfully updated application MoveinSync SSO credentials'.

Certificates & secrets

Got a second to give us some feedback? →

Credentials enable confidential applications to identify themselves to the authentication service when receiving tokens at a web addressable location (using an HTTPS scheme). For a higher level of assurance, we recommend using a certificate (instead of a client secret) as a credential.

Application registration certificates, secrets and federated credentials can be found in the tabs below.

Certificates (0) Client secrets (1) Federated credentials (0)

A secret string that the application uses to prove its identity when requesting a token. Also can be referred to as application password.

+ New client secret

Description	Expires	Value	Secret ID
mis Prod	25/09/2026	fcb8Q~m-xxbQcLqqCGFt1KFbN4hxFUbp...	21e865d8-3662-47d9-b48c-ef45e383eb1

App Registration: Step - 4: API Permissions :

Search

Refresh | Got feedback?

- Overview
- Quickstart
- Integration assistant
- Diagnose and solve problems
- Manage
 - Branding & properties
 - Authentication
 - Certificates & secrets
 - Token configuration
 - API permissions
 - Expose an API
 - App roles
 - Owners
 - Roles and administrators
 - Manifest
- Support + Troubleshooting

You are editing permission(s) to your application, users will have to consent even if they've already done so previously.

Granting tenant-wide consent may revoke permissions that have already been granted tenant-wide for that application. Permissions that users have already granted on their own behalf aren't affected. [Learn more](#)

The "Admin consent required" column shows the default value for an organization. However, user consent can be customized per permission, user, or app. This column may not reflect the value in your organization, or in organizations where this app will be used. [Learn more](#)

Configured permissions

Applications are authorized to call APIs when they are granted permissions by users/admins as part of the consent process. The list of configured permissions should include all the permissions the application needs. [Learn more about permissions and consent](#)

+ Add a permission ✓ Grant admin consent for MoveinSync Technology Solutions Pvt Ltd

API / Permissions name	Type	Description	Admin consent requ...	Status
Microsoft Graph (3)				...
email	Delegated	View users' email address	No	...
openid	Delegated	Sign users in	No	...
User.Read	Delegated	Sign in and read user profile	No	...

To view and manage consented permissions for individual apps, as well as your tenant's consent settings, try [Enterprise applications](#).