


SSO With workinsync using OKTA

Document Control	
Document Name	SSO with SCIM to WorkInSync (OKTA)
Version No	1.1
Classification	Confidential
Date	Jul 15, 2022

Version Control				
Ver No.	Author	Approved by	Approved Date	Description
1.0	Rishabh	Ujjwal		First Version
1.1	Aditya Dutta	Ujjwal	27/06/2023	Mobile SSO section


Task 1: Launch the Wizard

1. In the Admin Console, go to **Applications > Applications**.
2. Click **Create App Integration**.
3. Select **SAML 2.0** as the **Sign-on method**.
4. Click **Next**.



Task 2: Configure general settings

- **App name:** Specify a name for your integration using UTF-8 3-byte characters.
- **App logo:** Optional. Add a logo to accompany your integration in the Okta org. The logo file must be PNG, JPG, or GIF format and be smaller than 1 MB in size. For best results, use a PNG image with a transparent background and a landscape orientation. Use a minimum resolution of 420 x 120 pixels to prevent upscaling.



Task 3: Configure SAML settings

A SAML 2.0 configuration requires a combination of information from both your org and the target app. For help with completing each field, use your app-specific documentation and the Okta tool tips.

- **Single sign-on URL:** The location to send the SAML assertion using a POST operation. This URL is required and serves as the default Assertion Consumer Services (ACS) URL value for the Service Provider (SP). This URL is always used for Identity Provider (IdP) initiated sign-on requests.
 - **Use this for Recipient URL and Destination URL:** Select this checkbox if you want the recipient and destination URL to be the same.
 - **Recipient URL:** (Appears if the previous checkbox isn't selected.) The location where the application can present the SAML assertion. This is usually the Single Sign-On (SSO) URL.
 - **Destination URL:** (Appears if the previous checkbox isn't selected.) The location where the SAML Response is intended to be sent inside the SAML assertion. This should be the same location as the **Single sign on URL** unless your application explicitly defines a specific value.

- **Audience URI (SP Entity ID):** The intended audience of the SAML assertion. This is usually the Entity ID of your application.
- **Default RelayState:** The page where users land after a successful sign-in using SAML into the SP. This should be a valid URL. Consult the SP documentation to get this information.
- **Name ID format:** The username format that you're sending in the SAML Response. Consult the SP documentation to determine which format to use, but use the default (**Unspecified**) if the application doesn't explicitly specify a format.
- **Application username:** The default value to use for the username with the application.

```
<?xml version="1.0" encoding="UTF-8"?><EntityDescriptor xmlns="urn:oasis:names:tc:SAML:2.0:metadata"
entityID="https://richemont.eu.workinsync.io/authorization/saml2/service-provider-metadata/richemont">
  <SPSSODescriptor md="urn:oasis:names:tc:SAML:2.0:metadata" wantAssertionSigned="true"
  protocolSupportEnumeration="urn:oasis:names:tc:SAML:2.0:protocol">
    <KeyDescriptor use="signing">
      <KeyInfo ds="http://www.w3.org/2000/09/xmldsig#">
        <X509Data>
          <X509Certificate>MIIDUjCCAqggAwIBAgIEUOLITANBgkqhkiG9w0BAQUFADBQMqswCQYDVQQGEwJGSTEQMA4GA1UECBMHVXZaWlhYTERMA8GA1UEBxMISGVsc2lua2kxGDA
          WBgNVBAoTDlJNNzBTb2Z0d2FyZSBPeTEEMMAoGA1UECwwDUiZEMQ8wDQYDVQQDEwZhcG9sbG8wHhcNMjMwMTAxMTEyODAwWjBrMQswCQYDVQQGEwJGSTE
          QMA4GA1UECBMHVXZaWlhYTERMA8GA1UEBxMISGVsc2lua2kxGDAWBgNVBAoTDlJNNzBTb2Z0d2FyZSBPeTEEMMAoGA1UECwwDUiZEMQ8wDQYDVQQDEwZhcG9sbG8wHhcNMjMwMTAxMTEyODAwWjBrMQswCQYDVQQGEwJGSTE
          GSIB3DQEBAAUAAIBDWAwwgEKAoIBAQCXqP0wqL2AilhaeTj0alwsLafhrDtUt00E5xc7kdD7PISRA270ZmpYMB4W24Uk2QkuwaBp6dI/yRdUvPfoT45YzrqIXMe2451PAQWtEKM
          F5213F0J4/1B71TtrzyH94RnqSHXFFvRN8EY/rzuEzrpZrHdtNs9LRyLqCRXTMMO4z7QghBuxh3K5gu7KqxpHx6No83WNZj4B3gvWLRWv05nbXh/F9YMeQCLTXli1BNAhLQxWhwXM
          KB4uliPQ/KSaal3R26pONUUmqlqVtU1guQozSTPD8HvsDgGg19v2+/N3uf5dRytvEFfwXN3wiY+/R93vBA61n15nTctZIRayg0Gv5AgMBAAEwDQYJKoZIhvcNAQEFBQADggEBAFQ
          wAAUJso1VwjDc2kypK/RRcB8bMAUUIG0hLGL82IvnKouGixGgAcULwQKiVt6uGmlgbSG6Gn5R0b2mlBztXqQ49zRvi5qWNRrtir6eyqwrFGOM6A8rxj3Jhxi2Vb/MJn7XzeVHH
          LzAlv5hwl/2PLnaL2h9Wyg9QwBbwtmkMEqUt/dgixKblRvby/tBuRogWgPONNSACiW+Z5o8UdAoQNMZQozD/1lgOjBXoF0F50ksjQN7xoQZLj9xXefxCFQ69FPcFDeEWbHwSoBy
          5hLPNALaEua5zPDwlxwRjFQtC5XXaRpgIjy/2gsL8+Y5QRhyXnLgg067B1LYW/GuHE=</X509Certificate>
        </X509Data>
      </KeyInfo>
    </KeyDescriptor>
    <KeyDescriptor use="encryption">
      <KeyInfo ds="http://www.w3.org/2000/09/xmldsig#">
        <X509Data>
          <X509Certificate>MIIDUjCCAqggAwIBAgIEUOLITANBgkqhkiG9w0BAQUFADBQMqswCQYDVQQGEwJGSTEQMA4GA1UECBMHVXZaWlhYTERMA8GA1UEBxMISGVsc2lua2kxGDA
          WBgNVBAoTDlJNNzBTb2Z0d2FyZSBPeTEEMMAoGA1UECwwDUiZEMQ8wDQYDVQQDEwZhcG9sbG8wHhcNMjMwMTAxMTEyODAwWjBrMQswCQYDVQQGEwJGSTE
          QMA4GA1UECBMHVXZaWlhYTERMA8GA1UEBxMISGVsc2lua2kxGDAWBgNVBAoTDlJNNzBTb2Z0d2FyZSBPeTEEMMAoGA1UECwwDUiZEMQ8wDQYDVQQDEwZhcG9sbG8wHhcNMjMwMTAxMTEyODAwWjBrMQswCQYDVQQGEwJGSTE
          GSIB3DQEBAAUAAIBDWAwwgEKAoIBAQCXqP0wqL2AilhaeTj0alwsLafhrDtUt00E5xc7kdD7PISRA270ZmpYMB4W24Uk2QkuwaBp6dI/yRdUvPfoT45YzrqIXMe2451PAQWtEKM
          F5213F0J4/1B71TtrzyH94RnqSHXFFvRN8EY/rzuEzrpZrHdtNs9LRyLqCRXTMMO4z7QghBuxh3K5gu7KqxpHx6No83WNZj4B3gvWLRWv05nbXh/F9YMeQCLTXli1BNAhLQxWhwXM
          KB4uliPQ/KSaal3R26pONUUmqlqVtU1guQozSTPD8HvsDgGg19v2+/N3uf5dRytvEFfwXN3wiY+/R93vBA61n15nTctZIRayg0Gv5AgMBAAEwDQYJKoZIhvcNAQEFBQADggEBAFQ
          wAAUJso1VwjDc2kypK/RRcB8bMAUUIG0hLGL82IvnKouGixGgAcULwQKiVt6uGmlgbSG6Gn5R0b2mlBztXqQ49zRvi5qWNRrtir6eyqwrFGOM6A8rxj3Jhxi2Vb/MJn7XzeVHH
          LzAlv5hwl/2PLnaL2h9Wyg9QwBbwtmkMEqUt/dgixKblRvby/tBuRogWgPONNSACiW+Z5o8UdAoQNMZQozD/1lgOjBXoF0F50ksjQN7xoQZLj9xXefxCFQ69FPcFDeEWbHwSoBy
          5hLPNALaEua5zPDwlxwRjFQtC5XXaRpgIjy/2gsL8+Y5QRhyXnLgg067B1LYW/GuHE=</X509Certificate>
        </X509Data>
      </KeyInfo>
    </KeyDescriptor>
    <AssertionConsumerService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST"
    Location="https://richemont.eu.workinsync.io/authorization/login/saml2/sso/richemont" index="1"/>
  </SPSSODescriptor>
</EntityDescriptor>
```



rishabh.m@movein...
okta-dev-24747639

Create SAML Integration

1 General Settings

2 Configure SAML

3 Feedback

A SAML Settings

General

Single sign on URL ⓘ

☒ Use this for Recipient URL and Destination URL

Audience URI (SP Entity ID) ⓘ

Default RelayState ⓘ

If no value is set, a blank RelayState is sent

Name ID format ⓘ

EmailAddress ▼

Application username ⓘ

Email ▼

Update application username on

Create and update ▼

[Show Advanced Settings](#)

What does this form do?

This form generates the XML needed for the app's SAML request.

Where do I find the info this form needs?

The app you're trying to integrate with should have its own documentation on using SAML. You'll need to find that doc, and it should outline what information you need to specify in this form.


SAML Settings

[Edit](#)

GENERAL

Single Sign On URL	https://ssouser.stage.moveinsync.com/authorization/login/saml2/sso/ssouser
Recipient URL	https://ssouser.stage.moveinsync.com/authorization/login/saml2/sso/ssouser
Destination URL	https://ssouser.stage.moveinsync.com/authorization/login/saml2/sso/ssouser
Audience Restriction	https://ssouser.stage.moveinsync.com/authorization/saml2/service-provider-metadata/ssouser
Default Relay State	
Name ID Format	EmailAddress
Response	Signed
Assertion Signature	Signed
Signature Algorithm	RSA_SHA1
Digest Algorithm	SHA256
Assertion Encryption	Unencrypted
SAML Single Logout	Disabled

Share the metadata file back to WorkInSync Team to complete the process.



The screenshot shows the Okta Admin console interface. On the left is a navigation sidebar with options like Dashboard, Directory, Customizations, Applications, Self Service, Security, Workflow, Reports, and Settings. The main content area is titled 'SAML Signing Certificates' and contains a table with columns: Type, Created, Expires, Status, and Actions. There are two certificates listed: SHA-1 (Inactive) and SHA-2 (Active). The 'Actions' dropdown for the SHA-2 certificate is open, showing options like 'View IdP metadata', 'Download certificate', and 'Edit'. A red rectangle highlights the 'View IdP metadata' option. To the right of the table, there is a 'SAML Setup' section with a 'View SAML setup instructions' link. Below the table is a 'User authentication' section with links for 'Authentication policy', 'Password factor only', and 'View policy details'.

OKTA Documentation

https://help.okta.com/en-us/Content/Topics/Apps/Apps_App_Integration_Wizard_SAML.htm