

Replica-Port27017

```

>_ mongosh: 127.0.0.1:27017  >_ mongosh: 127.0.0.1:27018  >_ mongosh: 127.0.0.1:27019  >_ mongosh: 127.0.0.1:27020
>_ MONGOSH
> use college
< switched to db college
> db.college.drop()
< true
> db.students.insertOne({
  name: "Rudraksh",
  course: "MongoDB"
})
< {
  acknowledged: true,
  insertedId: ObjectId('6a2969c0827be3a2592a92ad')
}
> db.students.insertOne({
  name: "Akash",
  course: "MongoDB"
})
< {
  acknowledged: true,
  insertedId: ObjectId('6a2969d3827be3a2592a92ae')
}
college> |
```

Replica-Port27018

```
>_ mongosh: 127.0.0.1:27017 >_ mongosh: 127.0.0.1:27018 >_ mongosh: 127.0.0.1:27019 >_ mongosh: 127.0.0.1:27119 >_ mongosh: 127.0.0.1:27111 +
>_MONGOSH
> use college
< switched to db college
> show collections
< students
> db.college.find()
<
> db.college.find.pretty()
❌ ▶ TypeError: db.college.find.pretty is not a function
> db.college.find().pretty()
<
> db.students.find().pretty()
< {
  _id: ObjectId('6a296445deac5ca203efeb89'),
  name: 'Divyansh',
  course: 'MongoDB'
}
{
  _id: ObjectId('6a2969c0827be3a2592a92ad'),
  name: 'Divyansh',
  course: 'MongoDB'
}
{
  _id: ObjectId('6a2969d3827be3a2592a92ae'),
  name: 'Akash',
  course: 'MongoDB'
}
> rs.status()
< {
  set: 'myReplSet',
  date: 2026-06-10T13:46:19.386Z,
  myState: 1,
  term: Long('5'),
  syncSourceHost: '',
  syncSourceId: -1,
  heartbeatIntervalMillis: Long('2000'),
```

>_MONGOSH

> rs.status()

```
< {
  set: 'myReplSet',
  date: 2026-06-10T13:46:19.386Z,
  myState: 1,
  term: Long('5'),
  syncSourceHost: '',
  syncSourceId: -1,
  heartbeatIntervalMillis: Long('2000'),
  majorityVoteCount: 2,
  writeMajorityCount: 2,
  votingMembersCount: 3,
  writableVotingMembersCount: 3,
  optimes: {
    lastCommittedOpTime: { ts: Timestamp({ t: 1781099175, i: 1 }), t: Long('5') },
    lastCommittedWallTime: 2026-06-10T13:46:15.510Z,
    readConcernMajorityOpTime: { ts: Timestamp({ t: 1781099175, i: 1 }), t: Long('5') },
    appliedOpTime: { ts: Timestamp({ t: 1781099175, i: 1 }), t: Long('5') },
    durableOpTime: { ts: Timestamp({ t: 1781099175, i: 1 }), t: Long('5') },
    writtenOpTime: { ts: Timestamp({ t: 1781099175, i: 1 }), t: Long('5') },
    lastAppliedWallTime: 2026-06-10T13:46:15.510Z,
    lastDurableWallTime: 2026-06-10T13:46:15.510Z,
    lastWrittenWallTime: 2026-06-10T13:46:15.510Z
  },
  lastStableRecoveryTimestamp: Timestamp({ t: 1781099155, i: 1 }),
  electionCandidateMetrics: {
    lastElectionReason: 'stepUpRequestSkipDryRun',
    lastElectionDate: 2026-06-10T13:45:25.421Z,
    electionTerm: Long('5'),
    lastCommittedOpTimeAtElection: { ts: Timestamp({ t: 1781099116, i: 1 }), t: Long('4') },
    lastSeenWrittenOpTimeAtElection: { ts: Timestamp({ t: 1781099116, i: 1 }), t: Long('4') },
    lastSeenOpTimeAtElection: { ts: Timestamp({ t: 1781099116, i: 1 }), t: Long('4') },
    numVotesNeeded: 2,
    priorityAtElection: 1,
  }
}
```

```

    priorityAtElection: 1
  },
  members: [
    {
      _id: 0,
      name: '127.0.0.1:27017',
      health: 0,
      state: 8,
      stateStr: '(not_reachable/healthy)',
      uptime: 0,
      optime: { ts: Timestamp({ t: 0, i: 0 }), t: Long('-1') },
      optimeDurable: { ts: Timestamp({ t: 0, i: 0 }), t: Long('-1') },
      optimeWritten: { ts: Timestamp({ t: 0, i: 0 }), t: Long('-1') },
      optimeDate: 1970-01-01T00:00:00.000Z,
      optimeDurableDate: 1970-01-01T00:00:00.000Z,
      optimeWrittenDate: 1970-01-01T00:00:00.000Z,
      lastAppliedWallTime: 2026-06-10T13:45:32.974Z,
      lastDurableWallTime: 2026-06-10T13:45:32.974Z,
      lastWrittenWallTime: 2026-06-10T13:45:32.974Z,
      lastHeartbeat: 2026-06-10T13:46:15.370Z,
      lastHeartbeatRecv: 2026-06-10T13:45:39.966Z,
      pingMs: Long('0'),
      lastHeartbeatMessage: 'Error connecting to 127.0.0.1:27017 :: caused by :: onInvoke :: caused by :: No connection could be made because the t
      syncSourceHost: '',
      syncSourceId: -1,
      infoMessage: '',
      configVersion: 1,
      configTerm: 5
    },
  ],

```

```

  {
    _id: 1,
    name: '127.0.0.1:27018',
    health: 1,
    state: 1,
    stateStr: 'PRIMARY',
    uptime: 378,
    optime: { ts: Timestamp({ t: 1781099175, i: 1 }), t: Long('5') },
    optimeDate: 2026-06-10T13:46:15.000Z,
    optimeWritten: { ts: Timestamp({ t: 1781099175, i: 1 }), t: Long('5') },
    optimeWrittenDate: 2026-06-10T13:46:15.000Z,
    lastAppliedWallTime: 2026-06-10T13:46:15.510Z,
    lastDurableWallTime: 2026-06-10T13:46:15.510Z,
    lastWrittenWallTime: 2026-06-10T13:46:15.510Z,
    syncSourceHost: '',
    syncSourceId: -1,
    infoMessage: '',
    electionTime: Timestamp({ t: 1781099125, i: 1 }),
    electionDate: 2026-06-10T13:45:25.000Z,
    configVersion: 1,
    configTerm: 5,
    self: true,
    lastHeartbeatMessage: ''
  },

```

```
,
{
  _id: 2,
  name: '127.0.0.1:27019',
  health: 1,
  state: 2,
  stateStr: 'SECONDARY',
  uptime: 346,
  optime: { ts: Timestamp({ t: 1781099175, i: 1 }), t: Long('5') },
  optimeDurable: { ts: Timestamp({ t: 1781099175, i: 1 }), t: Long('5') },
  optimeWritten: { ts: Timestamp({ t: 1781099175, i: 1 }), t: Long('5') },
  optimeDate: 2026-06-10T13:46:15.000Z,
  optimeDurableDate: 2026-06-10T13:46:15.000Z,
  optimeWrittenDate: 2026-06-10T13:46:15.000Z,
  lastAppliedWallTime: 2026-06-10T13:46:15.510Z,
  lastDurableWallTime: 2026-06-10T13:46:15.510Z,
  lastWrittenWallTime: 2026-06-10T13:46:15.510Z,
  lastHeartbeat: 2026-06-10T13:46:17.697Z,
  lastHeartbeatRecv: 2026-06-10T13:46:18.304Z,
  pingMs: Long('0'),
  lastHeartbeatMessage: '',
  syncSourceHost: '127.0.0.1:27018',
  syncSourceId: 1,
  infoMessage: '',
  configVersion: 1,
  configTerm: 5
}
],
```

```

    },
    ok: 1,
    '$clusterTime': {
      clusterTime: Timestamp({ t: 1781099175, i: 1 }),
      signature: {
        hash: Binary.createFromBase64('AAAAAAAAAAAAAAAAAAAAAAAAAA=', 0),
        keyId: Long('0')
      }
    },
    operationTime: Timestamp({ t: 1781099175, i: 1 })
  }
> use college

db.students.insertOne({
  name: "Rahul",
  course: "Failover Test"
})
< already on db college
> db.students.insertOne({
  name: "Rahul",
  course: "Failover Test"
})
< {
  acknowledged: true,
  insertedId: ObjectId('6a296ac5306b79eda6d1ec96')
}
college> |

```

Replica-Port 27019

```

> use college
< switched to db college
> db.students.find().pretty()
< {
  _id: ObjectId('6a2969c0827be3a2592a92ad'),
  name: 'Divyansh',
  course: 'MongoDB'
}
{
  _id: ObjectId('6a2969d3827be3a2592a92ae'),
  name: 'Akash',
  course: 'MongoDB'
}
{
  _id: ObjectId('6a296ac5306b79eda6d1ec96'),
  name: 'Rahul',
  course: 'Failover Test'
}
> rs.status()
< {
  set: 'myRepSet',
  date: 2026-06-10T13:47:52.659Z,
  myState: 2,
  term: Long('5'),
  syncSourceHost: '127.0.0.1:27018',
  syncSourceId: 1,
  heartbeatIntervalMillis: Long('2000'),
  majorityVoteCount: 2,
  writeMajorityCount: 2,
  votingMembersCount: 3,
  writableVotingMembersCount: 3,
  optimes: {
    lastCommittedOpTime: { ts: Timestamp({ t: 1781099265, i: 1 }), t: Long('5') },
    lastCommittedWallTime: 2026-06-10T13:47:45.595Z,
    readConcernMajorityOpTime: { ts: Timestamp({ t: 1781099265, i: 1 }), t: Long('5') },
  }
}

```

```

members: [
  {
    _id: 0,
    name: '127.0.0.1:27017',
    health: 1,
    state: 2,
    stateStr: 'SECONDARY',
    uptime: 13,
    optime: { ts: Timestamp({ t: 1781099265, i: 1 }), t: Long('5') },
    optimeDurable: { ts: Timestamp({ t: 1781099265, i: 1 }), t: Long('5') },
    optimeWritten: { ts: Timestamp({ t: 1781099265, i: 1 }), t: Long('5') },
    optimeDate: 2026-06-10T13:47:45.000Z,
    optimeDurableDate: 2026-06-10T13:47:45.000Z,
    optimeWrittenDate: 2026-06-10T13:47:45.000Z,
    lastAppliedWallTime: 2026-06-10T13:47:45.595Z,
    lastDurableWallTime: 2026-06-10T13:47:45.595Z,
    lastWrittenWallTime: 2026-06-10T13:47:45.595Z,
    lastHeartbeat: 2026-06-10T13:47:51.434Z,
    lastHeartbeatRecv: 2026-06-10T13:47:51.917Z,
    pingMs: Long('0'),
    lastHeartbeatMessage: '',
    syncSourceHost: '127.0.0.1:27018',
    syncSourceId: 1,
    infoMessage: '',
    configVersion: 1,
    configTerm: 5
  },

```

```

{
  _id: 1,
  name: '127.0.0.1:27018',
  health: 1,
  state: 1,
  stateStr: 'PRIMARY',
  uptime: 439,
  optime: { ts: Timestamp({ t: 1781099265, i: 1 }), t: Long('5') },
  optimeDurable: { ts: Timestamp({ t: 1781099265, i: 1 }), t: Long('5') },
  optimeWritten: { ts: Timestamp({ t: 1781099265, i: 1 }), t: Long('5') },
  optimeDate: 2026-06-10T13:47:45.000Z,
  optimeDurableDate: 2026-06-10T13:47:45.000Z,
  optimeWrittenDate: 2026-06-10T13:47:45.000Z,
  lastAppliedWallTime: 2026-06-10T13:47:45.595Z,
  lastDurableWallTime: 2026-06-10T13:47:45.595Z,
  lastWrittenWallTime: 2026-06-10T13:47:45.595Z,
  lastHeartbeat: 2026-06-10T13:47:50.840Z,
  lastHeartbeatRecv: 2026-06-10T13:47:52.180Z,
  pingMs: Long('0'),
  lastHeartbeatMessage: '',
  syncSourceHost: '',
  syncSourceId: -1,
  infoMessage: '',
  electionTime: Timestamp({ t: 1781099125, i: 1 }),
  electionDate: 2026-06-10T13:45:25.000Z,
  configVersion: 1,
  configTerm: 5
},


```



```
{
  _id: 2,
  name: '127.0.0.1:27019',
  health: 1,
  state: 2,
  stateStr: 'SECONDARY',
  uptime: 440,
  optime: { ts: Timestamp({ t: 1781099265, i: 1 }), t: Long('5') },
  optimeDate: 2026-06-10T13:47:45.000Z,
  optimeWritten: { ts: Timestamp({ t: 1781099265, i: 1 }), t: Long('5') },
  optimeWrittenDate: 2026-06-10T13:47:45.000Z,
  lastAppliedWallTime: 2026-06-10T13:47:45.595Z,
  lastDurableWallTime: 2026-06-10T13:47:45.595Z,
  lastWrittenWallTime: 2026-06-10T13:47:45.595Z,
  syncSourceHost: '127.0.0.1:27018',
  syncSourceId: 1,
  infoMessage: '',
  configVersion: 1,
  configTerm: 5,
  self: true,
  lastHeartbeatMessage: ''
},
ok: 1,
'$clusterTime': {
  clusterTime: Timestamp({ t: 1781099265, i: 1 }),
  signature: {
    hash: Binary.createFromBase64('AAAAAAAAAAAAAAAAAAAAAAAAAA=', 0),
    keyId: Long('0')
  }
},
operationTime: Timestamp({ t: 1781099265, i: 1 })
}
college>|
```

Sharding:

Config Server Replica Set:



The screenshot shows a MongoDB shell interface with four tabs at the top, each labeled 'mongosh: 127.0.0.1:27119', 'mongosh: 127.0.0.1:27112', 'mongosh: 127.0.0.1:27020', and 'mongosh: 127.0.0.1:27111'. The active tab is the first one. The shell prompt is '> _MONGOSH'. The user has entered the command 'rs.initiate({ _id: "configReplSet", configsvr: true, members: [{ _id: 0, host: "127.0.0.1:27119" }] })'. The output is a JSON object: '{ ok: 1, '\$clusterTime': { clusterTime: Timestamp({ t: 1781099891, i: 1 }), signature: { hash: Binary.createFromBase64('AAAAAAAAAAAAAAAAAAAAAAAAAAAA=', 0), keyId: Long('0') }, }, operationTime: Timestamp({ t: 1781099891, i: 1 }) }'. The prompt is now 'configReplSet [direct: primary] test>'.


```
> _MONGOSH
> rs.initiate({
  _id: "configReplSet",
  configsvr: true,
  members: [
    {
      _id: 0,
      host: "127.0.0.1:27119"
    }
  ]
})
< {
  ok: 1,
  '$clusterTime': {
    clusterTime: Timestamp({ t: 1781099891, i: 1 }),
    signature: {
      hash: Binary.createFromBase64('AAAAAAAAAAAAAAAAAAAAAAAAAAAA=', 0),
      keyId: Long('0')
    }
  },
  operationTime: Timestamp({ t: 1781099891, i: 1 })
}
configReplSet [direct: primary] test>
```

Shard 1:

```
>_MONGOSH

> rs.initiate({
  _id: "shard1ReplSet",
  members: [
    {
      _id: 0,
      host: "127.0.0.1:27111"
    }
  ]
})
< {
  ok: 1,
  '$clusterTime': {
    clusterTime: Timestamp({ t: 1781100006, i: 1 }),
    signature: {
      hash: Binary.createFromBase64('AAAAAAAAAAAAAAAAAAAAAAAAA=', 0),
      keyId: Long('0')
    }
  },
  operationTime: Timestamp({ t: 1781100006, i: 1 })
}
shard1ReplSet [direct: primary] test>
```

Shard2:



```
>_MONGOSH

> rs.initiate({
  _id: "shard2ReplSet",
  members: [
    {
      _id: 0,
      host: "127.0.0.1:27112"
    }
  ]
})
< {
  ok: 1,
  '$clusterTime': {
    clusterTime: Timestamp({ t: 1781100504, i: 1 }),
    signature: {
      hash: Binary.createFromBase64('AAAAAAAAAAAAAAAAAAAAAAAAAA=', 0),
      keyId: Long('0')
    }
  },
  operationTime: Timestamp({ t: 1781100504, i: 1 })
}
```

mongos (Query Router)

```

> sh.addShard("shard1ReplSet/127.0.0.1:27111")
< {
  shardAdded: 'shard1ReplSet',
  ok: 1,
  '$clusterTime': {
    clusterTime: Timestamp({ t: 1781100670, i: 40 }),
    signature: {
      hash: Binary.createFromBase64('AAAAAAAAAAAAAAAAAAAAAAAAAA=', 0),
      keyId: Long('0')
    }
  },
  operationTime: Timestamp({ t: 1781100670, i: 40 })
}
> sh.addShard("shard2ReplSet/127.0.0.1:27112")
< {
  shardAdded: 'shard2ReplSet',
  ok: 1,
  '$clusterTime': {
    clusterTime: Timestamp({ t: 1781100687, i: 36 }),
    signature: {
      hash: Binary.createFromBase64('AAAAAAAAAAAAAAAAAAAAAAAAAA=', 0),
      keyId: Long('0')
    }
  },
  operationTime: Timestamp({ t: 1781100687, i: 36 })
}
> sh.status()
<
shardingVersion

{
  _id: ObjectId('6a296d738f421348038a1809'),
  clusterId: ObjectId('6a296d738f421348038a1808')
}

```

shards

```
[
  {
    _id: 'shard1ReplSet',
    host: 'shard1ReplSet/127.0.0.1:27111',
    topologyTime: Timestamp({ t: 1781100670, i: 14 }),
    replSetConfigVersion: -1
  },
  {
    _id: 'shard2ReplSet',
    host: 'shard2ReplSet/127.0.0.1:27112',
    topologyTime: Timestamp({ t: 1781100687, i: 12 }),
    replSetConfigVersion: -1
  }
]
```

active mongoses

```
[
  {
    '8.3.2': 1
  }
]
```

autosplit

```
{
  'Currently enabled': 'yes'
}
```

balancer

```
{
  'Currently enabled': 'yes',
  'Currently running': 'no',
  'Failed balancer rounds in last 5 attempts': 0,
  'Migration Results for the last 24 hours': 'No recent migrations'
}
```

shardedDataDistribution

```
[]
```

databases

```
[
  {
    database: {
      _id: 'config',
      primary: 'config',
      partitioned: true
    },
    collections: {}
  }
]
```

```

>_MONGOSH
> sh.enableSharding("college")
< {
  ok: 1,
  '$clusterTime': {
    clusterTime: Timestamp({ t: 1781100763, i: 4 }),
    signature: {
      hash: Binary.createFromBase64('AAAAAAAAAAAAAAAAAAAAAAAAA=', 0),
      keyId: Long('0')
    }
  },
  operationTime: Timestamp({ t: 1781100763, i: 4 })
}
> use college
< switched to db college
> db.students.createIndex({ rollNo: 1 })
< rollNo_1
> sh.shardCollection("college.students", { rollNo: 1 })
< {
  collectionsharded: 'college.students',
  ok: 1,
  '$clusterTime': {
    clusterTime: Timestamp({ t: 1781100867, i: 45 }),
    signature: {
      hash: Binary.createFromBase64('AAAAAAAAAAAAAAAAAAAAAAAAA=', 0),
      keyId: Long('0')
    }
  },
  operationTime: Timestamp({ t: 1781100867, i: 44 })
}
> for (let i = 1; i <= 20; i++) {
  db.students.insertOne({
    rollNo: i,
    name: "Student" + i,
    course: "MongoDB"
  });
}

```



```

    }
    > for (let i = 1; i <= 20; i++) {
      db.students.insertOne({
        rollNo: i,
        name: "Student" + i,
        course: "MongoDB"
      });
    }
  < {
    acknowledged: true,
    insertedId: ObjectId('6a297159e2e4f03b492493ee')
  }
  > db.students.getShardDistribution()
  <
  Shard shard2ReplSet at shard2ReplSet/127.0.0.1:27112

  {
    data: '1KiB',
    docs: 20,
    chunks: 1,
    'estimated data per chunk': '1KiB',
    'estimated docs per chunk': 20
  }

  Totals

  {
    data: '1KiB',
    docs: 20,
    chunks: 1,
    'Shard shard2ReplSet': [
      '100 % data',
      '100 % docs in cluster',
      '73B avg obj size on shard'
    ]
  }
}

```

```

>_MONGOSH
}
> for(let i = 21; i <= 5000; i++){
  db.students.insertOne({
    rollNo: i,
    name: "Student" + i
  });
}
< {
  acknowledged: true,
  insertedId: ObjectId('6a2972d8e2e4f03b4924a762')
}
> db.students.getShardDistribution()
<
Shard shard2ReplSet at shard2ReplSet/127.0.0.1:27112

{
  data: '272KiB',
  docs: 5000,
  chunks: 1,
  'estimated data per chunk': '272KiB',
  'estimated docs per chunk': 5000
}

Totals

{
  data: '272KiB',
  docs: 5000,
  chunks: 1,
  'Shard shard2ReplSet': [
    '100 % data',
    '100 % docs in cluster',
    '55B avg obj size on shard'
  ]
}
[direct: mongos] college>

```