DisputeDesk — Phase 2.1 Report

Security review and corrections to the Phase 2 sign-in and access-control foundation

Date **3 November 2026** Commit **bd1f620** (not pushed) Builds on **aa15514** (Phase 2) Branch **master**

Summary. All nine review items were checked. Three problems were fixed: failed sign-ins on one account locked every local account, there were no security headers, and the health route answered without a session. CSRF protection gained a `Sec-Fetch-Site` check, and three test gaps were closed. Every fix has a regression test that failed before the fix. All tests pass, and 22 browser checks pass on both the production build and the dev server. No PayPal or Gemini calls were made.

113/113	53/53	22/22	22/22	0
Server tests (9 new)	Client tests (3 new)	Browser checks, production build	Browser checks, dev server	Secrets or new dependencies


1. Results

Check	Result
Server tests (`cd server && npm test`)	113 / 113 pass (104 before; 9 new)
Client tests (`cd client && npm test`)	53 / 53 pass (50 before; 3 new)
Type checks	Server and client pass
Production build	Passes; no inline scripts, no demo records, hashes or passwords in the bundle
Browser checks	22 / 22 on `localhost:4173` (production build) and 22 / 22 on `localhost:5173` (dev)
Original PayPal sandbox scripts	`draft-response.js` and `evidence-checklist.js` still run
Secret scan of the commit	0 `.env` values, 0 demo passwords, 0 key-shaped strings; `.env` not staged
Live PayPal or Gemini calls	None (server log shows only its startup line)
Existing tests removed or weakened	None (3 extended, see section 5)

2. Skills and tools used

Skill or tool	Why it was used
`security-and-hardening`	Threat model, header list, rate-limit and dependency-audit rules
`test-driven-development`	Every regression test written first and seen failing before the fix
`api-and-interface-design`	Kept one error format (`{error: {code, message}}`) and the existing routes
Ponytail	Smallest change; no new dependencies
ECC	`security-review` checklist for the final pass; GateGuard hook active on every new file
Built-in browser and headless Chrome (DevTools protocol, no install)	Real-browser header, cookie and CSP checks and these screenshots. ECC's chrome-devtools connector failed to connect, so it was not used.

3. How a request is checked now



Sign-in also passes the limiter before the password check: 10 failures per email and 100 per address in 15 minutes.

4. The nine review items

1. Address-based sign-in limit

Fixed

Finding	The Vite proxy connects from `127.0.0.1`, so every browser counted as one address. 10 failed sign-ins on *any* accounts locked *every* account for 15 minutes. Failure records for one-off emails were also never cleaned up. `X-Forwarded-For` is not trusted, so the address can't be faked.
Change	`server/src/auth.ts`: new `LOGIN_MAX_FAILURES_PER_ADDRESS = 100`; `blocked(keys, max)` takes a per-key limit; every failure clears expired records. `app.ts` checks the email at 10 and the address at 100.
Tests	"failed sign-ins on one account don't lock the other accounts that share the local address"; "100 failed sign-ins from one address lock sign-in from it for 15 minutes"; "a key can have its own, higher limit, and expired failures are dropped from memory".
Evidence	Figures 2 and 3: Merchant B locked after 10 wrong passwords, while Merchant A still signs in.

2. Security headers

Fixed

Finding	Neither the API nor the page sent any security headers.
Change	API headers on every response in `app.ts`. Page headers in the new `client/src/security-headers.ts`, used by `vite.config.ts` for dev and preview. Full values in section 6.
Tests	"every API response carries the security headers, errors included" (200, 401, 404, 400, 502 and sign-in); client: "the production page has a strict CSP…", "both the dev and production pages refuse framing and sniffing…".
Evidence	Browser: page and API headers present through the proxy; 0 CSP violations on the production build while using every screen (figure 4).

3. Admin read-only, frontend and backend

Verified, test gap closed

Finding	Already correct: no PUT, PATCH or DELETE routes, the AI draft is merchant-only, and the UI hides the draft button. But nothing would catch a future write route that forgot to block admin.
Change	Tests only. A route inventory reads every route Express registered; the role table now also asserts admin's only write-method routes are `/api/analysis` and `/api/analysis/ai/example`, which compute an answer and change nothing.
Tests	"every registered route is either public sign-in/out or in the protected list"; the role-matrix test, extended.
Evidence	Figures 6 and 7. Browser: no Generate AI draft button, AI route 403, DELETE on accounts 404.

4. Session expiry, logout and revocation

Verified, test gap closed

Finding	Already correct: 30-minute idle and 8-hour absolute expiry, a new token on every sign-in, logout ends the session on the server, a stale cookie is cleared after a 401. No test replayed a signed-out cookie on every route.
Change	Tests only.
Tests	"a signed-out cookie is refused on every protected route" (admin, merchant and buyer).
Evidence	Browser: sign-out removes the cookie; replaying the old cookie gets 401. Figure 8: a session ended on the server returns the app to sign-in.

5. Consistent localhost cookie

Fixed

Finding	The cookie was already host-only (`__Host-`). But Vite would quietly move to another port when 5173 was busy, changing the page's origin.
Change	`vite.config.ts` : `host: "localhost"` , fixed ports 5173 and 4173, `strictPort: true` for dev and preview, one shared proxy setting with `changeOrigin: false` .
Tests	"the page must use one hostname: localhost and 127.0.0.1 are different origins"; client: "Vite serves the headers, keeps one hostname and port...".
Evidence	Browser: cookie `HttpOnly, Secure, SameSite=Strict, Path=/` , no Domain attribute (host-only; browser storage lists the host as `localhost`); `document.cookie` empty; `127.0.0.1:5173` and `:4173` refuse connections.

6. Origin validation and CSRF

Hardened

Finding	`SameSite=Strict` plus the Origin check already held. A write request with no Origin header was let through, and `Sec-Fetch-Site` was ignored.
Change	`app.ts` : a write request marked `Sec-Fetch-Site: cross-site` or `same-site` is refused even without an Origin.
Tests	"a write request the browser marks cross-site or same-site is refused even without an Origin" (also covers sign-out).
Evidence	Browser: another site's page auto-submitted a sign-out form while signed in. It got **403** and the session survived. The page itself can't reach other origins (CSP and CORP).

7. Account isolation on every route

Fixed

Finding	All 10 routes isolate accounts correctly, except `/api/health` : it needed no session and revealed the AI model, why AI was off, and whether PayPal was set up.
Change	`/api/health` now requires a merchant or admin session. The client calls it only after sign-in, and buyers never call it.
Tests	"health needs a merchant or admin session"; health added to the protected list and the role matrix.
Evidence	Browser: health 401 signed out, 403 for Buyer B, 200 for Merchant A. Figure 5: Buyer B sees only their own 2 disputes.

8. Sensitive data in logs or responses

Verified

Finding	No issue. Requests are not logged. Error logs record only error codes. Validation errors never repeat the input. Password hashes never leave the server. Emails appear only in your own `/api/auth/me` and the admin account list.
Change	None needed. The Phase 2.1 changes add no logging.
Tests	Existing: "admin can read every account but never sees password hashes", "health reports configured state without secrets", "a wrong password and an unknown email get the same answer".
Evidence	Scan of the commit: 0 new `console.*` lines; 0 `innerHTML` , `eval` or `localStorage` .

9. Dependency vulnerability audit

Plan ready, needs approval

Finding	`npm audit` has never run. It contacts `registry.npmjs.org`, so it waits for your approval.
Change	An offline inventory was taken; the audit plan is in section 8.
Tests	Not applicable.
Evidence	Offline `npm ls`: 3 lockfiles, 12 direct packages.

5. Regression tests

Each test below was run before its fix. The ones marked **guard** passed from the start: they lock in behaviour that was already correct.

File	Test	Item	Before the fix
server/app.test.ts	every API response carries the security headers, errors included	2	failed
server/app.test.ts	failed sign-ins on one account don't lock the other accounts that share the local address	1	failed
server/app.test.ts	100 failed sign-ins from one address lock sign-in from it for 15 minutes	1	failed
server/auth.test.ts	a key can have its own, higher limit, and expired failures are dropped from memory	1	failed
server/app.test.ts	a signed-out cookie is refused on every protected route	4	failed (health)
server/app.test.ts	a write request the browser marks cross-site or same-site is refused even without an Origin	6	failed
server/app.test.ts	health needs a merchant or admin session	7	failed
server/app.test.ts	the page must use one hostname: localhost and 127.0.0.1 are different origins	5	guard
server/app.test.ts	every registered route is either public sign-in/out or in the protected list	3, 7	guard
client/security-headers.test.ts	the production page has a strict CSP: own scripts and styles only, no inline code, no framing	2	failed
client/security-headers.test.ts	both the dev and production pages refuse framing and sniffing and send no referrer	2	failed
client/security-headers.test.ts	Vite serves the headers, keeps one hostname and port, and forwards the browser's Host to the API	5	failed

Existing tests extended (none removed, no assertion weakened)

- **Protected-route list:** `/api/health` added, so the missing, forged and expired-session test now covers it too.
- **Role matrix:** a health row was added. The test now also fails if any protected route is missing from the matrix, or if admin is allowed a write route outside the read-only list.
- **Host guard:** this test used `/api/health` as a check that needed no sign-in. It now asserts `401 not_signed_in`, which still proves the request got past the host guard.


6. Security headers

Header	API (every response)	Page, production build	Page, dev server
`X-Content-Type-Options`	nosniff	nosniff	nosniff
`X-Frame-Options`	DENY	DENY	DENY
`Referrer-Policy`	no-referrer	no-referrer	no-referrer
`Cross-Origin-Resource-Policy`	same-origin	—	—
`Cross-Origin-Opener-Policy`	—	same-origin	same-origin
`Content-Security-Policy`	`default-src 'none'; frame-ancestors 'none'`	`default-src 'self'; script-src 'self'; style-src 'self'; img-src 'self' data:; connect-src 'self'; font-src 'self'; object-src 'none'; base-uri 'none'; form-action 'self'; frame-ancestors 'none'`	`object-src 'none'; base-uri 'none'; form-action 'self'; frame-ancestors 'none'`
`X-Powered-By`	removed	—	—


- **Why dev is looser:** Vite's React live reload injects an inline script and serves CSS as inline `<style>` tags. A strict `script-src` or `style-src` would break it. The production build has no inline code, so it gets the strict policy.
- **No HSTS:** browsers ignore it over plain HTTP, and it does nothing on localhost. A hosted version needs HTTPS plus HSTS.
- `img-src data:` exists only for the empty favicon in `index.html`.

7. Browser walkthrough (production build, localhost:4173)


Captured with headless Chrome on the production build under the strict CSP. Passwords show only as masked dots. The deliberate Merchant B lockout was cleared by restarting the API afterwards.




1. Sign-in, production build. Served with the strict CSP; no violations.




2. Merchant B locked after 10 wrong passwords, even with the right one (429).




3. Merchant A still signs in straight after Merchant B's lockout, from the same address. Before Phase 2.1 this was refused too.




4. Validation example under the strict CSP. The richest screen renders fully with no inline scripts or styles and no CSP violations.




5. Buyer B. Only their 2 disputes, status and amount only. Health and merchant routes return 403.



6. Admin. All 3 disputes and the "Admin (read-only)" badge.



7. Admin read-only. No Generate AI draft button; the AI route itself returns 403.



8. Session ended on the server. The next request returns 401 and the app returns to sign-in with a notice.

Browser checks (identical on 4173 and 5173)

#	Check	4173	5173
1	Page headers: X-Frame-Options, nosniff, Referrer-Policy	PASS	PASS
2	Signed out: `/api/auth/me` is 401	PASS	PASS
3	Signed out: `/api/health` is 401	PASS	PASS
4	Cookie: HttpOnly, Secure, SameSite=Strict, Path=/. No Domain attribute is sent (host-only). Browser storage lists the host as localhost.	PASS	PASS
5	`document.cookie` is empty	PASS	PASS
6	API security headers arrive through the proxy	PASS	PASS
7	Merchant A sees DEMO-1001 and DEMO-1002 only	PASS	PASS
8	Merchant A: DEMO-1003 is 404	PASS	PASS
9	Merchant A: health 200	PASS	PASS
10	Merchant A: analysis and validation example render	PASS	PASS
11	The page can't fetch another origin	PASS	PASS
12	Cross-site form POST to sign-out is refused (403)	PASS	PASS
13	...and the session is unaffected	PASS	PASS
14	Sign-out removes the cookie from the browser	PASS	PASS
15	Replaying the signed-out cookie gets 401	PASS	PASS
16	Buyer B sees 2 disputes	PASS	PASS
17	Buyer B: health and merchant list 403	PASS	PASS
18	Admin: no Generate AI draft button	PASS	PASS

19	Admin: AI route 403	PASS	PASS
20	Admin: DELETE on accounts 404	PASS	PASS
21	No CSP violations	PASS	PASS
22	No console errors besides the deliberate 4xx checks	PASS	PASS

Also checked: `127.0.0.1:5173` and `127.0.0.1:4173` refuse connections, so the page lives on `localhost` only.

8. Dependency audit plan

Offline inventory (`npm ls` , no network)

Folder	Runs in production	Build and test only	Total entries
root	`dotenv` 18.0.9	—	1
`server/`	`express` 5.3.0	`typescript` 7.0.2, `@types/express` 5.0.6, `@types/node` 26.6.6	163
`client/`	`react` , `react-dom` 19.3.1	`vite` 8.3.5, `@vitejs/plugin-react` 6.1.2, `typescript` 7.0.2, `@types/react` , `@types/react-dom`	90

Steps, after approval

1. Run `npm audit --json` and `npm audit signatures` in the root, `server/` and `client/` . They send only package names and versions to `registry.npmjs.org` : no code and no `.env` values.
2. Triage by where the package runs: production packages first (`express` , `react` , `react-dom` , `dotenv`), then build tools.
3. No `npm audit fix --force` . Upgrade one package at a time, read its changelog, and re-run all tests and the browser checks.
4. Record any finding left unfixed with a reason and a review date. Repeat before every release.

9. Changed files (commit bd1f620)

File	Change
`server/src/auth.ts`	Per-address limit of 100; `blocked(keys, max)` ; expired records cleaned up; `size()`
`server/src/app.ts`	Security headers middleware; `Sec-Fetch-Site` check; separate email and address limits; `/api/health` needs merchant or admin
`server/src/app.test.ts`	8 new tests; protected list, role matrix and host-guard test extended
`server/src/auth.test.ts`	1 new limiter test
`client/src/security-headers.ts` (new)	Page headers for the production build and dev
`client/src/security-headers.test.ts` (new)	3 tests for the headers and the Vite settings
`client/vite.config.ts`	`host: "localhost"` , fixed ports, `strictPort` , headers, shared proxy for dev and preview
`README.md` , `CLAUDE.md`	Limits, headers, the production preview command, new guarantees
`.claude/launch.json`	`client-preview` entry for checking the production build

10. Remaining production risks

Risk	Impact	When to fix
Sessions and sign-in limits live in memory	A restart signs everyone out; works with one server process only	With the persistent store
Rate limit covers sign-in only	Other routes are unlimited (the AI route allows one request per dispute at a time)	Before hosting
Targeted lockout	Anyone can lock a known email for 15 minutes with 10 wrong passwords	Consider progressive delays
Dev server page CSP is looser	Strict CSP applies to the production build only	Accepted for local development
No HTTPS or HSTS	Fine on localhost only	Before hosting; also set `trust proxy` to the real proxy
Demo passwords in the README	Acceptable only while the accounts are synthetic and the server is local	Real accounts need real sign-up
Dependency audit not run	Known package vulnerabilities not yet checked	On your approval (section 8)
Not tested in Safari	Safari's handling of `Secure` cookies on `http://localhost` is unverified	When a Mac is available